Name = Babar Zareen
sap id = 74760
lab task = oop

Question No = 01

Abstract Class method :

code:

```java
abstract class vehicle { //name babar zaree sap id 74760
    int tyres;
    abstract void start();
}
class car extends vehicle {//name babar zaree sap id 74760
    int tyres = 4;
    void start(){
            System.out.println("car start with key:");
    }
}
class Bike extends vehicle {
    int tyres = 2;
    void start(){ //name babar zaree sap id 74760
            System.out.println("Bike start with kick:");
    }
}
public class Exe{
    public static void main(String[] args){
        car c = new car();
        c.start();

        Bike b = new Bike();
        b.start();
    }
}
```

output:

```
car start with key:
Bike start with kick:


...Program finished with exit code 0
Press ENTER to exit console.
```

Question No = 02

Employee Data System Abstract Class method:

code:

```java
abstract class Employee { //name babar zaree sap id 74760
    String name;
    int id;
    int salary;
    abstract void calculatesalary();
}
class manager extends Employee {//name babar zaree sap id 74760
    String name = "Babar zareen:";
    int id = 74760;

    void calculatesalary(){
    System.out.println("name babar zareen:");
    System.out.println("id 74760:");
    }
}
class programmer  extends Employee{
    int salary = 50000;

    void calculatesalary(){ //name babar zaree sap id 74760
    System.out.println("salary 50000:");
    }
}
```

```java
public class Exe{
    public static void main(String[] args){
        manager m = new manager();
        m.calculatesalary();

        programmer p = new programmer();
        p.calculatesalary();
    }
}

```

output

```
name babar zareen:
id 74760:
salary 50000:


...Program finished with exit code 0
Press ENTER to exit console.
```

Question No = 03

Abstract interface:

code:

```
interface I1{ //name babar zaree sap id 74760
public void start();
}

class Test implements I1{//name babar zaree sap id 74760
public void start(){;
   System.out.println("car start with key:");
    }
}
public class Exe{
    public static void main(String[] args){
        Test t = new Test();
        t.start();

    }
}
```

Output

```
car start with key:


...Program finished with exit code 0
Press ENTER to exit console.
```

Question No = 04

Abstract interface play physical game:

Code:

```java
interface playable{ //name babar zaree sap id 74760
public void play();
}

class football implements playable{//name babar zaree sap id 74760
public void play(){
   System.out.println("play football:");
    }
}

class volleyball implements playable{//name babar zaree sap id 74760
public void play(){
   System.out.println("play volleyball:");
    }
}

class basketball implements playable{//name babar zaree sap id 74760
public void play(){
   System.out.println("play basketball:");
    }
}
public class Exe{
    public static void main(String[] args){
        football f = new football();
        f.play();

        volleyball v = new volleyball(); //name babar zaree sap id 74760
        v.play();

        basketball b = new basketball();
        b.play();
    }
}
```

output:

```
play football:
play volleyball:
play basketball:


...Program finished with exit code 0
Press ENTER to exit console.
```