

Begin: 2023-03-28
20:33 UTC+3



End: 2023-05-19
12:33 UTC+3

Elapsed: 15:16:38:27

Running

Remaining:
35:23:21:32

Overview

Problem

Status

Rank (15:16:38:22)

0 Comments

Setting

☆Favorite

A B C D E

Submit

Status

My Status

Translate

PDF

Time limit

1000 ms

Mem limit

1048576 kB

OS

Linux

A - Boiling Vegetables



The trick to boiling vegetables is to make sure all pieces are about the same size. If they are not, the small ones get too soft or the large ones get undercooked (or both). Fortunately, you have heard of the kitchen knife, but your parents' warnings of using sharp instruments still echoes in your head. Therefore you better use it as little as possible. You can take a piece of a vegetable of weight w and cut it arbitrarily in two pieces of weight w_{left} and w_{right} , where $w_{\text{left}} + w_{\text{right}} = w$. This operation constitutes a “cut”. Given a set of pieces of vegetables, determine the minimum number of cuts needed to make the ratio between the smallest and the largest resulting piece go above a given threshold.



Input

The input starts with a floating point number T with 2 decimal digits, $0.5 < T < 1$, and a positive integer $N \leq 1\,000$. Next follow N positive integer weights w_1, w_2, \dots, w_N . All weights are less than 10^6 .

Output

Output the minimum number of cuts needed to make the ratio between the resulting minimum weight piece and the resulting maximum weight piece be above T . You may assume that the number of cuts needed is less than 500.

To avoid issues with floating point numbers, you can assume that the optimal answer for ratio T is the same as for ratio $T + 0.0001$.

Sample 1

Input	copy	Output	copy
0.99 3 2000 3000 4000		6	

Sample 2

Input	copy	Output	copy
-------	------	--------	------

0.80 2
1000 1400

3

All Copyright Reserved © 2010-2023 [Xu Han](#)
Server Time: 2023-04-13 13:11:27 UTC+3

