

GENERAL (Cont'd)

ITEM		SPECIFICATIONS
ENGINE	Cylinder arrangement	2 cylinders 90° V transverse
	Bore and stroke	100.0 × 63.6 mm (3.94 × 2.50 in)
	Displacement	999 cm ³ (60.9 cu-in)
	Compression ratio	10.8 : 1
	Valve train	Gear driven, DOHC
	Intake valve opens	20° BTDC (At 1 mm lift)
	Intake valve closes	50° ABDC (At 1 mm lift)
	Exhaust valve opens	50° BBDC (At 1 mm lift)
	Exhaust valve closes	20° ATDC (At 1 mm lift)
	Lubrication system	Forced pressure and wet sump
	Oil pump type	Trochoid
	Cooling system	Liquid cooled
CARBURETION	Air filtration	Paper element
	Engine dry weight	70.5 kg (155.4 lbs)
	Firing order	Front—270° Rear—450°—Front
DRIVE TRAIN	Type	Programmed Fuel Injection (PGM-FI)
	Throttle bore ('00—'01)	54 mm (2.1 in)
	(After '01)	62 mm (2.4 in)
ELECTRICAL	Clutch system	Multi-plate, wet
	Clutch operation system	Hydraulic operating
	Transmission	Constant mesh, 6 speeds
	Primary reduction	1.700 (68/40)
	Final reduction	2.500 (40/16)
	Gear ratio 1st	2.461 (32/13)
	2nd	1.812 (29/16)
	3rd	1.428 (30/21)
	4th	1.240 (31/25)
	5th	1.080 (27/25)
ELECTRICAL	6th	0.962 (25/26)
	Gearshift pattern	Left foot operated return system, 1—N—2—3—4—5—6
	Ignition system	Computer-controlled digital transistorized
	Starting system	Electric starter motor
	Charging system	Triple phase output alternator
	Regulator/rectifier	SCR shorted, triple phase full wave rectification
ELECTRICAL	Lighting system	Battery