

Transactions

The Transactions API allows you create and manage payments on your integration.

Initialize Transaction

Initialize a transaction from your backend

Headers

authorization

Set value to

Bearer SECRET_KEY

string

content-type

Set value to

application/json

string

Body Parameters

amount

Amount should be in the subunit of the supported currency

string

email

Customer's email address

string

► [Show optional parameters](#)

POST /transaction/initialize

```
1 #!/bin/sh
2 url="https://api.paystack.co/transaction/initialize"
3 authorization="Authorization: Bearer YOUR_SECRET_KEY"
4 content_type="Content-Type: application/json"
5 data='{
```



Sample Response

```
1 {
2   "status": true,
3   "message": "Authorization URL created",
4   "data": {
5     "authorization_url": "https://checkout.paystack.com/3ni8kdavz62431k",
6     "access_code": "3ni8kdavz62431k",
7     "reference": "re4lyvq3s3"
8   }
9 }
```

Verify Transaction

Confirm the status of a transaction

 Transaction ID data type

If you plan to store or make use of the the transaction ID, you should represent it as a unsigned 64-bit integer. To le [check out our changelog](#).

Headers

authorization

Set value to

Bearer SECRET_KEY

string

Path Parameters

reference

The transaction reference used to initiate the transaction

string



```
1 url="https://api.paystack.co/transaction/verify/{reference}"
2 authorization="Authorization: Bearer YOUR_SECRET_KEY"
3
4
5 curl "$url" -H "$authorization" -X GET
```

Sample Response

```
1 {
2   "status": true,
3   "message": "Verification successful",
4   "data": {
5     "id": 4099260516,
6     "domain": "test",
7     "status": "success",
8     "reference": "re4lyvq3s3",
9     "receipt_number": null,
10    "amount": 40333,
11    "message": null,
12    "gateway_response": "Successful",
```

List Transactions

List transactions carried out on your integration

 Transaction ID data type

If you plan to store or make use of the the transaction ID, you should represent it as a unsigned 64-bit integer. To le [check out our changelog](#).

Headers

authorization

Set value to

Bearer SECRET_KEY

string

Query Parameters

perPage

Specify how many records you want to retrieve per page. If not specify we use a default value of 50.

integer

n

tion

ction

on

is

on

zation

on Timeline

als

ions

its

ial

sts



Docs

[API](#)[► Show optional parameters](#)

GET /transaction

```
1 #!/bin/sh
2 url="https://api.paystack.co/transaction"
3 authorization="Authorization: Bearer YOUR_SECRET_KEY"
4
5 curl "$url" -H "$authorization" -X GET
```

Sample Response

```
1 {
2   "status": true,
3   "message": "Transactions retrieved",
4   "data": [
5     {
6       "id": 4099260516,
7       "domain": "test",
8       "status": "success",
9       "reference": "re4lyvq3s3",
10      "amount": 40333,
11      "message": null,
12      "gateway_response": "Successful",
```

Fetch Transaction

Get details of a transaction carried out on your integration

⚠ Transaction ID data type

If you plan to store or make use of the the transaction ID, you should represent it as a unsigned 64-bit integer. To le [check out our changelog](#).

Headers

authorization

string

Set value to



n
tion

ction
on
is
on
zation
on Timeline
als
ions

its

al

GET /transaction/:id

```
1  #!/bin/sh
2  url="https://api.paystack.co/transaction/{id}"
3  authorization="Authorization: Bearer YOUR_SECRET_KEY"
4
5  curl "$url" -H "$authorization" -X GET
```

Sample Response

```
1  {
2    "status": true,
3    "message": "Transaction retrieved",
4    "data": {
5      "id": 4099260516,
6      "domain": "test",
7      "status": "success",
8      "reference": "re4lyvq3s3",
9      "receipt_number": null,
10     "amount": 40333,
11     "message": null,
12     "gateway_response": "Successful",
```

Charge Authorization

All authorizations marked as reusable can be charged with this endpoint whenever you need to receive payments

Headers

authorization

Set value to

string



Body Parameters

amount	Amount should be in the subunit of the supported currency
string	
email	Customer's email address
string	
authorization_code	Valid authorization code to charge
string	

► [Show optional parameters](#)

```
POST /transaction/charge_authorization

1  #!/bin/sh
2  url="https://api.paystack.co/transaction/charge_authorization"
3  authorization="Authorization: Bearer YOUR_SECRET_KEY"
4  content_type="Content-Type: application/json"
5  data='{
6    "email": "customer@email.com",
7    "amount": "20000",
8    "authorization_code": "AUTH_72btv547"
9  }'
10
11 curl "$url" -H "$authorization" -H "$content_type" -d "$data" -X POST
```

Sample Response

```
1  {
2    "status": true,
3    "message": "Charge attempted",
4    "data": {
5      "amount": 35247,
6      "currency": "NGN",
7      "transaction_date": "2024-08-22T10:53:49.000Z",
8      "status": "success",
9      "reference": "0m7frfnr47ezyl",
10     "domain": "test",
```



View Transaction Timeline

View the timeline of a transaction

Headers

authorization

Set value to

Bearer SECRET_KEY

string

Path Parameters

id_or_reference

The ID or the reference of the transaction

string

GET /transaction/timeline/:id_or_reference

```
1 #!/bin/sh
2 url="https://api.paystack.co/transaction/timeline/{id_or_reference}"
3 authorization="Authorization: Bearer YOUR_SECRET_KEY"
4
5 curl "$url" -H "$authorization" -X GET
```

Sample Response

```
1 {
2   "status": true,
3   "message": "Timeline retrieved",
4   "data": {
5     "start_time": 1724318098,
6     "time_spent": 4,
7     "attempts": 1,
8     "errors": 0,
9     "success": true,
10    "mobile": false,
11    "input": [],
12    "history": [
```



Headers

authorization

Set value to

Bearer SECRET_KEY

string

Query Parameters

perPage

Specify how many records you want to retrieve per page. If not specify we use a default value of 50.

integer

page

Specify exactly what page you want to retrieve. If not specify we use a default value of 1.

integer

► [Show optional parameters](#)

GET /transaction/totals

```
1 #!/bin/sh
2 url="https://api.paystack.co/transaction/totals"
3 authorization="Authorization: Bearer YOUR_SECRET_KEY"
4
5 curl "$url" -H "$authorization" -X GET
```

Sample Response

```
1 {
2   "status": true,
3   "message": "Transaction totals",
4   "data": {
5     "total_transactions": 42670,
6     "total_volume": 6617829946,
7     "total_volume_by_currency": [
8       {
9         "currency": "NGN",
10        "amount": 6617829946
11      },
```




Export a list of transactions carried out on your integration

Headers

authorization

Set value to

Bearer SECRET_KEY

string

Query Parameters

perPage

Specify how many records you want to retrieve per page. If not specify we use a default value of 50

integer

page

Specify exactly what page you want to retrieve. If not specify we use a default value of 1.

integer

► [Show optional parameters](#)

GET /transaction/export

```
1 #!/bin/sh
2 url="https://api.paystack.co/transaction/export"
3 authorization="Authorization: Bearer YOUR_SECRET_KEY"
4
5 curl "$url" -H "$authorization" -X GET
```

Sample Response

```
1 {
2   "status": true,
3   "message": "Export successful",
4   "data": {
5     "path": "https://s3.eu-west-1.amazonaws.com/files.paystack.co/exports/463433/transactions/"
6     "expiresAt": "2024-08-22 11:01:23"
7   }
}
```



Partial Debit

Retrieve part of a payment from a customer

Headers

authorization	Set value to	Bearer SECRET_KEY
string		
content-type	Set value to	application/json
string		

Body Parameters

authorization_code	Authorization Code
string	
currency	Specify the currency you want to debit. Allowed values are NGN or GHS.
string	
amount	Amount should be in the subunit of the supported currency
string	
email	Customer's email address (attached to the authorization code)
string	

► [Show optional parameters](#)

```
POST /transaction/partial_debit

1  #!/bin/sh
2  url="https://api.paystack.co/transaction/partial_debit"
3  authorization="Authorization: Bearer YOUR_SECRET_KEY"
4  content_type="Content-Type: application/json"
```

Q

Docs [API](#)

```
10 }'  
11  
12 curl -X POST -H "Content-Type: application/json" -d '{"data": {"amount": 50000, "currency": "NGN", "transaction_date": "2024-08-22T11:13:48.000Z", "status": "success", "reference": "ofuhmnzw05vny9j", "domain": "test", "metadata": "", "gateway_response": "Approved", "message": "Charge attempted", "status": true}}'
```

n
tion

Sample Response

```
1 {  
2   "status": true,  
3   "message": "Charge attempted",  
4   "data": {  
5     "amount": 50000,  
6     "currency": "NGN",  
7     "transaction_date": "2024-08-22T11:13:48.000Z",  
8     "status": "success",  
9     "reference": "ofuhmnzw05vny9j",  
10    "domain": "test",  
11    "metadata": "",  
12    "gateway_response": "Approved",
```

ction
on
is
on
zation
on Timeline
als
ions

its

|

al

sts