

sage X3

Create a web portal

Using Sage X3 web services
Update 10

15 06 16



The purpose of this document is to explain how to invoke SOAP X3 Web services from a web portal in PHP.

The portal gives you access to your data in Sage X3 such as orders or customer information in real-time. You do not need to share large files across networks or via email. Because the data stays in X3, not saved out to an external server, it is more secure. Remote employees like sales professions can not only view data, but they can also create new data such as sales orders from any computer with internet access via a browser.

You can create the portal using Sage X3 SOAP web services functionality and WampServer® is a Windows web development environment that allows you to create web applications with Apache2, PHP, and a MySQL database. In addition, PhpMyAdmin allows you to easily manage your databases. [Source: wampserver.com].

Audience

This document is intended for experienced Sage X3 users with administrator level permissions who may or may not have prior experience with publishing web services. There is also a section specifically for developers who have advanced coding and web services knowledge.

Contents

REQUIREMENTS	4
Install Microsoft Visual C++ 2012 Redistributable (x64)	4
BUILD THE PORTAL	5
Install and configure WampServer	5
Configure the X3 server and the pool of X3 Web service	6
Install and configure the PHP Web portal	8
Download the PHP web portal project files	8
Configure the portal	10
Install the X3 patch	11
Publish the web service	12
USE THE PORTAL	13
Access the portal	13
Read an order	14
Create an order	15
Create an order	15
FOR DEVELOPERS	17
List the orders	18
Read an order	21
Create an order while logged in	23

Requirements

To build the PHP web portal, you need the following:


- Windows 64 bit operating system
- Sage X3 9.0.2 or above
- Microsoft Visual C++ 2012 Redistributable (x64)

Install Microsoft Visual C++ 2012 Redistributable (x64)

From <https://www.microsoft.com/en-US/download/details.aspx?id=30679>

Select your language from the pull-down menu and click **Download**.

There are multiple files available for this download. When prompted, select **VSU_4/vcredist_x64.exe**.



Choose the download you want	
<input type="checkbox"/>	File Name
<input checked="" type="checkbox"/>	VSU_4\vcredist_x64.exe
<input type="checkbox"/>	VSU_4\vcredist_x86.exe
<input type="checkbox"/>	VSU4\vcredist_arm.exe

Install Microsoft Visual C++ 2015 Redistributable (x64)

From <https://www.microsoft.com/en-us/download/details.aspx?id=48145>

Build the portal

Install and configure WampServer

You can download WampServer from www.wampserver.com. On the homepage, scroll down and download this one:

WAMP SERVER (64 BITS & PHP 5.5) 2.5



By default, WampServer installs to **c:\sage\wamp**, but you can select a different folder when prompted.

Next, you need to choose a default browser such as Chrome or IE.


Navigate to the EXE file on your computer.

Select the file and click Open.

Examples for IE and Chrome are shown below.



You need to change the default http port, which is **80**. You can, for example, change it to **8125**, or to another port.



Navigate to **c:\Sage\wamp\bin\apache2.4.9\conf**

In Notepad ++, open **httpd.conf** and edit the file as follows:

```
#
# Listen: Allows you to bind Apache to specific IP addresses and/or
# ports, instead of the default. See also the <VirtualHost>
# directive.
#
# Change this to Listen on specific IP addresses as shown below to
# prevent Apache from seizing all bound IP addresses.
#
#Listen 12.34.56.78:80
Listen [::0]:8125
```

Save this file and restart all services for WampServer.

Right-click the WampServer icon on your desktop or taskbar, and select **Restart All Services**.

Note: You can use this same menu to start and stop all services for WampServer at any time.

Leave **All Services Running** while you set up the portal.

Configure the X3 server and the pool of X3 Web service

In Sage X3, complete follow these steps.

Note: the Host name etc. are examples. You might have other names.

Open Administration > Administration > Servers > **Hosts**.

Click the edit icon next to your host name.

On the next screen, in the **Number of Web service child processes** field, enter 1.

The screenshot shows the Sage X3 administration interface for editing a host. The host name is X3PU9TRAINVM. Below the host name is a table of connections. At the bottom, there are two input fields: 'Number of child processes' (set to 2) and 'Number of Web service child processes' (set to 1, highlighted with a red circle).

Port	Active	SSL	Client authentication	Server certificate	Client certificate
8124	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		
80	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		
443	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	x3pu9trainvm	

Open **Classic SOAP pools configuration** from Administration > Administration > Web Services.

Click **Create soapClassicPool**.

Complete the following fields:

Alias: Enter the name of the pool to be used in the web service call.

Initialization size: Enter 1.

Represents the number of clients (per node.js process) that are initialized during the pool startup.

Maximum size: Enter 1.

Represents the maximum number of clients (per node.js process) that can be started on this pool.

Auto start: Leave unchecked.

If checked, the pool starts when the Syracuse server starts.

X3 server TAGS: Leave blank.

This field is best used by Developers with classic SOAP pool configuration.

Endpoint: Enter the endpoint (folder) to be used for web service requests.

Locale: Enter your language and location. (In this example, English.)

User: Enter the user name. In this case **Admin**.

Pool configuration:

Alias *
SEED

☐ Auto start

Initialization size *
1

Endpoint *
SEED folder, X3PU9TRAIN solution, local doc
Endpoints describe services locations

Locale *
English (United States) en-US
Regional preferences

X3 server TAGS
Tags can be used to prefer some X3 process server defined in X3 solution

Maximum size *
1


User *
admin
's profile

To continue setting up the PHP web portal, you need to start the pool.

After you create the pool based on the previous steps, it displays in the list of soapClassicPools.

Click the name of the pool you just created.

From the right panel, click **Start/Update**.



Install and configure the PHP Web portal


If you have not already done so, start the web service pool you just created. See steps in the previous section for details.

Download the PHP web portal project files


The project file for the PHP web portal is available from GitHub. The project file is open to everyone, so you do not need a GitHub account. The download file contains everything you need to create and configure the portal including the X3 patch for the YOSOH web service.

From GitHub <https://github.com/Sage-ERP-X3/sample-x3-ws-php-webportal>, click **Download**.


If you are logged in to GitHub, you have the option to Clone or download. Be sure to download the ZIP file.



Save the **sample-x3-ws-php-webportal-master.zip** file to **C:\Sage\wamp\www**.



Extract all files to **C:\Sage\wamp\www\sagex3**.



Configure the portal

Next, you need to configure the portal to communicate with Sage X3.

In the folder **C:\Sage\wamp\www\sagex3\config**, open the **Config.php** file.

The following fields should match what you entered when you configured your web service pool in X3:

WSDL URL Your X3 server

CODE_LANG

POOL_ALIAS

WS_ORDER YOSOH for orders, is just for this example. You might set up a different web service.

WEB_SITE_LOGIN and WEB_SITE_PASSWD represent the credentials you will share with those who will be accessing these web services via the web portal.

```
<?php
```

```
class Config {  
    public static $WSDL          = "http://x3pu9trainvm:8124/soap-wsdl/syracuse/collaboration/syracuse/CAdxWebServiceXmlCC?wsdl";  
    public static $CODE_LANG     = "ENG";  
    public static $CODE_USER     = "admin";  
    public static $PASSWORD     = "admin";  
    public static $POOL_ALIAS    = "SEED";  
    public static $REQUEST_CONFIG = "adxwss.optreturn=XML";  
    public static $WS_ORDER      = "YOSOH";  
  
    public static $WEB_SITE_LOGIN = "websage";  
    public static $WEB_SITE_PASSWD = "websage";  
  
}  
?>
```


Do not change the punctuation and formatting.

From the WampServer menu, **Restart All Services**.

Enter the URL for your portal in your default browser. In this example the URL is <http://x3pu9trainvm:8125/sagex3/>

This is the name of X3 Syracuse server and the number was configured in **httpd.conf**.


This is an example of what your portal could look like.



Install the X3 patch

You need to install the X3 patch containing the YOSOH web services. The file was downloaded in the ZIP file from GitHub.

The name of file is **SRC_SVG_WEB_PHP_YYYYMMDD_NN.dat** and it is located in the following directory: C:\Sage\wamp\www\X3\PATCH_X3.



Important! You can only install the patch to the SEED folder, not to the X3 folder.

The patch contains the following X3 objects:


Type	Objects	Comments
ACV	YSWPH	Activity code PHP Web portal
EXE	SUBSLC	Generate Sales entry transaction
TRT	YSWPHPSTOCK	Script Available stock
ASU	YSWPHPSTOCK~STOCK	Sub program YSWPHPSTOCK~STOCK Available stock
AWE	YOSOH	Web service YOSOH Sales orders
AWE	YSSTOCKPHP	Web service YSSTOCKPHP Available stock
SLT	STRTYP=2 & STRNUM='WS'	Sales entry transaction WS: Web service for the web service YOSOH

Publish the web service

After installing the patch with the web service, you need to publish the service. This validates the web service so that it is visible.

In X3, navigate to Development > Script dictionary > Scripts and open **Web services** (GESAWC).

Click **Global publication**.



Use the portal

Now that the web service has been published, you can begin accessing Sage X3 data in real-time via the portal.

WampServer needs to be running to access the portal and Sage X3 services.

Access the portal

Using the default browser you set earlier, enter the URL for your web portal.


For this example, the URL is <http://x3pu9trainvm:8125/sagex3>.

Click **CONNECTION** and log in with the username and password you set up when configured the portal.


Note: It is not required to be logged in to the portal to view orders.

Remember, because this web service is based on YOSOH for sales information, this portal provides access to orders in Sage X3.

From the **ORDERS X3** pull-down menu, select **LIST OF ORDERS**.



You can now see a list of current orders in your Sage X3 instance.



RESULT

Order num	Client	Order date	Reference	Sales rep	Delivery status	Postal code
SOWFR0120004	FR002	05/04/2016		FR252	Not delivered	13770
SOWFR0120003	FR001	04/04/2016		FR251	Not delivered	44000
SOWFR0120002	FR004	04/04/2016		FR252	Not delivered	95370
SOWFR0120001	FR004	04/04/2016		FR252	Not delivered	95370


When you look at this data in Sage X3, you can see that it is the same.

Read an order

You can read orders by selecting from the list or by selecting **READ AN ORDER** from the **ORDERS X3** menu and entering the order number. For either method, you do not need to be logged in to the portal.

Click the order number for one of the orders in the list. This example uses order SOWFR0120004.

Clicking the order number or enter the order number provides detailed information about that order.



Selection

Order number


RESULT

Site	Order num	Reference	order date
FR012	SOWFR0120004		05-04-2016
Client	Name of site		
FR002	Vélo Attitudes		

Product	Designation	Quantity
DIS010	Laser Printer B&W 10ppm	10
DIS009	Standard 22" screen 1610	20

Create an order

You can create an order in X3 using the portal. You need to be logged in to the portal to do this.



Remember, you defined the login and password for your portal in Config.php.

Open the file Config.php

```
need to connect to create an order; don't need to login to view orders
<?php
```

```
class Config {
    ...

    public static $WEB_SITE_LOGIN    = "websage";
    public static $WEB_SITE_PASSWD  = "websage";

}
?>
```


Create an order

In addition to viewing orders, you can create a new order through the portal.

Note: To create a new order, you need to be logged in to the portal.

From the **ORDERS X3** pull-down menu, select **CREATE AN ORDER**.

Enter the relevant information as you would if you were working directly in Sage X3 and click **Submit**.




Form

Site	FR011 - Comptech SA
Date	05/04/2016
Currency	EUR
Client	FR003 - Cybertek

Product	Quantity	
DIS009 - Standard 22" screen 1610	1	+
DIS010 - Laser Printer D5W110nm	2	+

When the order has been created, click the order number to view details.



Selection

Order number

RESULT

Site	Order num	Reference	order date
FR011	SOWFR0110008		05-04-2016
Client	Name of site		
FR003	Cybertek		

Product	Designation	Quantity
DIS009	Standard 22" screen 16:10	1
DIS010	Laser Printer B&W 10ppm	2

In Sage X3 entry transaction WS, you can see the same order.

Sage X3 ★ ● Orders

Orders Clear filter

Order no. Sold-to

SOWFR0110008 FR003

All > Sales > Orders Super administrator SEED folder, X3PU3TRAIN solution, local doc MODEL

Sales order WS : Web services

K I P N

Sales site *	Type *	Number	Revision
FR011	WEB	SOWFR0110008	0
Comptech SA		WEB	

Reference	Date *	Currency
	04/05/16	EUR
EURO		

Sold-to *	
FR003	Cybertek

Delivery **Lines**

	Product	Standard description	Major version	Minor version	Ordered qty.
1	DIS009	Standard 22" screen 16:10			1
2	DIS010	Laser Printer B&W 10ppm			2
3					0

For developers

This section provides details specifically for developers who have advanced coding and web services knowledge. It uses the same YOSOH web service as an example.

This describes how to initiate these calls without the external application, but instead with the X3 test tool. It also shows the PHP or C# codes that call the same X3 web services.

This web service is an object web service with the optimized transaction WS.

All > Development > Script dictionary > Scripts

Super administratorSEED folder, X3PU9TRAIN solution, lo

Web services

Publication name

YOSOH

Type *

Object

Sub-program

Definition

Mapping

Object

Transaction

SOH

WS

Orders

Invisible fields

Service

Script

Subprograms

Information

Published on

By

Program

20160401190309

ADMIN

WJYOSOH

List the orders

In the PHP code:

Remember, the name of the X3 web service Order is SOH.

Config::\$WS_ORDER → YSOH

In /sagex3/page_soh_list.php

```
<?php

require_once
('WebService/models/Order.php');

try {

    $order = new Order ();
    echo ($order->showListe ());

} catch ( SoapFault

$e ) {

ToolsWS::printError

( "X3 Web service not available" );

}

?>
```

In /sagex3/WebService/models/Order.php


```
function showListe() {
    $WS = "*";
    $this->CAdxResultXml = $this->query ( Config::$WS_ORDER, $WS,100);
    ...
}
```

In the X3 tool:


Navigate to Administration > Administration > Web Services and select **Classic SOAP Web Services**.

From the list of SOAP Generic Web Services, select this web service.

On the next screen, click the down arrow to see the list of Operations.



From the list of Operations, click **query**.



Super administrator

SEED folder, X3PU9TRAIN solution, local doc

Back

Forward

query

query \$request : Get X3 objects list

Request

BODY *

QUERY *

CALL CONTEXT *

Language code

ENG

Pool alias

SEED

Pool ID

Request configuration

adxwss.optreturn=JSON&adxwss.beautify=true

Public name *

YOSOH

Object keys

+

Key	Value
No data to display	

List size *

20

The request configuration

`adxwss.optreturn=JSON&adxwss.beautify=true`

means

`adxwss.optreturn=JSON`

The output data format is JSON or XML, where

`adxwss.beautify=true`

This action improves the presentation as shown below.

query

query \$request : Get X3 objects list

Request Response 9 ✕

BODY

QUERY RESPONSE

QUERY RETURN

Messages

+

Message	Type
No data to display	

Result XML/JSON

[

{

"SOHNUM": "SOWFR0120004",

The web service is working without error when the status is 1.

There are only two status possibilities:

- 1 = OK
- 0= ERROR

Status	1
TECHNICAL INFORMATION	
Busy	✕

Read an order

In the PHP code:

In `/sagex3/page_soh_read.php`

```
<?php
```

```
...
```

```
echo
```

```
($order->showOne ( $sohnum ));
```

```
...
```

```
?>
```

In /sagex3/WebService/models/Order.php

```
function showOne($crit) {  
    ...  
    $cle = new CAdxParamKeyValue ();  
    $cle->key = "SOHNUM";  
    $cle->value = $crit;  
  
    $this->CAdxResultXml = $this->read  
(Config::$WS_ORDER,Array($cle));  
    ...  
}
```

In the X3 tool:

You must call the Read operation with the key of the order.

read

read \$request : Read X3 object

Request

BODY *

READ *

CALL CONTEXT *

Language code

Pool alias

Pool ID

Request configuration


Public name *

Object keys


+

Key

No data to display

Object keys		
+		
	Key	Value
	SOHNUM	SOWFR0110009

After selecting **Invoke**



Create an order while logged in

Using the X3 tool:

At first you can copy the result of the JSON data from the read:

```
{
  "SOH0_1": {
    "SALFCY": "FR011",
    "ZSALFCY": "Comptech SA",
    "SOHTYP": "WEB",
    "ZSOHTYP": "WEB",
    "SOHNUM": " SOWFR0110009 ",
    "REVNUM": "0",
    "CUSORDREF": "",
    "ORDDAT": "20160406",
    "CUR": "EUR",
    ...
  }
}
```

Replace the line: "SOHNUM": " SOWFR0110009 ", with "SOHNUM": " ",

In the X3 tool, enter this data into the **Object Xml** field.

save

save \$request : Create X3 object

Request

Response 5 ✕

BODY *

SAVE *

CALL CONTEXT *

Language code

ENG

Pool alias

SEED

Pool ID

Request configuration

adxwss.optreturn=JSON&adxwss.beautify=true

Public name *

YOSOH

Object Xml *

```
{
  "SOH0_1": {
    "SALFCY": "FR011",
    "ZSALFCY": "Comptech SA",
    "SOHTYP": "WEB",
    "ZSOHTYP": "WEB",
    "SOHNUM": "SOWFR0110012",
```

Invoke

Result XML/JSON

```
{
  "SOH0_1": {
    "SALFCY": "FR011",
    "ZSALFCY": "Comptech SA",
    "SOHTYP": "WEB",
    "ZSOHTYP": "WEB",
    "SOHNUM": "SOWFR0110012",
```

The code for the order that was created is in the JSON result:
The status have the value 1.

Status

1

TECHNICAL INFORMATION

PHP code:

In /sagex3/page_soh_create_action.php

```
<?php
...
try {
    $order = new Order ();
    echo ($order->create ( $WS ));
} catch ( SoapFault $e ) {
    ToolsWS::printError ( "X3 web service not available" );
}
...
?>
```

In /sagex3/WebService/models/Order.php

```
function create($WS) {
    $this->CAdxResultXml = $this->save ( Config::$WS_ORDER, $WS );
    ...
}
```



www.sage.com

© 2016 The Sage Group plc or its licensors. All rights reserved. Sage, Sage logos, and Sage product and service names mentioned herein are the trademarks of The Sage Group plc or its licensors. All other trademarks are the property of their respective owners.