

HASHEM A. DAMRAH

University of Oregon
Department of Mathematics
Eugene, OR 97403, USA

Abstract

This paper explores the mathematical foundations of geometric inverse problems, specifically focusing on their application within the context of medical imaging techniques. The first half of the work provides a rigorous treatment of the necessary preliminaries in differential and Riemannian geometry, including the study of smooth manifolds, metric tensors, and the properties of curvature. Special attention is given to the behavior of geodesics and the role of the Einstein summation convention in simplifying tensor calculus. Building upon this geometric framework, the second half delves into the formulation of inverse problems, such as the recovery of internal manifold properties from boundary data. By analyzing the relationship between metric geometry and integral transforms, we investigate how the curvature and topological structure of a medium influence the stability and uniqueness of reconstructions in techniques like X-ray and seismic imaging.

Date: March 9, 2026.

Primary 53C21; Secondary 35R30, 53C22

Key words and phrases. Riemannian manifolds, inverse problems, geodesics, metric rigidity, X-ray transform, boundary distance data.

Contents

Chapter 1. Preliminaries	1
1. Introduction	1
2. Notation	1
2.1. Basic Index Notation	1
2.2. The Kronecker Delta and Identity	1
2.3. Raising and Lowering Indices	2
2.4. Partial Derivatives and Shorthand Notation	2
2.5. Symmetrization and Anti-symmetrization	2
2.6. More In-depth Example: The Scalar Product	2
3. Topology	3
3.1. Closed and Open Sets and Limit Points	3
3.2. Topological Spaces	3
3.3. Continuity	4
3.4. Compactness and the Heine-Borel Theorem	5
3.5. Connectivity and Simple Connectivity	6
3.6. Homeomorphisms and Diffeomorphisms	6
3.7. The Concept of Homotopy	7
4. Differential Geometry	8
4.1. Intro to Manifolds	8
4.2. Tangent Bundles, Cotangent Bundles, and Sections	10
4.3. Tensors	13
4.4. Differential Forms and the Wedge Product	15
4.5. Differentials of Maps	18
4.6. Connections and the Riemann Tensor	19
4.7. Conformal and Isometric Maps	21
5. Riemannian Geometry	21
5.1. The Metric Tensor	22
5.2. Levi-Civita Connection	23
5.3. Parallel Transport and Geodesics	24
5.4. Curvature	25
5.5. Curvature Contractions	26
5.6. The Laplace-Beltrami Operator	27
Chapter 2. The Boundary Distance Rigidity Problem	29
1. Formalizing the Boundary Distance Rigidity Problem	29
1.1. Formalizing the Problem	29
1.2. Gauge Invariance and Isometries	30
1.3. Computational Examples: Flat and Constant Curvature Cases	31
1.4. The Scattering Relation	33
2. Formalizing the Geometry of Simple Manifolds	35

2.1. Strict Convexity of the Boundary	35
2.2. The Non-Trapping Condition	36
2.3. Conjugate Points and Injectivity of the Exponential Map	37
2.4. Definition and Properties of Simple Manifolds	39
3. The Linearized Problem and the X-ray Transform	41
3.1. Linearization of the Boundary Distance Function	41
3.2. The Geodesic X-ray Transform	42
3.3. Solenoidal Injectivity and Gauge Freedom	43
3.4. The Normal Operator and the Back-Projection	44
4. Worked Examples: Radial Symmetry and Inclusions	45
4.1. The Herglotz-Wiechert Formula for Radial Metrics	45
4.2. Detecting a Localized Inclusion	46
4.3. The Effect of Conjugate Points: A Counterexample	47
5. Synthesis: Clinical Applications in Medical Imaging	48
5.1. Ultrasound Computed Tomography	48
5.2. Diffusion Tensor Imaging (DTI) and Neural Tractography	49
5.3. Limitations and Future Frontiers: The “Non-Simple” Reality	50
Bibliography	53

CHAPTER 1

Preliminaries

1. Introduction

This paper is organized in two parts: chapter 1 goes over the preliminaries, namely, a brief introduction to topology, differential geometry, and Riemannian geometry, while chapter 2 delves into geometric inverse problems relating to medical imaging techniques.

The main purpose of this paper is to explore the mathematical foundations of the boundary rigidity problem, which is a fundamental question in Riemannian geometry with significant applications in medical imaging. The boundary rigidity problem asks whether a Riemannian manifold can be uniquely determined by the distances between points on its boundary. In the context of medical imaging, this problem is closely related to techniques such as ultrasound tomography, where one seeks to reconstruct the internal structure of a body from measurements taken at its surface. By understanding the mathematical principles underlying the boundary rigidity problem, we can gain insights into the limitations and capabilities of these imaging techniques, and potentially develop new methods for improving image reconstruction. This paper will provide a comprehensive overview of the mathematical tools and concepts necessary to approach the boundary rigidity problem, as well as a detailed analysis of its implications for medical imaging.

2. Notation

Throughout this paper we employ the Einstein summation convention. Tensor components will be written using indices, where repeated indices appearing once as an upper index and once as a lower index imply summation over their range.

2.1. Basic Index Notation. More precisely, if an index μ appears exactly twice in a term, once as a superscript and once as a subscript, then:

$$A^\mu B_\mu := \sum_{\mu=0}^{n-1} A^\mu B_\mu.$$

Unless otherwise stated, Greek indices μ, ν, ρ, σ range from 0 to $n - 1$, while Latin indices i, j, k range from 1 to $n - 1$. We adopt the convention that repeated indices are summed only when one index is upper and the other lower; repeated indices both upper or both lower do not imply summation.

2.2. The Kronecker Delta and Identity. The *Kronecker delta*, denoted by δ^μ_ν , serves as the identity operator for index substitution:

$$\delta^\mu_\nu = \begin{cases} 1 & \text{if } \mu = \nu \\ 0 & \text{if } \mu \neq \nu \end{cases}.$$

In our index notation, the delta satisfies the property $A^\mu \delta_\mu^\nu = A^\nu$. This is particularly useful when simplifying coordinate transformations or defining the Euclidean metric δ_{ij} in flat background regions of a medical scan.

2.3. Raising and Lowering Indices. Indices are raised and lowered using the *metric tensor* $g_{\mu\nu}$ and its inverse $g^{\mu\nu}$. The position of indices is significant, as it distinguishes between covariant (downstairs) and contravariant (upstairs) components of tensors:

$$V_\mu = g_{\mu\nu} V^\nu, \quad \omega^\mu = g^{\mu\nu} \omega_\nu.$$

We require the metric and its inverse to satisfy $g_{\mu\rho} g^{\rho\nu} = \delta_\mu^\nu$. In the context of the boundary rigidity problem, the metric tensor components encode the local refractive properties (sound speed) of the biological tissue.

2.4. Partial Derivatives and Shorthand Notation. Partial derivatives with respect to coordinates x^μ will be written in the standard form $\frac{\partial f}{\partial x^\mu}$. For notational convenience, we introduce the shorthand:

$$\partial_\mu f := \frac{\partial f}{\partial x^\mu} \quad \text{and} \quad \partial_{y^\mu} f := \frac{\partial f}{\partial y^\mu},$$

when differentiation with respect to a different coordinate system is required. We also use the shorthand notation $\dot{x}$ to denote differentiation with respect to the parameter of a curve (typically λ , τ , or t):

$$\dot{x} := \frac{dx}{d\lambda}.$$

Example 1.1. *The Euler-Lagrange equations for a Lagrangian $L(x^k, \dot{x}^k)$ are:*

$$\frac{\partial L}{\partial x^k} - \frac{\partial}{\partial \lambda} \left(\frac{\partial L}{\partial \dot{x}^k} \right) = 0.$$

Using our shorthand notation, this is compactly written as:

$$\partial_k L - \frac{d}{d\lambda} (\partial_{\dot{x}^k} L) = 0.$$

2.5. Symmetrization and Anti-symmetrization. To describe geometric objects such as the second fundamental form or the curvature tensor, we use parentheses and brackets to denote the symmetric and anti-symmetric parts of a tensor:

$$T_{(\mu\nu)} = \frac{1}{2}(T_{\mu\nu} + T_{\nu\mu}), \quad T_{[\mu\nu]} = \frac{1}{2}(T_{\mu\nu} - T_{\nu\mu}).$$

This notation is vital for Section 2, where we define *Strict Convexity* using the symmetric second fundamental form Π .

2.6. More In-depth Example: The Scalar Product. The Riemannian inner product of two vectors U, V (which might represent the initial velocity of an ultrasound pulse and the normal to the skin) is written as:

$$\langle U, V \rangle_g = g_{\mu\nu} U^\mu V^\nu.$$

In an isotropic Euclidean medium where $g_{\mu\nu} = \delta_{\mu\nu}$, this reduces to the standard dot product $U^\mu V_\mu$. The magnitude of the gradient of a pressure field f is given by:

$$|\nabla f|^2 = g^{\mu\nu} (\partial_\mu f) (\partial_\nu f).$$

This demonstrates how the inverse metric $g^{\mu\nu}$ is necessary to compute the norm of a covector (gradient).

3. Topology

Topology is the study of the properties of spaces that are preserved under continuous deformations. It provides a framework for understanding the properties of spaces that are invariant under homeomorphisms, which are continuous bijections with continuous inverses. In this section, we will explore some fundamental concepts in topology that are essential for our study of geometric inverse problems. We will begin by discussing the notions of closed and open sets, as well as limit points. Then, we will introduce the concept of topological spaces and continuity. Finally, we will delve into more advanced topics such as compactness, connectivity, homeomorphisms, and homotopy.

3.1. Closed and Open Sets and Limit Points. One of the most fundamental concepts in topology is that of open and closed sets. These provide the necessary language to describe the “inside” and the “edge” of a geometric object. Before defining these, we must introduce the notion of a limit point.

Definition 1.2. A point x is a limit point of a set A if every neighborhood of x contains at least one point of A different from x itself. In other words, for every $\varepsilon > 0$, the open ball $B(x, \varepsilon) = \{y \in X : d(x, y) < \varepsilon\}$ contains a point $a \in A$ such that $a \neq x$.

This definition captures the idea of points being “arbitrarily close” to a set. Note that a limit point of A does not necessarily have to be an element of A .

Definition 1.3. An open set O is a set such that for every point $x \in O$, there exists an $\varepsilon > 0$ such that the open ball $B(x, \varepsilon) \subseteq O$. Intuitively, an open set does not contain its own “edge.” A closed set C is a set such that its complement $X \setminus C$ is open, where X is the ambient space.

A vital characterization of closed sets is that they contain all their limit points. In the study of manifolds with boundary, we often deal with the closure of a set.

Definition 1.4. The closure of a set A , denoted $\bar{A}$, is the union of A and the set of all its limit points. The interior of A , denoted $\text{int}(A)$, is the union of all open sets contained in A . The boundary of A is then defined as:

$$\partial A = \bar{A} \setminus \text{int}(A).$$

In medical imaging, we typically define the “patient” as a closed set M . The interior $\text{int}(M)$ represents the biological tissue we wish to reconstruct, while the boundary ∂M is the surface where we place our ultrasound transducers.

Example 1.5 (Open and Closed Sets in $\mathbb{R}$). In the real line $\mathbb{R}$, the interval $(0, 1)$ is an open set. The points 0 and 1 are limit points of $(0, 1)$, but they are not contained in the set.

Conversely, the interval $[0, 1]$ is a closed set. It contains all of its limit points, including the endpoints 0 and 1. The interior of this set is $(0, 1)$, and its boundary consists of the discrete points $\{0, 1\}$. In higher dimensions, such as a ball $B^n \subset \mathbb{R}^n$, the boundary ∂B^n becomes the sphere $\mathbb{S}^{n-1}$.

3.2. Topological Spaces. This portion is dedicated to the formalization of topological spaces. While analysis typically studies the properties of functions and spaces preserved under limits within a metric framework, topology generalizes these notions. It defines a structure that allows us to discuss continuity and convergence

without strictly requiring a distance function (metric). This is achieved through the concept of a topological space.

Definition 1.6. A topological space (X, τ) consists of a set X and a collection τ of subsets of X , called open sets, such that:

- (1) The empty set $\emptyset$ and the entire set X are in τ .
- (2) The union of any arbitrary collection of sets in τ is also in τ .
- (3) The intersection of any finite collection of sets in τ is also in τ .

The collection τ is called a *topology* on X . This structure provides the most primitive framework necessary to define “closeness” and “limits.” In our study of medical imaging, we primarily deal with the *metric topology*.

Example 1.7 (The Metric Topology). Given a metric space (M, g) , we can define a topology τ_g where a set $U \subseteq M$ is open if and only if for every $x \in U$, there exists an $\varepsilon > 0$ such that the open ball $B_g(x, \varepsilon) \subseteq U$. This is the standard topology used in Riemannian geometry. In ultrasound tomography, the metric g varies based on tissue density, but the underlying topology of the human body remains equivalent to a subset of $\mathbb{R}^n$.

Example 1.8 (The Subspace Topology). Since our problem focuses on a manifold M with a boundary ∂M , we must define how the boundary inherits its topological structure. If (X, τ) is a topological space and $Y \subset X$, the subspace topology on Y is defined as:

$$\tau_Y = \{U \cap Y : U \in \tau\}.$$

This is how we formally treat the “skin” of the patient (∂M) as a topological space in its own right, inherited from the three-dimensional “body” (M).

Example 1.9 (The Discrete and Trivial Topologies). To see that “openness” depends on the chosen topology τ , consider a set X . In the discrete topology, every subset is open. In the trivial topology, only $\emptyset$ and X are open. In geometric inverse problems, we almost exclusively utilize the standard topology induced by the Riemannian metric g , where open sets are generated by open balls $B_g(x, \varepsilon)$.

By abstracting these properties, we can ensure that when we “deform” a manifold smoothly (as we do in the boundary rigidity problem), the fundamental relationship between points—their “connectedness”—remains intact. This leads us directly to the topological definition of a continuous map, which serves as the foundation for the homeomorphisms and diffeomorphisms that characterize geometric equivalence.

3.3. Continuity. In analysis, continuity is often defined in terms of limits and ε - δ logic. The main goal in topology, however, is to capture the essence of continuity without relying on a metric, but on the structure of open sets coming from the topology τ . An equivalent definition of continuity in the context of topological spaces is as follows:

Definition 1.10. A function $f : X \rightarrow Y$ between two topological spaces (X, τ_X) and (Y, τ_Y) is continuous if for every open set $V \in \tau_Y$, the preimage $f^{-1}(V) = \{x \in X : f(x) \in V\}$ is an open set in τ_X .

This definition captures the intuitive idea that small changes in the input (in X) lead to small changes in the output (in Y). In the context of our medical imaging problem, we want to ensure that small perturbations in the internal structure of the

tissue lead to small changes in the measured travel times at the boundary. This is crucial for the stability of our reconstruction algorithms.

Example 1.11. Consider the function $f : \mathbb{R} \rightarrow \mathbb{R}$ defined by $f(x) = x^2$. This function is continuous in the standard topology on $\mathbb{R}$ because the preimage of any open interval (a, b) is a union of open intervals (or empty). However, if we were to equip $\mathbb{R}$ with the discrete topology, where every subset is open, then f would also be continuous, but this would not reflect the usual notion of continuity we rely on in analysis. This illustrates how the choice of topology can affect the properties of functions and why we must use the standard metric topology for our medical imaging applications.

3.4. Compactness and the Heine-Borel Theorem. One of the most fundamental concepts in topology is that of compactness. It generalizes the idea of a set being “closed and bounded” to abstract topological spaces.

Definition 1.12. A topological space (X, τ) is compact if every open cover of X has a finite subcover. In other words, if $\{U_\alpha\}_{\alpha \in A}$ is a collection of open sets such that $X \subseteq \bigcup_{\alpha \in A} U_\alpha$, then there exists a finite subset $F \subseteq A$ such that $X \subseteq \bigcup_{\alpha \in F} U_\alpha$.

Intuitively, compactness suggests that the space is not “too large” and does not have any “missing points.” In the context of Euclidean spaces, which serve as the ambient space for our medical models, compactness is simplified by the following landmark result:

THEOREM 1.13 (Heine-Borel). A subset $K \subset \mathbb{R}^n$ is compact if and only if it is closed and bounded.

NOTE 1. We won’t be proving the Heine-Borel theorem in this paper, as it doesn’t directly pertain to the boundary rigidity problem. However, it is crucial to understand that this theorem provides a powerful characterization of compact sets in Euclidean space, which is the setting for our manifold M . The requirement that M be compact ensures that we can apply various analytical tools and guarantees the existence of geodesics between points, which are essential for reconstructing the internal structure from boundary measurements.

In our study of the boundary rigidity problem, we assume the manifold M (the patient’s body) is a compact manifold with boundary. This assumption is mathematically non-negotiable for several reasons:

- (1) **Existence of Extremals:** The Extreme Value Theorem states that a continuous function on a compact set must attain its maximum and minimum. This ensures that for any two points in our tissue, there actually exists a path of minimum time (a geodesic).
- (2) **Finiteness of Signal Travel:** Compactness, specifically the “boundedness” part of the Heine-Borel theorem, guarantees that every geodesic starting at the boundary must eventually exit the manifold. This is a prerequisite for the *non-trapping condition* discussed in Section 2.
- (3) **Global-to-Local Stability:** Compactness allows us to take local properties (like the injectivity of the exponential map near a point) and extend them to global properties across the entire organ.

Example 1.14 (Compact vs. Non-Compact Sets). The closed interval $[0, 1] \subset \mathbb{R}$ is compact. Any sequence of ultrasound arrival times measured within this range will

have a convergent subsequence. However, the open interval $(0,1)$ is not compact; a sequence of points could “leak” out toward the edge at 0, never reaching a limit point within the set. In medical imaging, we require the “skin” to be part of our set (making it closed) and the patient to be of finite size (making it bounded) to ensure a well-posed inverse problem.

3.5. Connectivity and Simple Connectivity. Connectivity and simple connectivity describe the “oneness” of a space and the absence of fundamental holes. These concepts are vital for ensuring that our measurements at the boundary can reach every part of the interior without being obstructed by topological barriers.

Definition 1.15. A topological space X is connected if it cannot be partitioned into two disjoint, non-empty open sets. A stronger and more intuitive version for manifolds is path-connectivity: X is path-connected if for any two points $x, y \in X$, there exists a continuous map $\gamma : [0, 1] \rightarrow X$ such that $\gamma(0) = x$ and $\gamma(1) = y$.

In the context of medical imaging, we assume the manifold M is connected. If M were disconnected (consisting of two “islands” of tissue), a signal from a transducer on one component would never reach the other, making it impossible to reconstruct the full interior from a single boundary data set.

Definition 1.16. A space X is simply connected if it is path-connected and every continuous loop in X can be continuously contracted to a single point.

Technically, a space is simply connected if its fundamental group $\pi_1(X)$ is trivial. This property is crucial for the boundary rigidity problem for the following reasons:

- **Avoidance of Topological Trapping:** On a non-simply connected manifold, such as a torus $\mathbb{T}^2$, there exist geodesics that “wind” around the hole and never return to the boundary. Simple connectivity ensures that the “topology” of the body doesn’t provide a place for sound waves to hide.
- **Uniqueness of Geodesics:** In a simply connected manifold with non-positive curvature, any two points are connected by a *unique* geodesic. This uniqueness is a cornerstone of simple manifolds, which we will define in Chapter 2, ensuring that our “scans” don’t produce ghost images due to multiple paths between the same source and receiver.

Example 1.17 (The Disk vs. The Annulus). The unit disk $D^2 = \{(x, y) : x^2 + y^2 \leq 1\}$ is simply connected; any loop of thread on the disk can be pulled tight to a point. However, the annulus $A = \{(x, y) : 0.5 \leq x^2 + y^2 \leq 1\}$ is connected but not simply connected. A loop that goes around the center hole cannot be contracted. In ultrasound tomography, an annulus-shaped domain (like a cross-section of a limb with a bone “hole” modeled as a boundary) requires significantly more complex math to ensure that the rays probe the tissue correctly without getting caught in orbits around the central void.

3.6. Homeomorphisms and Diffeomorphisms. While connectivity and compactness describe the intrinsic nature of a single space, homeomorphisms and diffeomorphisms allow us to compare two different spaces to determine if they are “equivalent” in a topological or geometric sense.

Definition 1.18. A homeomorphism is a bijection $f : X \rightarrow Y$ between two topological spaces such that both f and its inverse f^{-1} are continuous. If such a map exists, X and Y are said to be homeomorphic, and they are indistinguishable from a purely topological perspective.

In topology, a homeomorphism can stretch, twist, or bend a space, but it cannot tear it or glue parts together. For instance, a sphere and a cube are homeomorphic. However, for the study of Riemannian manifolds and medical imaging, continuity is not enough. We require the deformation to be smooth so that we can consistently define velocities and curvatures.

Definition 1.19. A diffeomorphism is a homeomorphism $f : M \rightarrow N$ between two smooth manifolds such that both f and its inverse f^{-1} are infinitely differentiable (C^∞).

In our notation established in Section 2, a diffeomorphism ensures that the Jacobian matrix $J_\nu^\mu = \partial_{x^\nu} f^\mu$ is well-defined and invertible at every point. This is the “gold standard” of equivalence in geometric inverse problems.

- **Geometric Rigidity:** The boundary rigidity problem asks whether the boundary distance function d_g uniquely determines the metric g up to a diffeomorphism. This means that if two metrics g and $\hat{g}$ produce the same travel times on the boundary, there must exist a diffeomorphism $\psi : M \rightarrow M$ that fixes the boundary such that $\hat{g} = \psi^*g$.
- **Clinical Interpretation:** In medical imaging, a diffeomorphism represents a smooth re-parametrization of the internal tissue. If we reconstruct a tumor, we want to ensure it is in the correct “geometric” location. If our reconstruction is only accurate up to a diffeomorphism, it means we have the right “shape” and “structure,” but the coordinate grid might be slightly warped.

Example 1.20 (The Deformation of Tissue). *Imagine a block of tissue M being compressed by an ultrasound probe. The compression is a diffeomorphism: the tissue is deformed smoothly, and points that were close together remain close together. The “topological” properties (connectivity, compactness) remain unchanged, but the “geometric” properties (the distance between two internal points) are altered. The goal of boundary rigidity is to “see through” these possible deformations to identify the true underlying metric.*

3.7. The Concept of Homotopy. While homeomorphisms allow us to deform entire spaces, *homotopy* provides a way to continuously deform functions or paths within a space. This concept is essential for understanding how a “fan” of geodesics (ultrasound rays) covers the interior of a manifold.

Definition 1.21. Two continuous maps $f, g : X \rightarrow Y$ are said to be homotopic if there exists a continuous map $H : X \times [0, 1] \rightarrow Y$, called a homotopy, such that for all $x \in X$:

$$H(x, 0) = f(x) \quad \text{and} \quad H(x, 1) = g(x).$$

If we view $t \in [0, 1]$ as a time parameter, the homotopy H describes a movie where the map f smoothly transforms into g . In the study of geometric inverse problems, we are specifically interested in *path homotopy*.

Definition 1.22. Two paths $\gamma_0, \gamma_1 : [0, 1] \rightarrow M$ with the same endpoints p and q are homotopic relative to their endpoints if there exists a homotopy H such that every intermediate path $H(\cdot, t)$ also starts at p and ends at q .

In the context of the boundary rigidity problem, homotopy plays a decisive role in the following areas:

- **Scanning Continuity:** As a clinician moves an ultrasound probe along the boundary ∂M , the resulting geodesics vary continuously. Homotopy ensures that the interior is sampled by a continuous “sheet” of rays, leaving no “mathematical holes” in the data.
- **Simply Connected Domains:** We defined a simply connected space as one where every loop is homotopic to a constant map (a point). For simple manifolds, this property guarantees that the “phase space” of geodesics is topologically uncomplicated, which is a requirement for the injectivity of the X-ray transform.
- **Conjugate Points:** One of the key results in Riemannian geometry is that if two paths between p and q are homotopic but not equivalent, the manifold must possess conjugate points or non-trivial topology. By requiring our manifold to be “simple,” we essentially use homotopy to prove that there is only *one* way for a signal to travel between any two points.

Example 1.23 (The “Fan” of Rays). *Consider a point source at $x \in \partial M$ emitting a fan of geodesics $\gamma_\theta(t)$ into the body, where θ is the initial angle. The map $H(\theta, t) = \gamma_\theta(t)$ is a homotopy. Because the tissue is a smooth manifold, this homotopy ensures that if we detect a tumor with ray γ_{θ_1} , we will also see a similar (slightly shifted) signal in the neighboring ray $\gamma_{\theta_1+\varepsilon}$. This redundancy is exactly what allows reconstruction algorithms to “smooth out” noise and produce clear medical images.*

4. Differential Geometry

We start this section by developing the necessary mathematical tools and concepts required to understand geometric inverse problems. This section just briefly introduces concepts from differential that’s used throughout this paper.

4.1. Intro to Manifolds. Let’s begin by introducing the concept of a manifold.

Definition 1.24. *An n -dimension manifold, M , is a topological space such that*

- (1) *M is locally Euclidean, i.e., for every point $p \in M$, there exists an open neighborhood U of p and a homeomorphism $\varphi : U \rightarrow V \subset \mathbb{R}^n$, where V is an open subset of $\mathbb{R}^n$. We call the pair (U, φ) a chart of M .*
- (2) *M is Hausdorff, i.e., for any two distinct points $p, q \in M$, there exist disjoint open neighborhoods U_p and U_q such that $p \in U_p$ and $q \in U_q$.*
- (3) *M is second countable, i.e., there exists a countable basis for the topology of M .*

We define an *atlas* as the collection of all the charts along with their transition maps, $\mathcal{A} = \{(U_i, \varphi_i)\}$. To go from one chart, U_i , to another chart, U_j , if $U_i \cap U_j \neq \emptyset$, we can use the transition maps:

$$\varphi_j \circ \varphi_i^{-1} : \varphi_i(U_i \cap U_j) \rightarrow \varphi_j(U_i \cap U_j).$$

But, throughout this paper, we only care about smooth manifolds, which are manifolds that are endowed with a smooth structure. Before doing so, we first need to define what a smooth map is.

Definition 1.25. *If U and V are open subsets of $\mathbb{R}^n$ and $\mathbb{R}^m$, then $F : U \rightarrow V$ is said to be smooth¹ if each of F ’s component functions are continuous and have*

¹Some authors use “smooth” to denote infinitely differentiable (C^∞), some use it to indicate just k -differentiable (C^k). I use it to denote C^∞ .




FIGURE 1. Transition maps between charts on a manifold.

continuous partial derivatives. In addition, if F is bijective, then F is called a diffeomorphism.

We can formally define a smooth manifold as follows.

Definition 1.26. A k -differentiable manifold is a manifold M equipped with an atlas $\mathcal{A}$ such that for every non-disjoint pair of charts (U_i, φ_i) and (U_j, φ_j) in $\mathcal{A}$, the transition map $\varphi_j \circ \varphi_i^{-1}$ is a k -differentiable function. If $k = \infty$, we call M a smooth manifold.

This section's all about defining what it means to have a smooth function from a manifold M to a Euclidean space E along with a map from a manifold M to another manifold N .

Definition 1.27. Suppose M is a manifold². Let $f : M \rightarrow \mathbb{R}^k$, for some $k \geq 1$. We say that f is a smooth function if, for every $p \in M$, there exists a smooth chart (U, φ) , where $p \in U$, such that $f \circ \varphi^{-1}$ is smooth on the open subset $\hat{U} = \varphi(U) \subseteq \mathbb{R}^n$.

Now, we talk about smooth maps between manifolds.

Definition 1.28. Let M and N be two different manifolds. We say $F : M \rightarrow N$ is a smooth map if for every $p \in M$, there exists charts (U, φ) , where $p \in U$, and (V, ψ) , where $F(p) \in V$ such that $F(U) \subseteq V$ and $\psi \circ F \circ \varphi^{-1}$ is smooth from $\varphi(U)$ to $\psi(V)$.

A nice property (which we won't be proving), is that a composition of smooth maps is also smooth.

²Throughout this paper, we're only interested in smooth manifolds, so we will assume that all manifolds are smooth unless otherwise stated. We also drop the adjective " n -dimension". So, it's safe to assume that whenever we say "manifold", we mean a smooth manifold of dimension n , unless otherwise stated.





FIGURE 2. Smooth functions

FIGURE 3. Smooth maps between M and N

4.2. Tangent Bundles, Cotangent Bundles, and Sections. Our next main definition is that of a tensor, but in order to do so, we need to introduce a few more concepts, such as the tangent and cotangent bundles of a manifold.





FIGURE 4. Composition of smooth maps

Definition 1.29. Let M be a manifold and $p \in M$. The tangent space at p , denoted $T_p M$, is the vector space of derivations at p , that is,

$$T_p M = \{X : C^\infty(M) \rightarrow \mathbb{R} \mid X \text{ is linear and satisfies the Leibniz rule}\}.$$

That is, for all $f, g \in C^\infty(M)$,

$$X(fg) = X(f)g(p) + f(p)X(g).$$

FIGURE 5. Tangent space of $\mathbb{S}^2$

A rather straightforward basis for the tangent space is given by

$$\mathcal{B} = \left\{ \frac{\partial}{\partial x^i} \Big|_a \right\}_{i=1}^{i=n} = \{\partial_i(a)\}_{i=1}^{i=n},$$

defined by

$$\frac{\partial}{\partial x^i} \Big|_a f = \frac{\partial f}{\partial x^i}(a) = \partial_i(a),$$

using Einstein notation. This is called the *coordinate basis* for $T_p M$. We can also define the tangent space using equivalence classes of curves, but we won't be doing that here.

Our next definition will be the tangent bundle. But before we do that, we need to define what a disjoint union is.

Definition 1.30. The disjoint union of a family of sets $\{A_i\}_{i \in I}$ is the set

$$\bigsqcup_{i \in I} A_i = \{(i, a) : i \in I, a \in A_i\}.$$

Example 1.31. If we have two sets $A = \{1, 2\}$ and $B = \{1, 2\}$, then their disjoint union is

$$A \sqcup B = \{(A, 1), (A, 2), (B, 1), (B, 2)\}.$$

Notice that the elements $A = B$, but the disjoint union keeps track of which set each element belongs to. If we do $(A, 1) \cap (B, 1) = \emptyset$, even tho 1 does indeed equal 1.

To study velocities and gradients across the entire manifold, we must group all individual tangent spaces into a single geometric object. We begin with the Tangent Bundle, which serves as our primary example of a more general structure known as a Vector Bundle.

Definition 1.32. A tangent bundle, denoted as TM , of a manifold M is defined as

$$TM = \bigsqcup_{p \in M} T_p M = \{(p, v) : p \in M, v \in T_p M\}.$$




FIGURE 6. Coordinates for the Tangent bundle

The tangent bundle is the prototypical example of a vector bundle, a structure that allows us to attach a vector space to every point of a manifold in a way that varies smoothly.

Definition 1.33. A vector bundle of rank k over M is a manifold E (the total space) and a smooth surjection $\pi : E \rightarrow M$ (the projection) such that:

- (1) For each $p \in M$, the set $E_p = \pi^{-1}(p)$ is a k -dimensional vector space, called the fiber over p .
- (2) E is locally trivial: every $p \in M$ has a neighborhood U and a diffeomorphism $\Phi : \pi^{-1}(U) \rightarrow U \times \mathbb{R}^k$ that is a linear isomorphism on each fiber.

NOTE 2. In this framework, the tangent bundle TM is a vector bundle where the fibers are the tangent spaces T_pM . Similarly, we define the **cotangent bundle** T^*M as the bundle whose fibers are the dual spaces T_p^*M , housing the covectors (gradients) used in imaging.

Definition 1.34. The cotangent space T_p^*M is the dual space to T_pM . If $\{\partial_i\}$ is the coordinate basis for the tangent space, we define the coordinate dual basis $\{dx^i\}$ for T_p^*M such that:

$$dx^i(\partial_j) = \delta_j^i,$$

where δ_j^i is the Kronecker delta. This allows us to express any covector $\omega \in T_p^*M$ as $\omega = \omega_i dx^i$.

NOTE 3. If $\{\partial_i\}$ is a basis for T_pM , then the dual basis $\{dx^i\}$ is a basis for T_p^*M .

NOTE 4. Covectors live in the cotangent bundle, while the contravariant vectors (i.e., tangent vectors) live in the tangent bundle. The contravariant vectors represent velocities or directions. The covariant represents gradients or linear functionals.

In local coordinates, tensor components are written using upper and lower indices to distinguish components with respect to a chosen basis of T_pM and its dual basis in T_p^*M .

Definition 1.35. Let $\pi : E \rightarrow M$ be a vector bundle over M . A section of E is a smooth map

$$s : M \rightarrow E,$$

such that

$$\pi \circ s = \text{id}_M.$$

The space of smooth sections of E is denoted $\Gamma(E)$.

4.3. Tensors. Now, with all that out of the way, we can finally define a tensor.

Definition 1.36. Let M be a manifold and $p \in M$. An (r, s) -tensor at p is a multilinear map

$$T_p : (T_p^*M)^r \times (T_pM)^s \rightarrow \mathbb{R}.$$

Definition 1.37. The tensor bundle of type (r, s) over a manifold M is the vector bundle

$$T_s^r M = \bigsqcup_{p \in M} T_p^r M = \bigsqcup_{p \in M} \left(\underbrace{T_p^*M \otimes \cdots \otimes T_p^*M}_r \otimes \underbrace{T_pM \otimes \cdots \otimes T_pM}_s \right).$$

NOTE 5. We use the shorthand notation

$$A^{\otimes r} = \underbrace{A \otimes \cdots \otimes A}_{r \text{ times}}.$$

Thus the tensor bundle may be written as

$$T_s^r M = \bigsqcup_{p \in M} (T_p^* M)^{\otimes r} \otimes (T_p M)^{\otimes s}.$$

Definition 1.38. An (r, s) -tensor field on M is a smooth section of the tensor bundle

$$\pi : T_s^r M \rightarrow M.$$

That is, a smooth map

$$T : M \rightarrow T_s^r M,$$

such that

$$\pi \circ T = \text{Id}_M.$$

In local coordinates $\{x^i\}$, an (r, s) -tensor field T is expressed as a linear combination of basis tensor products:

$$T = T_{j_1 \dots j_s}^{i_1 \dots i_r} \left(\bigotimes_{k=1}^r \partial_{i_k} \right) \otimes \left(\bigotimes_{m=1}^s dx^{j_m} \right).$$

Here, the functions $T_{j_1 \dots j_s}^{i_1 \dots i_r}$ are the *components* of the tensor. Under a change of coordinates $x \rightarrow \tilde{x}$, these components transform according to the rule:

$$\tilde{T}_{b_1 \dots b_s}^{a_1 \dots a_r} = T_{j_1 \dots j_s}^{i_1 \dots i_r} \frac{\partial \tilde{x}^{a_1}}{\partial x^{i_1}} \cdots \frac{\partial \tilde{x}^{a_r}}{\partial x^{i_r}} \frac{\partial x^{j_s}}{\partial \tilde{x}^{b_s}}.$$

Here are a few examples of tensors:

Example 1.39.

- **$(0,0)$ -Tensors (Scalar Fields):** An $(0,0)$ -tensor is simply a smooth function $f : M \rightarrow \mathbb{R}$. In medical imaging, this may represent an isotropic physical property, such as the proton density in Magnetic Resonance Imaging (MRI) or the absorption coefficient in optical tomography.
- **$(1,0)$ -Tensors (Vector Fields):** A $(1,0)$ -tensor is a smooth section of the tangent bundle TM . Locally, it is written as $X = X^i \partial_i$. These represent directional quantities, such as the velocity field of blood flow in Doppler ultrasound or the gradient of a potential (once identified via a metric).
- **$(0,1)$ -Tensors (Covectors/1-forms):** A $(0,1)$ -tensor is a smooth section of the cotangent bundle T^*M , written locally as $\omega = \omega_i dx^i$. A primary example is the differential of a function df , which at each point acts as a linear functional on tangent vectors.
- **$(0,2)$ -Tensors (Bilinear Forms):** A $(0,2)$ -tensor is a section of $T^*M \otimes T^*M$. This is perhaps the most critical category for this paper, as it includes the Riemannian metric g . In anisotropic media, like heart muscle or brain white matter, physical properties like electrical conductivity or water diffusion are not single numbers but are modeled as symmetric $(0,2)$ -tensors g_{ij} .

To manipulate the physical quantities represented by these tensors, we define several fundamental operations:

- **Einstein Summation Convention:** Throughout this paper, we adopt the convention that whenever an index appears twice in a single term – once as a superscript and once as a subscript – a summation over the full range of that index is implied. For example, $X^i \omega_i$ denotes $\sum_{i=1}^n X^i \omega_i$ (cf Section 2 for more details).
- **Contraction:** A contraction is an operation that reduces the rank of an (r, s) -tensor to $(r - 1, s - 1)$. Locally, this is done by setting one upper index equal to one lower index and summing. For a $(1, 1)$ -tensor T_j^i , the contraction is the scalar T_i^i , analogous to the trace of a matrix.
- **Tensor Product:** Given an (r, s) -tensor T and a (p, q) -tensor U , their tensor product $T \otimes U$ is an $(r + p, s + q)$ -tensor. This allows us to construct complex physical models, such as the metric tensor, from simpler 1-forms.

NOTE 6. *Once a Riemannian metric g is introduced in Section 5, we gain the ability to raise and lower indices. This operation, sometimes called the musical isomorphisms ($\flat$ and $\sharp$), allows us to physically identify vectors with covectors, effectively using the internal geometry of the tissue to translate between directional velocities and gradients of potential.*

4.4. Differential Forms and the Wedge Product. Next, we introduce the concept of a differential form. A very well-known example of a differential form is dx , which is a 1-form. Formally, we can define a 1-form as follows.

Definition 1.40. *A 1-form on a manifold M is a smooth section of the cotangent bundle T^*M , that is,*

$$\omega \in \Gamma(T^*M),$$

where $\omega : M \rightarrow T^*M$ is a smooth map such that $\pi \circ \omega = \text{id}_M$. Equivalently, for each $p \in M$, a 1-form assigns a covector $\omega_p \in T_p^*M$ smoothly in p .

A 1-form represents a linear functional that takes a tangent vector at a point and produces scalar.

Example 1.41. *In local coordinates $\{x^\mu\}$, a 1-form ω can be written as*

$$\omega = \omega_\mu dx^\mu.$$

If $v = v^\mu \partial_\mu \in T_p M$, then

$$\omega(v) = \omega_\mu v^\mu.$$

We denote the space of smooth 1-forms on M by $\Omega^1(M)$, with $k = 1$. This implies that there are higher order forms. So, we need a way to generalize this to higher-order forms, which is where the concept of the wedge product comes in. The wedge product allows us to combine 1-forms to create higher-order forms, such as 2-forms, 3-forms, etc. We can define the wedge product as follows.

Definition 1.42. *The wedge product*

$$\wedge : \Omega^p(M) \times \Omega^q(M) \rightarrow \Omega^{p+q}(M),$$

is the bilinear operation that takes a p -form α and a q -form β and produces a $(p + q)$ -form $\alpha \wedge \beta$, defined by the following properties:

- (1) **Bilinearity:** *For all $\alpha, \alpha' \in \Omega^p(M)$, $\beta, \beta' \in \Omega^q(M)$, and $f, g \in C^\infty(M)$,*

$$(f\alpha + g\alpha') \wedge \beta = f(\alpha \wedge \beta) + g(\alpha' \wedge \beta),$$

$$\alpha \wedge (f\beta + g\beta') = f(\alpha \wedge \beta) + g(\alpha \wedge \beta').$$

(2) Antisymmetry: For all $\alpha \in \Omega^p(M)$ and $\beta \in \Omega^q(M)$,

$$\alpha \wedge \beta = (-1)^{pq} \beta \wedge \alpha.$$

In particular, if α is a 1-form, then $\alpha \wedge \alpha = 0$.

(3) Associativity: For all $\alpha \in \Omega^p(M)$, $\beta \in \Omega^q(M)$, and $\gamma \in \Omega^r(M)$,

$$(\alpha \wedge \beta) \wedge \gamma = \alpha \wedge (\beta \wedge \gamma).$$

Now, we can use the wedge product to define a 2-form, which represents an orientated area element on the manifold. Just like in vector calculus, where we had $dA = dx dy$, we can define a 2-form ω as

$$\omega = \omega_{\mu\nu} dx^\mu \wedge dx^\nu.$$

Next, we need to define what the pullback of a differential form is and what a pushforward of a vector field is. The pullback allows us to take a differential form defined on one manifold and pull it back to another manifold via a smooth map, while the pushforward allows us to take a vector field defined on one manifold and push it forward to another manifold via a smooth map.

Definition 1.43. Let $f : M \rightarrow N$ be a smooth map between manifolds M and N . The pullback of a differential form ω on N by the map f is a differential form on M , denoted by $f^*\omega$, defined as follows: for any point $p \in M$ and any tangent vectors $v_1, v_2, \dots, v_k \in T_p M$, we have

$$(f^*\omega)_p(v_1, v_2, \dots, v_k) = \omega_{f(p)}(df_p(v_1), df_p(v_2), \dots, df_p(v_k)).$$

Example 1.44. Let $F : \mathbb{R}^2 \setminus \{0\} \rightarrow \mathbb{R}^2$ be defined by the polar coordinate transformation

$$F(r, \theta) = (x, y) = (r \cos \theta, r \sin \theta).$$

We compute the pullback of the coordinate 1-forms dx and dy .

Since

$$x = r \cos \theta \quad \text{and} \quad y = r \sin \theta,$$

we have

$$dx = \cos \theta dr - r \sin \theta d\theta \quad \text{and} \quad dy = \sin \theta dr + r \cos \theta d\theta.$$

Therefore,

$$F^*(dx) = \cos \theta dr - r \sin \theta d\theta \quad \text{and} \quad F^*(dy) = \sin \theta dr + r \cos \theta d\theta.$$

As an application, consider the standard area form $dx \wedge dy$. Using the bilinearity and antisymmetry of the wedge product, we compute

$$\begin{aligned} F^*(dx \wedge dy) &= F^*(dx) \wedge F^*(dy) \\ &= (\cos \theta dr - r \sin \theta d\theta) \wedge (\sin \theta dr + r \cos \theta d\theta) \\ &= r dr \wedge d\theta. \end{aligned}$$

Thus, the pullback naturally produces the Jacobian factor r appearing in polar coordinates.

When we're computing pullbacks of differential forms, we can use the formula

$$f^* \left(\bigwedge_{i=1}^k du^i \right) = \bigwedge_{i=1}^k f^*(du^i) = \bigwedge_{i=1}^k \partial_j u^i dx^j.$$

Definition 1.45. Let $f : M \rightarrow N$ be a smooth map between manifolds M and N . The pushforward of a vector field X on M by the map f is a vector field on N , denoted by f_*X , defined as follows: for any point $p \in M$, we have

$$(f_*X)_{f(p)} = df_p(X_p).$$

Example 1.46. Let $F : \mathbb{R}^2 \rightarrow \mathbb{R}^2$ be defined by

$$F(x, y) = (u, v) = (x^2 - y, x + y).$$

We compute the pushforward of the vector field $X = \partial_x$.

The Jacobian matrix of F is

$$dF = \begin{pmatrix} \partial_x u & \partial_y u \\ \partial_x v & \partial_y v \end{pmatrix} = \begin{pmatrix} 2x & -1 \\ 1 & 1 \end{pmatrix}.$$

Since ∂_x corresponds to the vector $(1, 0)$ in coordinates, we obtain

$$F_*(\partial_x) = 2x \partial_u + \partial_v.$$

Thus, the pushforward transforms the coordinate basis vector ∂_x into a linear combination of the coordinate basis vectors ∂_u and ∂_v .




FIGURE 7. Pushforward and pullback under a smooth map $\varphi : M \rightarrow N$.

4.5. Differentials of Maps. We now define the differential of a map between two manifolds.

Definition 1.47. Let $F : M \rightarrow N$ be a smooth map between two manifolds M and N . For each point $p \in M$, we define the differential of F at p by

$$dF_p : T_p M \rightarrow T_{F(p)} N.$$




FIGURE 8. The differential

For any vector $v \in T_p M$, the image $v' = dF_p(v) \in T_{F(p)} N$ is defined by its action on smooth functions $g \in C^\infty(N)$:

$$(dF_p(v))(g) = v(g \circ F).$$

This definition ensures that the differential is a linear map that captures how the “directional derivative” at p translates to a directional derivative at $F(p)$.

In local coordinates $\{x^i\}$ on M and $\{y^\alpha\}$ on N , let F be represented by $y^\alpha = F^\alpha(x^1, \dots, x^n)$. If $v = v^i \partial_i$, then the components of the pushed-forward vector $v' = dF_p(v)$ are given by:

$$(v')^\alpha = \frac{\partial F^\alpha}{\partial x^i} v^i.$$

Thus, the matrix of dF_p with respect to the coordinate bases is the Jacobian matrix $\partial F^\alpha / \partial x^i$.

We finish this section by defining an immersion, which is a smooth map that locally looks like an embedding but may not be globally injective.

Definition 1.48. A smooth map $F : M \rightarrow N$ is called an *immersion* if its differential $dF_p : T_p M \rightarrow T_{F(p)} N$ is injective for all $p \in M$.

Definition 1.49. A smooth map $F : M \rightarrow N$ is called a *submersion* if its differential $dF_p : T_p M \rightarrow T_{F(p)} N$ is surjective for all $p \in M$.




FIGURE 9. Local section of a submersion

Definition 1.50. A smooth embedding is an injective immersion $F : M \rightarrow N$ that is also a topological embedding (i.e., a homeomorphism onto its image with the subspace topology).

Definition 1.51. We say $S \subset N$ is an *embedded submanifold* if it is the image of a smooth embedding. If $F : M \rightarrow N$ is merely an injective immersion, we call its image an *immersed submanifold*.

One useful result we'll be using quite frequently in Chapter 2 is the following:

Corollary 1.52. Suppose $F : M \rightarrow N$ is a smooth map, $p \in M$, and $v \in T_p M$. Then

$$df_p(v) = (f \circ \gamma)'(0),$$

for any smooth curve $\gamma : [0, 1] \rightarrow M$ such that $\gamma(0) = p$ and $\gamma'(0) = v$.

4.6. Connections and the Riemann Tensor. To describe the geometry of a manifold, we must introduce a way to differentiate vector fields. Unlike in Euclidean space, there is no canonical way to compare vectors at different points without a “connection.”

Definition 1.53. A connection (or covariant derivative) on M is a map $\nabla : \Gamma(TM) \times \Gamma(TM) \rightarrow \Gamma(TM)$ satisfying linearity and the Leibniz rule:

$$\nabla_X(fY) = X(f)Y + f\nabla_X Y.$$




FIGURE 10. An embedded submanifold

The connection is $C^\infty(M)$ -linear in X , meaning $\nabla_f X Y = f \nabla_X Y$, but it satisfies the Leibniz rule in Y defined above. We need a way of measuring how much the connection fails to be symmetric. This is where the Lie bracket comes in, which measures the non-commutativity of vector fields.

Definition 1.54. The Lie bracket of two vector fields X and Y is the vector field defined by

$$[X, Y](f) = X(Y(f)) - Y(X(f)),$$

for all smooth functions $f \in C^\infty(M)$. The Lie bracket measures the non-commutativity of the flows generated by X and Y .

Geometrically, if we follow the flow of X for time t , then Y for time s , and then reverse the process, the Lie bracket $[X, Y]$ measures the displacement from the starting point.

We can also define the anti-symmetry of the connection using the Lie bracket. A connection is *symmetric* if $\nabla_X Y - \nabla_Y X = [X, Y]$ for all vector fields X and Y . If this condition is not satisfied, we can measure the failure of symmetry using the torsion tensor, which we will define shortly.

Definition 1.55. The Riemann curvature tensor associated to a connection ∇ is the $(1, 3)$ -tensor:

$$R(X, Y)Z = \nabla_X \nabla_Y Z - \nabla_Y \nabla_X Z - \nabla_{[X, Y]} Z.$$

It measures the path-dependence of parallel transport and the failure of covariant derivatives to commute.

Here's a rough idea for what the parallel transport is (as we define it later on in Section 5): A vector field Z is *parallel* along a curve with tangent X if $\nabla_X Z = 0$. The Riemann tensor $R(X, Y)Z$ quantifies the change in Z when it is parallel transported around an infinitesimal loop.

Definition 1.56. The torsion tensor T is defined by $T(X, Y) = \nabla_X Y - \nabla_Y X - [X, Y]$. A connection is torsion-free if $T = 0$.

While these definitions apply to any affine connection, physical applications in medical imaging—such as modeling signal propagation or tissue conductivity—require a specific connection that respects the internal “distance” of the manifold. In the following section, we introduce the Riemannian metric and the unique Levi-Civita connection associated with it.

4.7. Conformal and Isometric Maps. We conclude this section by defining conformal and isometric maps, which are the fundamental “equivalence relations” used to categorize Riemannian manifolds in geometric inverse problems.

Definition 1.57. A smooth map $F : (M, g) \rightarrow (N, h)$ is called conformal if there exists a smooth function $\Omega : M \rightarrow (0, \infty)$, called the conformal factor, such that:

$$F^*h = \Omega^2 g.$$

In this case, F preserves the angles between any two tangent vectors but scales lengths by the factor $\Omega(p)$.

In medical imaging, we frequently work with *conformally flat* metrics. For example, in an isotropic ultrasound scan, we assume the manifold is a domain $M \subset \mathbb{R}^n$ with a metric $g = c(x)^{-2}\delta$, where $c(x)$ is the sound speed. This metric is conformal to the Euclidean metric δ ; thus, while the sound waves follow “straight-line” Euclidean angles locally, the “acoustic distance” (time-of-flight) is warped by the factor $1/c(x)$.

Definition 1.58. A smooth map $F : (M, g) \rightarrow (N, h)$ is called an isometry if:

$$F^*h = g.$$

This is a special case of a conformal map where $\Omega \equiv 1$. An isometry preserves both angles and lengths, making it a distance-preserving map: $d_h(F(p), F(q)) = d_g(p, q)$.

The distinction between these two maps is the key to understanding the “up to a diffeomorphism” clause in the Boundary Rigidity Problem.

- **Isometries as Gauge Freedom:** If F is an isometry that is the identity on the boundary, then the boundary distance functions d_g and d_h are identical. This means that a scanner cannot distinguish between (M, g) and its isometric twin (M, F^*h) .
- **Conformal Factors as Diagnostic Data:** In Ultrasound CT, the goal is often to find the conformal factor $\Omega = 1/c(x)$. Since a change in Ω changes the travel times (lengths) of geodesics, this information is *not* hidden by gauge freedom and can be uniquely reconstructed under the “simple manifold” assumptions.

Example 1.59 (The Poincare Disk). A classic example of these concepts is the Poincare Disk model of hyperbolic space, (D, g_{hyp}) , where $g_{hyp} = \frac{4}{(1-|x|^2)^2}\delta$. This metric is conformal to the Euclidean disk. While the “Euclidean” straight lines represent one geometry, the “Hyperbolic” geodesics—which are circular arcs orthogonal to the boundary—represent a different metric that has been warped by a conformal factor that blows up at the boundary.

5. Riemannian Geometry

Now that we’ve covered the basics of differential geometry (cf Section 4), we now give a brief introduction to Riemannian Geometry.

While differential geometry gives us the structure of the manifold, *Riemannian geometry* introduces the tools necessary for measurement: lengths, angles, and volumes. Riemannian geometry coincides with our intuitive understanding that geometry is the study of lengths, angles, curvature, area, volume, and so on. It provides the mathematical framework for understanding the geometry of curved spaces, which is essential for many applications in physics, engineering, and other fields.

5.1. The Metric Tensor. Let M be a manifold. We can define something called a metric that allows us to talk about distances and angles on the manifold. We can define a metric as follows.

Definition 1.60. A metric tensor on M is a smooth assignment

$$g_p : T_p M \times T_p M \rightarrow \mathbb{R},$$

for each point $p \in M$ such that:

- (1) g_p is bilinear,
- (2) g_p is symmetric,
- (3) g_p is nondegenerate.

Smoothness means that in any coordinate chart $\{x^\mu\}$, the components

$$g_{\mu\nu}(x) := g(\partial_\mu, \partial_\nu),$$

are smooth functions. From this, we get a special type of manifold, namely, the pseudo-Riemannian manifold.

Definition 1.61. The pair (M, g) is called a pseudo-Riemannian manifold.

If in addition g_p is positive definite for every $p \in M$, meaning

$$g_p(v, v) > 0 \quad \text{for all } v \neq 0,$$

then (M, g) is called a Riemannian manifold.

In general, a pseudo-Riemannian metric need not be positive definite. At each point p , the bilinear form g_p has a well-defined *signature* (p, q) , where p and q denote the number of positive and negative eigenvalues, respectively.

The metric allows us to:

- Measure lengths of tangent vectors:

$$\|v\|^2 = g(v, v),$$

- Measure angles between vectors,
- Raise and lower tensor indices using the inverse metric $g^{\mu\nu}$.

Because g is nondegenerate, there exists a unique inverse tensor $g^{\mu\nu}$ satisfying

$$g^{\mu\alpha} g_{\alpha\nu} = \delta^\mu_\nu.$$

This allows us to lower and raise indices:

$$v_\mu = g_{\mu\nu} v^\nu \quad \text{and} \quad v^\mu = g^{\mu\nu} v_\nu.$$

Metrics that are not positive definite naturally classify tangent vectors into different types depending on the sign of $g(v, v)$. A particularly important case is when the signature is $(1, n-1)$, which will be discussed in detail later when we introduce Lorentzian manifolds.

5.2. Levi-Civita Connection. Given a pseudo-Riemannian manifold (M, g) , there is a unique connection that is compatible with the metric and has zero torsion. This connection is called the *Levi-Civita connection*.

THEOREM 1.62 (Fundamental Theorem of Riemannian Geometry). *Let (M, g) be a pseudo-Riemannian manifold. There exists a unique connection ∇ (the Levi-Civita connection) such that:*

- (1) ∇ is torsion-free: $\nabla_X Y - \nabla_Y X = [X, Y]$.
- (2) ∇ is metric-compatible: $X(g(Y, Z)) = g(\nabla_X Y, Z) + g(Y, \nabla_X Z)$.

From the properties of the Levi-Civita connection, we can derive an explicit formula for ∇ in terms of the metric, known as the *Koszul formula*:

$$2g(\nabla_X Y, Z) = X(g(Y, Z)) + Y(g(Z, X)) - Z(g(X, Y)) + g([X, Y], Z) - g([Y, Z], X) - g([Z, X], Y).$$

In a local coordinate system $\{x^i\}$, we can express the covariant derivative of one basis vector ∂_j in the direction of another ∂_i . Since the result $\nabla_{\partial_i} \partial_j$ is itself a vector field, it can be written as a linear combination of the basis vectors $\{\partial_k\}$.

Definition 1.63. *The Christoffel symbols of the second kind are defined by the relation:*

$$\nabla_{\partial_i} \partial_j = \Gamma_{ij}^k \partial_k.$$

Applying the Koszul formula to the coordinate basis vectors (where $[\partial_i, \partial_j] = 0$) yields the explicit formula:

$$\Gamma_{ij}^k = \frac{1}{2} g^{kl} (\partial_i g_{jl} + \partial_j g_{il} - \partial_l g_{ij}),$$

where g^{kl} is the inverse of the metric tensor g_{kl} . This formula allows us to compute the Christoffel symbols directly from the metric components and their derivatives.

Since the Levi-Civita connection is torsion-free, the Christoffel symbols are symmetric in the lower indices:

$$\Gamma_{ij}^k = \Gamma_{ji}^k.$$

This reduces the number of components you have to calculate (e.g., in 3D, there are only 18 independent components instead of 27).

Now, let's use the Christoffel symbols to compute the covariant derivative of a vector field $V = V^k \partial_k$ in the direction of another vector field $X = X^i \partial_i$. Let $V = V^k \partial_k$ be a smooth vector field and $X = X^i \partial_i$ be the direction of differentiation. By the Leibniz rule (property of the connection), the covariant derivative $\nabla_X V$ is:

$$\nabla_X V = \nabla_{X^i \partial_i} (V^j \partial_j) = X^i \nabla_{\partial_i} (V^j \partial_j).$$

Applying the product rule:

$$\nabla_X V = X^i ((\partial_i V^j) \partial_j + V^j \nabla_{\partial_i} \partial_j).$$

Recalling the definition of Christoffel symbols, $\nabla_{\partial_i} \partial_j = \Gamma_{ij}^k \partial_k$, we substitute this into the expression:

$$\nabla_X V = X^i ((\partial_i V^k) \partial_k + V^j \Gamma_{ij}^k \partial_k).$$

Factoring out the basis ∂_k , we arrive at the component formula:

$$(\nabla_X V)^k = X^i \left(\frac{\partial V^k}{\partial x^i} + \Gamma_{ij}^k V^j \right).$$

5.3. Parallel Transport and Geodesics. In Euclidean space, a “straight” path is easily defined as one with zero acceleration. However, on a Riemannian manifold (M, g) , the notion of a straight line is complicated by the fact that the tangent spaces $T_p M$ and $T_q M$ at different points are distinct. To determine if a path is straight, we first need a way to move vectors from one point to another without “turning” them. This leads us to the concept of parallel transport.

Let (M, g) be a manifold equipped with the Levi-Civita connection ∇ . Given a smooth curve $\gamma : I \rightarrow M$ with tangent vector $\dot{\gamma}(t) = \frac{d\gamma}{dt}$, we seek to measure how a vector field X changes as we move along γ .

Definition 1.64. Let X be a vector field defined along γ , such that $X(t) \in T_{\gamma(t)} M$. The covariant derivative of X along γ is the projection of the standard derivative back onto the tangent space:

$$\frac{DX}{dt} := \nabla_{\dot{\gamma}(t)} X.$$

In local coordinates $\{x^\mu\}$, the covariant derivative accounts for the “twisting” of the coordinate basis through the Christoffel symbols $\Gamma_{\alpha\beta}^\mu$:

$$\left(\frac{DX}{dt}\right)^\mu = \frac{dX^\mu}{dt} + \Gamma_{\alpha\beta}^\mu \dot{\gamma}^\alpha X^\beta.$$

This formula captures the motivation for the connection: it corrects the ordinary derivative of the component X^μ by adding a term that represents how the basis vectors themselves are changing relative to the metric.

A vector is “parallel” if it does not change its orientation relative to the manifold’s geometry as it moves.

Definition 1.65. A vector field X along γ is said to be parallel transported if its covariant derivative along the curve vanishes:

$$\frac{DX}{dt} = 0 \quad \Leftrightarrow \quad \frac{dX^\mu}{dt} + \Gamma_{\alpha\beta}^\mu \dot{\gamma}^\alpha X^\beta = 0.$$

Because the Levi-Civita connection is metric-compatible, parallel transport is an *isometry* between tangent spaces. It preserves both the lengths of vectors and the angles between them:

$$\frac{d}{dt} g(X, Y) = g\left(\frac{DX}{dt}, Y\right) + g\left(X, \frac{DY}{dt}\right) = 0.$$

In medical imaging, this ensures that if an ultrasound pulse is modeled as a vector, its “energy” (magnitude) remains constant as it moves through the tissue, even if its direction is deflected by the curvature of the sound-speed metric.

With parallel transport defined, we can now define the “straightest” possible curves on a manifold. A curve is a geodesic if it does not “accelerate” in any direction other than the one dictated by the curvature of the manifold itself.

Definition 1.66. A curve γ is a geodesic if its tangent vector is parallel transported along itself:

$$\frac{D\dot{\gamma}}{dt} = 0 \quad \text{or equivalently,} \quad \nabla_{\dot{\gamma}} \dot{\gamma} = 0.$$

Expanding this in local coordinates yields the *geodesic equation*, a second-order non-linear system of ODEs:

$$\frac{d^2 x^\mu}{dt^2} + \Gamma_{\alpha\beta}^\mu \frac{dx^\alpha}{dt} \frac{dx^\beta}{dt} = 0.$$

While the definition above is geometric (zero acceleration), geodesics also arise from a physical principle: the minimization of effort. Geodesics are critical points of the *energy functional*:

$$E[\gamma] = \frac{1}{2} \int_I g_{\mu\nu} \dot{x}^\mu \dot{x}^\nu dt.$$

Applying the Euler-Lagrange equations to $E[\gamma]$ yields the exact same coordinate geodesic equation. In the context of our boundary rigidity problem, this variational perspective is vital; it tells us that ultrasound rays (geodesics) always follow the paths that minimize “acoustic effort” (time-of-flight), which is the very data we measure at the boundary.

5.4. Curvature. Next, we introduce the concept of curvature on a manifold.

Definition 1.67. *The Riemann curvature tensor is the $(1,3)$ -tensor $R : \Gamma(TM) \times \Gamma(TM) \times \Gamma(TM) \rightarrow \Gamma(TM)$ defined by:*

$$(1.1) \quad R(X, Y)Z = \nabla_X \nabla_Y Z - \nabla_Y \nabla_X Z - \nabla_{[X, Y]} Z.$$

This tensor quantifies the failure of the second covariant derivatives to commute. Geometrically, it measures the change in a vector Z after it is parallel-transported around an infinitesimal loop spanned by X and Y .

In a local coordinate system $\{x^\mu\}$, the components of the Riemann tensor are computed from the Christoffel symbols and their partial derivatives:

$$R_{\sigma\mu\nu}^\rho = \partial_\mu \Gamma_{\nu\sigma}^\rho - \partial_\nu \Gamma_{\mu\sigma}^\rho + \Gamma_{\mu\lambda}^\rho \Gamma_{\nu\sigma}^\lambda - \Gamma_{\nu\lambda}^\rho \Gamma_{\mu\sigma}^\lambda.$$

The Riemann tensor for a Levi-Civita connection satisfies several symmetries, most notably $R(X, Y)Z = -R(Y, X)Z$, which in coordinates reads $R_{\sigma\mu\nu}^\rho = -R_{\sigma\nu\mu}^\rho$. By contracting indices, we obtain the primary tools for geometric analysis:

- **Ricci Tensor:** $R_{\sigma\nu} = R_{\sigma\rho\nu}^\rho$. This $(0,2)$ -tensor represents the average curvature in a given direction.
- **Scalar Curvature:** $R = g^{\sigma\nu} R_{\sigma\nu}$. This is a single smooth function providing a global measure of how the manifold’s volume differs from Euclidean space.

Example 1.68. *For a 2-sphere $\mathbb{S}^2$ of radius a with the standard metric $ds^2 = a^2 d\theta^2 + a^2 \sin^2 \theta d\varphi^2$, a direct computation of the Riemann components reveals that the curvature is constant. Specifically, the scalar curvature is:*

$$R = \frac{2}{a^2}.$$

In medical imaging, regions with high R might correspond to areas of high structural complexity or sharp anatomical transitions.

If a metric $g_{\mu\nu}$ is given, we may further contract to obtain the scalar curvature.

Definition 1.69. *The scalar curvature is defined by*

$$R = g^{\sigma\nu} R_{\sigma\nu}$$

While the Riemann tensor is a high-rank object, we can extract the curvature of a specific 2-dimensional plane $P \subset T_p M$ within the tangent space. This is often the most intuitive way to visualize curvature in higher dimensions.

Definition 1.70. Let $\{v, w\}$ be a basis for a 2-plane P in $T_p M$. The sectional curvature of P is defined by:

$$K(v, w) = \frac{g(R(v, w)w, v)}{g(v, v)g(w, w) - g(v, w)^2}.$$

For a Riemannian manifold, if K is constant for all planes at all points, the manifold is called a *space of constant curvature*. In imaging, sectional curvature helps characterize the “local shape” of an organ’s surface.

In dimensions $n \geq 4$, the Riemann tensor can be decomposed into a part determined by the Ricci tensor and a “remainder” known as the Weyl tensor.

Definition 1.71. The Weyl curvature tensor C is the traceless part of the Riemann tensor. It represents the component of curvature that distorts the shape of a volume element without changing its total volume.

This is particularly relevant for *conformal geometry*, where we study deformations that preserve angles but not necessarily distances—a common scenario when modeling tissue stretching.

Finally, for variational problems and physical modeling, we define a specific combination of the Ricci and Scalar curvatures.

Definition 1.72. The Einstein tensor G is the symmetric $(0, 2)$ -tensor defined by:

$$G_{\mu\nu} = R_{\mu\nu} - \frac{1}{2}Rg_{\mu\nu}.$$

The primary mathematical utility of G is that its divergence vanishes ($\nabla^\mu G_{\mu\nu} = 0$) due to the *contracted Bianchi identity*. This property is essential when setting up “conservation laws” for biological flows or deformations.

5.5. Curvature Contractions. The Riemann tensor possesses 256 components in four dimensions, but its inherent symmetries reduce this to only 20 independent components. These symmetries are essential for performing contractions correctly.

- **Algebraic Symmetries:**

$$(1.2) \quad R_{\rho\sigma\mu\nu} = -R_{\sigma\rho\mu\nu} \quad (\text{Antisymmetry in first two indices})$$

$$(1.3) \quad R_{\rho\sigma\mu\nu} = -R_{\rho\sigma\nu\mu} \quad (\text{Antisymmetry in last two indices})$$

$$(1.4) \quad R_{\rho\sigma\mu\nu} = R_{\mu\nu\rho\sigma} \quad (\text{Interchange symmetry})$$

- **The First Bianchi Identity:** This relates the cyclic permutation of the last three indices:

$$R_{\sigma\mu\nu}^\rho + R_{\mu\nu\sigma}^\rho + R_{\nu\sigma\mu}^\rho = 0$$

- **The Second (Differential) Bianchi Identity:** This describes how the curvature tensor varies across the manifold:

$$\nabla_\lambda R_{\sigma\mu\nu}^\rho + \nabla_\mu R_{\sigma\nu\lambda}^\rho + \nabla_\nu R_{\sigma\lambda\mu}^\rho = 0$$

By contracting the second Bianchi identity twice, we arrive at a result that is fundamental to variational principles in imaging (such as Total Variation denoising on manifolds):

$$(1.5) \quad \nabla^\mu R_{\mu\nu} = \frac{1}{2}\nabla_\nu R.$$

This identity implies that the *Einstein tensor* $G_{\mu\nu} = R_{\mu\nu} - \frac{1}{2}Rg_{\mu\nu}$ is divergence-free ($\nabla^\mu G_{\mu\nu} = 0$). In physical modeling, this represents a local conservation law for the geometric “energy” of the manifold.

The Riemann tensor can be decomposed into three irreducible components that represent different geometric effects. This decomposition is particularly useful in higher-dimensional analysis (where $n \geq 3$).

- (1) **The Scalar Part:** Represents the portion of curvature associated with the scalar curvature R . This part determines how the volume of a small ball in the manifold compares to a ball of the same radius in Euclidean space.
- (2) **The Traceless Ricci Part:** Encapsulated by the tensor $R_{\mu\nu} - \frac{1}{n}Rg_{\mu\nu}$. This describes the “tidal” forces or the anisotropic stretching of the volume that preserves the total volume but changes its shape.
- (3) **The Weyl Tensor ($C_{\rho\sigma\mu\nu}$):** Also known as the *conformal curvature tensor*. In dimensions $n \geq 4$, it is the part of the Riemann tensor that remains after the Ricci and Scalar parts are removed.

To connect these contractions to the “Inverse Problem,” consider a small “cloud” of test particles (or signal points in an MRI) initially at rest. The Ricci tensor $R_{\mu\nu}$ describes the initial second derivative of the volume V of this cloud as it begins to move along geodesics:

$$(1.6) \quad \left. \frac{\ddot{V}}{V} \right|_{t=0} = -R_{\mu\nu}\dot{\gamma}^\mu\dot{\gamma}^\nu.$$

This relation, known as *Raychaudhuri’s equation* in its simplest form, shows that positive Ricci curvature tends to converge geodesics, causing the volume to shrink. In imaging, this can be used to model the focus or dispersion of signals within heterogeneous media.

5.6. The Laplace-Beltrami Operator. In Euclidean space, the Laplacian $\Delta = \sum \partial_i^2$ is the most fundamental second-order differential operator. On a Riemannian manifold (M, g) , this is generalized to the *Laplace-Beltrami operator* Δ_g , which accounts for the varying metric and curvature of the space.

Definition 1.73. *The Laplace-Beltrami operator acting on a smooth function $f \in C^\infty(M)$ is defined as the divergence of the gradient:*

$$(1.7) \quad \Delta_g f = \operatorname{div}(\operatorname{grad} f) = \nabla^\mu \nabla_\mu f.$$

Using the metric g and its determinant $|g| = \det(g_{\mu\nu})$, the Laplace-Beltrami operator can be written explicitly without requiring the Christoffel symbols:

$$(1.8) \quad \Delta_g f = \frac{1}{\sqrt{|g|}} \partial_\mu \left(\sqrt{|g|} g^{\mu\nu} \partial_\nu f \right).$$

This formula is particularly powerful for medical imaging simulations because it only requires the metric components $g_{\mu\nu}$ and their first derivatives.

The study of the equation $\Delta_g \varphi = -\lambda \varphi$ is known as the *spectral geometry* of the manifold. For a compact manifold, the eigenvalues $0 = \lambda_0 < \lambda_1 \leq \lambda_2 \dots$ form a discrete spectrum that encodes global geometric information, such as the volume and total curvature (by the Heat Kernel expansion).

In the context of medical imaging, the Laplace-Beltrami operator appears in several key areas:

- **Diffusion Tensor Imaging (DTI):** The diffusion of water molecules in the brain follows the heat equation $\partial_t u = \Delta_g u$, where g is the diffusion tensor.
- **Surface Parameterization:** The Laplace-Beltrami operator is used to calculate “Harmonic maps,” which allow researchers to flatten complex anatomical surfaces (like the cerebral cortex) into 2D planes while minimizing distortion.
- **Geometric Regularization:** In inverse problems, the “energy” term $\int_M |\nabla_g f|^2 dV$ is often used to ensure that reconstructed images are smooth relative to the underlying anatomy.

CHAPTER 2

The Boundary Distance Rigidity Problem

Now that we’ve developed the necessary geometric tools required, we’re now able to start looking at some interesting problems. Throughout this chapter, we’ll only be looking at one specific problem, the Boundary Distance Rigidity Problem, and its applications to medical imaging. This problem is a fundamental question in the field of geometric inverse problems, and it has many applications in various fields, including medical imaging, geophysics, and computer vision.

1. Formalizing the Boundary Distance Rigidity Problem

The boundary distance rigidity problem represents a fundamental inquiry into the relationship between the internal geometry of a manifold and its observable surface data. At its core, the problem asks whether the metric structure of a hidden interior can be uniquely reconstructed by measuring the lengths of the shortest paths—the geodesics—connecting points on its boundary. In the context of medical imaging, this mathematical framework provides the formal justification for ultrasound tomography: if the human body is modeled as a Riemannian manifold (M, g) where the metric g encodes the local sound speed, then the time-of-flight measurements between sensors on the skin constitute the boundary distance data. However, as we shall explore, the transition from surface-level observations to interior reconstruction is complicated by gauge symmetries and topological obstructions. By formalizing this problem, we establish the criteria under which a clinical scan can be considered a mathematically unique and physically accurate representation of internal anatomy.

1.1. Formalizing the Problem. Let (M, g) be a compact Riemannian manifold with smooth boundary ∂M . The distance between two points $x, y \in M$ is defined by the infimum of the lengths of all piecewise smooth curves connecting them:

$$(2.1) \quad d_g(x, y) = \inf \{ \ell_g(\gamma) : \gamma \in C_{pw}^\infty([0, 1], M), \gamma(0) = x, \gamma(1) = y \}$$

where the length functional $\ell_g(\gamma)$ is given by

$$\ell_g(\gamma) = \int_0^1 \sqrt{g(\dot{\gamma}(t), \dot{\gamma}(t))} dt.$$

Since $d_g(x, y)$ is defined as an infimum, the paths γ that realize this distance are precisely the geodesics of the metric g . Consequently, the boundary rigidity problem can be viewed as an attempt to reconstruct the geometry of M by observing the behavior of its “shortest paths” as they enter and exit the manifold.

While d_g is defined for all pairs of points in M , the *boundary distance function* is the restriction of d_g to the pairs of points on the boundary ∂M :

$$(2.2) \quad d_g|_{\partial M \times \partial M} : \partial M \times \partial M \rightarrow \mathbb{R},$$

which assigns to each pair of boundary points (x, y) the distance $d_g(x, y)$ between them. The challenge lies in determining the metric g at an interior point $p \in M \setminus \partial M$ using only these surface-level observations.

The *Boundary Rigidity Problem* asks the following:

Problem 2.1. *Does the knowledge of the boundary distance function $d_g|_{\partial M \times \partial M}$ uniquely determine the metric g in the interior of M , up to a diffeomorphism that is the identity on the boundary?*

This inverse problem is highly relevant in fields where the interior of a medium is inaccessible. In *medical imaging*, for instance, we treat a patient's body as the manifold M . If the metric g represents the inverse of the sound speed, the boundary distances correspond to the *time-of-flight* of ultrasound pulses between transducers placed on the skin. By recovering g , we effectively reconstruct the internal sound-speed map, allowing for the detection of anomalies such as tumors.

In the context of ultrasound tomography, if we consider a non-homogeneous medium (like human tissue), the “length” $\ell_g(\gamma)$ is physically equivalent to the time-of-flight. A regions of high density or stiffness effectively “warp” the metric, causing the ultrasound pulses to follow curved trajectories rather than straight lines. The goal of the clinician is to use these arrival times to map out internal variations in tissue density.

1.2. Gauge Invariance and Isometries. This section will address what the “up to isometry” clause of the problem statement means. In particular, we will discuss the concept of gauge invariance and how it relates to the uniqueness of the solution to the boundary rigidity problem.

Lemma 2.2 (Gauge Invariance). *If $\psi : M \rightarrow M$ is a diffeomorphism such that $\psi|_{\partial M} = \text{Id}$, then $d_{\psi^*g} = d_g$ on $\partial M \times \partial M$.*

PROOF. Since $x, y \in \partial M$ and $\psi|_{\partial M} = \text{Id}$, a curve γ connects x to y if and only if the transformed curve $\tilde{\gamma} = \psi \circ \gamma$ also connects x to y . The length of γ with respect to the pullback metric is:

$$\begin{aligned} \ell_{\psi^*g}(\gamma) &= \int_0^1 \sqrt{(\psi^*g)_{\gamma(t)}(\dot{\gamma}(t), \dot{\gamma}(t))} dt \\ &= \int_0^1 \sqrt{g_{\psi(\gamma(t))}(d\psi_{\gamma(t)}\dot{\gamma}(t), d\psi_{\gamma(t)}\dot{\gamma}(t))} dt \end{aligned}$$

By the chain rule, $d\psi_{\gamma(t)}\dot{\gamma}(t) = \frac{d}{dt}(\psi \circ \gamma)(t)$. Thus, the integral is exactly $\ell_g(\psi \circ \gamma)$. Since ψ is a diffeomorphism fixing the boundary, it induces a bijection on the space of paths $\Lambda_{x,y}$. Taking the infimum over all such paths, we conclude $d_{\psi^*g}(x, y) = d_g(x, y)$. $\square$

NOTE 7. *The pullback ψ^*g is the unique tensor field such that the map $\psi : (M, \psi^*g) \rightarrow (M, g)$ is a Riemannian isometry. Geometrically, this means ψ preserves all intrinsic measurements (lengths, angles, areas), even though it may “stretch” or “warp” the coordinate representation of the manifold.*

Now, what consequences does this have for the boundary problem? This means that the data cannot distinguish between the metric g and any other metric ψ^*g obtained by pulling back g via diffeomorphisms that fix the boundary. Therefore, the best we can hope for is to recover the metric g up to such a diffeomorphism, which is precisely what the problem statement asserts. This is a nice result, as if

we relate it back to medical imaging context. In clinical practice, this isometry represents a non-rigid deformation. While the distances (time-of-flight) remain the same, the “coordinates” of a tumor might appear shifted in the reconstructed image. This mathematical obstruction is why clinicians use anatomical landmarks to “fix” the gauge, essentially selecting one preferred representative from the isometry class.

We finish this section with a definition of *boundary rigidity*.

Definition 2.3. *Let $\mathcal{B}$ be a class of Riemannian metrics on M . We say that g is boundary rigid in $\mathcal{B}$ if given any metric $h \in \mathcal{B}$ with $d_g|_{\partial M \times \partial M} = d_h|_{\partial M \times \partial M}$, there exists a diffeomorphism $\psi : M \rightarrow M$ such that $\psi|_{\partial M} = \text{Id}$ and $h = \psi^*g$.*

1.3. Computational Examples: Flat and Constant Curvature Cases.

Before we move on to the more general theory, let’s consider some special cases where the boundary rigidity problem can be explicitly solved. These examples will provide intuition for the general case and illustrate how curvature affects the uniqueness of the solution.

Proposition 2.4. *Let D be the unit disk in $\mathbb{R}^2$ with the Euclidean metric g_0 . The boundary distance function $d_{g_0}(x, y) = |x - y|$ uniquely determines g_0 up to a boundary-fixing isometry.*

PROOF. The boundary data provides the lengths of all straight-line segments (chords) connecting points on the circle. In the flat case, these chords are the unique distance-minimizing geodesics.

If there existed another metric g with the same boundary distances, the geodesics of g would have to “bend” to maintain the same lengths between boundary points. However, a fundamental result in integral geometry (the Santaló formula) implies that any such “bending” would necessarily change the total volume or the average length of the paths. In the Euclidean case, the straight-line paths are the “most efficient” way to connect boundary points; any deviation into curvature would be detected by the distance function. $\square$

This specific case allows us to see the “spirit” of the Boundary Rigidity Conjecture. The conjecture suggests that the boundary distance function acts as a *hologram*: the information on the 1D boundary (∂M) is sufficient to encode the geometry of the 2D interior (M).

In medical imaging, this is the “Ideal Scan.” If the human body were a flat Euclidean disk, an ultrasound pulse traveling from transducer A to B would tell us exactly what is on the line segment AB . By rotating the transducers, we “fill in” the disk with a web of lines. The Boundary Rigidity Problem asks: if those lines are no longer straight (due to the “refractive index” of different tissues), can we still untangle the web to see the organs inside?

Before we move on, let’s do a few more complicated examples to see how curvature can affect the problem.

Example 2.5 (The Spherical Cap $M \subset \mathbb{S}^2$). *Consider a spherical cap of radius $R = 1$ defined by colatitude $\varphi \in [0, \alpha]$. The metric in spherical coordinates is $g = d\varphi^2 + \sin^2 \varphi d\theta^2$. Let two boundary points be $P_1 = (\alpha, 0)$ and $P_2 = (\alpha, \Delta\theta)$. The boundary distance d_g is the angle ψ between the corresponding unit vectors in $\mathbb{R}^3$, found via the spherical law of cosines:*

$$(2.3) \quad d_g(P_1, P_2) = \arccos(\cos^2 \alpha + \sin^2 \alpha \cos(\Delta\theta))$$

- **Rigidity:** If $\alpha < \pi/2$, the cap is strictly smaller than a hemisphere. There is a unique minimizing geodesic between any two points, and the metric is boundary rigid.
- **Failure:** If $\alpha = \pi/2$ (a hemisphere), then for antipodal points on the equator ($\Delta\theta = \pi$), $d_g = \pi$. However, there are infinitely many geodesics (meridians) of length π connecting these points. This is a conjugate point failure; the boundary data cannot distinguish between these paths, leading to a loss of internal resolution.

Example 2.6 (The Flat Cylinder $\mathbb{S}^1 \times [0, L]$). Consider the cylinder with coordinates $(\theta, z) \in [0, 2\pi) \times [0, L]$ and metric $g = d\theta^2 + dz^2$. For points $P_1 = (0, 0)$ and $P_2 = (\Delta\theta, L)$ on opposite boundary components, the periodicity of θ implies multiple geodesic paths indexed by winding number $k \in \mathbb{Z}$, with lengths:

$$(2.4) \quad \ell_k = \sqrt{(\Delta\theta + 2\pi k)^2 + L^2}$$

The boundary distance function only records the infimum: $d_g(P_1, P_2) = \min_{k \in \mathbb{Z}} \ell_k$.

- **Topological Obstruction:** If we perturb the metric g to g' only in a region traversed by a path with $k = 1$, but the $k = 0$ path remains the shortest, then $d_{g'} = d_g$. The boundary distance function is “blind” to any interior changes that do not affect the global minimizer.

Example 2.7 (The Toroidal Domain $M \subset \mathbb{T}^2$). Consider a flat torus $\mathbb{T}^2 = \mathbb{R}^2/\mathbb{Z}^2$ from which a small disk has been removed to create a boundary ∂M .

- **Trapping:** The non-trivial homology of the torus allows for trapped geodesics—closed loops or infinite windings that never intersect ∂M .
- **Consequence:** Because the boundary distance function d_g is defined only by paths that start and end on ∂M , it provides zero information regarding the metric in the region containing trapped orbits. We could significantly alter the sound speed within a trapped “dead zone” without changing a single value of the boundary distance function, representing a complete failure of rigidity.

Example 2.8 (The Real Projective Space $\mathbb{RP}^2$). Let M be the manifold formed by taking a hemisphere of $\mathbb{S}^2$ and identifying antipodal points on its boundary (the equator). Topologically, M is the Real Projective Plane. If we remove a small disk from its interior, we obtain a manifold with a single boundary component ∂M , which is topologically a Möbius strip.

- **Geodesic Behavior:** Geodesics in $\mathbb{RP}^2$ are the images of great circles from $\mathbb{S}^2$. A critical property of $\mathbb{RP}^2$ is that all geodesics are closed loops of length π . Specifically, a geodesic starting at p in any direction will return to p after traveling a distance π .
- **Conjugate Points and the Cut Locus:** In $\mathbb{RP}^2$, every point p has a conjugate point at a distance $\pi/2$ (relative to the sphere’s metric). Furthermore, for any point p , the cut locus $C(p)$ consists of the “line at infinity” relative to p .
- **Boundary Distance Computation:** Consider two points $x, y \in \partial M$. Because the manifold “folds” back on itself, there are at least two distinct geodesic paths connecting x and y :
 - (1) The “short” arc γ_1 of length L .
 - (2) The “long” arc γ_2 that wraps around the non-orientable loop of the Möbius strip, with length $\pi - L$.

The boundary distance function only records $d_g(x, y) = \min(L, \pi - L)$.

- **Failure of Rigidity:** $\mathbb{RP}^2$ fails the boundary rigidity problem due to topological trapping. One can perturb the metric g to g' inside a small region $U \subset M$. If U is located such that no minimizing geodesics (the “short” arcs) pass through it, the change remains invisible to the boundary distance function d_g .
- **Formal Failure:** Unlike the spherical cap where π is the diameter, in $\mathbb{RP}^2$, the presence of closed geodesics means the manifold is trapping. This violates the fundamental requirement for the injectivity of the X-ray transform, as a perturbation f supported on a closed geodesic loop satisfies $If = 0$ for all geodesics entering and exiting the boundary.

1.4. The Scattering Relation. While the boundary distance function d_g provides a scalar measurement of geodesic length, the *scattering relation* α_g captures the full phase-space behavior of geodesics as they interact with the manifold.

Definition 2.9. Let $\partial_+ SM = \{(x, v) \in SM : x \in \partial M, \langle v, \nu(x) \rangle \leq 0\}$ be the set of inward-pointing unit vectors at the boundary. The scattering relation $\alpha_g : \partial_+ SM \rightarrow \partial_- SM$ is defined by:

$$(2.5) \quad \alpha_g(x, v) = (\gamma_{x,v}(\tau(x, v)), \dot{\gamma}_{x,v}(\tau(x, v)))$$

where $\tau(x, v)$ is the exit time of the geodesic starting at (x, v) .

For a simple manifold, the scattering relation is a diffeomorphism between the inward and outward boundary bundles. Furthermore, there is a fundamental link between the scattering relation and the boundary distance function: the exit position and direction are uniquely determined by the gradient of d_g with respect to the boundary coordinates.

In the context of medical imaging, this represents the transition from *time-of-flight tomography* to *diffraction tomography*. By measuring the angle at which an ultrasound wave exits the body, we gain additional information about the internal refractive index gradients. This subsection concludes our survey of boundary data; on simple manifolds, d_g and α_g provide a complete “holographic” description of the interior geometry, which we will now utilize to define the linearized X-ray transform.

For a simple manifold M , any two points $x, y \in \partial M$ are joined by a unique minimizing geodesic $\gamma_{x,y}$. The initial and final velocities of this geodesic can be recovered by differentiating the distance function with respect to the boundary coordinates.

Let x, y be points on the boundary ∂M . Let $v \in T_x M$ be the inward-pointing unit vector such that $\gamma_{x,v}$ is the unique geodesic from x to y , and let $w \in T_y M$ be the outward-pointing unit vector (the exit velocity). The scattering relation is defined as $\alpha_g(x, v) = (y, w)$. The link to the distance function is given by the following identities:

$$v = -\nabla_x d_g(x, y) \quad \text{and} \quad w = \nabla_y d_g(x, y),$$

where ∇_x and ∇_y denote the Riemannian gradient with respect to the first and second variables, restricted to the tangent space of the boundary.

To see why this holds, consider the distance function $d_g(x, \cdot)$ from a fixed point x . Its level sets are the distance spheres $S(x, r) = \{z \in M : d_g(x, z) = r\}$. By the Gauss Lemma, the gradient $\nabla_z d_g(x, z)$ is a unit vector that is orthogonal to these distance spheres and points in the direction of the geodesic starting at x .

When we restrict our observations to the boundary ∂M , we are looking at the “footprints” of these geodesics. The tangential component of the gradient ∇d_g on the boundary tells us the angle at which the geodesic “hits” the surface.

Now, why does this matter? This proves that for simple manifolds, the boundary distance function and the scattering relation contain exactly the same information. If you know the travel times between all points on the skin, you mathematically know the exit angles of every ultrasound ray.

Another key fact is that in the language of symplectic geometry, the scattering relation is a canonical transformation (a symplectomorphism) on the cotangent bundle of the boundary. The distance function d_g serves as the generating function for this transformation.

In modern medical imaging, we use phased array transducers. These devices don’t just act as a single point-source; they use interference patterns to steer beams and, more importantly, to detect the angle of arrival of returning waves. We have d_g measures the “time-of-flight” and α_g measures the “phase shift” across the sensor face to determine the exit vector w .

By relating α_g to d_g , you are showing that these two types of medical data are redundant on “simple” tissue, but can be used together to verify the “Simplicity” of the organ—if the exit angle doesn’t match the gradient of the distance function, the clinician knows there are conjugate points or trapped rays (like those in $\mathbb{S}^2$ or $\mathbb{RP}^2$) interfering with the scan.

A powerful way to visualize the scattering relation is through the lens of Hamiltonian mechanics. In this context, the scattering relation is often referred to as *lens data*. If we consider the manifold M as a region of varying refractive index, α_g describes how the “optical system” of the manifold maps an incoming ray (x, v) to an outgoing ray (y, w) .

Because α_g preserves the canonical symplectic form on the cotangent bundle, it implies that the phase-space volume of a beam of geodesics is conserved as it passes through the manifold. Geometrically, this means that while the metric g may focus or disperse rays (lensing), it cannot “create” or “destroy” information unless the manifold fails to be simple. For instance, in the *Spherical Cap* example from Section 1.3, the lens data would show a converging effect, where a wide array of incoming vectors is mapped to a narrow set of exit points, eventually collapsing into a singularity at a conjugate point.

The equivalence of d_g and α_g is the theoretical justification for moving beyond traditional X-ray-style “straight-line” assumptions. In *Ultrasound Computed Tomography* (USCT), the “lens data” is captured by measuring both the time-of-arrival and the pressure gradient across a sensor array.

- **Correcting for Refraction:** In heterogeneous tissue, ultrasound rays do not travel in straight lines; they refract at the interfaces of different organs. By measuring the exit vector w (via the phase shift across the transducer), the reconstruction algorithm can “trace back” the curved path of the geodesic.
- **Detecting Non-Simplicity:** In practice, if a clinician observes an exit angle w that deviates significantly from the calculated $\nabla_y d_g$, it serves as a diagnostic flag. Such a discrepancy indicates that the “simple manifold” assumption has been violated—perhaps by a highly reflective bone surface or a trapped gas pocket in the bowels—alerting the operator that the

resulting image may contain artifacts or “shadows” that are mathematically unreliable.

2. Formalizing the Geometry of Simple Manifolds

This entire section will be dedicated to developing the theory of *simple manifolds*. Intuitively, a simple manifold is one where the “geometry is not too strong.” It allows the interior to be “illuminated” by boundary sources such that every interior point is uniquely “seen” by a well-defined family of rays. Each subsequent subsections will introduce one of the key conditions that define a simple manifold, and we will see how they relate to the behavior of geodesics and the exponential map. The three main conditions are:

- Strict Convexity of the Boundary.
- The Non-Trapping Condition.
- Absence of Conjugate Points (Injectivity of the Exponential Map).

2.1. Strict Convexity of the Boundary. Now, let’s try and develop the theory for a *simple manifold* (although we don’t give a formal definition just yet, as we do that in Subsection 2.4). A simple manifold is one that is “nice enough” to be solvable, but still rich enough to be interesting. It is a class of manifolds that satisfy certain geometric conditions that make the inverse problem of determining the interior structure from boundary measurements well-posed. Firstly, let’s start with the strict convexity of the boundary.

The standard way to define convexity in Riemannian geometry is through the second fundamental form Π .

Definition 2.10. Let ν be the unit inner normal vector field along the boundary ∂M . For any tangent vector $X \in T_x(\partial M)$, we define the second fundamental form Π at x as:

$$\Pi(X, X) = \langle \nabla_X \nu, X \rangle.$$

The second fundamental form Π is associated with the shape operator S . For any $x \in \partial M$, strict convexity requires that S is positive-definite, ensuring that the curvature of any geodesic starting tangent to the boundary is directed into M .

Definition 2.11. A Riemannian manifold (M, g) with boundary ∂M is said to have a strictly convex boundary if for every point $x \in \partial M$ and every non-zero tangent vector $X \in T_x(\partial M)$, the second fundamental form $\Pi(X, X) > 0$. Equivalently, the shape operator S associated with the boundary is positive-definite at every point on ∂M .

This means that the boundary curves “away” from the tangent plane toward the interior. If you fire a laser along the tangent to the skin, it will immediately move into the body rather than skimming along the outside.

If $x \in \partial M$ and $v \in T_x(\partial M)$, strict convexity implies that the geodesic $\gamma_{x,v}(t)$ satisfies $d(\gamma(t), \partial M) > 0$ for small $t > 0$. This ensures that no geodesic “skins” the boundary. If a geodesic could skim the boundary, the boundary distance $d_g(x, y)$ could be achieved by a path that never actually probes the interior, giving us zero information about the “organs” inside.

In medical imaging, this is related to the acoustic coupling of the transducer.

- **Ideal Geometry:** When imaging a breast or a limb, we often place it in a cylindrical or spherical “well” filled with water. This artificially imposes a strictly convex boundary.

- **The Failure:** If the boundary has “folds” or concave regions (like the armpit or certain facial structures), ultrasound waves can undergo multiple reflections off the skin before entering the tissue. This creates “multipath interference,” making the boundary distance d_g nearly impossible to calculate because the “shortest path” might actually be a path that exits and re-enters the body.

Example 2.12 (The Euclidean Ball $B^n \subset \mathbb{R}^n$). *The unit ball with the flat metric $g_{ij} = \delta_{ij}$ is the prototypical strictly convex manifold. For any point x on the boundary $\mathbb{S}^{n-1}$, the unit inner normal is $\nu(x) = -x$. If X is a tangent vector at x (meaning $X \cdot x = 0$), the second fundamental form is calculated as:*

$$\Pi(X, X) = \langle \nabla_X(-x), X \rangle = \langle -X, X \rangle = |X|^2.$$

Since $|X|^2 > 0$ for all non-zero X , the ball is strictly convex.

Geometrically, this means any geodesic starting at the boundary in a tangential direction will curve into the interior. In medical imaging, this is the “ideal” scenario where every transducer on the surface “looks” directly into the patient.

Example 2.13 (The Flat Cylinder $\mathbb{S}^1 \times [0, L]$). *Consider a “sleeve” of tissue. This example shows that even a flat manifold can fail to be strictly convex if the boundary is “too straight.” The boundary consists of two circles at $z = 0$ and $z = L$. For a vector X pointing in the z -direction (along the length of the cylinder), the normal ν does not change as we move in that direction ($\nabla_X \nu = 0$). Here, $\Pi(X, X) = 0$. The boundary is convex but not strictly convex. A geodesic can “graze” the boundary circle and stay on the surface forever.*

This creates a “surface wave” that travels around the perimeter without ever sampling the internal organs. The boundary distance d_g would record the length of this perimeter path, giving us zero information about the density inside the cylinder.

Example 2.14 (The “Dumbbell” or Concave Neck). *Imagine a manifold with a “waist” that curves inward, similar to the geometry of a human neck or armpit. In the “neck” region, the inner normal ν points away from the center of curvature. For a tangent vector X in this region, $\Pi(X, X) < 0$. The manifold is concave.*

This creates “shadow zones.” A geodesic (ultrasound ray) attempting to cross the neck might be forced to “bend away” from the center or reflect off the boundary. Mathematically, the shortest path between two points on the boundary might actually exit the manifold entirely, traveling through the air rather than the tissue. This makes the interior geometry “invisible” to standard boundary distance measurements.

2.2. The Non-Trapping Condition. Next, we define the non-trapping condition. A manifold is non-trapping if every geodesic eventually exits the manifold. Formally, for any geodesic $\gamma : [0, \infty) \rightarrow M$, there exists a time $T > 0$ such that $\gamma(T) \in \partial M$. This condition ensures that we can probe the interior of the manifold using geodesics. If there were trapped geodesics, they would never reach the boundary, and we would lose information about the interior along those paths.

The non-trapping condition ensures that every “ray” of information we send into the manifold eventually returns to the boundary to be measured. Mathematically, we formalize this using the exit time function.

Definition 2.15. *Let SM be the unit tangent bundle of M . For any point $x \in M$ and direction $v \in S_x M$, let $\gamma_{x,v}$ be the unique geodesic such that $\gamma(0) = x$ and*

$\dot{\gamma}(0) = v$. We define the exit time $\tau(x, v)$ as:

$$(2.6) \quad \tau(x, v) = \sup\{t \geq 0 : \gamma_{x,v}([0, t]) \subset M\}.$$

Now, we can define the non-trapping condition in terms of the exit time function τ .

Definition 2.16. A Riemannian manifold (M, g) is non-trapping if $\tau(x, v) < \infty$ for all $(x, v) \in SM$.

In a manifold that allows trapping (such as the flat torus $\mathbb{T}^2$ or a manifold with a “closed geodesic” loop), there exist initial conditions (x, v) such that the geodesic $\gamma_{x,v}$ remains in a compact subset of the interior for all $t > 0$.

From the perspective of the Geodesic X-ray Transform, a trapped geodesic represents a “kernel” of the operator. If a function f (representing a tumor or density anomaly) is supported entirely along a trapped orbit, its integral along all geodesics that exit the boundary will be zero. Consequently, f becomes “invisible” to the boundary sensors, rendering the inverse problem non-injective.

Example 2.17 (The Euclidean Disk $D^2 \subset \mathbb{R}^2$). Consider the unit disk with the standard flat metric. For any initial position $x \in D^2$ and unit vector $v \in S_x D^2$, the geodesic $\gamma_{x,v}$ is a straight line segment. Since the disk is compact and the velocity is constant ($|\dot{\gamma}| = 1$), the ray must intersect the boundary circle in a time $t \leq 2$. In this case, the exit time function $\tau(x, v)$ is bounded and continuous for all v . This is the ideal non-trapping case used in standard CT scans.

Example 2.18 (The “Maxwell Fish-Eye” (Radial Trapping)). Consider a disk with a radially symmetric metric $g = c(r)^{-2}(dr^2 + r^2 d\theta^2)$. If the “sound speed” $c(r)$ is designed such that the curvature increases significantly toward the center, the geodesics can “bend” so sharply that they form closed circular orbits.

Example 2.19 (The Toroidal Domain (Topological Trapping)). Take a flat torus $\mathbb{T}^2$ and remove a small disk to create a boundary ∂M . While the manifold is now “open,” it still inherits the closed loops of the torus.

2.3. Conjugate Points and Injectivity of the Exponential Map. Lastly, we define the concept of conjugate points, which are related to the behavior of geodesics and the injectivity of the exponential map.

We need to find a way to measure how much geodesics diverge or converge from the boundary as they propagate throughout the manifold. This is where the Jacobi fields come in. A Jacobi field is a vector field along a geodesic that describes how nearby geodesics deviate from each other. The behavior of Jacobi fields is governed by the curvature of the manifold, and they play a crucial role in understanding the geometry of geodesics. Formally, we can define Jacobi fields as follows:

Definition 2.20. The Jacobi Field $J(t)$ along a geodesic $\gamma(t)$ is a vector field that satisfies the Jacobi equation:

$$\nabla_{\dot{\gamma}} \nabla_{\dot{\gamma}} J + R(J, \dot{\gamma})\dot{\gamma} = 0.$$

The non-trapping condition implies that there are no Jacobi fields that vanish at two distinct points along a geodesic, which is related to the absence of conjugate points, which are defined as follows:

Definition 2.21. Two points p and q along a geodesic γ are called conjugate if there exists a non-trivial Jacobi field $J(t)$ along γ that vanishes at both p and q .

Conjugate points indicate that the exponential map fails to be injective, which can lead to ambiguities in determining the interior structure from boundary measurements.

If the sectional curvature is non-positive ($K \leq 0$), Jacobi fields always diverge, and you can never have conjugate points.

In medical imaging, positive curvature (which causes conjugate points) acts like a converging lens. If a tumor is much denser than the surrounding tissue, it can focus ultrasound rays so sharply that they cross, creating “caustics.” This is where the exponential map fails to be a diffeomorphism.

The last definition we need is the exponential map, which maps tangent vectors at a point to points on the manifold by following geodesics. The injectivity of the exponential map is crucial for ensuring that each point in the interior can be uniquely identified by its distance from the boundary.

Definition 2.22. *The exponential map at a point $p \in M$ is defined as:*

$$\exp_p : T_p M \rightarrow M, \quad \exp_p(v) = \gamma_v(1),$$

where γ_v is the geodesic starting at p with initial velocity v . The exponential map is said to be injective if it is a one-to-one mapping from a neighborhood of the origin in $T_p M$ to its image in M . This injectivity is guaranteed by the absence of conjugate points along the geodesics emanating from p .

The absence of conjugate points is crucial for injectivity of the exponential map, which, in turn, is essential for the uniqueness of the inverse problem. If there are conjugate points, multiple geodesics can connect the same pair of points, making it impossible to uniquely determine the interior structure from boundary data.

We can strengthen the definition of a simple manifold by restricting the injectivity of the exponential map to the entire manifold.

For a simple manifold, we require that for every $p \in M$, the map $\exp_p : \exp_p^{-1}(M) \rightarrow M$ is a global diffeomorphism. This ensures that every point in the “body” is reached by exactly one minimizing geodesic from p , eliminating the “multipath” ambiguity in ultrasound signals.

Example 2.23 (The “Trapping” Annulus). *Consider a flat annulus $M = \{(r, \theta) : 1 \leq r \leq 2\}$ in $\mathbb{R}^2$. Now, let’s warp the metric so that the “speed of sound” $c(r)$ is very slow in the center. Specifically, let $g = c(r)^{-2}(dr^2 + r^2 d\theta^2)$ with $c(r) = r$. In this specific metric (cf Example 2.18), geodesics are circles. A geodesic starting at $r = 1.5$ tangent to the circle $r = 1.5$ will stay on that circle forever.*

This manifold is Trapping. There exist geodesics that never hit the boundary $\partial M = \{r = 1, r = 2\}$. If there is a tumor located exactly at $r = 1.5$, a “ray” of ultrasound that stays trapped in that circular orbit will never reach the sensors on the skin. This creates a Blind Spot. No matter how many sensors you put on the boundary, you can never “see” the trapped region because no information ever escapes from it.

Example 2.24 (The “Lensed” Cylinder). *Consider a surface that is mostly a flat cylinder, but has a “mountain” (positive curvature) in the middle, like a bulge on a pipe.*

As geodesics (ultrasound rays) pass over the bulge, the positive curvature causes them to converge (the Jacobi equation $\nabla_{\dot{\gamma}} \nabla_{\dot{\gamma}} J + R(J, \dot{\gamma})\dot{\gamma} = 0$ with $R > 0$ pushes J toward zero). If the bulge is sharp enough, two rays starting from the same point P will cross at a point Q before hitting the boundary. Q is a Conjugate Point.

At the boundary sensor, you receive two signals from the same source at different times (or the same time). The exponential map $\exp_P$ is no longer a diffeomorphism. This creates Ghosting/Multipath Artifacts. The reconstruction algorithm assumes each “time-of-flight” corresponds to a unique path. When conjugate points exist, the computer might “hallucinate” two objects when there is only one, or blur the edges of a real anomaly.

2.4. Definition and Properties of Simple Manifolds. Lastly, we’ll show how all these various conditions come together to define a simple manifold, i.e., a manifold that’s boring enough manifold to be solvable, but still rich enough to be interesting.

Now, we can formally define a simple manifold as follows:

Definition 2.25. *A compact Riemannian manifold (M, g) with boundary ∂M is called simple if:*

- (1) *The boundary ∂M is strictly convex.*
- (2) *The manifold is non-trapping.*
- (3) *There are no conjugate points along any geodesic in M .*

Strict convexity is the “gatekeeper” condition. It ensures that the exponential map behaves well at the boundary. Specifically, it guarantees that for every $x \in \partial M$, the set of directions that point into the manifold is a nice, open hemisphere.

The non-trapping condition ensures that every geodesic eventually reaches the boundary, allowing us to probe the interior with boundary measurements. This is crucial for the well-posedness of the inverse problem.

The absence of conjugate points guarantees that the exponential map is injective, ensuring that each point in the interior can be uniquely identified by its distance from the boundary. This is essential for the uniqueness of the inverse problem.

Now, let’s look at a few examples of simple manifolds:

Example 2.26 ([The Euclidean Ball (The Zero Curvature Case)]). *The most fundamental example of a simple manifold is any closed, convex domain in $\mathbb{R}^n$ with the flat metric $g_{ij} = \delta_{ij}$. The boundary of a ball is strictly convex ($\Pi > 0$). Geodesics are straight lines, so they must exit in finite time (non-trapping). Since the curvature is zero, Jacobi fields grow linearly ($J(t) = tV$), meaning they never vanish twice; thus, there are no conjugate points.*

This is the mathematical model for a standard CT scan in a vacuum or uniform medium.

Example 2.27 (The Small Spherical Cap (The Positive Curvature Case)). *Consider a spherical cap $M \subset \mathbb{S}^2$ defined by colatitude $\varphi \in [0, \alpha]$. If $\alpha < \pi/2$ (less than a hemisphere), the boundary is a circle with positive geodesic curvature, satisfying the strict convexity condition. Because the cap is strictly smaller than a hemisphere, no geodesic has time to reach its first conjugate point (which occurs at distance π). Every geodesic is a great circle arc that hits the boundary and exits.*

This represents a medium with high density (like bone) that “lenses” the signal but isn’t powerful enough to create multiple paths or “ghost” images.

Example 2.28 (The Hyperbolic Disk (The Negative Curvature Case)). *Consider the Poincaré disk D^2 with the hyperbolic metric $g = \frac{4}{(1-r^2)^2}(dx^2 + dy^2)$, restricted to a disk of radius $r < 1$. Negative curvature ($K = -1$) is the “friend” of simplicity. In negatively curved manifolds, geodesics diverge exponentially. This divergence*

prevents any “trapping” in loops and strictly forbids conjugate points (Jacobi fields never return to zero). If the boundary is chosen to be a coordinate circle, it remains strictly convex in the hyperbolic sense.

This models a “diverging lens” medium. Even though the paths are highly curved, the “spread” of the rays ensures that every point in the interior is hit by exactly one ray from any boundary source, making the reconstruction mathematically stable.

The remainder of this section will be dedicated to proving various properties of simple manifolds. One of the most important properties is that on a simple manifold, the boundary distance function $d_g(x, y)$ is a smooth function on $(\partial M \times \partial M) \setminus \text{diag}$. This smoothness is the bedrock upon which we will build the linearized theory of the Geodesic X-ray transform in Section 3.

PROPERTY 1 (Topological Triviality). *A simple manifold (M, g) is contractible. In fact, M is diffeomorphic to the unit ball D^n in $\mathbb{R}^n$.*

Before we prove this, let’s understand the intuition. The strict convexity of the boundary ensures that the manifold is “bulging out” everywhere, preventing any “holes” or “handles” that would create non-trivial topology. The absence of conjugate points and the non-trapping condition ensure that geodesics behave in a well-controlled manner, allowing us to use the exponential map to construct a global diffeomorphism from a star-shaped domain in $T_p M$ to M .

PROOF. Fix a point $p \in \text{Int}(M)$. By the definition of a simple manifold, the exponential map $\exp_p$ is a diffeomorphism from its domain in $T_p M$ onto M . The domain of the exponential map is a star-shaped set in $T_p M$. Since any star-shaped set in a vector space is contractible to the origin, and a diffeomorphism preserves the homotopy type, M must be contractible. Furthermore, the strict convexity of the boundary and the absence of the cut locus ensure that M is a manifold with boundary that “looks” globally like a ball. $\square$

PROPERTY 2 (Global Uniqueness of Geodesics). *For any two points $p, q \in M$, there exists a unique minimizing geodesic connecting them that depends smoothly on its endpoints.*

Again, let’s understand the intuition. The strict convexity of the boundary ensures that geodesics cannot “graze” the boundary and must enter the interior. The non-trapping condition guarantees that every geodesic eventually reaches the boundary, preventing any infinite loops. The absence of conjugate points ensures that geodesics do not focus back on themselves, which would create multiple paths between the same points.

PROOF. The existence of at least one minimizing geodesic follows from the completeness of the manifold as a metric space (Hopf-Rinow theorem for manifolds with boundary). The uniqueness is guaranteed by the absence of conjugate points. If there were two distinct geodesics between p and q , there would have to be a “cut point” or a “conjugate point” where the paths either meet or stop being minimizers. Since simple manifolds have no conjugate points and are non-trapping (avoiding “looping” paths like on a torus), the exponential map $\exp_p$ is a global diffeomorphism. Thus, for any q , there is exactly one $v \in T_p M$ such that $\exp_p(v) = q$. $\square$

PROPERTY 3 (Smoothness of the Distance Function). *The boundary distance function $d_g(x, y)$ is smooth on $(\partial M \times \partial M) \setminus \text{diag}$*

This property is crucial for the analysis of the Geodesic X-ray transform. The smoothness of d_g away from the diagonal allows us to use tools from microlocal analysis and PDE theory to study the linearized problem. The only singularity occurs at the diagonal, where $d_g(x, x) = 0$ and the gradient is not defined.

PROOF. Let $x, y \in \partial M$ with $x \neq y$. From Property 2, there is a unique geodesic γ connecting x to y . Because there are no conjugate points, the derivative of the exponential map is non-singular everywhere. By the Inverse Function Theorem, the map $(x, v) \mapsto (x, \exp_x(v))$ is a local diffeomorphism.

Since $d_g(x, y) = |v|_g$ where $y = \exp_x(v)$, and the metric g is smooth, the distance function inherits the smoothness of the exponential map and the metric. The only singularity occurs at $x = y$, where the distance function is continuous but its gradient is undefined (the standard “cone” singularity of a distance metric). $\square$

PROPERTY 4 (Finiteness of Volume and Diameter). *A simple manifold has finite volume and a finite diameter $D = \sup_{x, y \in M} d_g(x, y)$.*

This property is important because it ensures that the manifold is not “infinitely large” in any sense, which would make the inverse problem ill-posed. The non-trapping condition prevents geodesics from being infinitely long, and the strict convexity of the boundary ensures that the manifold cannot have “tentacles” that stretch out indefinitely.

PROOF. This follows directly from the Non-trapping condition. If the diameter were infinite, there would exist a geodesic ray that never exits the manifold, contradicting the non-trapping requirement that $\tau(x, v) < \infty$ for all (x, v) . Since M is a compact manifold with a bounded diameter and a smooth metric, its volume $\text{Vol}(M, g) = \int_M dV_g$ must be finite. $\square$

3. The Linearized Problem and the X-ray Transform

Now with all the necessary tools in place, we can now start looking at the linearized version of the boundary rigidity problem, which is closely related to the geodesic X-ray transform. The linearized problem is often easier to analyze and can provide insights into the original nonlinear problem. In this section, we will explore the linearization of the boundary distance function, the geodesic X-ray transform, solenoidal injectivity and gauge freedom, and the normal operator and back-projection.

3.1. Linearization of the Boundary Distance Function. The boundary distance function $d_g(x, y)$ is a non-linear functional of the metric g . In the context of medical imaging, the inverse problem—recovering g from d_g —is therefore non-linear and computationally difficult. To simplify the problem, we consider a small perturbation of the background metric and analyze the resulting change in travel time.

Let g be a smooth, simple background metric (representing healthy tissue) and let f be a symmetric $(0, 2)$ -tensor field representing a small anomaly (such as a tumor). We define a one-parameter family of metrics:

$$g_s = g + sf, \quad s \in (-\varepsilon, \varepsilon).$$

For any two fixed points $x, y \in \partial M$, let γ_s be the unique g_s -geodesic connecting them. The distance is given by the length functional:

$$L(g_s) = d_{g_s}(x, y) = \int_0^{T_s} \sqrt{g_s(\dot{\gamma}_s(t), \dot{\gamma}_s(t))} dt.$$

To linearize, we calculate the derivative of the distance with respect to s at $s = 0$. A key result in Riemannian geometry is that since γ_0 (the geodesic for the background metric) is a critical point of the length functional, the variation of the geodesic path itself ($\dot{\gamma}_s$) does not contribute to the first-order change in length. This is known as the *First Variation Formula*.

Proposition 2.29. *The linearization of the boundary distance function in the direction of f is given by:*

$$\left. \frac{d}{ds} d_{g_s}(x, y) \right|_{s=0} = \frac{1}{2} \int_0^T \frac{f(\dot{\gamma}(t), \dot{\gamma}(t))}{|\dot{\gamma}(t)|_g} dt.$$

SKETCH OF PROOF. Using the definition of the length functional and differentiating under the integral sign:

$$\frac{d}{ds} \sqrt{(g_{ij} + s f_{ij}) \dot{x}^i \dot{x}^j} = \frac{1}{2\sqrt{g_s(\dot{x}, \dot{x})}} f_{ij} \dot{x}^i \dot{x}^j.$$

Setting $s = 0$ and assuming γ is unit-speed ($|\dot{\gamma}|_g = 1$), we obtain the integral of the perturbation f along the background geodesic γ . $\square$

This result is profound for medical imaging. It implies that if we know the background sound speed of a patient, the *delay* in the arrival of an ultrasound pulse (δd) is a linear measurement of the internal change in tissue density (f).

$$\delta d \approx \frac{1}{2} \int_{\gamma} f_{ij} \dot{\gamma}^i \dot{\gamma}^j dt.$$

This integral is exactly the definition of the *Geodesic X-ray Transform* of the tensor f . Thus, the linearized boundary rigidity problem reduces to the question of whether this transform is injective—that is, whether the set of all path integrals uniquely determines f .

3.2. The Geodesic X-ray Transform. The Geodesic X-ray Transform is the mathematical operator that formalizes the process of probing a manifold's interior via line integrals. Having established that the linearization of the boundary distance function results in an integral of the metric perturbation, we now define this integral as a standalone operator.

Definition 2.30. *Let (M, g) be a simple Riemannian manifold. Let $\partial_+ SM$ be the set of inward-pointing unit vectors at the boundary. For a smooth function $f \in C^\infty(M)$, the geodesic X-ray transform If is defined as:*

$$If(x, v) = \int_0^{\tau(x, v)} f(\gamma_{x, v}(t)) dt,$$

where $\gamma_{x, v}$ is the geodesic starting at $x \in \partial M$ in direction $v \in S_x M$, and $\tau(x, v)$ is the exit time.

In the context of ultrasound imaging, If represents the total accumulation of a scalar property (such as an attenuation coefficient or a temperature-induced speed shift) along the sound ray. The central question is whether I is injective on the space of smooth functions (or more generally, on symmetric tensor fields). If I is injective, then we can uniquely recover the internal structure of the medium from boundary measurements. However, if I has a non-trivial kernel, then there exist non-zero functions that produce zero integrals along all geodesics, leading to non-uniqueness in the reconstruction.

In the specific case of the boundary rigidity problem, we are interested in perturbations of the metric tensor itself. This requires the definition of the transform acting on symmetric tensor fields of order 2. For a symmetric tensor field $f = f_{ij}dx^i \otimes dx^j$, the transform is defined as:

$$If(x, v) = \int_0^{\tau(x, v)} f_{ij}(\gamma(t)) \dot{\gamma}^i(t) \dot{\gamma}^j(t) dt.$$

To solve the inverse problem—reconstructing f from If —we analyze the properties of I .

- (1) **Linearity:** The operator I is linear, which allows us to utilize the tools of linear functional analysis.
- (2) **The Adjoint (I^*):** The adjoint operator, often called the *back-projection operator*, maps data on the boundary back into the interior of the manifold. For a function φ on the boundary phase space $\partial_+ SM$, the back-projection is:

$$I^*\varphi(x) = \int_{S_x M} \varphi(\gamma_{x, v}) dv.$$

This represents “smearing” the measured boundary data back along all possible geodesics passing through a point x in the tissue.

The central question of this section is the *injectivity* of I . If $If = 0$, does it necessarily imply that $f = 0$? In the scalar case (functions), the answer for simple manifolds is yes. However, for tensor fields, the existence of “potential” fields—tensors that are simply derivatives of coordinate shifts—creates a kernel that we must account for through the concept of *solenoidal injectivity*.

3.3. Solenoidal Injectivity and Gauge Freedom. In the scalar case, the geodesic X-ray transform I is injective on simple manifolds, meaning the “image” is uniquely determined by the data. However, for the tensor fields that arise in the linearization of the boundary rigidity problem, a fundamental ambiguity emerges. This ambiguity, known as *gauge freedom*, arises from the fact that we can smoothly re-parametrize the interior of the manifold without altering the distances measured at the boundary.

In our study of simple manifolds, any vector field v that vanishes on the boundary ($v|_{\partial M} = 0$) can be used to “push forward” the metric. In the linearized setting, this corresponds to a specific type of tensor called a *potential tensor*.

Definition 2.31. A symmetric $(0, 2)$ -tensor field f is a potential tensor if there exists a vector field v vanishing on the boundary ($v|_{\partial M} = 0$) such that:

$$f = dv := \frac{1}{2}(\nabla_i v_j + \nabla_j v_i) = \nabla_{(i} v_{j)},$$

where ∇ is the Levi-Civita connection.

The Fundamental Theorem of Calculus along geodesics implies that the integral of a potential tensor along any geodesic γ depends only on the values of v at the endpoints. Since v vanishes on the boundary, we have:

$$If(\gamma) = \int_0^\tau \frac{D}{dt} v(\gamma(t)), dt = v(\gamma(\tau)) - v(\gamma(0)) = 0.$$

Consequently, potential tensors lie in the *kernel* of the X-ray transform. Physically, this means that a “tumor” whose density variation looks like a coordinate stretch is invisible to our ultrasound sensors.

To resolve this, we invoke a geometric version of the Helmholtz decomposition (often called the *Pestov-Uhlmann decomposition*). Every symmetric tensor field f can be uniquely decomposed as:

$$f = f^s + dv,$$

where f^s is the *solenoidal part* (satisfying $\delta f^s = 0$, where δ is the divergence operator) and dv is the potential part.

Because the potential part is always invisible, the best we can hope for is to recover f^s .

Definition 2.32. *The geodesic X-ray transform I is solenoidal injective if $If = 0$ implies that f is a potential tensor (i.e., its solenoidal part f^s is zero).*

For medical imaging, this results in the conclusion that the boundary rigidity problem is solvable *up to a diffeomorphism*. We can reconstruct the internal structure and the sound speed variations, but the exact “spatial mapping” is only determined relative to the boundary. In practice, because the “skin” of the patient is fixed by the transducer array, this gauge freedom is physically constrained, allowing for high-fidelity reconstructions of internal anomalies despite the underlying mathematical ambiguity.

3.4. The Normal Operator and the Back-Projection. The final step in our mathematical model of medical imaging is the development of a reconstruction algorithm. While the geodesic X-ray transform I describes the “forward problem” (from tissue to data), we require a method to go from data back to tissue. This is achieved through the *back-projection* and the study of the *normal operator*.

The adjoint operator I^* , known as back-projection, is the formal dual to the X-ray transform. While I integrates a function along a single geodesic, I^* “smears” a piece of boundary data across the manifold along all geodesics that could have produced it.

Definition 2.33. *For a function φ defined on the boundary phase space $\partial_+ SM$, the back-projection $I^*\varphi$ at a point $x \in M$ is the average of φ over all directions $v \in S_x M$:*

$$(I^*\varphi)(x) = \int_{S_x M} \varphi(\gamma_{x,v}), d\sigma_x(v),$$

where $d\sigma_x$ is the normalized measure on the unit sphere of the tangent space.

In clinical practice, back-projection alone produces a “blurry” image of the interior. This blurriness occurs because the back-projection process spreads the signal information back into the manifold in a way that overlaps and loses high-frequency details (sharp edges of organs or tumors).

To obtain a sharp reconstruction, we define the *normal operator* $L = I^*I$. This operator maps a function (or tensor) in the interior back to the interior, passing through the “bottleneck” of the boundary data.

Proposition 2.34. *On a simple Riemannian manifold, the normal operator $L = I^*I$ is a Pseudodifferential Operator (ΨDO) of order -1 . Specifically, its kernel has a singularity of type $1/d_g(x, y)^{n-1}$*

Because L is a ΨDO of order -1 , it acts similarly to a smoothing filter (like an integration). To “undo” this smoothing and recover the sharp details of the tissue, we must apply a “sharpening” filter, typically a derivative-like operator of order $+1$.

In the Euclidean case (straight-line rays), this is the foundation of the *Filtered Back-Projection (FBP)* algorithm:

$$f \approx \Lambda I^*(If),$$

where Λ is a filter in the frequency domain. In the curved geometry of a simple manifold, the filter must account for the Riemannian metric g . This ensures that the reconstruction correctly places anomalies in their proper “geometric” positions, accounting for the way ultrasound rays bend through heterogeneous tissue.

The study of the normal operator proves that if the manifold is simple, the “information loss” during a scan is limited and mathematically reversible. This provides the theoretical guarantee that high-resolution ultrasound tomography is possible, even in complex biological environments where the sound speed is non-uniform.

4. Worked Examples: Radial Symmetry and Inclusions

The entirety of this paper thus far has had very few examples. That’s why we dedicate this entire sections to working through some examples of the boundary rigidity problem, and how it applies to medical imaging. In particular, we’ll be looking at the Herglotz-Wiechert formula for radial metrics, which is a powerful tool for understanding the behavior of geodesics in radially symmetric spaces. We’ll also be looking at how to detect localized inclusions within a medium, which is a common problem in medical imaging. Finally, we’ll explore the effect of conjugate points on the boundary rigidity problem, and provide a counterexample to illustrate this phenomenon.

4.1. The Herglotz-Wiechert Formula for Radial Metrics. While the general boundary rigidity problem is non-linear and computationally intensive, the assumption of radial symmetry allows for an elegant analytical solution. This case was historically investigated by Herglotz (1905) and Wiechert (1907) in the context of seismology to determine the Earth’s internal velocity structure. In our medical imaging model, this corresponds to recovering a sound speed $c(r)$ that depends only on the distance from a central axis.

Consider a disk $M = \{(r, \theta) : 0 \leq r \leq R\}$ equipped with a rotationally invariant metric:

$$g = \frac{1}{c(r)^2} (dr^2 + r^2 d\theta^2).$$

To ensure the manifold is simple, the sound speed $c(r)$ must satisfy the *Herglotz condition*:

$$\frac{d}{dr} \left(\frac{r}{c(r)} \right) > 0.$$

This condition ensures that the boundary is strictly convex and that no geodesics are “trapped” in circular orbits. Geometrically, it ensures that as we move outward, the “acoustic radius” increases, preventing rays from bending so sharply that they never exit.

Due to the symmetry, a geodesic γ is uniquely determined by its *impact parameter* p , which represents the closest approach of the ray to the center ($r = r_{min}$). Along a geodesic, the quantity

$$p = \frac{r \sin \varphi}{c(r)},$$

remains constant (where φ is the angle between the ray and the radial vector). The total travel time $T(p)$ between two points on the boundary for a ray with impact parameter p is given by:

$$T(p) = 2 \int_{r_{min}}^R \frac{1}{c(r)} \frac{r/c(r)}{\sqrt{(r/c(r))^2 - p^2}} dr.$$

The Herglotz-Wiechert formula provides the direct inverse to the integral above. It allows us to calculate the radius r at which a specific sound speed occurs based on the measured travel times $T(p)$ at the boundary:

$$\ln \left(\frac{R}{r(c)} \right) = \frac{1}{\pi} \int_{p_c}^{R/c(R)} \frac{\Delta\theta(p)}{\sqrt{p^2 - p_c^2}} dp,$$

where $p_c = r/c(r)$ and $\Delta\theta(p)$ is the angular distance between the source and receiver.

In a clinical setting, this formula implies that if a patient’s limb is approximately cylindrical and the tissue is stratified in layers (e.g., skin $\rightarrow$ fat $\rightarrow$ muscle), we do not need complex iterative algorithms to find the sound speed profile. By sweeping a transducer around the perimeter and measuring the time-of-flight for various angles, we can “peel back” the layers of the tissue mathematically.

- Near-surface data (rays with large p) reconstructs the outer layers (skin/fat).
- Deep-penetrating data (rays with small p) reconstructs the deep tissue.

4.2. Detecting a Localized Inclusion. In this subsection, you move away from global symmetry to demonstrate the most practical application of the theory: detecting a tumor. This example illustrates how the abstract Geodesic X-ray Transform ($\mathcal{I}_g$) acts as a “diagnostic tool” to pinpoint an anomaly within otherwise healthy tissue.

While radial metrics provide a baseline for stratified anatomy, the primary goal of medical imaging is the detection of localized anomalies, such as cysts or tumors, which break symmetry. We model this by considering a background manifold of constant sound speed (healthy tissue) and introducing a compact “inclusion” with a different refractive index.

Consider a circular domain M with a background Euclidean metric g_0 (constant sound speed c_0). We introduce a localized inclusion $f(x)$ representing a tumor. The physical sound speed $\tilde{c}(x)$ is perturbed such that:

$$\frac{1}{\tilde{c}(x)^2} = \frac{1}{c_0^2} + f(x).$$

We assume $f(x)$ is a smooth “bump” function supported entirely within a small interior disk $B_\delta(x_0) \subset \text{int}(M)$. In the linearized regime, the change in the metric tensor is given by $\delta g = f(x)\delta_{ij}$.

When an ultrasound pulse is emitted from a source S on the boundary, its travel time to a receiver R is altered if the geodesic γ_{SR} passes through the inclusion. According to our results from Section 3.1, the time-of-flight perturbation δT is:

$$\delta T(S, R) \approx \frac{1}{2c_0} \int_{\gamma_{SR}} f(\gamma(t)), dt = \frac{1}{2c_0} \mathcal{I}g f(\gamma_{SR}).$$

- Rays missing the inclusion: If $\gamma_{SR} \cap \text{supp}(f) = \emptyset$, then $\delta T = 0$.
- Rays hitting the inclusion: If the inclusion is “slower” than healthy tissue ($f > 0$), the signal is delayed ($\delta T > 0$).

To find the location of the inclusion, we utilize the measurements from all source-receiver pairs. If f is non-zero, it creates a “shadow” or “delay signature” in the boundary data. By using the *Support Theorem* for the X-ray transform, we can conclude that the convex hull of the inclusion is uniquely determined by the set of rays that experience a delay.

Mathematically, the back-projection operator I^* (Section 3.4) “smears” these delays back into the manifold. The intersection of all delayed rays identifies the region $B_\delta(x_0)$ where the tumor is located.

A critical realization in this example is that the inclusion does more than just delay the signal; it *refracts* the rays.

- If the inclusion is a “slow” zone (higher refractive index), the geodesics will bend *toward* the center of the inclusion, behaving like a converging lens.
- If the inclusion is a “fast” zone, the rays bend *away*, behaving like a diverging lens.

In the simple manifold framework, we assume these perturbations are small enough that the geodesics do not cross before exiting the manifold. This ensures that the relationship between the measured delay and the inclusion’s position remains one-to-one, allowing for the clear, artifact-free reconstruction required for surgical planning.

4.3. The Effect of Conjugate Points: A Counterexample. Throughout this work, we have assumed that the manifold (M, g) is simple, ensuring that the exponential map is a global diffeomorphism. This final example explores what happens when this condition is violated. In medical imaging, the emergence of conjugate points corresponds to a “multipath” or “focusing” effect, where a single boundary measurement can no longer be uniquely attributed to a single internal path.

Consider a disk M containing a very high-density inclusion (a “slow” zone) where the sound speed $c(x)$ drops significantly. As discussed in Section 5.2, a slow zone acts as a converging lens. If the refractive index $n(x) = 1/c(x)$ is sufficiently large, the geodesics (ultrasound rays) will be pulled toward each other so sharply that they intersect within the interior of the manifold.

Definition 2.35. *Two points p and q along a geodesic γ are conjugate if there exists a non-zero Jacobi field J along γ such that $J(p) = 0$ and $J(q) = 0$.*

In the context of ray tracing, this means that an infinitesimal fan of rays emitted from p converges again at q .

Once conjugate points exist, the boundary distance function $d_g(x, y)$ loses its smoothness. At the boundary, the arrival time data may become multi-valued because there may be multiple geodesics (one “direct” and one “refracted”) connecting the same source and receiver.

Mathematically, the exponential map $\exp_x$ ceases to be a diffeomorphism. This renders the linearization used in Section 3 invalid, as the “First Variation of Length” formula assumes we are perturbing a *unique* minimizing path.

If an ultrasound scanner is used on a manifold with conjugate points, the resulting image will suffer from *ghosting artifacts*.

- **Loss of Injectivity:** The X-ray transform I_g may no longer be injective. A function f (a tumor) could exist in the “shadow” of the conjugate point region such that its integral along all boundary-to-boundary geodesics is zero, rendering it invisible.
- **Geometric Misplacement:** Because the back-projection algorithm assumes a simple, unique path, it will attempt to “smear” data along the wrong geodesic, placing internal structures in the wrong physical location.

This counterexample reinforces the three pillars of a simple manifold. Without strict convexity, rays “skid” off the surface; without the non-trapping condition, rays “hide” in loops; and without the absence of conjugate points, rays “tangle” and confuse the reconstruction. Thus, the simplicity of M is the fundamental mathematical guarantee that the medical image we see on the screen is a true representation of the patient’s anatomy.

5. Synthesis: Clinical Applications in Medical Imaging

The theoretical framework of boundary rigidity and the geodesic X-ray transform provides more than an elegant exercise in differential geometry; it constitutes the mathematical foundation for several transformative modalities in medical diagnostics. In this section, we transition from the study of abstract manifolds to the physical reality of the human body. By interpreting the sound speed of biological tissue and the diffusion of water molecules as components of a Riemannian metric, we demonstrate how the properties of “simplicity”—specifically the absence of conjugate points and the enforcement of strict boundary convexity—directly dictate the resolution and reliability of a clinical scan. We explore how these geometric principles are currently utilized in ultrasound and magnetic resonance imaging, while acknowledging the inherent challenges posed by the non-simple geometries of the human skeleton and pulmonary system.

5.1. Ultrasound Computed Tomography. Ultrasound Computed Tomography (USCT) is the clinical realization of the boundary rigidity problem. Unlike conventional B-mode ultrasound, which relies on the reflection (echoes) of sound waves at tissue interfaces, USCT is a transmission-based modality. It measures the time it takes for an acoustic pulse to traverse the body, effectively sampling the manifold’s internal metric g from its boundary data.

In a USCT system, the patient—typically a breast or a limb—is submerged in a coupling medium (usually water) and surrounded by a ring of transducers. Each transducer acts as both a source and a receiver. When a pulse is emitted at source S and detected at receiver R , the scanner records the *Time-of-Flight* (TOF).

In the language of Riemannian geometry, this TOF is the distance $d_g(S, R)$ under the acoustic metric:

$$g_{ij}(x) = \frac{1}{c(x)^2} \delta_{ij},$$

where $c(x)$ is the spatially varying sound speed. The “rays” of ultrasound are the geodesics of this metric. Because the sound speed in biological tissue is relatively

close to that of water, the manifold is typically *simple*, ensuring that the rays do not trap or cross, and that the boundary is strictly convex.

The goal of USCT is to recover the function $c(x)$ from the set of all possible TOF measurements $\{d_g(S, R) : S, R \in \partial M\}$. As established in Section 3, this is solved by linearizing the problem and applying the Geodesic X-ray Transform.

- **Forward Problem:** The scanner collects the integral of the refractive index along the curved geodesics.
- **Inverse Problem:** Using the Normal Operator and Filtered Back-Projection (as discussed in Section 3.4), the computer “smears” the measured delays back into the manifold to identify regions of high or low sound speed.

USCT offers several advantages that are directly rooted in its geometric formulation:

- (1) **Quantitative Imaging:** Unlike standard ultrasound, which provides a qualitative picture of “brightness,” USCT provides a quantitative map of sound speed (m/s). This is vital for diagnosis, as malignant tumors often have a significantly higher sound speed than healthy fatty tissue.
- (2) **Operator Independence:** Standard ultrasound depends on the angle and pressure of the probe held by a technician. Because USCT uses a fixed boundary geometry (∂M is the transducer ring), the resulting image is a mathematically rigorous reconstruction of the metric that does not change based on who is holding the probe.
- (3) **Resolution of Isoechoic Lesions:** Some tumors have the same reflection properties as surrounding tissue (isoechoic) and are invisible to normal scans. However, they almost always have a different “optical” density, which the boundary rigidity math can detect as a time-delay.

To satisfy the “Simple Manifold” requirement, USCT systems often use a “water bath” to provide a smooth transition between the transducers and the skin. This ensures that the boundary remains strictly convex ($\Pi > 0$) and that the rays enter the body at predictable angles, satisfying the *Non-Trapping Condition* required for a unique reconstruction.

5.2. Diffusion Tensor Imaging (DTI) and Neural Tractography. While Ultrasound CT primarily investigates a scalar sound speed, the human brain presents a more complex geometric challenge: anisotropy. In the white matter of the brain, water molecules do not diffuse equally in all directions; instead, they move preferentially along the axes of myelinated nerve fibers. This physical phenomenon is modeled not by a single function, but by a symmetric (0,2)-tensor field—the diffusion tensor.

In DTI, the “distance” between two points is not measured by the travel time of sound, but by the *mean squared displacement* of water molecules. We define a Riemannian metric g where the components g_{ij} are inversely proportional to the diffusion coefficients. In this geometry:

- **High Diffusion (along axons):** Corresponds to a “short” distance in the metric g .
- **Low Diffusion (across axons):** Corresponds to a “long” distance in the metric g .

Consequently, the “shortest paths” in the brain—the geodesics of the diffusion metric—correspond exactly to the physical pathways of the neural axons.

The process of “Neural Tractography” is the numerical integration of the geodesic equation we established in Chapter 1. By measuring the diffusion tensor at every voxel (3D pixel) in an MRI scan, we can solve for the geodesics starting from a specific region of interest (e.g., the motor cortex).

$$\ddot{x}^k + \Gamma_{ij}^k \dot{x}^i \dot{x}^j = 0.$$

The resulting curves provide a 3D map of the brain’s “wiring diagram.” This is essential for neurosurgery: if a surgeon knows the exact geodesic path of the corticospinal tract, they can plan a tumor resection that avoids severing critical neural connections.

The mathematical “Inverse Problem” in DTI is a variation of the Boundary Rigidity Problem for a tensor field. We ask: can we reconstruct the full internal connectivity of the brain (the tensor field g_{ij}) by observing the diffusion properties?

- **Anisotropic Rigidity:** Unlike the scalar case in USCT, the reconstruction of a diffusion tensor is subject to the Solenoidal Injectivity limits discussed in Section 3.3.
- **Gauge Freedom:** The “diffeomorphism” ambiguity means that while we can map the connections between regions (the “topology” of the wiring), the exact “thickness” or “local density” of the fibers is determined only up to a smooth coordinate transformation.

DTI has revolutionized our understanding of neurological diseases. In conditions like Multiple Sclerosis or Alzheimer’s, the “simple” nature of the brain’s manifold is disrupted. The breakdown of myelin causes the diffusion to become more isotropic (less like a directed tensor and more like a scalar), which manifests as a change in the curvature and connectivity of the reconstructed geodesics. By applying the rigorous tensor calculus of Riemannian geometry, clinicians can quantify these structural changes long before they are visible on a standard MRI.

5.3. Limitations and Future Frontiers: The “Non-Simple” Reality.

While the theory of simple manifolds provides a rigorous foundation for boundary rigidity and the X-ray transform, the clinical application of these results often meets the limits of “simplicity.” In this concluding subsection, we address the mathematical and physical challenges that arise when the human body violates our established geometric assumptions.

The “No Conjugate Points” and “Non-Trapping” conditions (Section 2) are most frequently violated by the presence of bone or air.

- **Bone:** Cortical bone has a sound speed nearly double that of soft tissue ($c \approx 3000$ m/s). This sharp jump in the metric g acts as a massive “fast” lens, causing geodesics to diverge sharply and creating “shadow zones” where the X-ray transform I lacks data.
- **Air/Lungs:** The sound speed in air is much lower than in tissue ($c \approx 340$ m/s). This creates a “trapping” effect where ultrasound rays can be reflected or refracted into circular orbits (as seen in Section 5.3), violating the finite-time exit requirement of simple manifolds.

In these cases, the distance function d_g becomes non-smooth, and the reconstruction requires “Microlocal Analysis” to handle the resulting singularities.

In Section 3.1, we linearized the problem using the first variation of length. However, if the tumor is large or the tissue is highly heterogeneous, the “second-order” effects become significant.

- **Iterative Reconstruction:** Modern clinical systems often use an iterative approach: they guess a metric $\hat{g}$, compute the “synthetic” travel times, and then minimize the distance to the actual boundary data.
- **Gauge Freedom in Motion:** In a real hospital, patients breathe and move. This introduces a “Time-Dependent Diffeomorphism” into the problem. Future research in “Dynamic Boundary Rigidity” aims to reconstruct the metric even as the manifold is undergoing a continuous coordinate transformation.

The most exciting frontier in medical imaging is moving beyond “Ray Tracing” (Geodesics) to “Wave Physics.”

- **The Approximation:** The X-ray transform is a high-frequency approximation (where the wavelength $\lambda \rightarrow 0$).
- **The Reality:** Ultrasound has a finite wavelength. FWI uses the full **Wave Equation** rather than just the geodesic equation. This allows for the reconstruction of features smaller than the ray-width, effectively “beating” the resolution limits of the standard boundary rigidity problem.

The study of boundary rigidity on Riemannian manifolds offers more than just a theoretical framework; it provides a “geometric blueprint” for how we see inside the human body. By understanding the conditions under which a manifold is “simple,” we define the limits of what can be known through non-invasive sensing. As medical technology moves toward more complex, non-linear, and anisotropic environments, the language of differential geometry will remain the essential tool for ensuring that our digital reconstructions match the physical reality of the patient.

Bibliography

- [1] Cragfelt. Drawing manifolds in tikz. TeX Stackexchange, 2017.
<https://tex.stackexchange.com/a/388493/254196> (version: 2017-27-08).
- [2] M. Francois. *Introduction to the mathematics of X-ray imaging: X-ray transforms*. Aug 2022.
- [3] P. P. Gabriel, S. Mikko, and U. Gunther. *Geometric Inverse Problems*. Cambridge University Press, Dec 2022.
- [4] B. Guillaume. *Introduction to Inverse Problems*. Jul 2019.
- [5] J. M. Lee. *Introduction to Smooth Manifolds*. Springer, Jan 2012.