

# Isabelle/FOL — First-Order Logic

Larry Paulson and Markus Wenzel

April 15, 2020

## Contents

<b>1</b>	<b>Intuitionistic first-order logic</b>	<b>2</b>
1.1	Syntax and axiomatic basis	2
1.1.1	Equality	2
1.1.2	Propositional logic	3
1.1.3	Quantifiers	3
1.1.4	Definitions	3
1.1.5	Old-style ASCII syntax	4
1.2	Lemmas and proof tools	4
1.2.1	Sequent-style elimination rules for $\wedge \longrightarrow$ and $\forall$	4
1.2.2	Negation rules, which translate between $\neg P$ and $P \longrightarrow \textit{False}$	5
1.2.3	Modus Ponens Tactics	6
1.3	If-and-only-if	6
1.3.1	Destruct rules for $\longleftrightarrow$ similar to Modus Ponens	6
1.4	Unique existence	7
1.4.1	$\longleftrightarrow$ congruence rules for simplification	8
1.5	Equality rules	9
1.5.1	Polymorphic congruence rules	10
1.5.2	Congruence rules for predicate letters	11
1.6	Simplifications of assumed implications	11
1.7	Intuitionistic Reasoning	13
1.8	Atomizing meta-level rules	15
1.9	Atomizing elimination rules	16
1.10	Calculational rules	16
1.11	“Let” declarations	16
1.12	Intuitionistic simplification rules	17
1.12.1	Conversion into rewrite rules	18
1.12.2	More rewrite rules	18

<b>2</b>	<b>Classical first-order logic</b>	<b>19</b>
2.1	The classical axiom . . . . .	19
2.2	Lemmas and proof tools . . . . .	19
2.2.1	Classical introduction rules for $\forall$ and $\exists$ . . . . .	20
2.3	Special elimination rules . . . . .	21
2.3.1	Tactics for implication and contradiction . . . . .	21
<b>3</b>	<b>Classical Reasoner</b>	<b>22</b>
3.1	Classical simplification rules . . . . .	24
3.1.1	Miniscoping: pushing quantifiers in . . . . .	24
3.1.2	Named rewrite rules proved for IFOL . . . . .	25
3.2	Other simple lemmas . . . . .	26
3.2.1	Monotonicity of implications . . . . .	26
3.3	Proof by cases and induction . . . . .	27

## 1 Intuitionistic first-order logic

```
theory IFOL
imports Pure
begin
```

```
ML-file <~~/src/Tools/misc-legacy.ML>
ML-file <~~/src/Provers/splitter.ML>
ML-file <~~/src/Provers/hypsubst.ML>
ML-file <~~/src/Tools/IsaPlanner/zipper.ML>
ML-file <~~/src/Tools/IsaPlanner/isand.ML>
ML-file <~~/src/Tools/IsaPlanner/rw-inst.ML>
ML-file <~~/src/Provers/quantifier1.ML>
ML-file <~~/src/Tools/intuitionistic.ML>
ML-file <~~/src/Tools/project-rule.ML>
ML-file <~~/src/Tools/atomize-elim.ML>
```

### 1.1 Syntax and axiomatic basis

```
setup Pure-Thy.old-appl-syntax-setup
setup <Proofterm.set-preproc (Proof-Rewrite-Rules.standard-preproc [])>
```

```
class term
default-sort <term>
```

```
typedecl o
```

```
judgment
  Trueprop :: <o  $\Rightarrow$  prop> (<(-)> 5)
```

#### 1.1.1 Equality

```
axiomatization
```

$eq :: \langle [a, a] \Rightarrow o \rangle$  (**infixl**  $\langle \Rightarrow \rangle$  50)  
**where**  
 $refl :: \langle a = a \rangle$  **and**  
 $subst :: \langle a = b \Rightarrow P(a) \Rightarrow P(b) \rangle$

### 1.1.2 Propositional logic

#### axiomatization

$False :: \langle o \rangle$  **and**  
 $conj :: \langle [o, o] \Rightarrow o \rangle$  (**infixr**  $\langle \wedge \rangle$  35) **and**  
 $disj :: \langle [o, o] \Rightarrow o \rangle$  (**infixr**  $\langle \vee \rangle$  30) **and**  
 $imp :: \langle [o, o] \Rightarrow o \rangle$  (**infixr**  $\langle \longrightarrow \rangle$  25)  
**where**  
 $conjI :: \langle \llbracket P; Q \rrbracket \Rightarrow P \wedge Q \rangle$  **and**  
 $conjunct1 :: \langle P \wedge Q \Rightarrow P \rangle$  **and**  
 $conjunct2 :: \langle P \wedge Q \Rightarrow Q \rangle$  **and**  
  
 $disjI1 :: \langle P \Rightarrow P \vee Q \rangle$  **and**  
 $disjI2 :: \langle Q \Rightarrow P \vee Q \rangle$  **and**  
 $disjE :: \langle \llbracket P \vee Q; P \Rightarrow R; Q \Rightarrow R \rrbracket \Rightarrow R \rangle$  **and**  
  
 $impI :: \langle (P \Rightarrow Q) \Rightarrow P \longrightarrow Q \rangle$  **and**  
 $mp :: \langle \llbracket P \longrightarrow Q; P \rrbracket \Rightarrow Q \rangle$  **and**  
  
 $FalseE :: \langle False \Rightarrow P \rangle$

### 1.1.3 Quantifiers

#### axiomatization

$All :: \langle (a \Rightarrow o) \Rightarrow o \rangle$  (**binder**  $\langle \forall \rangle$  10) **and**  
 $Ex :: \langle (a \Rightarrow o) \Rightarrow o \rangle$  (**binder**  $\langle \exists \rangle$  10)  
**where**  
 $allI :: \langle (\bigwedge x. P(x)) \Rightarrow (\forall x. P(x)) \rangle$  **and**  
 $spec :: \langle (\forall x. P(x)) \Rightarrow P(x) \rangle$  **and**  
 $exI :: \langle P(x) \Rightarrow (\exists x. P(x)) \rangle$  **and**  
 $exE :: \langle \llbracket \exists x. P(x); \bigwedge x. P(x) \Rightarrow R \rrbracket \Rightarrow R \rangle$

### 1.1.4 Definitions

**definition**  $\langle True \equiv False \longrightarrow False \rangle$

**definition**  $Not \langle (\neg \neg) [40] 40 \rangle$

**where**  $not-def :: \langle \neg P \equiv P \longrightarrow False \rangle$

**definition**  $iff$  (**infixr**  $\langle \longleftrightarrow \rangle$  25)

**where**  $\langle P \longleftrightarrow Q \equiv (P \longrightarrow Q) \wedge (Q \longrightarrow P) \rangle$

**definition**  $Ex1 :: \langle (a \Rightarrow o) \Rightarrow o \rangle$  (**binder**  $\langle \exists ! \rangle$  10)

**where**  $ex1-def :: \langle \exists ! x. P(x) \equiv \exists x. P(x) \wedge (\forall y. P(y) \longrightarrow y = x) \rangle$

**axiomatization where** — Reflection, admissible

*eq-reflection*:  $\langle (x = y) \implies (x \equiv y) \rangle$  **and**

*iff-reflection*:  $\langle (P \longleftrightarrow Q) \implies (P \equiv Q) \rangle$

**abbreviation** *not-equal* ::  $\langle [ 'a, 'a ] \Rightarrow o \rangle$  (**infixl**  $\langle \neq \rangle$  50)

**where**  $\langle x \neq y \equiv \neg (x = y) \rangle$

### 1.1.5 Old-style ASCII syntax

**notation** (*ASCII*)

*not-equal* (**infixl**  $\langle \sim = \rangle$  50) **and**

*Not* ( $\langle \sim \rightarrow \rangle$  [40] 40) **and**

*conj* (**infixr**  $\langle \& \rangle$  35) **and**

*disj* (**infixr**  $\langle | \rangle$  30) **and**

*All* (**binder**  $\langle ALL \rangle$  10) **and**

*Ex* (**binder**  $\langle EX \rangle$  10) **and**

*Ex1* (**binder**  $\langle EX! \rangle$  10) **and**

*imp* (**infixr**  $\langle \longrightarrow \rangle$  25) **and**

*iff* (**infixr**  $\langle \longleftrightarrow \rangle$  25)

## 1.2 Lemmas and proof tools

**lemmas** *strip* = *impI allI*

**lemma** *TrueI*:  $\langle True \rangle$

**unfolding** *True-def* **by** (*rule impI*)

### 1.2.1 Sequent-style elimination rules for $\wedge \longrightarrow$ and $\forall$

**lemma** *conjE*:

**assumes** *major*:  $\langle P \wedge Q \rangle$

**and** *r*:  $\langle \llbracket P; Q \rrbracket \implies R \rangle$

**shows**  $\langle R \rangle$

**apply** (*rule r*)

**apply** (*rule major* [*THEN conjunct1*])

**apply** (*rule major* [*THEN conjunct2*])

**done**

**lemma** *impE*:

**assumes** *major*:  $\langle P \longrightarrow Q \rangle$

**and**  $\langle P \rangle$

**and** *r*:  $\langle Q \implies R \rangle$

**shows**  $\langle R \rangle$

**apply** (*rule r*)

**apply** (*rule major* [*THEN mp*])

**apply** (*rule*  $\langle P \rangle$ )

**done**

**lemma** *allE*:

**assumes** *major*:  $\langle \forall x. P(x) \rangle$

```

    and r:  $\langle P(x) \implies R \rangle$ 
  shows  $\langle R \rangle$ 
  apply (rule r)
  apply (rule major [THEN spec])
  done

```

Duplicates the quantifier; for use with `eresolve_tac`.

```

lemma all-dupE:
  assumes major:  $\langle \forall x. P(x) \rangle$ 
    and r:  $\langle \llbracket P(x); \forall x. P(x) \rrbracket \implies R \rangle$ 
  shows  $\langle R \rangle$ 
  apply (rule r)
  apply (rule major [THEN spec])
  apply (rule major)
  done

```

### 1.2.2 Negation rules, which translate between $\neg P$ and $P \longrightarrow False$

```

lemma notI:  $\langle (P \implies False) \implies \neg P \rangle$ 
  unfolding not-def by (erule impI)

```

```

lemma notE:  $\langle \llbracket \neg P; P \rrbracket \implies R \rangle$ 
  unfolding not-def by (erule mp [THEN FalseE])

```

```

lemma rev-notE:  $\langle \llbracket P; \neg P \rrbracket \implies R \rangle$ 
  by (erule notE)

```

This is useful with the special implication rules for each kind of  $P$ .

```

lemma not-to-imp:
  assumes  $\langle \neg P \rangle$ 
    and r:  $\langle P \longrightarrow False \implies Q \rangle$ 
  shows  $\langle Q \rangle$ 
  apply (rule r)
  apply (rule impI)
  apply (erule notE [OF  $\langle \neg P \rangle$ ])
  done

```

For substitution into an assumption  $P$ , reduce  $Q$  to  $P \longrightarrow Q$ , substitute into this implication, then apply `impI` to move  $P$  back into the assumptions.

```

lemma rev-mp:  $\langle \llbracket P; P \longrightarrow Q \rrbracket \implies Q \rangle$ 
  by (erule mp)

```

Contrapositive of an inference rule.

```

lemma contrapos:
  assumes major:  $\langle \neg Q \rangle$ 
    and minor:  $\langle P \implies Q \rangle$ 
  shows  $\langle \neg P \rangle$ 
  apply (rule major [THEN notE, THEN notI])

```

```

apply (erule minor)
done

```

### 1.2.3 Modus Ponens Tactics

Finds  $P \longrightarrow Q$  and  $P$  in the assumptions, replaces implication by  $Q$ .

```

ML <
  fun mp-tac ctxt i =
    eresolve-tac ctxt @{\thms notE impE} i THEN assume-tac ctxt i;
  fun eq-mp-tac ctxt i =
    eresolve-tac ctxt @{\thms notE impE} i THEN eq-assume-tac i;
  >

```

### 1.3 If-and-only-if

```

lemma iffI:  $\langle \llbracket P \Longrightarrow Q; Q \Longrightarrow P \rrbracket \Longrightarrow P \longleftrightarrow Q \rangle$ 
  apply (unfold iff-def)
  apply (rule conjI)
  apply (erule impI)
  apply (erule impI)
done

```

```

lemma iffE:
  assumes major:  $\langle P \longleftrightarrow Q \rangle$ 
  and r:  $\langle P \longrightarrow Q \Longrightarrow Q \longrightarrow P \Longrightarrow R \rangle$ 
  shows  $\langle R \rangle$ 
  apply (insert major, unfold iff-def)
  apply (erule conjE)
  apply (erule r)
  apply assumption
done

```

#### 1.3.1 Destruct rules for $\longleftrightarrow$ similar to Modus Ponens

```

lemma iffD1:  $\langle \llbracket P \longleftrightarrow Q; P \rrbracket \Longrightarrow Q \rangle$ 
  apply (unfold iff-def)
  apply (erule conjunct1 [THEN mp])
  apply assumption
done

```

```

lemma iffD2:  $\langle \llbracket P \longleftrightarrow Q; Q \rrbracket \Longrightarrow P \rangle$ 
  apply (unfold iff-def)
  apply (erule conjunct2 [THEN mp])
  apply assumption
done

```

```

lemma rev-iffD1:  $\langle \llbracket P; P \longleftrightarrow Q \rrbracket \Longrightarrow Q \rangle$ 
  apply (erule iffD1)
  apply assumption

```

```

done

lemma rev-iffD2:  $\langle \llbracket Q; P \longleftrightarrow Q \rrbracket \Longrightarrow P \rangle$ 
  apply (erule iffD2)
  apply assumption
done

lemma iff-refl:  $\langle P \longleftrightarrow P \rangle$ 
  by (rule iffI)

lemma iff-sym:  $\langle Q \longleftrightarrow P \Longrightarrow P \longleftrightarrow Q \rangle$ 
  apply (erule iffE)
  apply (rule iffI)
  apply (assumption | erule mp)+
done

lemma iff-trans:  $\langle \llbracket P \longleftrightarrow Q; Q \longleftrightarrow R \rrbracket \Longrightarrow P \longleftrightarrow R \rangle$ 
  apply (rule iffI)
  apply (assumption | erule iffE | erule (1) notE impE)+
done

```

## 1.4 Unique existence

NOTE THAT the following 2 quantifications:

- $\exists!x$  such that  $[\exists!y \text{ such that } P(x,y)]$  (sequential)
- $\exists!x,y$  such that  $P(x,y)$  (simultaneous)

do NOT mean the same thing. The parser treats  $\exists!x y.P(x,y)$  as sequential.

```

lemma ex1I:  $\langle P(a) \Longrightarrow (\bigwedge x. P(x) \Longrightarrow x = a) \Longrightarrow \exists!x. P(x) \rangle$ 
  apply (unfold ex1-def)
  apply (assumption | rule exI conjI allI impI)+
done

```

Sometimes easier to use: the premises have no shared variables. Safe!

```

lemma ex-ex1I:  $\langle \exists x. P(x) \Longrightarrow (\bigwedge x y. \llbracket P(x); P(y) \rrbracket \Longrightarrow x = y) \Longrightarrow \exists!x. P(x) \rangle$ 
  apply (erule exE)
  apply (rule ex1I)
  apply assumption
  apply assumption
done

```

```

lemma ex1E:  $\langle \exists! x. P(x) \Longrightarrow (\bigwedge x. \llbracket P(x); \forall y. P(y) \longrightarrow y = x \rrbracket \Longrightarrow R) \Longrightarrow R \rangle$ 
  apply (unfold ex1-def)
  apply (assumption | erule exE conjE)+
done

```

### 1.4.1 $\longleftrightarrow$ congruence rules for simplification

Use *iffE* on a premise. For *conj-cong*, *imp-cong*, *all-cong*, *ex-cong*.

**ML**  $\langle$

```
  fun iff-tac ctxt prems i =
    resolve-tac ctxt (prems RL @ {thms iffE}) i THEN
    REPEAT1 (eresolve-tac ctxt @ {thms asm-rl mp} i);
```

$\rangle$

**method-setup** *iff* =

```
  (Attrib.thms >>
   (fn prems => fn ctxt => SIMPLE-METHOD' (iff-tac ctxt prems)))
```

**lemma** *conj-cong*:

```
  assumes  $\langle P \longleftrightarrow P' \rangle$ 
    and  $\langle P' \Longrightarrow Q \longleftrightarrow Q' \rangle$ 
  shows  $\langle (P \wedge Q) \longleftrightarrow (P' \wedge Q') \rangle$ 
  apply (insert assms)
  apply (assumption | rule iffI conjI | erule iffE conjE mp | iff assms)+
  done
```

Reversed congruence rule! Used in ZF/Order.

**lemma** *conj-cong2*:

```
  assumes  $\langle P \longleftrightarrow P' \rangle$ 
    and  $\langle P' \Longrightarrow Q \longleftrightarrow Q' \rangle$ 
  shows  $\langle (Q \wedge P) \longleftrightarrow (Q' \wedge P') \rangle$ 
  apply (insert assms)
  apply (assumption | rule iffI conjI | erule iffE conjE mp | iff assms)+
  done
```

**lemma** *disj-cong*:

```
  assumes  $\langle P \longleftrightarrow P' \rangle$  and  $\langle Q \longleftrightarrow Q' \rangle$ 
  shows  $\langle (P \vee Q) \longleftrightarrow (P' \vee Q') \rangle$ 
  apply (insert assms)
  apply (erule iffE disjE disjI1 disjI2 |
    assumption | rule iffI | erule (1) notE impE)+
  done
```

**lemma** *imp-cong*:

```
  assumes  $\langle P \longleftrightarrow P' \rangle$ 
    and  $\langle P' \Longrightarrow Q \longleftrightarrow Q' \rangle$ 
  shows  $\langle (P \longrightarrow Q) \longleftrightarrow (P' \longrightarrow Q') \rangle$ 
  apply (insert assms)
  apply (assumption | rule iffI impI | erule iffE | erule (1) notE impE | iff assms)+
  done
```

**lemma** *iff-cong*:  $\langle \llbracket P \longleftrightarrow P'; Q \longleftrightarrow Q' \rrbracket \Longrightarrow (P \longleftrightarrow Q) \longleftrightarrow (P' \longleftrightarrow Q') \rangle$

```
  apply (erule iffE | assumption | rule iffI | erule (1) notE impE)+
  done
```



```

lemma not-cong:  $\langle P \longleftrightarrow P' \implies \neg P \longleftrightarrow \neg P' \rangle$ 
  apply (assumption | rule iffI notI | erule (1) notE impE | erule iffE notE)+
  done

lemma all-cong:
  assumes  $\langle \bigwedge x. P(x) \longleftrightarrow Q(x) \rangle$ 
  shows  $\langle (\forall x. P(x)) \longleftrightarrow (\forall x. Q(x)) \rangle$ 
  apply (assumption | rule iffI allI | erule (1) notE impE | erule allE | iff assms)+
  done

lemma ex-cong:
  assumes  $\langle \bigwedge x. P(x) \longleftrightarrow Q(x) \rangle$ 
  shows  $\langle (\exists x. P(x)) \longleftrightarrow (\exists x. Q(x)) \rangle$ 
  apply (erule exE | assumption | rule iffI exI | erule (1) notE impE | iff assms)+
  done

lemma ex1-cong:
  assumes  $\langle \bigwedge x. P(x) \longleftrightarrow Q(x) \rangle$ 
  shows  $\langle (\exists! x. P(x)) \longleftrightarrow (\exists! x. Q(x)) \rangle$ 
  apply (erule ex1E spec [THEN mp] | assumption | rule iffI ex1I | erule (1) notE
impE | iff assms)+
  done

```

## 1.5 Equality rules

```

lemma sym:  $\langle a = b \implies b = a \rangle$ 
  apply (erule subst)
  apply (rule refl)
  done

lemma trans:  $\langle [a = b; b = c] \implies a = c \rangle$ 
  apply (erule subst, assumption)
  done

lemma not-sym:  $\langle b \neq a \implies a \neq b \rangle$ 
  apply (erule contrapos)
  apply (erule sym)
  done

```

Two theorems for rewriting only one instance of a definition: the first for definitions of formulae and the second for terms.

```

lemma def-imp-iff:  $\langle (A \equiv B) \implies A \longleftrightarrow B \rangle$ 
  apply unfold
  apply (rule iff-refl)
  done

lemma meta-eq-to-obj-eq:  $\langle (A \equiv B) \implies A = B \rangle$ 
  apply unfold

```

```

apply (rule refl)
done

```

```

lemma meta-eq-to-iff:  $\langle x \equiv y \implies x \longleftrightarrow y \rangle$ 
by unfold (rule iff-refl)

```

Substitution.

```

lemma ssubst:  $\langle \llbracket b = a; P(a) \rrbracket \implies P(b) \rangle$ 
apply (drule sym)
apply (erule (1) subst)
done

```

A special case of *ex1E* that would otherwise need quantifier expansion.

```

lemma ex1-equalsE:  $\langle \llbracket \exists !x. P(x); P(a); P(b) \rrbracket \implies a = b \rangle$ 
apply (erule ex1E)
apply (rule trans)
apply (rule-tac [2] sym)
apply (assumption | erule spec [THEN mp])+
done

```

### 1.5.1 Polymorphic congruence rules

```

lemma subst-context:  $\langle a = b \implies t(a) = t(b) \rangle$ 
apply (erule ssubst)
apply (rule refl)
done

```

```

lemma subst-context2:  $\langle \llbracket a = b; c = d \rrbracket \implies t(a,c) = t(b,d) \rangle$ 
apply (erule ssubst)+
apply (rule refl)
done

```

```

lemma subst-context3:  $\langle \llbracket a = b; c = d; e = f \rrbracket \implies t(a,c,e) = t(b,d,f) \rangle$ 
apply (erule ssubst)+
apply (rule refl)
done

```

Useful with **eresolve\_tac** for proving equalities from known equalities.

$a = b \text{ --- } c = d$

```

lemma box-equals:  $\langle \llbracket a = b; a = c; b = d \rrbracket \implies c = d \rangle$ 
apply (rule trans)
apply (rule trans)
apply (rule sym)
apply assumption+
done

```

Dual of *box-equals*: for proving equalities backwards.

```

lemma simp-equals:  $\langle \llbracket a = c; b = d; c = d \rrbracket \implies a = b \rangle$ 

```

```

apply (rule trans)
apply (rule trans)
apply assumption+
apply (erule sym)
done

```

### 1.5.2 Congruence rules for predicate letters

```

lemma pred1-cong:  $\langle a = a' \implies P(a) \longleftrightarrow P(a') \rangle$ 
apply (rule iffI)
apply (erule (1) subst)
apply (erule (1) ssubst)
done

```

```

lemma pred2-cong:  $\langle \llbracket a = a'; b = b' \rrbracket \implies P(a,b) \longleftrightarrow P(a',b') \rangle$ 
apply (rule iffI)
apply (erule subst)+
apply assumption
apply (erule ssubst)+
apply assumption
done

```

```

lemma pred3-cong:  $\langle \llbracket a = a'; b = b'; c = c' \rrbracket \implies P(a,b,c) \longleftrightarrow P(a',b',c') \rangle$ 
apply (rule iffI)
apply (erule subst)+
apply assumption
apply (erule ssubst)+
apply assumption
done

```

Special case for the equality predicate!

```

lemma eq-cong:  $\langle \llbracket a = a'; b = b' \rrbracket \implies a = b \longleftrightarrow a' = b' \rangle$ 
apply (erule (1) pred2-cong)
done

```

## 1.6 Simplifications of assumed implications

Roy Dyckhoff has proved that *conj-impE*, *disj-impE*, and *imp-impE* used with `mp_tac` (restricted to atomic formulae) is COMPLETE for intuitionistic propositional logic.

See R. Dyckhoff, Contraction-free sequent calculi for intuitionistic logic (preprint, University of St Andrews, 1991).

```

lemma conj-impE:
assumes major:  $\langle P \wedge Q \longrightarrow S \rangle$ 
and r:  $\langle P \longrightarrow (Q \longrightarrow S) \implies R \rangle$ 
shows  $\langle R \rangle$ 
by (assumption | rule conjI impI major [THEN mp] r)+

```

**lemma** *disj-impE*:  
**assumes** *major*:  $\langle (P \vee Q) \longrightarrow S \rangle$   
**and** *r*:  $\langle \llbracket P \longrightarrow S; Q \longrightarrow S \rrbracket \Longrightarrow R \rangle$   
**shows**  $\langle R \rangle$   
**by** (*assumption* | *rule disjI1 disjI2 impI major [THEN mp] r*)+

Simplifies the implication. Classical version is stronger. Still UNSAFE since Q must be provable – backtracking needed.

**lemma** *imp-impE*:  
**assumes** *major*:  $\langle (P \longrightarrow Q) \longrightarrow S \rangle$   
**and** *r1*:  $\langle \llbracket P; Q \longrightarrow S \rrbracket \Longrightarrow Q \rangle$   
**and** *r2*:  $\langle S \Longrightarrow R \rangle$   
**shows**  $\langle R \rangle$   
**by** (*assumption* | *rule impI major [THEN mp] r1 r2*)+

Simplifies the implication. Classical version is stronger. Still UNSAFE since P must be provable – backtracking needed.

**lemma** *not-impE*:  $\langle \neg P \longrightarrow S \Longrightarrow (P \Longrightarrow \text{False}) \Longrightarrow (S \Longrightarrow R) \Longrightarrow R \rangle$   
**apply** (*drule mp*)  
**apply** (*rule notI*)  
**apply** *assumption*  
**apply** *assumption*  
**done**

Simplifies the implication. UNSAFE.

**lemma** *iff-impE*:  
**assumes** *major*:  $\langle (P \longleftrightarrow Q) \longrightarrow S \rangle$   
**and** *r1*:  $\langle \llbracket P; Q \longrightarrow S \rrbracket \Longrightarrow Q \rangle$   
**and** *r2*:  $\langle \llbracket Q; P \longrightarrow S \rrbracket \Longrightarrow P \rangle$   
**and** *r3*:  $\langle S \Longrightarrow R \rangle$   
**shows**  $\langle R \rangle$   
**apply** (*assumption* | *rule iffI impI major [THEN mp] r1 r2 r3*)  
**done**

What if  $(\forall x. \neg \neg P(x)) \longrightarrow \neg \neg (\forall x. P(x))$  is an assumption? UNSAFE.

**lemma** *all-impE*:  
**assumes** *major*:  $\langle (\forall x. P(x)) \longrightarrow S \rangle$   
**and** *r1*:  $\langle \bigwedge x. P(x) \rangle$   
**and** *r2*:  $\langle S \Longrightarrow R \rangle$   
**shows**  $\langle R \rangle$   
**apply** (*rule allI impI major [THEN mp] r1 r2*)  
**done**

Unsafe:  $\exists x. P(x) \longrightarrow S$  is equivalent to  $\forall x. P(x) \longrightarrow S$ .

**lemma** *ex-impE*:  
**assumes** *major*:  $\langle (\exists x. P(x)) \longrightarrow S \rangle$   
**and** *r*:  $\langle P(x) \longrightarrow S \Longrightarrow R \rangle$   
**shows**  $\langle R \rangle$

```

apply (assumption | rule exI impI major [THEN mp] r)+
done

```

Courtesy of Krzysztof Grabczewski.

```

lemma disj-imp-disj:  $\langle P \vee Q \implies (P \implies R) \implies (Q \implies S) \implies R \vee S \rangle$ 
  apply (erule disjE)
  apply (rule disjI1) apply assumption
  apply (rule disjI2) apply assumption
done

```

```

ML <
structure Project-Rule = Project-Rule
(
  val conjunct1 = @{thm conjunct1}
  val conjunct2 = @{thm conjunct2}
  val mp = @{thm mp}
)
>

```

**ML-file**  $\langle fologic.ML \rangle$

```

lemma thin-refl:  $\langle \llbracket x = x; PROP W \rrbracket \implies PROP W \rangle$  .

```

```

ML <
structure Hypsubst = Hypsubst
(
  val dest-eq = FOLogic.dest-eq
  val dest-Trueprop = FOLogic.dest-Trueprop
  val dest-imp = FOLogic.dest-imp
  val eq-reflection = @{thm eq-reflection}
  val rev-eq-reflection = @{thm meta-eq-to-obj-eq}
  val imp-intr = @{thm impI}
  val rev-mp = @{thm rev-mp}
  val subst = @{thm subst}
  val sym = @{thm sym}
  val thin-refl = @{thm thin-refl}
);
open Hypsubst;
>

```

**ML-file**  $\langle intprover.ML \rangle$

## 1.7 Intuitionistic Reasoning

```

setup  $\langle Intuitionistic.method-setup \textbf{binding} \langle iprover \rangle \rangle$ 

```

```

lemma impE':
  assumes 1:  $\langle P \longrightarrow Q \rangle$ 
  and 2:  $\langle Q \implies R \rangle$ 

```

```

    and  $\beta$ :  $\langle P \longrightarrow Q \Longrightarrow P \rangle$ 
  shows  $\langle R \rangle$ 
proof -
  from  $\beta$  and 1 have  $\langle P \rangle$  .
  with 1 have  $\langle Q \rangle$  by (rule impE)
  with 2 show  $\langle R \rangle$  .
qed

lemma allE':
  assumes 1:  $\langle \forall x. P(x) \rangle$ 
    and 2:  $\langle P(x) \Longrightarrow \forall x. P(x) \Longrightarrow Q \rangle$ 
  shows  $\langle Q \rangle$ 
proof -
  from 1 have  $\langle P(x) \rangle$  by (rule spec)
  from this and 1 show  $\langle Q \rangle$  by (rule 2)
qed

lemma notE':
  assumes 1:  $\langle \neg P \rangle$ 
    and 2:  $\langle \neg P \Longrightarrow P \rangle$ 
  shows  $\langle R \rangle$ 
proof -
  from 2 and 1 have  $\langle P \rangle$  .
  with 1 show  $\langle R \rangle$  by (rule notE)
qed

lemmas [Pure.elim!] = disjE iffE FalseE conjE exE
  and [Pure.intro!] = iffI conjI impI TrueI notI allI refl
  and [Pure.elim 2] = allE notE' impE'
  and [Pure.intro] = exI disjI2 disjI1

setup  $\langle$ 
  Context-Rules.addSWrapper
    (fn ctxt => fn tac => hyp-subst-tac ctxt ORELSE' tac)
 $\rangle$ 

lemma iff-not-sym:  $\langle \neg (Q \longleftrightarrow P) \Longrightarrow \neg (P \longleftrightarrow Q) \rangle$ 
  by iprover

lemmas [sym] = sym iff-sym not-sym iff-not-sym
  and [Pure.elim?] = iffD1 iffD2 impE

lemma eq-commute:  $\langle a = b \longleftrightarrow b = a \rangle$ 
  apply (rule iffI)
  apply (erule sym)+
  done

```

## 1.8 Atomizing meta-level rules

**lemma** *atomize-all* [*atomize*]:  $\langle (\bigwedge x. P(x)) \equiv \text{Trueprop } (\forall x. P(x)) \rangle$

**proof**

**assume**  $\langle \bigwedge x. P(x) \rangle$

**then show**  $\langle \forall x. P(x) \rangle$  ..

**next**

**assume**  $\langle \forall x. P(x) \rangle$

**then show**  $\langle \bigwedge x. P(x) \rangle$  ..

**qed**

**lemma** *atomize-imp* [*atomize*]:  $\langle (A \implies B) \equiv \text{Trueprop } (A \longrightarrow B) \rangle$

**proof**

**assume**  $\langle A \implies B \rangle$

**then show**  $\langle A \longrightarrow B \rangle$  ..

**next**

**assume**  $\langle A \longrightarrow B \rangle$  **and**  $\langle A \rangle$

**then show**  $\langle B \rangle$  **by** (*rule mp*)

**qed**

**lemma** *atomize-eq* [*atomize*]:  $\langle (x \equiv y) \equiv \text{Trueprop } (x = y) \rangle$

**proof**

**assume**  $\langle x \equiv y \rangle$

**show**  $\langle x = y \rangle$  **unfolding**  $\langle x \equiv y \rangle$  **by** (*rule refl*)

**next**

**assume**  $\langle x = y \rangle$

**then show**  $\langle x \equiv y \rangle$  **by** (*rule eq-reflection*)

**qed**

**lemma** *atomize-iff* [*atomize*]:  $\langle (A \equiv B) \equiv \text{Trueprop } (A \longleftrightarrow B) \rangle$

**proof**

**assume**  $\langle A \equiv B \rangle$

**show**  $\langle A \longleftrightarrow B \rangle$  **unfolding**  $\langle A \equiv B \rangle$  **by** (*rule iff-refl*)

**next**

**assume**  $\langle A \longleftrightarrow B \rangle$

**then show**  $\langle A \equiv B \rangle$  **by** (*rule iff-reflection*)

**qed**

**lemma** *atomize-conj* [*atomize*]:  $\langle (A \&\&\& B) \equiv \text{Trueprop } (A \wedge B) \rangle$

**proof**

**assume** *conj*:  $\langle A \&\&\& B \rangle$

**show**  $\langle A \wedge B \rangle$

**proof** (*rule conjI*)

**from** *conj* **show**  $\langle A \rangle$  **by** (*rule conjunctionD1*)

**from** *conj* **show**  $\langle B \rangle$  **by** (*rule conjunctionD2*)

**qed**

**next**

**assume** *conj*:  $\langle A \wedge B \rangle$

**show**  $\langle A \&\&\& B \rangle$

**proof** –

**from** *conj* **show**  $\langle A \rangle$  ..  
**from** *conj* **show**  $\langle B \rangle$  ..  
**qed**  
**qed**

**lemmas** [*symmetric, rulify*] = *atomize-all atomize-imp*  
**and** [*symmetric, defn*] = *atomize-all atomize-imp atomize-eq atomize-iff*

## 1.9 Atomizing elimination rules

**lemma** *atomize-exL*[*atomize-elim*]:  $\langle (\bigwedge x. P(x) \implies Q) \equiv ((\exists x. P(x)) \implies Q) \rangle$   
**by** *rule iprover+*

**lemma** *atomize-conjL*[*atomize-elim*]:  $\langle (A \implies B \implies C) \equiv (A \wedge B \implies C) \rangle$   
**by** *rule iprover+*

**lemma** *atomize-disjL*[*atomize-elim*]:  $\langle ((A \implies C) \implies (B \implies C) \implies C) \equiv ((A \vee B \implies C) \implies C) \rangle$   
**by** *rule iprover+*

**lemma** *atomize-elimL*[*atomize-elim*]:  $\langle (\bigwedge B. (A \implies B) \implies B) \equiv \text{Trueprop}(A) \rangle$  ..

## 1.10 Calculational rules

**lemma** *forw-subst*:  $\langle a = b \implies P(b) \implies P(a) \rangle$   
**by** (*rule ssubst*)

**lemma** *back-subst*:  $\langle P(a) \implies a = b \implies P(b) \rangle$   
**by** (*rule subst*)

Note that this list of rules is in reverse order of priorities.

**lemmas** *basic-trans-rules* [*trans*] =  
*forw-subst*  
*back-subst*  
*rev-mp*  
*mp*  
*trans*

## 1.11 “Let” declarations

**nonterminal** *letbinds* **and** *letbind*

**definition** *Let* ::  $\langle ['a::\{\}, 'a \Rightarrow 'b] \Rightarrow ('b::\{\}) \rangle$   
**where**  $\langle \text{Let}(s, f) \equiv f(s) \rangle$

**syntax**

*-bind*        ::  $\langle [\text{pttrn}, 'a] \Rightarrow \text{letbind} \rangle$                  $\langle (2- =/ -) \rangle 10$   
              ::  $\langle \text{letbind} \Rightarrow \text{letbinds} \rangle$                  $\langle (-) \rangle$   
*-binds*        ::  $\langle [\text{letbind}, \text{letbinds}] \Rightarrow \text{letbinds} \rangle$      $\langle (-;/ -) \rangle$   
*-Let*         ::  $\langle [\text{letbinds}, 'a] \Rightarrow 'a \rangle$                  $\langle (\text{let } (-) / \text{ in } (-)) \rangle 10$



**translations**

$$\begin{aligned} \text{-Let}(\text{-binds}(b, bs), e) &== \text{-Let}(b, \text{-Let}(bs, e)) \\ \text{let } x = a \text{ in } e &== \text{CONST Let}(a, \lambda x. e) \end{aligned}$$
**lemma LetI:**

**assumes**  $\langle \bigwedge x. x = t \implies P(u(x)) \rangle$   
**shows**  $\langle P(\text{let } x = t \text{ in } u(x)) \rangle$   
**apply** (unfold Let-def)  
**apply** (rule refl [THEN assms])  
**done**

**1.12 Intuitionistic simplification rules****lemma conj-simps:**

$\langle P \wedge \text{True} \longleftrightarrow P \rangle$   
 $\langle \text{True} \wedge P \longleftrightarrow P \rangle$   
 $\langle P \wedge \text{False} \longleftrightarrow \text{False} \rangle$   
 $\langle \text{False} \wedge P \longleftrightarrow \text{False} \rangle$   
 $\langle P \wedge P \longleftrightarrow P \rangle$   
 $\langle P \wedge P \wedge Q \longleftrightarrow P \wedge Q \rangle$   
 $\langle P \wedge \neg P \longleftrightarrow \text{False} \rangle$   
 $\langle \neg P \wedge P \longleftrightarrow \text{False} \rangle$   
 $\langle (P \wedge Q) \wedge R \longleftrightarrow P \wedge (Q \wedge R) \rangle$   
**by** iprover+

**lemma disj-simps:**

$\langle P \vee \text{True} \longleftrightarrow \text{True} \rangle$   
 $\langle \text{True} \vee P \longleftrightarrow \text{True} \rangle$   
 $\langle P \vee \text{False} \longleftrightarrow P \rangle$   
 $\langle \text{False} \vee P \longleftrightarrow P \rangle$   
 $\langle P \vee P \longleftrightarrow P \rangle$   
 $\langle P \vee P \vee Q \longleftrightarrow P \vee Q \rangle$   
 $\langle (P \vee Q) \vee R \longleftrightarrow P \vee (Q \vee R) \rangle$   
**by** iprover+

**lemma not-simps:**

$\langle \neg (P \vee Q) \longleftrightarrow \neg P \wedge \neg Q \rangle$   
 $\langle \neg \text{False} \longleftrightarrow \text{True} \rangle$   
 $\langle \neg \text{True} \longleftrightarrow \text{False} \rangle$   
**by** iprover+

**lemma imp-simps:**

$\langle (P \longrightarrow \text{False}) \longleftrightarrow \neg P \rangle$   
 $\langle (P \longrightarrow \text{True}) \longleftrightarrow \text{True} \rangle$   
 $\langle (\text{False} \longrightarrow P) \longleftrightarrow \text{True} \rangle$   
 $\langle (\text{True} \longrightarrow P) \longleftrightarrow P \rangle$   
 $\langle (P \longrightarrow P) \longleftrightarrow \text{True} \rangle$   
 $\langle (P \longrightarrow \neg P) \longleftrightarrow \neg P \rangle$

**by** *iprover*+

**lemma** *iff-simps*:

$\langle (True \longleftrightarrow P) \longleftrightarrow P \rangle$   
 $\langle (P \longleftrightarrow True) \longleftrightarrow P \rangle$   
 $\langle (P \longleftrightarrow P) \longleftrightarrow True \rangle$   
 $\langle (False \longleftrightarrow P) \longleftrightarrow \neg P \rangle$   
 $\langle (P \longleftrightarrow False) \longleftrightarrow \neg P \rangle$   
**by** *iprover*

The  $x = t$  versions are needed for the simplification procedures.

**lemma** *quant-simps*:

$\langle \bigwedge P. (\forall x. P) \longleftrightarrow P \rangle$   
 $\langle (\forall x. x = t \longrightarrow P(x)) \longleftrightarrow P(t) \rangle$   
 $\langle (\forall x. t = x \longrightarrow P(x)) \longleftrightarrow P(t) \rangle$   
 $\langle \bigwedge P. (\exists x. P) \longleftrightarrow P \rangle$   
 $\langle \exists x. x = t \rangle$   
 $\langle \exists x. t = x \rangle$   
 $\langle (\exists x. x = t \wedge P(x)) \longleftrightarrow P(t) \rangle$   
 $\langle (\exists x. t = x \wedge P(x)) \longleftrightarrow P(t) \rangle$   
**by** *iprover*

These are NOT supplied by default!

**lemma** *distrib-simps*:

$\langle P \wedge (Q \vee R) \longleftrightarrow P \wedge Q \vee P \wedge R \rangle$   
 $\langle (Q \vee R) \wedge P \longleftrightarrow Q \wedge P \vee R \wedge P \rangle$   
 $\langle (P \vee Q \longrightarrow R) \longleftrightarrow (P \longrightarrow R) \wedge (Q \longrightarrow R) \rangle$   
**by** *iprover*

### 1.12.1 Conversion into rewrite rules

**lemma** *P-iff-F*:  $\langle \neg P \Longrightarrow (P \longleftrightarrow False) \rangle$

**by** *iprover*

**lemma** *iff-reflection-F*:  $\langle \neg P \Longrightarrow (P \equiv False) \rangle$

**by** (*rule* *P-iff-F* [*THEN* *iff-reflection*])

**lemma** *P-iff-T*:  $\langle P \Longrightarrow (P \longleftrightarrow True) \rangle$

**by** *iprover*

**lemma** *iff-reflection-T*:  $\langle P \Longrightarrow (P \equiv True) \rangle$

**by** (*rule* *P-iff-T* [*THEN* *iff-reflection*])

### 1.12.2 More rewrite rules

**lemma** *conj-commute*:  $\langle P \wedge Q \longleftrightarrow Q \wedge P \rangle$  **by** *iprover*

**lemma** *conj-left-commute*:  $\langle P \wedge (Q \wedge R) \longleftrightarrow Q \wedge (P \wedge R) \rangle$  **by** *iprover*

**lemmas** *conj-comms* = *conj-commute conj-left-commute*

**lemma** *disj-commute*:  $\langle P \vee Q \longleftrightarrow Q \vee P \rangle$  **by** *iprover*

**lemma** *disj-left-commute*:  $\langle P \vee (Q \vee R) \longleftrightarrow Q \vee (P \vee R) \rangle$  **by** *iprover*

```

lemmas disj-comms = disj-commute disj-left-commute

lemma conj-disj-distribL:  $\langle P \wedge (Q \vee R) \longleftrightarrow (P \wedge Q \vee P \wedge R) \rangle$  by iprover
lemma conj-disj-distribR:  $\langle (P \vee Q) \wedge R \longleftrightarrow (P \wedge R \vee Q \wedge R) \rangle$  by iprover

lemma disj-conj-distribL:  $\langle P \vee (Q \wedge R) \longleftrightarrow (P \vee Q) \wedge (P \vee R) \rangle$  by iprover
lemma disj-conj-distribR:  $\langle (P \wedge Q) \vee R \longleftrightarrow (P \vee R) \wedge (Q \vee R) \rangle$  by iprover

lemma imp-conj-distrib:  $\langle (P \longrightarrow (Q \wedge R)) \longleftrightarrow (P \longrightarrow Q) \wedge (P \longrightarrow R) \rangle$  by
iprover
lemma imp-conj:  $\langle ((P \wedge Q) \longrightarrow R) \longleftrightarrow (P \longrightarrow (Q \longrightarrow R)) \rangle$  by iprover
lemma imp-disj:  $\langle (P \vee Q \longrightarrow R) \longleftrightarrow (P \longrightarrow R) \wedge (Q \longrightarrow R) \rangle$  by iprover

lemma de-Morgan-disj:  $\langle (\neg (P \vee Q)) \longleftrightarrow (\neg P \wedge \neg Q) \rangle$  by iprover

lemma not-ex:  $\langle (\neg (\exists x. P(x))) \longleftrightarrow (\forall x. \neg P(x)) \rangle$  by iprover
lemma imp-ex:  $\langle ((\exists x. P(x)) \longrightarrow Q) \longleftrightarrow (\forall x. P(x) \longrightarrow Q) \rangle$  by iprover

lemma ex-disj-distrib:  $\langle (\exists x. P(x) \vee Q(x)) \longleftrightarrow ((\exists x. P(x)) \vee (\exists x. Q(x))) \rangle$ 
by iprover

lemma all-conj-distrib:  $\langle (\forall x. P(x) \wedge Q(x)) \longleftrightarrow ((\forall x. P(x)) \wedge (\forall x. Q(x))) \rangle$ 
by iprover

end

```

## 2 Classical first-order logic

```

theory FOL
imports IFOL
keywords print-claset print-induct-rules :: diag
begin

```

```

ML-file  $\langle \sim\sim / \text{src} / \text{Provers} / \text{classical.ML} \rangle$ 
ML-file  $\langle \sim\sim / \text{src} / \text{Provers} / \text{blast.ML} \rangle$ 
ML-file  $\langle \sim\sim / \text{src} / \text{Provers} / \text{clasimp.ML} \rangle$ 

```

### 2.1 The classical axiom

```

axiomatization where
  classical:  $\langle (\neg P \Longrightarrow P) \Longrightarrow P \rangle$ 

```

### 2.2 Lemmas and proof tools

```

lemma ccontr:  $\langle (\neg P \Longrightarrow \text{False}) \Longrightarrow P \rangle$ 
by (erule FalseE [THEN classical])

```

### 2.2.1 Classical introduction rules for $\vee$ and $\exists$

```

lemma disjCI:  $\langle (\neg Q \implies P) \implies P \vee Q \rangle$ 
  apply (rule classical)
  apply (assumption | erule meta-mp | rule disjI1 notI) +
  apply (erule notE disjI2) +
  done

```

Introduction rule involving only  $\exists$

```

lemma ex-classical:
  assumes  $r$ :  $\langle \neg (\exists x. P(x)) \implies P(a) \rangle$ 
  shows  $\langle \exists x. P(x) \rangle$ 
  apply (rule classical)
  apply (rule exI, erule  $r$ )
  done

```

Version of above, simplifying  $\neg\exists$  to  $\forall\neg$ .

```

lemma exCI:
  assumes  $r$ :  $\langle \forall x. \neg P(x) \implies P(a) \rangle$ 
  shows  $\langle \exists x. P(x) \rangle$ 
  apply (rule ex-classical)
  apply (rule notI [THEN allI, THEN r])
  apply (erule notE)
  apply (erule exI)
  done

```

```

lemma excluded-middle:  $\langle \neg P \vee P \rangle$ 
  apply (rule disjCI)
  apply assumption
  done

```

```

lemma case-split [case-names True False]:
  assumes  $r1$ :  $\langle P \implies Q \rangle$ 
  and  $r2$ :  $\langle \neg P \implies Q \rangle$ 
  shows  $\langle Q \rangle$ 
  apply (rule excluded-middle [THEN disjE])
  apply (erule  $r2$ )
  apply (erule  $r1$ )
  done

```

**ML**  $\langle$

```

  fun case-tac ctxt a fixes =
    Rule-Insts.res-inst-tac ctxt [(((P, 0), Position.none), a)] fixes @ {thm case-split};
   $\rangle$ 

```

**method-setup** *case-tac* =  $\langle$

```

  Args.goal-spec -- Scan.lift (Args.embedded-inner-syntax -- Parse.for-fixes)
  >>
  (fn (quant, (s, fixes)) => fn ctxt => SIMPLE-METHOD'' quant (case-tac ctxt
    s fixes))

```

› *case-tac emulation (dynamic instantiation!)*

## 2.3 Special elimination rules

Classical implies ( $\longrightarrow$ ) elimination.

```
lemma impCE:
  assumes major:  $\langle P \longrightarrow Q \rangle$ 
  and r1:  $\langle \neg P \Longrightarrow R \rangle$ 
  and r2:  $\langle Q \Longrightarrow R \rangle$ 
  shows  $\langle R \rangle$ 
  apply (rule excluded-middle [THEN disjE])
  apply (erule r1)
  apply (rule r2)
  apply (erule major [THEN mp])
  done
```

This version of  $\longrightarrow$  elimination works on  $Q$  before  $P$ . It works best for those cases in which  $P$  holds “almost everywhere”. Can’t install as default: would break old proofs.

```
lemma impCE':
  assumes major:  $\langle P \longrightarrow Q \rangle$ 
  and r1:  $\langle Q \Longrightarrow R \rangle$ 
  and r2:  $\langle \neg P \Longrightarrow R \rangle$ 
  shows  $\langle R \rangle$ 
  apply (rule excluded-middle [THEN disjE])
  apply (erule r2)
  apply (rule r1)
  apply (erule major [THEN mp])
  done
```

Double negation law.

```
lemma notnotD:  $\langle \neg \neg P \Longrightarrow P \rangle$ 
  apply (rule classical)
  apply (erule notE)
  apply assumption
  done
```

```
lemma contrapos2:  $\langle \llbracket Q; \neg P \Longrightarrow \neg Q \rrbracket \Longrightarrow P \rangle$ 
  apply (rule classical)
  apply (drule (1) meta-mp)
  apply (erule (1) notE)
  done
```

### 2.3.1 Tactics for implication and contradiction

Classical  $\longleftrightarrow$  elimination. Proof substitutes  $P = Q$  in  $\neg P \Longrightarrow \neg Q$  and  $P \Longrightarrow Q$ .

```

lemma iffCE:
  assumes major:  $\langle P \longleftrightarrow Q \rangle$ 
    and r1:  $\langle \llbracket P; Q \rrbracket \Longrightarrow R \rangle$ 
    and r2:  $\langle \llbracket \neg P; \neg Q \rrbracket \Longrightarrow R \rangle$ 
  shows  $\langle R \rangle$ 
  apply (rule major [unfolded iff-def, THEN conjE])
  apply (elim impCE)
    apply (erule (1) r2)
    apply (erule (1) notE)+
  apply (erule (1) r1)
done

lemma alt-ex1E:
  assumes major:  $\langle \exists! x. P(x) \rangle$ 
    and r:  $\langle \bigwedge x. \llbracket P(x); \forall y y'. P(y) \wedge P(y') \longrightarrow y = y' \rrbracket \Longrightarrow R \rangle$ 
  shows  $\langle R \rangle$ 
  using major
proof (rule ex1E)
  fix x
  assume *:  $\langle \forall y. P(y) \longrightarrow y = x \rangle$ 
  assume  $\langle P(x) \rangle$ 
  then show  $\langle R \rangle$ 
proof (rule r)
  {
    fix y y'
    assume  $\langle P(y) \rangle$  and  $\langle P(y') \rangle$ 
    with * have  $\langle x = y \rangle$  and  $\langle x = y' \rangle$ 
    by - (tactic IntPr.fast-tac context 1)+
    then have  $\langle y = y' \rangle$  by (rule subst)
  } note r' = this
  show  $\langle \forall y y'. P(y) \wedge P(y') \longrightarrow y = y' \rangle$ 
    by (intro strip, elim conjE) (rule r')
qed
qed

lemma imp-elim:  $\langle P \longrightarrow Q \Longrightarrow (\neg R \Longrightarrow P) \Longrightarrow (Q \Longrightarrow R) \Longrightarrow R \rangle$ 
  by (rule classical) iprover

lemma swap:  $\langle \neg P \Longrightarrow (\neg R \Longrightarrow P) \Longrightarrow R \rangle$ 
  by (rule classical) iprover

```

### 3 Classical Reasoner

```

ML <
structure Cla = Classical
(
  val imp-elim = @{thm imp-elim}

```

```

    val not-elim = @{thm notE}
    val swap = @{thm swap}
    val classical = @{thm classical}
    val sizef = size-of-thm
    val hyp-subst-tacs = [hyp-subst-tac]
  );

structure Basic-Classical: BASIC-CLASSICAL = Cla;
open Basic-Classical;
)

lemmas [intro!] = refl TrueI conjI disjCI impI notI iffI
  and [elim!] = conjE disjE impCE FalseE iffCE
ML <val prop-cs = claset-of context>

lemmas [intro!] = allI ex-ex1I
  and [intro] = exI
  and [elim!] = exE alt-ex1E
  and [elim] = allE
ML <val FOL-cs = claset-of context>

ML <
  structure Blast = Blast
  (
    structure Classical = Cla
    val Trueprop-const = dest-Const const <Trueprop>
    val equality-name = const-name <eq>
    val not-name = const-name <Not>
    val notE = @{thm notE}
    val ccontr = @{thm ccontr}
    val hyp-subst-tac = Hypsubst.blast-hyp-subst-tac
  );
  val blast-tac = Blast.blast-tac;
)

lemma ex1-functional: <[ $\exists!$  z. P(a,z); P(a,b); P(a,c)]  $\implies$  b = c>
  by blast

Elimination of True from assumptions:

lemma True-implies-equals: <(True  $\implies$  PROP P)  $\equiv$  PROP P>
proof
  assume <True  $\implies$  PROP P>
  from this and TrueI show <PROP P> .
next
  assume <PROP P>
  then show <PROP P> .

```

qed

**lemma** *uncurry*:  $\langle P \longrightarrow Q \longrightarrow R \Longrightarrow P \wedge Q \longrightarrow R \rangle$   
**by** *blast*

**lemma** *iff-allI*:  $\langle (\bigwedge x. P(x) \longleftrightarrow Q(x)) \Longrightarrow (\forall x. P(x)) \longleftrightarrow (\forall x. Q(x)) \rangle$   
**by** *blast*

**lemma** *iff-exI*:  $\langle (\bigwedge x. P(x) \longleftrightarrow Q(x)) \Longrightarrow (\exists x. P(x)) \longleftrightarrow (\exists x. Q(x)) \rangle$   
**by** *blast*

**lemma** *all-comm*:  $\langle (\forall x y. P(x,y)) \longleftrightarrow (\forall y x. P(x,y)) \rangle$   
**by** *blast*

**lemma** *ex-comm*:  $\langle (\exists x y. P(x,y)) \longleftrightarrow (\exists y x. P(x,y)) \rangle$   
**by** *blast*

### 3.1 Classical simplification rules

Avoids duplication of subgoals after *expand-if*, when the true and false cases boil down to the same thing.

**lemma** *cases-simp*:  $\langle (P \longrightarrow Q) \wedge (\neg P \longrightarrow Q) \longleftrightarrow Q \rangle$   
**by** *blast*

#### 3.1.1 Miniscoping: pushing quantifiers in

We do NOT distribute of  $\forall$  over  $\wedge$ , or dually that of  $\exists$  over  $\vee$ .

Baaz and Leitsch, On Skolemization and Proof Complexity (1994) show that this step can increase proof length!

Existential miniscoping.

**lemma** *int-ex-simps*:  
 $\langle \bigwedge P Q. (\exists x. P(x) \wedge Q) \longleftrightarrow (\exists x. P(x)) \wedge Q \rangle$   
 $\langle \bigwedge P Q. (\exists x. P \wedge Q(x)) \longleftrightarrow P \wedge (\exists x. Q(x)) \rangle$   
 $\langle \bigwedge P Q. (\exists x. P(x) \vee Q) \longleftrightarrow (\exists x. P(x)) \vee Q \rangle$   
 $\langle \bigwedge P Q. (\exists x. P \vee Q(x)) \longleftrightarrow P \vee (\exists x. Q(x)) \rangle$   
**by** *iprover+*

Classical rules.

**lemma** *cla-ex-simps*:  
 $\langle \bigwedge P Q. (\exists x. P(x) \longrightarrow Q) \longleftrightarrow (\forall x. P(x)) \longrightarrow Q \rangle$   
 $\langle \bigwedge P Q. (\exists x. P \longrightarrow Q(x)) \longleftrightarrow P \longrightarrow (\exists x. Q(x)) \rangle$   
**by** *blast+*

**lemmas** *ex-simps = int-ex-simps cla-ex-simps*

Universal miniscoping.



**lemma** *int-all-simps*:

$\langle \bigwedge P Q. (\forall x. P(x) \wedge Q) \longleftrightarrow (\forall x. P(x)) \wedge Q \rangle$   
 $\langle \bigwedge P Q. (\forall x. P \wedge Q(x)) \longleftrightarrow P \wedge (\forall x. Q(x)) \rangle$   
 $\langle \bigwedge P Q. (\forall x. P(x) \longrightarrow Q) \longleftrightarrow (\exists x. P(x)) \longrightarrow Q \rangle$   
 $\langle \bigwedge P Q. (\forall x. P \longrightarrow Q(x)) \longleftrightarrow P \longrightarrow (\forall x. Q(x)) \rangle$   
**by** *iprover* +

Classical rules.

**lemma** *cla-all-simps*:

$\langle \bigwedge P Q. (\forall x. P(x) \vee Q) \longleftrightarrow (\forall x. P(x)) \vee Q \rangle$   
 $\langle \bigwedge P Q. (\forall x. P \vee Q(x)) \longleftrightarrow P \vee (\forall x. Q(x)) \rangle$   
**by** *blast* +

**lemmas** *all-simps* = *int-all-simps* *cla-all-simps*

### 3.1.2 Named rewrite rules proved for IFOL

**lemma** *imp-disj1*:  $\langle (P \longrightarrow Q) \vee R \longleftrightarrow (P \longrightarrow Q \vee R) \rangle$  **by** *blast*

**lemma** *imp-disj2*:  $\langle Q \vee (P \longrightarrow R) \longleftrightarrow (P \longrightarrow Q \vee R) \rangle$  **by** *blast*

**lemma** *de-Morgan-conj*:  $\langle (\neg (P \wedge Q)) \longleftrightarrow (\neg P \vee \neg Q) \rangle$  **by** *blast*

**lemma** *not-imp*:  $\langle \neg (P \longrightarrow Q) \longleftrightarrow (P \wedge \neg Q) \rangle$  **by** *blast*

**lemma** *not-iff*:  $\langle \neg (P \longleftrightarrow Q) \longleftrightarrow (P \longleftrightarrow \neg Q) \rangle$  **by** *blast*

**lemma** *not-all*:  $\langle \neg (\forall x. P(x)) \longleftrightarrow (\exists x. \neg P(x)) \rangle$  **by** *blast*

**lemma** *imp-all*:  $\langle ((\forall x. P(x)) \longrightarrow Q) \longleftrightarrow (\exists x. P(x) \longrightarrow Q) \rangle$  **by** *blast*

**lemmas** *meta-simps* =

*triv-forall-equality* — prunes params  
*True-implies-equals* — prune asms *True*

**lemmas** *IFOL-simps* =

*reft* [*THEN* *P-iff-T*] *conj-simps* *disj-simps* *not-simps*  
*imp-simps* *iff-simps* *quant-simps*

**lemma** *notFalseI*:  $\langle \neg \text{False} \rangle$  **by** *iprover*

**lemma** *cla-simps-misc*:

$\langle \neg (P \wedge Q) \longleftrightarrow \neg P \vee \neg Q \rangle$   
 $\langle P \vee \neg P \rangle$   
 $\langle \neg P \vee P \rangle$   
 $\langle \neg \neg P \longleftrightarrow P \rangle$   
 $\langle (\neg P \longrightarrow P) \longleftrightarrow P \rangle$   
 $\langle (\neg P \longleftrightarrow \neg Q) \longleftrightarrow (P \longleftrightarrow Q) \rangle$  **by** *blast* +

**lemmas** *cla-simps* =

*de-Morgan-conj* *de-Morgan-disj* *imp-disj1* *imp-disj2*

*not-imp not-all not-ex cases-simp cla-simps-misc*

**ML-file**  $\langle \text{simpdata.ML} \rangle$

**simproc-setup** *defined-Ex*  $\langle \exists x. P(x) \rangle = \langle \text{fn } - \Rightarrow \text{Quantifier1.rearrange-ex} \rangle$   
**simproc-setup** *defined-All*  $\langle \forall x. P(x) \rangle = \langle \text{fn } - \Rightarrow \text{Quantifier1.rearrange-all} \rangle$

**ML**  $\langle$

*(\*intuitionistic simprules only\*)*

*val IFOF-ss =*

*put-simpset FOL-basic-ss* **context**

*addsimps*  $\@ \{ \text{thms meta-simps IFOF-simps int-ex-simps int-all-simps} \}$

*addsimprocs*  $[ \textbf{simproc} \langle \text{defined-All} \rangle, \textbf{simproc} \langle \text{defined-Ex} \rangle ]$

*|> Simplifier.add-cong*  $\@ \{ \text{thm imp-cong} \}$

*|> simpset-of;*

*(\*classical simprules too\*)*

*val FOL-ss =*

*put-simpset IFOF-ss* **context**

*addsimps*  $\@ \{ \text{thms cla-simps cla-ex-simps cla-all-simps} \}$

*|> simpset-of;*

$\rangle$

**setup**  $\langle$

*map-theory-simpset*  $(\text{put-simpset FOL-ss}) \#>$

*Simplifier.method-setup Splitter.split-modifiers*

$\rangle$

**ML-file**  $\langle \sim \sim / \text{src} / \text{Tools} / \text{eqsubst.ML} \rangle$

## 3.2 Other simple lemmas

**lemma**  $[ \text{simp} ]$ :  $\langle ((P \longrightarrow R) \longleftrightarrow (Q \longrightarrow R)) \longleftrightarrow ((P \longleftrightarrow Q) \vee R) \rangle$   
*by blast*

**lemma**  $[ \text{simp} ]$ :  $\langle ((P \longrightarrow Q) \longleftrightarrow (P \longrightarrow R)) \longleftrightarrow (P \longrightarrow (Q \longleftrightarrow R)) \rangle$   
*by blast*

**lemma** *not-disj-iff-imp*:  $\langle \neg P \vee Q \longleftrightarrow (P \longrightarrow Q) \rangle$   
*by blast*

### 3.2.1 Monotonicity of implications

**lemma** *conj-mono*:  $\langle \llbracket P1 \longrightarrow Q1; P2 \longrightarrow Q2 \rrbracket \Longrightarrow (P1 \wedge P2) \longrightarrow (Q1 \wedge Q2) \rangle$   
*by fast*

**lemma** *disj-mono*:  $\langle \llbracket P1 \longrightarrow Q1; P2 \longrightarrow Q2 \rrbracket \Longrightarrow (P1 \vee P2) \longrightarrow (Q1 \vee Q2) \rangle$   
*by fast*

**lemma** *imp-mono*:  $\langle \llbracket Q1 \longrightarrow P1; P2 \longrightarrow Q2 \rrbracket \Longrightarrow (P1 \longrightarrow P2) \longrightarrow (Q1 \longrightarrow Q2) \rangle$

**by** *fast*

**lemma** *imp-refl*:  $\langle P \longrightarrow P \rangle$

**by** (*rule impI*)

The quantifier monotonicity rules are also intuitionistically valid.

**lemma** *ex-mono*:  $\langle (\bigwedge x. P(x) \longrightarrow Q(x)) \Longrightarrow (\exists x. P(x)) \longrightarrow (\exists x. Q(x)) \rangle$

**by** *blast*

**lemma** *all-mono*:  $\langle (\bigwedge x. P(x) \longrightarrow Q(x)) \Longrightarrow (\forall x. P(x)) \longrightarrow (\forall x. Q(x)) \rangle$

**by** *blast*

### 3.3 Proof by cases and induction

Proper handling of non-atomic rule statements.

**context**

**begin**

**qualified definition**  $\langle \text{induct-forall}(P) \equiv \forall x. P(x) \rangle$

**qualified definition**  $\langle \text{induct-implies}(A, B) \equiv A \longrightarrow B \rangle$

**qualified definition**  $\langle \text{induct-equal}(x, y) \equiv x = y \rangle$

**qualified definition**  $\langle \text{induct-conj}(A, B) \equiv A \wedge B \rangle$

**lemma** *induct-forall-eq*:  $\langle (\bigwedge x. P(x)) \equiv \text{Trueprop}(\text{induct-forall}(\lambda x. P(x))) \rangle$

**unfolding** *atomize-all induct-forall-def* .

**lemma** *induct-implies-eq*:  $\langle (A \Longrightarrow B) \equiv \text{Trueprop}(\text{induct-implies}(A, B)) \rangle$

**unfolding** *atomize-imp induct-implies-def* .

**lemma** *induct-equal-eq*:  $\langle (x \equiv y) \equiv \text{Trueprop}(\text{induct-equal}(x, y)) \rangle$

**unfolding** *atomize-eq induct-equal-def* .

**lemma** *induct-conj-eq*:  $\langle (A \&\& B) \equiv \text{Trueprop}(\text{induct-conj}(A, B)) \rangle$

**unfolding** *atomize-conj induct-conj-def* .

**lemmas** *induct-atomize* = *induct-forall-eq induct-implies-eq induct-equal-eq induct-conj-eq*

**lemmas** *induct-rulify* [*symmetric*] = *induct-atomize*

**lemmas** *induct-rulify-fallback* =

*induct-forall-def induct-implies-def induct-equal-def induct-conj-def*

Method setup.

**ML-file**  $\langle \sim \sim / \text{src} / \text{Tools} / \text{induct.ML} \rangle$

**ML**  $\langle$

*structure Induct = Induct*

$\langle$

*val cases-default = @{\thm case-split}*

```

    val atomize = @{thms induct-atomize}
    val rulify = @{thms induct-rulify}
    val rulify-fallback = @{thms induct-rulify-fallback}
    val equal-def = @{thm induct-equal-def}
    fun dest-def - = NONE
    fun trivial-tac - - = no-tac
  );
>

```

```

declare case-split [cases type: o]

```

```

end

```

```

ML-file ⟨~/src/Tools/case-product.ML⟩

```

```

hide-const (open) eq

```

```

end

```