

# Probabilistic framework for integration of mass spectrum and retention time information in small molecule identification

Eric Bach<sup>1,✉</sup>, Simon Rogers<sup>2</sup>, John Williamson<sup>2</sup>, and Juho Rousu<sup>1</sup>

<sup>1</sup>Helsinki institute for Information Technology (HIIT), Department of Computer Science, Aalto University, Espoo, Finland

<sup>2</sup>School of Computing Science, University of Glasgow, Glasgow, UK

## 1. Small Molecule Identification in Untargeted Metabolomics

- Challenge in untargeted metabolomics studies: **Identification of the small molecules** present in a biological sample
- LC-MS<sup>2</sup>** widely used analysis platform: Liquid chromatography (LC) coupled with tandem mass spectrometry (MS<sup>2</sup>) (Fig. 1)
- Most machine learning approaches for small molecule identification only utilize MS<sup>2</sup> information [3, 2]
- LC retention times (RT) can improve the small molecule annotation [5, 7]
- Challenges utilizing RT information:** (1) LC-system specific RT measurements and (2) public RT databases are limited in size and coverage




Fig. 1: LC-MS<sup>2</sup> analysis pipeline and resulting data used as input for our framework.

## 2. Retention Time (RT) Utilization for Small Molecule Identification

- Different approaches proposed in the literature
  - Multiple approaches to utilize RT for molecule annotation exist
  - (utilization of RT information, scalable, cross laboratories (LC-systems), RT reference free)
- Compare measured RTs with in-house reference RTs ✓, ✗, ✗, ✗
  - Compare measured RTs with projected reference RTs ✓, ✗, ○, ✗
  - Compare measured RTs with predicted RTs ✓, ✓, ○, ○
  - Compare measured RTs with predicted RTs proxies, e.g. LogP ✓, ✓, ✓, ✗
  - Compare measured retention orders with predicted ones ○, ✓, ✓, ✓
- Fully supported: ✓, Partially supported: ○, Not supported: ✗
  - RT comparison to prune candidate lists or (re)ranking [CITATION]

## 3. LC-MS<sup>2</sup> Experiment Data: Input and Output of our Framework

- Input:** Preprocessed LC-MS<sup>2</sup> data, i.e. after peak-picking and alignment (Fig.1):

$$\mathcal{D} = \{(x_i, t_i, C_i)\}_{i=1}^N$$

$x_i$  : MS Information; MS<sup>2</sup> or MS<sup>1</sup> (precursor m/z), if no fragmentation available  
 $t_i$  : Measured RT  
 $C_i$  : Molecular candidate sets, e.g. molecular structures found in PubChem by exact mass search  
 $N$  : Number of MS features

- Precomputed MS scoring assumed:** MS<sup>1</sup> deviation of candidate and precursor mass or MS<sup>2</sup> scores, e.g. by CSI:FingerID [3], MetFrag [5] or IOKR [2]
- Output:** Ranking of the molecular candidates in  $m_{ir} \in C_i$  for each MS feature  $i$
- Ranking based on MS and RT information

## 4. Probabilistic Framework to integrate MS and RT Information

- Graphical model**  $G$  superimposed on the LC-MS<sup>2</sup> data (Fig. 2)
- Let  $G = (V, E)$  be complete graph with a **node**  $i \in V$  for each MS feature, and an **edge**  $(i, j) \in E$  for each feature pair
- Discrete random variable  $z_i \in \mathcal{Z}_i = \{1, \dots, n_i\}$  associated with each node ( $n_i = |C_i|$ )
- Candidate annotation for the complete data  $\mathbf{z} = \{z_i | i \in V\} \in \mathcal{Z}_1 \times \dots \times \mathcal{Z}_N = \mathcal{Z}$
- Intuitively: Random variable  $z_i$  denotes the candidate  $m_{ir} \in C_i$  assigned to feature  $i$ .
- Pairwise **Markov Random Field** as probabilistic model [4]:

$$p(\mathbf{z}) = \frac{1}{Z} \prod_{i \in V} \psi_i(z_i) \prod_{(i,j) \in E} \psi_{ij}(z_i, z_j)$$

- Potential functions:  $\psi_i(z_i)$  MS score and  $\psi_{ij}(z_i, z_j)$  match of observed and **predicted retention order**
- Molecular **candidates ranked** based on max-marginals [4] (Fig. 2):

$$p_{\max}(z_i = r) = \max_{\{z' \in \mathcal{Z} | z'_i = r\}} p(\mathbf{z}')$$

- Intuitively: Maximum marginal probability of a candidate assignment with  $z_i = r$ .




Fig. 2: MRF probability distribution and candidate ranking, e.g. MS feature  $i = 3$  and candidate 4 ( $m_{34}$ ).

## 5. Encoding MS and Retention Order Information: $\psi_i$ and $\psi_{ij}$

- Node potential  $\psi_i : \mathcal{Z}_i \rightarrow \mathbb{R}_{>0}$ :  $\psi_i(z_i = r) = f(x_i, m_{ir})$
- $f$  returns the MS matching score  $\in (0, 1]$  of spectrum  $x_i$  and candidate  $m_{ir}$
- Edge potential  $\psi_{ij} : \mathcal{Z}_i \times \mathcal{Z}_j \rightarrow \mathbb{R}_{>0}$ , with  $\sigma$  being the sigmoid function:

$$\psi_{ij}(z_i = r, z_j = s) = \sigma(\underbrace{\text{sign}(t_i - t_j)}_{\text{observed retention order}} \cdot \underbrace{\langle \mathbf{w}, \phi(m_{ir}) - \phi(m_{js}) \rangle}_{\text{predicted retention order}})$$

- Intuitively: Matching observed and predicted retention orders receive high scores.
- Retention order prediction** using Ranking Support Vector Machine (RankSVM) w [1]
- Candidate molecules  $m_{ir}$  representation using non-linear features  $\phi$




Fig. 3: Example: Node and edge score for all candidate pairs of feature  $i = 4$  and  $j = 5$ .

## 6. Experiments and Results

- Evaluation datasets:** CASMI 2016 [6], EA subset from MassBank used by [5]
- 681 (MS<sup>2</sup>, RT)-tuples with median number of candidates between 120 and 919
- RankSVM training data:** 1248 RTs from PredRed [7] and CASMI 2016 training
- No evaluation set molecule in RankSVM training set
- Performance measure:** Top- $k$  accuracy, percentage of correct molecular candidates at rank  $\leq k$

### Experiment 1: Comparison to MetFrag + LogP Prediction

- MetFrag relaunched [5]: Prediction of LogP values for candidates, linear model mapping measured RTs to LogPs, candidate re-ranking based on LogP deviation

Method	Top-1	Top-5	Top-10	Top-20
MS <sup>2</sup> + RT (Our)	21.3	52.9	64.0	74.3
MS <sup>2</sup> + RT (MetFrag & LogP)	20.5	49.1	61.2	72.6
Only MS <sup>2</sup> (baseline)	16.7	49.5	60.4	70.6


### Experiment 2: Performance with different MS<sup>2</sup>-Scoring Methods

- MetFrag (in-silico fragmenter scores) and IOKR [2] as MS<sup>2</sup>-scoring methods

MS <sup>2</sup> -Scorer	Method	Top-1	Top-5	Top-10	Top-20
MetFrag	MS <sup>2</sup> + RT (our)	21.3	52.9	64.0	74.3
	Only MS <sup>2</sup> (baseline)	16.7	49.5	60.4	70.6
IOKR	MS <sup>2</sup> + RT (our)	26.7	52.1	62.5	70.3
	Only MS <sup>2</sup> (baseline)	25.1	49.5	60.3	67.6

### Experiment 3: Missing MS<sup>2</sup> Spectra

- Simulating missing MS<sup>2</sup> information: Varying from 0% (MS<sup>2</sup>) to 100%
- If only MS<sup>1</sup>: Use mass deviation between precursor and candidate molecule



## References

- [1] E. Bach, S. Szedmak, C. Brouard, S. Böcker, and J. Rousu. Liquid-chromatography retention order prediction for metabolite identification. *Bioinformatics*, 34(17):i875–i883, 2018.
- [2] C. Brouard, H. Shen, K. Dührkop, F. d'Alché-Buc, S. Böcker, and J. Rousu. Fast metabolite identification with Input Output Kernel Regression. *Bioinformatics*, 32(12):i28–i36, 2016.
- [3] K. Dührkop, M. Fleischauer, M. Ludwig, A. A. Aksenov, A. V. Melnik, M. Meusel, P. C. Dorrestein, J. Rousu, and S. Böcker. Sirius 4: a rapid tool for turning tandem mass spectra into metabolite structure information. *Nat Methods*, 2019. Doi 10.1038/s41592-019-0344-8.
- [4] D. J. MacKay. *Information theory, inference and learning algorithms*. Cambridge university press, 2005.
- [5] C. Ruttkies, E. L. Schymanski, S. Wolf, J. Hollender, and S. Neumann. Metfrag relaunched: incorporating strategies beyond in silico fragmentation. *Journal of Cheminformatics*, 8(1):3, Jan 2016.
- [6] E. L. Schymanski, C. Ruttkies, M. Krauss, C. Brouard, T. Kind, K. Dührkop, F. Allen, A. Vaniya, D. Verdegem, S. Böcker, J. Rousu, H. Shen, H. Tsugawa, T. Sajed, O. Fiehn, B. Ghesquière, and S. Neumann. Critical assessment of small molecule identification 2016: automated methods. *Journal of Cheminformatics*, 9(1):22, Mar 2017.
- [7] J. Stanstrup, S. Neumann, and U. Vrhovsek. Predret: Prediction of retention time by direct mapping between multiple chromatographic systems. *Analytical Chemistry*, 87(18):9421–9428, 2015. PMID: 26289378.