Router

Library version:	RENAT 0.1.13
Library scope:	test suite
Named arguments:	supported

Introduction

A class provides keywords for router control. An instance of Router class automatically assigned methods of a VChannel class (**Note**: this is not an inheritance but rather 1-to-1 relation)

See VChannel for more details about *VChannel*.

Device's `type` is defined in master `device.yaml` . The system will load appropriate modules for each device.

Details about keywords provided by modules could be found in document of each module likes:

- Juniper module
- Cisco module
- GR module

Keywords provides by above module could be executed through *Xrun* keyword or directly called from `Router` . Examples:

Router.*Switch*	vmx12
Router.*Xrun*	Load Config
Router.*Load Config*	

Shortcuts

Follow Mib · **X**run

Keywords

Keyword	Arguments	Documentation

Follow Mib	*node_list*, *wait_time=10s*, *interval_time=5s*, *len=12*, *percentile=80*, *threshold=75*, *max_len=300*, *factor=1*	Waits until all the nodes defined in `node_list` become `stable` .
		
		Stableness is checked by SNMP polling result. The MIB list is define by `mib` in `node` section Parameter:
		
		- `wait_time(1)` : the time before the evaluation starting
		- `interval_time(2)` : interval between SNMP polling time
		- `threshold` : below this value is evaluated as `stable`
		- `len(3)` : the size of the evaluation window (number of values that are used in each valuation)
		- `percentile` : real useful percentage of data (ignore top `100-percentile` percent)
		- `max_len(4)` : maximum waiting `lend` for this checking
		
		<pre>time sequence: --(1)--|-(2)-|-----|-----|----|-----|-----|
		          <--------(3)----------> poll poll
		              <--------(3)--------->
		              <--------------------(4)----------></pre>

Xrun	*cmd*, **args*, ***kwargs*	Runs the vendor independent keywords. Parametes: - `cmd` : a keyword - `args` : other argumemts Examples: `Router.Xrun` `Flap Interface` `ge-0/0/0` This keyword will then actually calling the correspond keyword for the device type.

Altogether 2 keywords.
Generated by Libdoc on 2019-03-11 23:22:03.