



CQ coding patterns: Sling vs JCR (part 2)

November 22, 2012

- Jörg Hoh

In the last posting I showed the benefits of Sling regarding resource access over plain JCR. But not only in resource access both frameworks offer similar functionality, but also in the important area of listening to changes in the repository. So today I want to compare JCR observation to Sling eventing.

JCR observation is a part of the JCR specification and is a very easy way to listen for changes in the repository.

```
@component (immediate=true, metatype=false)
@service
class Listener implements ObservationListener {

    @Reference
    SlingRepository repo;

    Session session;
    Logger log = LoggerFactory.getLogger (Listener.class);

    @activate
    protected void activate () {
        try {
            Session adminSession = repo.loginAdministrative(null);
            session = adminSession.impersonate (new SimpleCredentials("author",new char[0]));
            adminSession.logout();
            adminSession = null;
            session.getObservationManager.addEventListener( this, // listener
                NODE_CREATED|NODE_DELETED|NODE_MOVED, // eventTypes
                "/", // absPath
                true, // isDeep
                null, // uuid
                null, //nodeTypeNames
                true // noLocal
            );
        } catch (RepositoryException e) {
            log.error ("Error while registering observation", e);
        }
    }

    @deactivate
    protected void deactivate() {
        session.getObservationManager.removeListener(this);
        session.logout();
        session = null;
    }

    private handleEvents (Events events) {
        while (events.hasNext()) {
            Event e = events.next();
            ... // do here your event handling
        }
    }
}
```

In JCR the creation of an observation listener is straight forward, also the event listening. The observation process is tied to the lifetime of the session, which is started and stopped at activation/deactivation of this sling service. This kind of implementation is a common pattern.

...

Read the complete blog post at <http://cqdump.wordpress.com/2012/11/13/cq-coding-patterns-sling-vs-jcr-part-2/>

Adobe CQ Social Post

Tags

Adobe Adobe AEM
 Adobe CQ Amazon Apache
 AWS backup best practices Cloud
 Manager community
 CQ CRX custom widget DAM Dan
 Klco David McMahon Day Day.
 CQ Day Software developer
 development Digital Marketing disk
 space Dispatcher error feature pack
 FileJournal framework hotfix integration issue
 JCR Jörg Hoh OSGi performance
 programming Rackspace
 replication Samatha
 Vashishtha Scott
 Macdonald Sensei
 Martin SLING troubleshooting
 using WEM

Helpful CQ resources

Adobe CQ Documentation
 The Experience Delivers blog
 Adobe CQ forum

Categories

Announcement

Best practices

Cloud Manager

Developer

FAQ

How To

Performance

Samples

Tips and Tricks

Top Questions

Troubleshooting

Uncategorized

Workflows

Recent Posts

Launch the new Digital Marketing
 Support Community

Submitting Mobile Data to Adobe CQ
 using a Sling Post Servlet

Developing a Spring MVC project using
 Maven, JSTL tags, and data persistence

AEM5.6: Socoadmin: reply button and
 refresh issues in moderation UI

Tags: CQ, JCR, Jörg Hoh, SLING

Comments are closed.

[« Previous Post](#)

[Next Post »](#)

Copyright © 2012 Adobe Systems Incorporated. All rights reserved.

[Terms of Use](#) | [Privacy Policy and Cookies](#) [\(Updated\)](#)