

# Markdown to Jupyter notebook example

---

Here is a SugarTeX example with eq. 1 and fig. 1.

See [PDF of this source](#) if you do not have [excellent Unicode support](#).

```
\[ \begin{aligned} \nabla \times \{\mathbf{B}\} - \frac{1}{c} \frac{\partial \{\mathbf{E}\}}{\partial t} &= \\ \frac{4\pi}{c} \{\mathbf{j}\} \quad \nabla \cdot \{\mathbf{E}\} &= 4\pi\rho \quad \nabla \times \{\mathbf{E}\} + \\ \frac{1}{c} \frac{\partial \{\mathbf{B}\}}{\partial t} &= \{\mathbf{0}\} \quad \nabla \cdot \{\mathbf{B}\} &= 0 \\ \end{aligned} ,\quad(1)\]
```

where  $((\{\mathbf{B}\}, \{\mathbf{E}\}, \{\mathbf{j}\}): \mathbb{R}^4 \rightarrow \mathbb{R}^3)$  – vector functions of the form  $((t,x,y,z) \mapsto \{\mathbf{f}\}(t,x,y,z), \{\mathbf{f}\} = (f_{\mathrm{x}}, f_{\mathrm{y}}, f_{\mathrm{z}}))$ .




Figure 1: Sample image with cross-references.

In this version of Pandoc image caption fig. 1 works.

```

from IPython.display import Markdown
import pandas as pd
import numpy as np
import tabulatehelper as th

df = pd.DataFrame(np.random.random(16).reshape(4, 4))

Markdown(f'''
{th.md_table(df)}
: Table {{#tbl:table1}}
''')

```

Table 1: Table

0	1	2	3
0.305947	0.255349	0.876985	0.462509
0.971988	0.436516	0.131657	0.794084
0.800326	0.441889	0.0685123	0.812726
0.659657	0.506419	0.689123	0.216958

Text and tbl. 1

```

import pandas as pd
import numpy as np
df = pd.DataFrame(np.random.random(16).reshape(4, 4))
df

```

```

# R cell:
x <- c(10, 20)
x[1]

```

10

# Header

---

```
x <- c(10, 20)
x[1]
```

10

```
import math
Markdown(f'''
Markdown text with SugarTeX formula:  $\alpha^{\{math.pi:1.3f\}}$ $.
It works because of the Markdown display option and
SugarTeX Pandoc filter.
''')
```

Markdown text with SugarTeX formula:  $\alpha^{\{3.142\}}$ . It works because of the Markdown display option and SugarTeX Pandoc filter.

```
print('Hello!')
```