


cmta.

Rules Specification

**Functional specifications of the
Rules for CMTAT and RuleEngine
on Ethereum and EVM compatible blockchains.**

Rules version: v0.3.0

First published: April 2026



RuleEngine - Rules


Rules is a collection of on-chain compliance and transfer-restriction rules designed for use with the [CMTA RuleEngine](#) and the [CMTAT token standard](#).

Each rule can be used **standalone**, directly plugged into a CMTAT token, **or** managed collectively via a RuleEngine.

This project has not undergone an audit and is provided as-is without any warranties.

Schema

- Using rules with CMTAT and ERC-3643 tokens through a [RuleEngine](#)



- Using a rule directly with CMTAT and ERC-3643 tokens




Table of Contents

[RuleEngine - Rules](#)

[Schema](#)

[Table of Contents](#)

[Overview](#)

[Key Concepts](#)

[Quick Start](#)

Compatibility

Specifications

ERC-3643

ERC-721/ERC-1155

Architecture

Naming Conventions

Directory Layout

Rule - Code list

Rules as Standalone Compliance Contracts

Transfer Context Helper

Using Rules via RuleEngine

CMTAT

RuleEngine

Types of Rules

Validation Rules (Read-Only)

Operation Rules (Read-Write)

Deployment Guide

Choosing a Rule Variant

Validation Rules (Read-Only)

Operation Rules (Read-Write)

Rules details

Summary tab

Technical documentation

Operational Notes

RuleIdentityRegistry

RuleSanctionsList

RuleMaxTotalSupply

RuleWhitelistWrapper

RuleSpenderWhitelist

RuleERC2980

RuleConditionalTransferLight

General notes

Read-only (validation) rule

Whitelist

Spender whitelist

Whitelist wrapper

Architecture

Blacklist

ERC-2980 (Whitelist + Frozenlist)

Sanction list with Chainalysis

Max total supply

Identity registry

Read-Write (Operation) rule

Conditional transfer (light)

Access Control

`DEFAULT_ADMIN_ROLE` implicit role behaviour

Role Summary

Ownable2Step variants

Address List

Toolchains and Usage

Configuration

Toolchain installation

Initialization

Compilation

Contract size

- Testing
- Gas Benchmarks
- Coverage
- Other
 - Documentation
 - Format
 - Gas Snapshots
 - Anvil
 - Deploy
 - Cast
 - Help

API

- IRuleEngine
 - transferred
 - Parameters
- IERC1404
 - detectTransferRestriction
 - Parameters
 - Returns
 - messageForTransferRestriction
 - Parameters
 - Returns
- IERC1404Extend
 - REJECTED_CODE_BASE
 - detectTransferRestrictionFrom
 - Parameters
 - Returns
- IERC7551Compliance
 - canTransferFrom
 - Parameters
 - Returns
- IERC3643ComplianceRead
 - canTransfer
 - Parameters
 - Returns
- IERC3643IComplianceContract
 - transferred
 - Parameters
- Address List Management
 - addAddresses
 - Description
 - Details
 - Parameters
 - removeAddresses
 - Description
 - Details
 - Parameters
 - addAddress
 - Description
 - Details
 - Parameters
 - removeAddress
 - Description
 - Details
 - Parameters

listedAddressCount	
Description	
Returns	
contains	
Description	
Parameters	
Returns	
isAddressListed	
Description	
Parameters	
Returns	
areAddressesListed	
Description	
Parameters	
Returns	
Details	
Null address	
Duplicate address	
NonExistent Address	
IERC7943NonFungibleCompliance	
Functions	
canTransfer	
Description	
Details	
Parameters	
Returns	
IERC7943NonFungibleComplianceExtend	
Functions	
detectTransferRestriction	
Description	
Details	
Parameters	
Returns	
detectTransferRestrictionFrom	
Description	
Details	
Parameters	
Returns	
canTransferFrom	
Description	
Details	
Parameters	
Returns	
transferred	
Description	
Details	
Parameters	
RuleSanctionsList	
Constructor	
setSanctionListOracle	
Parameters	
Description	
Emits	
RuleMaxTotalSupply	
Constructor	

- setMaxTotalSupply
 - setTokenContract
- RuleConditionalTransferLight
 - bindToken
 - unbindToken
 - approveTransfer
 - cancelTransferApproval
 - approveAndTransferIfAllowed
 - approvedCount
- Security
 - Automated Analysis
 - Aderyn (v0.3.0)
 - Slither (v0.3.0)
 - Wake Arena (v0.2.0)
- Intellectual property

Overview

The **RuleEngine** is an external smart contract that applies transfer restrictions to security tokens such as **CMTAT** or [ERC-3643](#)-compatible tokens through a RuleEngine.

Rules are modular validator contracts that the `RuleEngine` or `CMTAT` compatible token can call on every transfer to ensure regulatory and business-logic compliance.

Key Concepts

- **Rules are controllers** that validate or modify token transfers.
- They can be applied:
 - Directly on **CMTAT** (no RuleEngine required), **or**
 - Through the [RuleEngine](#) (for multi-rule orchestration).
- Rules enforce conditions such as:
 - Whitelisting / blacklisting
 - Sanctions checks
 - Multi-party operator-managed lists
 - Conditional approvals
 - Arbitrary compliance logic

Quick Start

```
# 1. Clone the repository
git clone <repo-url>
cd Rules

# 2. Install Foundry (if not already installed)
# https://book.getfoundry.sh/getting-started/installation

# 3. Install submodule dependencies
forge install

# 4. Compile
forge build
```

```
# 5. Run tests
forge test
```

Compatibility

Component	Compatible Versions
Rules v0.1.0	CMTAT $\geq$ v3.0.0 RuleEngine v3.0.0-rc2

Each Rule implements the interface `IRuleEngine` defined in CMTAT.

This interface declares the ERC-3643 functions `transferred` (read-write) and `canTransfer` (read-only) with several other functions related to [ERC-1404](#), [ERC-7551](#) and [ERC-3643](#).

Specifications

ERC-3643

Each rule implements the following functions from the ERC-3643 `ICompliance` interface

```
function canTransfer(address _from, address _to, uint256 _amount) external view
returns (bool);
function transferred(address _from, address _to, uint256 _amount) external;
```

However, contrary to the RuleEngine, the whole interface is currently not implemented (e.g. `created` and `destroyed`) and as a result, the rule can not directly support ERC-3643 token.

The alternative to use a Rule with an ERC-3643 token is through the RuleEngine, which implements the whole `ICompliance` interface.

ERC-721/ERC-1155

To improve compatibility with [ERC-721](#) and [ERC-1155](#), most validation rules implement the interface `IERC7943NonFungibleComplianceExtend` which includes compliance functions with the `tokenId` argument. Operation rules (such as `RuleConditionalTransferLight`) are ERC-20 only and do not expose the ERC-721/1155 interfaces. `RuleMaxTotalSupply` is ERC-20 only as well and does not expose ERC-721/1155 interfaces.

While no rules currently apply restriction on the token id, the validation interfaces can be used to implement flexible restriction on ERC-721 or ERC-1155 tokens.

```
// IERC7943NonFungibleCompliance interface
// Read-only functions
function canTransfer(address from, address to, uint256 tokenId, uint256
amount) external view returns (bool allowed)

// IERC7943NonFungibleComplianceExtend interface
// Read-only functions
function detectTransferRestriction(address from, address to, uint256 tokenId,
uint256 amount) external view returns (uint8 code);
function detectTransferRestrictionFrom(address spender, address from, address
to, uint256 tokenId, uint256 value) external view returns (uint8 code);
function canTransferFrom(address spender, address from, address to, uint256
tokenId, uint256 value) external returns (bool allowed);

// State modifying functions (write)
function transferred(address from, address to, uint256 tokenId, uint256 value)
external;
function transferred(address spender, address from, address to, uint256
tokenId, uint256 value) external;
```

Architecture

Naming Conventions

- `*Base` contracts contain core logic without an access-control policy.
- `*InvariantStorage` contracts group constants, custom errors, and events.
- `*Common` contracts provide shared helper logic across variants (legacy naming retained for compatibility).

Directory Layout

- `src/modules/`: reusable modules shared across rules (`AccessControlModuleStandalone`, `MetaTxModuleStandalone`, `VersionModule`).
- `src/rules/interfaces/`: shared interfaces (`IAddressList`, `IIdentityRegistry`, `ISanctionsList`, `ITransferContext`).
- `src/rules/validation/abstract/`: shared base contracts and invariant storage.
- `src/rules/validation/abstract/base/`: base contracts with core rule logic (no access control).
- `src/rules/validation/abstract/core/`: shared adapters/validation helpers.
- `src/rules/validation/abstract/invariant/`: invariant storage contracts (constants, errors, events).
- `src/rules/validation/deployment/`: deployable validation rules (concrete contracts).
- `src/rules/operation/`: read-write (operation) rules that modify state on transfer.
- `test/`: Foundry tests, one folder per rule.
- `script/`: deployment scripts.

Rule - Code list

It is very important that each rule uses a unique code

Here is the list of codes used by the different rules

Contract	Constant name	Value
All	TRANSFER_OK (from CMTAT)	0
RuleWhitelist	CODE_ADDRESS_FROM_NOT_WHITELISTED	21
	CODE_ADDRESS_TO_NOT_WHITELISTED	22
	CODE_ADDRESS_SPENDER_NOT_WHITELISTED	23
	Reserved slot	24-29
RuleSanctionList	CODE_ADDRESS_FROM_IS_SANCTIONED	30
	CODE_ADDRESS_TO_IS_SANCTIONED	31
	CODE_ADDRESS_SPENDER_IS_SANCTIONED	32
	Reserved slot	33-35
RuleBlacklist	CODE_ADDRESS_FROM_IS_BLACKLISTED	36
	CODE_ADDRESS_TO_IS_BLACKLISTED	37
	CODE_ADDRESS_SPENDER_IS_BLACKLISTED	38
	Reserved slot	39-45
RuleConditionalTransferLight	CODE_TRANSFER_REQUEST_NOT_APPROVED	46
	Reserved slot	47-49
RuleMaxTotalSupply	CODE_MAX_TOTAL_SUPPLY_EXCEEDED	50
	Reserved slot	51-54
RuleIdentityRegistry	CODE_ADDRESS_FROM_NOT_VERIFIED	55
	CODE_ADDRESS_TO_NOT_VERIFIED	56
	CODE_ADDRESS_SPENDER_NOT_VERIFIED	57
	Reserved slot	58-59
RuleERC2980	CODE_ADDRESS_FROM_IS_FROZEN	60
	CODE_ADDRESS_TO_IS_FROZEN	61
	CODE_ADDRESS_SPENDER_IS_FROZEN	62
	CODE_ADDRESS_TO_NOT_WHITELISTED	63
	Reserved slot	64-65
RuleSpenderWhitelist	CODE_ADDRESS_SPENDER_NOT_WHITELISTED	66
	Reserved slot	67-70

Note:

- The CMTAT already uses the code 0-6 and the code 7-12 should be left free to allow further additions in the CMTAT.
- If you decide to create your own rules, we encourage you to use code > 100 to leave free the other restriction codes for future rules added in this project.
- Reserved slots are intentionally left unused for future rule expansion (maximum of 3 per rule).
- New rule code blocks should start at codes ending in `1` or `6` (e.g., `21`, `26`), leaving the remaining codes in the previous block for that prior rule's reserved slots.
- Current allocations are legacy; new rules should follow the start-at-1-or-6 policy without changing existing codes.

Rules as Standalone Compliance Contracts

Every rule implements the minimal interface expected by **CMTAT**, notably:

```
function transferred(address from, address to, uint256 value)
function transferred(address spender, address from, address to, uint256 value)
```

This makes rules directly pluggable into CMTAT without any intermediary RuleEngine.

Transfer Context Helper

Rules also expose an optional unified entrypoint using `MultiTokenTransferContext` / `FungibleTransferContext` (see `ITransferContext`) to pass a single struct instead of multiple arguments. This is a helper API inspired by [TokenF](#) and does not replace the standard ERC-3643 / RuleEngine interfaces. Validation rules generally expose both the non-fungible and fungible variants; `RuleConditionalTransferLight` and `RuleMaxTotalSupply` expose only the fungible variant.

Two struct variants are available:

```
// For ERC-721 / ERC-1155 (includes tokenId)
struct MultiTokenTransferContext {
    bytes4 selector; // function selector of the original call
    address sender; // operator/spender (address(0) for direct transfers)
    address from; // token sender
    address to; // token recipient
    uint256 value; // amount transferred
    uint256 tokenId; // token id (non-fungible)
    bytes data; // Optional token-provided metadata for rules
}

// For ERC-20 (no tokenId)
struct FungibleTransferContext {
    bytes4 selector; // function selector of the original call
    address sender; // operator/spender (address(0) for direct transfers)
    address from; // token sender
    address to; // token recipient
    uint256 value; // amount transferred
    bytes data; // Optional token-provided metadata for rules
}
```

Both structs are passed to `transferred(MultiTokenTransferContext calldata ctx)` or `transferred(FungibleTransferContext calldata ctx)`. If `ctx.sender` is non-zero, the spender-aware path is used internally; otherwise the standard two-party path is used. The `data` field is reserved for optional token-provided metadata that rules can interpret.

Using Rules via RuleEngine

When used through the RuleEngine, a rule must also implement:

```
interface IRule is IRuleEngine {
    function canReturnTransferRestrictionCode(uint8 restrictionCode)
        external
        view
        returns (bool);
}
```

The RuleEngine can then:

- Aggregate multiple rules
- Execute them sequentially on each transfer
- Return restriction codes
- Mutate rule state (operation rules)

CMTAT

Each rule can be directly plugged to a CMTAT token similar to a RuleEngine.

Indeed, each rule implements the required interface (`IRuleEngine`) with notably the following function as entrypoint.

```
function transferred(address from,address to,uint256 value)
function transferred(address spender,address from,address to,uint256 value)
```

```
/*
 * @title Minimum interface to define a RuleEngine
 */
interface IRuleEngine is IERC1404Extend, IERC7551Compliance,
    IERC3643IComplianceContract {
    /**
     * @notice
     * Function called whenever tokens are transferred from one wallet to
    another
     * @dev
     * Must revert if the transfer is invalid
     * Same name as ERC-3643 but with one supplementary argument `spender`
     * This function can be used to update state variables of the RuleEngine
    contract
     * This function can be called ONLY by the token contract bound to the
    RuleEngine
     * @param spender spender address (sender)
     * @param from token holder address
     * @param to receiver address
     * @param value value of tokens involved in the transfer
     */
```

```
function transferred(address spender, address from, address to, uint256
value) external;
}
```

RuleEngine

For a RuleEngine, each rule implements also the required entry point similar to CMTAT, and as well some specific interface for the RuleEngine through the implementation of `IRule` interface defined in the RuleEngine repository.

```
interface IRule is IRuleEngine {
    /**
     * @dev Returns true if the restriction code exists, and false otherwise.
     */
    function canReturnTransferRestrictionCode(
        uint8 restrictionCode
    ) external view returns (bool);
}
```

Types of Rules

There are two categories of rules: validation rules (read-only) and operation rules (read-write).

Validation Rules (Read-Only)

Validation rules only read blockchain state — they never modify it during a transfer. They implement `transferred()` as a `view` function: it re-runs the same restriction check and reverts if the transfer would be blocked, but writes nothing to storage.

All validation rules implement `IRuleEngine` to be usable both standalone (plugged directly into CMTAT) and via the RuleEngine.

Available validation rules: `RuleWhitelist`, `RuleWhitelistWrapper`, `RuleSpenderWhitelist`, `RuleBlacklist`, `RuleSanctionsList`, `RuleMaxTotalSupply`, `RuleIdentityRegistry`, `RuleERC2980`.

A community made project, [RuleSelf](#), which uses [Self](#), a zero-knowledge identity is also available but is not developed or maintained by CMTA.

Operation Rules (Read-Write)

Operation rules modify blockchain state during transfer execution. Their `transferred()` function is state-mutating: it consumes or updates stored data as part of the transfer flow.

Available operation rules: `RuleConditionalTransferLight`.

A full-featured variant, `RuleConditionalTransfer`, is maintained as a separate experimental repository at [CMTA/RuleConditionalTransfer](#).

Deployment Guide

1. Deploy the rule contract(s) with the desired admin and optional module addresses.
2. Configure the rule state and roles, including whitelist/blacklist entries and oracle or registry addresses.
3. Add rules to the RuleEngine, or set the rule directly on the CMTAT token.
4. Verify the transfer flow end-to-end with a small test transfer before enabling production flows.

Deployment scripts:

- `script/DeployCMTATWithWhitelist.s.sol`
- `script/DeployCMTATWithBlacklist.s.sol`
- `script/DeployCMTATWithBlacklistAndSanctionsList.s.sol` — CMTAT + RuleEngine with blacklist and sanctions rules

Choosing a Rule Variant

Several rules are available in multiple access-control variants. Use the simplest one that fits your needs:

- `AccessControl` variants: use when you need multi-operator roles or delegated administration.
- `Ownable2Step` variants: use when you want a safer two-step ownership transfer.

Validation Rules (Read-Only)

- Cannot modify blockchain state during transfers.
- Used for simple eligibility checks.
- Examples:
 - Whitelist
 - Whitelist Wrapper
 - Spender Whitelist
 - Blacklist
 - Sanction list (Chainalysis)
 - ERC-2980 (whitelist + frozenlist)

Operation Rules (Read-Write)

- Can update state during transfer calls.
- Example:
 - Conditional Transfer (approval-based)

Rules details

Summary tab

Rule	Type [read-only / read-write]	ERC-721 / ERC-1155	ERC-3643	Security Audit planned in the roadmap	Description
------	-------------------------------------	-----------------------	----------	---	-------------

Rule	Type [read-only / read-write]	ERC-721 / ERC-1155	ERC-3643	Security Audit planned in the roadmap	Description
RuleWhitelist	Read-only	✓	✓	✓	This rule can be used to restrict transfers from/to only addresses inside a whitelist.
RuleWhitelistWrapper	Read-Only	✓	✓	✓	This rule can be used to restrict transfers from/to only addresses inside a group of whitelist rules managed by different operators.
RuleBlacklist	Read-Only	✓	✓	✓	This rule can be used to forbid transfer from/to addresses in the blacklist
RuleSanctionList	Read-Only	✓	✓	✓	The purpose of this contract is to use the oracle contract from Chainalysis to forbid transfer from/to an address included in a sanctions designation (US, EU, or UN).
RuleMaxTotalSupply	Read-Only	✗	✓	✓	This rule limits minting so that the total supply never exceeds a configured maximum.
RuleIdentityRegistry	Read-Only	✓	✓	✓	This rule checks the ERC-3643 Identity Registry for transfer participants when configured.

Rule	Type [read-only / read-write]	ERC-721 / ERC-1155	ERC-3643	Security Audit planned in the roadmap	Description
RuleSpenderWhitelist	Read-Only	✓	✓	✓	This rule blocks <code>transferFrom</code> when the spender is not in the whitelist. Direct transfers are always allowed.
RuleERC2980	Read-Only	✓	✓	✓	ERC-2980 Swiss Compliant rule combining a whitelist (recipient-only) and a frozenlist (blocks sender, recipient, and spender for <code>transferFrom</code>). Frozenlist takes priority over whitelist.
RuleConditionalTransferLight	Read-Write	✗	✓	✓	This rule requires that transfers have to be approved by an operator before being executed. Each approval is consumed once and the same transfer can be approved multiple times.

Rule	Type [read-only / read-write]	ERC-721 / ERC-1155	ERC-3643	Security Audit planned in the roadmap	Description
RuleConditionalTransfer (external)	Read-Write	✗	✓	✗ (experimental rule)	Full-featured approval-based transfer rule implementing Swiss law <i>Vinkulierung</i> . Supports automatic approval after three months, automatic transfer execution, and a conditional whitelist for address pairs that bypass approval. Maintained in a separate repository.
RuleSelf (community)	—	✗	—	✗ (community project)	Use Self , a zero-knowledge identity solution to determine which is allowed to interact with the token. Community-maintained rule project. Not developed or maintained by CMTA.

All rules are compatible with CMTAT, as noted earlier in this README.

Technical documentation

Detailed technical documentation for each rule is available in [doc/technical/](#):

Rule	Document
RuleWhitelist	RuleWhitelist.md
RuleWhitelistWrapper	RuleWhitelistWrapper.md
RuleBlacklist	RuleBlacklist.md
RuleSanctionsList	RuleSanctionList.md
RuleMaxTotalSupply	RuleMaxTotalSupply.md

Rule	Document
RuleIdentityRegistry	RuleIdentityRegistry.md
RuleSpenderWhitelist	RuleSpenderWhitelist.md
RuleERC2980	RuleERC2980.md
RuleConditionalTransferLight	RuleConditionalTransferLight.md

Operational Notes

RuleIdentityRegistry

- `RuleIdentityRegistry`: allows burns (`to == address(0)`) even if the sender is not verified. This matters only if the token allows self-burn.
- `RuleIdentityRegistry`: can be disabled with `clearIdentityRegistry()`, which allows all transfers to pass this rule.
- `RuleIdentityRegistry`: constructor accepts `address(0)` to start in a disabled state.

RuleSanctionsList

- `RuleSanctionsList`: rejects zero address in `setSanctionListOracle`. Use `clearSanctionListOracle()` to disable checks.
- `RuleSanctionsList`: constructor accepts `address(0)` to start in a disabled state.

RuleMaxTotalSupply

- `RuleMaxTotalSupply`: trusts the configured `tokenContract` to return an accurate `totalSupply()`.
- `RuleMaxTotalSupply`: does not allow clearing the token contract; disable the rule by removing it from the RuleEngine or token.

RuleWhitelistWrapper

- `RuleWhitelistWrapper`: requires child rules that implement `IAddressList`. Gas cost grows with the number of rules, and a wrapper with zero rules rejects all transfers.

RuleSpenderWhitelist

- `RuleSpenderWhitelist`: only checks the spender in `transferFrom`; direct transfers always pass this rule.

RuleERC2980

- `RuleERC2980`: frozenlist takes priority over whitelist; an address that is both whitelisted and frozen is rejected.
- `RuleERC2980`: a frozen address acting as `transferFrom` spender is also blocked (code 62), even if `from` and `to` are not frozen.
- `RuleERC2980`: sender (`from`) does not need to be whitelisted; only recipient (`to`) must be whitelisted.

RuleConditionalTransferLight

- `RuleConditionalTransferLight`: approvals are keyed by `(from, to, value)` and are not nonce-based.
- `RuleConditionalTransferLight`: `approveAndTransferIfAllowed` approves and immediately executes `transferFrom` when this rule has allowance; it assumes token callback to `transferred()`.
- `RuleConditionalTransferLight`: `transferred()` is restricted to the single token bound via `bindToken`; second bind reverts with `RuleConditionalTransferLight_TokenAlreadyBound` until `unbindToken`.
- `RuleConditionalTransferLight`: `mints (from == address(0))` and `burns (to == address(0))` are exempt from approval checks; `created` and `destroyed` delegate to `_transferred`.

General notes

- All validation rules: read-only rules still implement `transferred()` for ERC-3643 and RuleEngine compatibility, but do not change state.
- All AccessControl variants: use `onlyRole(ROLE)` in `_authorize*` and mark internal helpers `virtual`.
- All AccessControl variants: use `AccessControlEnumerable`, so role members can be enumerated with `getRoleMember` / `getRoleMemberCount`; default admin is treated as having all roles via `hasRole`, but may not appear in role member lists unless explicitly granted.
- All meta-tx-enabled rules: `forwarderIrrevocable` is accepted as-is (including `address(0)`) and is not validated against ERC-165 because some forwarders do not implement it.
- All rules: implement `IERC3643Version` via `VersionModule` and expose `version()` returning `"0.3.0"`.

Read-only (validation) rule

Currently, there are eight validation rules: whitelist, whitelistWrapper, spender whitelist, blacklist, sanctionlist, max total supply, identity registry, and ERC-2980.

Whitelist

Only whitelisted addresses may hold or receive tokens.

Transfers are rejected if:

- `from` is not whitelisted
- `to` is not whitelisted

The rule is read-only: it only checks stored state.


- Constructor parameter `allowMintBurn` can pre-list `address(0)` for mint/burn flows.
- `allowMintBurn = false` keeps legacy behavior (operator adds `address(0)` manually if needed).

Example

During a transfer, this rule, called by the RuleEngine, will check if the address concerned is in the list, applying a read operation on the blockchain.

Usage scenario

An operator configures CMTAT to use `RuleWhitelist`. The issuer tries to mint to Alice via `mint / transfer` and the token calls `detectTransferRestriction / transferred`; Alice is not listed so the call reverts. The operator calls `addAddress (Alice)`. The issuer retries the mint and it succeeds.




Spender whitelist

This rule only checks `transferFrom` spender authorization:

- Direct transfers (`transfer`) are always allowed by this rule.
- `transferFrom` is rejected when `spender` is not listed.
- Restriction code: `66 (CODE_ADDRESS_SPENDER_NOT_WHITELISTED)`.

Usage scenario

The operator deploys `RuleSpenderWhitelist` and sets it in the token or `RuleEngine`. Alice calls `transfer` to Bob and it passes this rule. Bob then tries `transferFrom(Alice, Bob, amount)` and it is rejected until the operator calls `addAddress (Bob)` (or whichever spender account should be authorized).



Whitelist wrapper

Allows independent whitelist groups managed by different operators.


- Each operator manages a dedicated whitelist.
- A transfer is allowed only if both addresses belong to *at least one* operator-managed list.
- Enables multi-party compliance

Usage scenario

Two operators maintain separate whitelists using `addRule / setRules` and each child rule's `addAddress`. A transfer between Alice and Bob is allowed if at least one child whitelist returns `true` for both via `areAddressesListed`; otherwise `detectTransferRestriction` rejects it.

Architecture

This rule inherits from `RuleEngineValidationCommon`. Thus the whitelist rules are managed with the same architecture and code than for the ruleEngine. For example, rules are added with the functions `setRules` or `addRule`.




Blacklist

Opposite of whitelist:

- Transfer fails if **either** address is blacklisted.

Usage scenario

The operator sets `RuleBlacklist` on the token. The issuer tries to transfer to Bob; `detectTransferRestriction` passes. The operator calls `addAddress(Bob)`. A subsequent transfer to Bob is rejected until `removeAddress(Bob)` is called.




ERC-2980 (Whitelist + Frozenlist)

Implements the [ERC-2980](#) Swiss Compliant Asset Token transfer restriction using two independent address lists managed in a single rule:

- **Whitelist:** only whitelisted addresses may *receive* tokens. Senders do not need to be whitelisted and may freely transfer tokens they already hold.
- **Frozenlist:** frozen addresses are completely blocked — they can neither send nor receive tokens. Additionally, a frozen address acting as a `transferFrom` spender will have the transfer rejected (code 62), even if `from` and `to` are not frozen.
- **Priority:** frozenlist is checked first. If `from`, `to`, or `spender` is frozen, the transfer is rejected regardless of whitelist membership.
- **Burn/redemption handling:** burns (`to == address(0)`) follow the same recipient whitelist check. Constructor parameter `allowBurn` controls whether `address(0)` is whitelisted at deployment.
 - `allowBurn = false` (default-safe): burns are blocked with code 63.

- `allowBurn = true`: burns are allowed because `address(0)` is whitelisted.
- Constructors:
 - `RuleERC2980(address admin, address forwarderIrrevocable, bool allowBurn)`
 - `RuleERC2980Ownable2Step(address owner, address forwarderIrrevocable, bool allowBurn)`



Restriction codes:

Constant	Code	Meaning
<code>CODE_ADDRESS_FROM_IS_FROZEN</code>	60	Sender is frozen
<code>CODE_ADDRESS_TO_IS_FROZEN</code>	61	Recipient is frozen
<code>CODE_ADDRESS_SPENDER_IS_FROZEN</code>	62	Spender is frozen
<code>CODE_ADDRESS_TO_NOT_WHITELISTED</code>	63	Recipient is not whitelisted

Deviation from spec: the ERC-2980 `Whitelistable` / `Freezable` example interfaces define single-address management functions that return `bool` and do not revert on duplicates or missing entries. This implementation reverts on invalid single-item operations, consistent with the codebase convention. Batch operations remain non-reverting.

Usage scenario


The operator deploys `RuleERC2980` and chooses `allowBurn` according to the redemption policy. The issuer whitelists Alice with `addWhitelistAddress(Alice)`. A transfer to Alice succeeds. The compliance officer freezes Bob with `addFrozenlistAddress(Bob)`. Any transfer from or to Bob is now rejected even if Bob was previously whitelisted.

Sanction list with Chainalysis

Uses the [Chainalysis](#) Oracle to reject transfers involving sanctioned addresses.

- Checks lists for: **US**, **EU**, and **UN** sanctions.
- Documentation: *Chainalysis Oracle for sanctions screening*
- If `from` or `to` is sanctioned, transfer is rejected.

The documentation and contract addresses are available here: [Chainalysis oracle for sanctions screening](#).



Example


During a transfer, if either address (from or to) is in the sanction list of the Oracle, the rule will return false, and the transfer will be rejected by the CMTAT.

Usage scenario

The operator sets the Chainalysis oracle with `setSanctionListOracle`. The token's transfer path calls `detectTransferRestriction`; if the oracle flags `from` or `to`, the transfer is rejected. Calling `clearSanctionListOracle` disables checks.

Max total supply

Limits minting so that total supply never exceeds a configured maximum. Transfers and burns are not affected; only mints (`from == address(0)`) are checked.




Usage scenario

The operator deploys `RuleMaxTotalSupply` with `setMaxTotalSupply(1_000_000)` and sets the token with `setTokenContract`. When the issuer mints and `totalSupply + amount` exceeds the limit, `detectTransferRestriction` rejects the mint. Transfers between holders still pass.

Identity registry

If an identity registry address is set, this rule checks `isVerified` for the sender, recipient, and spender (for `transferFrom`). Zero addresses are ignored, and burns (`to == address(0)`) are always allowed so non-verified holders can burn.



Usage scenario


The operator calls `setIdentityRegistry(registry)`. The issuer attempts a transfer to Alice; `detectTransferRestriction` consults `isVerified` and rejects if Alice is unverified. After the registry marks Alice verified, the transfer succeeds. Calling `clearIdentityRegistry` disables checks.

Read-Write (Operation) rule

For the moment, there is only one operation rule available: `ConditionalTransferLight`.

Conditional transfer (light)

This rule requires that transfers must be approved by an operator before being executed. It hashes `(from, to, value)` to track approvals and allows the same transfer to be approved multiple times. Each successful transfer consumes one approval, applying a write operation on the blockchain. Mints (`from == address(0)`) and burns (`to == address(0)`) are exempt and always pass without requiring approval.



Usage scenario

An operator calls `approveTransfer(from, to, value)`. The compliance manager binds exactly one token with `bindToken(token)`; attempting to bind a second token reverts. The token calls `detectTransferRestriction` (passes) and later `transferred` to consume the approval. Without approval, `detectTransferRestriction` returns code 46 and the transfer is rejected. The operator can revoke with `cancelTransferApproval`. To migrate to a different token, the compliance manager must first call `unbindToken` before binding the new one.

Access Control

The module `AccessControlModuleStandalone` implements RBAC access control by inheriting from OpenZeppelin's `AccessControlEnumerable`.

Each rule implements its own access control by inheriting from `AccessControlModuleStandalone`. The default admin is the address passed as `admin` to the constructor at deployment.

`DEFAULT_ADMIN_ROLE` implicit role behaviour

`AccessControlModuleStandalone` overrides OpenZeppelin's `hasRole` so that any account holding `DEFAULT_ADMIN_ROLE` returns `true` for **every** role check. This is intentional: the OpenZeppelin `DEFAULT_ADMIN_ROLE` holder can already grant itself any role at any time, so treating it as implicitly holding all roles from the start removes unnecessary ceremony and makes access management easier in practice.

Practical consequences integrators must be aware of:

- **grantRole to a default admin is a no-op.** `_grantRole` checks `!hasRole(role, account)` before writing storage; since the admin already returns `true` via the override, the storage

write and the `RoleGranted` event are skipped. The admin will **not** appear in `getRoleMember` / `getRoleMemberCount` enumerations for non-default roles unless the role was explicitly granted before the admin was set.

- `revokeRole` / `renounceRole` on a non-default role for a default admin are misleading. They emit `RoleRevoked` and clear the storage flag, but `hasRole` continues to return `true` because the account still holds `DEFAULT_ADMIN_ROLE`. The effective privilege is unchanged. To fully remove access, `DEFAULT_ADMIN_ROLE` itself must be revoked.
- **Off-chain monitoring** should use `hasRole` queries, not role-membership events or enumeration, to determine the effective privileges of admin accounts.

See also [docs.openzeppelin.com - AccessControl](https://docs.openzeppelin.com/AccessControl)

Role Summary

Role	Hash	Functions (by rule)
<code>DEFAULT_ADMIN_ROLE</code>	<code>0x00</code>	<code>grantRole</code> , <code>revokeRole</code> , <code>renounceRole</code> (all AccessControl rules); <code>setCheckSpender</code> (RuleWhitelist, RuleWhitelistWrapper); <code>setMaxTotalSupply</code> , <code>setTokenContract</code> (RuleMaxTotalSupply); <code>setIdentityRegistry</code> , <code>clearIdentityRegistry</code> (RuleIdentityRegistry)
<code>ADDRESS_LIST_ADD_ROLE</code>	<code>0x1b03c849816e077359373cf0a8d6d8f741d643bc1e95273ffe11515f83beb61</code>	<code>addAddress</code> , <code>addAddresses</code> (RuleWhitelist, RuleBlacklist)
<code>ADDRESS_LIST_REMOVE_ROLE</code>	<code>0x1b94c92b564251ed6b49246d9a82eb7a486b6490f3b3a3bf3b28d2e99801f3ec</code>	<code>removeAddress</code> , <code>removeAddresses</code> (RuleWhitelist, RuleBlacklist)
<code>SANCTIONLIST_ROLE</code>	<code>0x30842281ac34bdc7d568c7ab276f84ba6fca1de1ae858b0afd35e716fb0650d</code>	<code>setSanctionListOracle</code> , <code>clearSanctionListOracle</code> (RuleSanctionsList)
<code>RULES_MANAGEMENT_ROLE</code>	<code>0xea5f4eb72290e50c32abd6c23e45de3d8300b3286e1cbc2e293114b92e034e5e</code>	<code>setRules</code> , <code>clearRules</code> , <code>addRule</code> , <code>removeRule</code> (RuleWhitelistWrapper)
<code>OPERATOR_ROLE</code>	<code>0x97667070c54ef182b0f5858b034beac1b6f3089aa2d3188bb1e8929f4fa9b929</code>	<code>approveTransfer</code> , <code>cancelTransferApproval</code> (RuleConditionalTransferLight)
<code>COMPLIANCE_MANAGER_ROLE</code>	<code>0xe5c50d0927e06141e032cb9a67e1d7092dc85c0b0825191f7e1ced600028568</code>	<code>bindToken</code> , <code>unbindToken</code> (RuleConditionalTransferLight)
<code>WHITELIST_ADD_ROLE</code>	<code>0x77c0b4c0975a0b0417d8ce295502737b95fee8923755fed0cce952907a1861ed</code>	<code>addWhitelistAddress</code> , <code>addWhitelistAddresses</code> (RuleERC2980)
<code>WHITELIST_REMOVE_ROLE</code>	<code>0xf4d11a530c5b90f459c6ab1e335d3d77156b8ff3093308e4fca6d10ee87ade9</code>	<code>removeWhitelistAddress</code> , <code>removeWhitelistAddresses</code> (RuleERC2980)
<code>FROZENLIST_ADD_ROLE</code>	<code>0xc52c49807a071974b9260f4b553ee09bd9fd85f687d8d4cc3232de7104ff7835</code>	<code>addFrozenlistAddress</code> , <code>addFrozenlistAddresses</code> (RuleERC2980)
<code>FROZENLIST_REMOVE_ROLE</code>	<code>0x8be92b33a413d98540bfb0edc9129253db6d924f6c2e32c4b7809d237f7b2aaa</code>	<code>removeFrozenlistAddress</code> , <code>removeFrozenlistAddresses</code> (RuleERC2980)

Ownable2Step variants

For simpler ownership-based control, `Ownable2Step` variants (two-step ownership transfer) are available:

- `RuleWhitelistOwnable2Step`
- `RuleBlacklistOwnable2Step`
- `RuleWhitelistWrapperOwnable2Step`
- `RuleSanctionsListOwnable2Step`
- `RuleIdentityRegistryOwnable2Step`

- `RuleMaxTotalSupplyOwnable2Step`
- `RuleERC2980Ownable2Step`
- `RuleConditionalTransferLightOwnable2Step`

`RuleConditionalTransferLightOwnable2Step` now grants approval and execution permissions exclusively to the owner.

All `Ownable2Step` variants enforce access using OpenZeppelin's `onlyOwner` modifier.

Address List

Common access control between `blacklistRule` and `WhitelistRule`

These roles are listed above in the Role Summary table.

Toolchains and Usage

Configuration

Here are the settings for [Hardhat](#) and [Foundry](#).

- `hardhat.config.js`
 - Solidity [v0.8.34](#)
 - EVM version: Prague (Pectra upgrade)
 - Optimizer: true, 200 runs
- `foundry.toml`
 - Solidity [v0.8.34](#)
 - EVM version: Prague (Pectra upgrade)
 - Optimizer: true, 200 runs
- Library
 - Foundry [v1.5.0](#)
 - Forge std [v1.12.0](#)
 - OpenZeppelin Contracts (submodule) [v5.6.1](#)
 - OpenZeppelin Contracts Upgradeable (submodule) [v5.6.1](#)
 - CMTAT [v3.2.0](#)
 - RuleEngine [v3.0.0-rc2](#)

Toolchain installation

This repository is primarily developed and tested with [Foundry](#), a smart contract development toolchain.

Hardhat configuration is also present to support contract compilation and a small smoke test with Hardhat.

To install the Foundry suite, please refer to the official instructions in the [Foundry book](#).

Initialization

You must first initialize the submodules, with

```
forge install
```

See also the command's [documentation](#).

Later you can update all the submodules with:

```
forge update
```

See also the command's [documentation](#).

Compilation

The official documentation is available in the Foundry [website](#)

```
forge build
```

Hardhat compilation (optional):

```
npm run hardhat:compile
```

Contract size

```
forge compile --sizes
```

Testing

You can run the tests with

```
forge test
```

Hardhat smoke test (optional):

```
npm run hardhat:test:smoke
```

To run a specific test, use

```
forge test --match-contract <contract name> --match-test <function name>
```

- For `RuleConditionalTransferLight` fuzz/integration tests, note that mint and burn paths (`from == address(0)` or `to == address(0)`) are intentionally exempt from approval consumption.
- Ownable2Step variants also include dedicated tests for ownership transfer and manager-only functions (`IdentityRegistry`, `MaxTotalSupply`, `SanctionsList`).
- Coverage-focused tests also target deployment wrappers and operation-rule overloads (`created`, `destroyed`, `spender-aware` `transferred`) to improve line/function coverage in `src/rules/operation` and `src/rules/validation/deployment`.

Generate gas report

```
forge test --gas-report
```

See also the test framework's [official documentation](#), and that of the [test commands](#).

Gas Benchmarks

Gas usage is tracked in two complementary files:

- **.gas-snapshot** — machine-generated file produced by `forge snapshot`. It records the gas cost of every test function and is checked into the repository so that gas regressions are visible in diffs. Regenerate it with:

```
forge snapshot
```

To check for regressions against the committed snapshot without overwriting it:

```
forge snapshot --check
```

- **doc/GAS.md** — human-readable summary of key operation costs (e.g. `addAddress`, `detectTransferRestriction`) with the date of the last measurement. Update it manually after running `forge snapshot` when behaviour or gas costs change.

Coverage

LCOV - code coverage report						
Current view: top level		Hit		Total	Coverage	
Test: lcov.info		Lines:	765	782	97.8 %	
Date: 2026-04-15 15:25:09		Functions:	270	287	94.1 %	
		Branches:	163	163	100.0 %	
Directory	Line Coverage	Functions	Branches			
src/modules	100.0 % 9 / 9	100.0 % 3 / 3	100.0 % 4 / 4			
src/rules/operation	100.0 % 18 / 18	100.0 % 6 / 6	- 0 / 0			
src/rules/operation/abstract	97.4 % 76 / 78	91.7 % 22 / 24	100.0 % 18 / 18			
src/rules/validation/abstract/RuleAddressSet	96.3 % 52 / 54	90.5 % 19 / 21	100.0 % 8 / 8			
src/rules/validation/abstract/RuleERC2988	100.0 % 36 / 36	100.0 % 12 / 12	100.0 % 8 / 8			
src/rules/validation/abstract/base	97.7 % 385 / 394	92.4 % 110 / 119	100.0 % 111 / 111			
src/rules/validation/abstract/core	93.3 % 56 / 60	82.6 % 19 / 23	100.0 % 14 / 14			
src/rules/validation/deployment	100.0 % 133 / 133	100.0 % 79 / 79	- 0 / 0			

Generated by: LCOV version 1.16

A code coverage is available in [index.html](#).

- Perform a code coverage

```
forge coverage
```

- Generate LCOV report

```
forge coverage --report lcov
```

- Generate `index.html`

```
forge coverage --no-match-coverage "(script|mocks|test)" --report lcov &&  
genhtml lcov.info --branch-coverage --prefix "$PWD/" --output-dir coverage
```

See [Solidity Coverage in VS Code with Foundry](#) & [Foundry forge coverage](#)

Other

Foundry is a blazing fast, portable and modular toolkit for Ethereum application development written in Rust.

Foundry consists of:

- **Forge**: Ethereum testing framework (like Truffle, Hardhat and DappTools).

- **Cast**: Swiss army knife for interacting with EVM smart contracts, sending transactions and getting chain data.
- **Anvil**: Local Ethereum node, akin to Ganache, Hardhat Network.
- **Chisel**: Fast, utilitarian, and verbose solidity REPL.

Documentation

<https://book.getfoundry.sh/>

Format

```
$ forge fmt
```

Gas Snapshots

```
$ forge snapshot
```

Anvil

```
$ anvil
```

Deploy

Warning — private key security

Passing `--private-key` directly on the command line is **not recommended** in production: the key is visible in your shell history and to any process that can read `/proc`. Prefer hardware wallets (`--ledger`, `--trezor`), encrypted keystores (`--account <keystore>`), or environment-variable signers. See [Foundry best practices](#) for details.

```
$ forge script script/DeployCMTATWithWhitelist.s.sol --rpc-url <your_rpc_url> -  
-private-key <your_private_key>  
$ forge script script/DeployCMTATWithBlacklist.s.sol --rpc-url <your_rpc_url> -  
-private-key <your_private_key>  
$ forge script script/DeployCMTATWithBlacklistAndSanctionsList.s.sol --rpc-url  
<your_rpc_url> --private-key <your_private_key>
```

Cast

```
$ cast <subcommand>
```

Help

```
$ forge --help  
$ anvil --help  
$ cast --help
```

API

IRuleEngine

All rules implement `IRuleEngine`. The behaviour of `transferred()` differs by rule type:

- **Validation rules** implement `transferred()` as `view`: it re-runs the restriction check and reverts if the transfer would be blocked, but does not modify state.
- **Operation rules** implement `transferred()` as a state-mutating function: it updates storage as part of the transfer (e.g. consuming an approval in `RuleConditionalTransferLight`).

transferred

```
function transferred(address spender, address from, address to, uint256 value)
    external;
```

Called by a token or RuleEngine after a transfer. For validation rules, enforces the restriction check. For operation rules, mutates internal state.

Parameters

Name	Type	Description
<code>spender</code>	<code>address</code>	Address executing the transfer (owner, operator, or approved).
<code>from</code>	<code>address</code>	Current token holder.
<code>to</code>	<code>address</code>	Recipient address.
<code>value</code>	<code>uint256</code>	Amount transferred.

IERC1404

detectTransferRestriction

```
function detectTransferRestriction(address from, address to, uint256 value)
    external
    view
    returns (uint8);
```

Returns a restriction code describing why a transfer is blocked.

Parameters

Name	Type	Description
<code>from</code>	<code>address</code>	Sender address.
<code>to</code>	<code>address</code>	Recipient address.
<code>value</code>	<code>uint256</code>	Amount being transferred.

Returns

Name	Type	Description
0	uint8	Transfer allowed.
other	uint8	Implementation-defined restriction code.

messageForTransferRestriction

```
function messageForTransferRestriction(uint8 restrictionCode)
    external
    view
    returns (string memory);
```

Returns a human-readable message associated with a restriction code.

Parameters

Name	Type	Description
restrictionCode	uint8	Restriction code returned by <code>detectTransferRestriction</code> .

Returns

Name	Type	Description
message	string	Explanation for the restriction code.

IERC1404Extend

REJECTED_CODE_BASE

```
enum REJECTED_CODE_BASE {
    TRANSFER_OK,
    TRANSFER_REJECTED_DEACTIVATED,
    TRANSFER_REJECTED_PAUSED,
    TRANSFER_REJECTED_FROM_FROZEN,
    TRANSFER_REJECTED_TO_FROZEN,
    TRANSFER_REJECTED_SPENDER_FROZEN,
    TRANSFER_REJECTED_FROM_INSUFFICIENT_ACTIVE_BALANCE
}
```

Base transfer restriction codes used by ERC-1404 extensions.

detectTransferRestrictionFrom

```
function detectTransferRestrictionFrom(
    address spender,
    address from,
    address to,
    uint256 value
)
    external
    view
    returns (uint8);
```

Restriction code for transfers performed by a spender (approved operator).

Parameters

Name	Type	Description
<code>spender</code>	<code>address</code>	Address performing the transfer.
<code>from</code>	<code>address</code>	Current token owner.
<code>to</code>	<code>address</code>	Recipient address.
<code>value</code>	<code>uint256</code>	Transfer amount.

Returns

Name	Type	Description
<code>code</code>	<code>uint8</code>	0 if transfer allowed, otherwise a restriction code.

IERC7551Compliance

canTransferFrom

```
function canTransferFrom(address spender, address from, address to, uint256
value)
    external
    view
    returns (bool);
```

Determines if a spender-initiated transfer is permitted.

Parameters

Name	Type	Description
<code>spender</code>	<code>address</code>	Caller executing transfer.
<code>from</code>	<code>address</code>	Token owner.
<code>to</code>	<code>address</code>	Recipient.

Name	Type	Description
<code>value</code>	<code>uint256</code>	Amount.

Returns

Name	Type	Description
<code>allowed</code>	<code>bool</code>	<code>true</code> if transfer permitted.

IERC3643ComplianceRead

canTransfer

```
function canTransfer(address from, address to, uint256 value)
    external
    view
    returns (bool isValid);
```

Returns whether a transfer is compliant.

Parameters

Name	Type	Description
<code>from</code>	<code>address</code>	Sender.
<code>to</code>	<code>address</code>	Receiver.
<code>value</code>	<code>uint256</code>	Transfer amount.

Returns

Name	Type	Description
<code>isValid</code>	<code>bool</code>	<code>true</code> if compliant.

IERC3643IComplianceContract

transferred

```
function transferred(address from, address to, uint256 value)
    external;
```

Hook invoked during an ERC-20 token transfer.

Parameters

Name	Type	Description
<code>from</code>	<code>address</code>	Previous owner.
<code>to</code>	<code>address</code>	New owner.
<code>value</code>	<code>uint256</code>	Amount transferred.

Address List Management

This API is common to whitelist and blacklist rules

addAddresses

```
function addAddresses(address[] calldata targetAddresses)
    public
    onlyAddressListAdd
```

Description

Adds multiple addresses to the internal address set.

Details

- Does **not** revert if one or more addresses are already listed.
- Restricted by the rule's access control policy (role- or owner-based).
- Emits `AddAddresses`. Skipped/added counts are not emitted to keep gas cost minimal.

Parameters

Name	Type	Description
<code>targetAddresses</code>	<code>address[]</code>	Array of addresses to be added to the set.

removeAddresses

```
function removeAddresses(address[] calldata targetAddresses)
    public
    onlyAddressListRemove
```

Description

Removes multiple addresses from the internal set.

Details

- Does **not** revert if an address is not currently listed.
- Restricted by the rule's access control policy (role- or owner-based).
- Emits `RemoveAddresses`. Skipped/removed counts are not emitted to keep gas cost minimal.

Parameters

Name	Type	Description
<code>targetAddresses</code>	<code>address[]</code>	Array of addresses to be removed.

addAddress

```
function addAddress(address targetAddress)
    public
    onlyAddressListAdd
```

Description

Adds a **single** address to the set.

Details

- **Reverts** if the address is already listed.
- Restricted by the rule's access control policy (role- or owner-based).
- Emits an `AddAddress` event.

Parameters

Name	Type	Description
<code>targetAddress</code>	<code>address</code>	Address to add.

removeAddress

```
function removeAddress(address targetAddress)
    public
    onlyAddressListRemove
```

Description

Removes a **single** address from the set.

Details

- **Reverts** if the address is not listed.
- Restricted by the rule's access control policy (role- or owner-based).
- Emits a `RemoveAddress` event.

Parameters

Name	Type	Description
<code>targetAddress</code>	<code>address</code>	Address to remove.

listedAddressCount

```
function listedAddressCount() public view returns (uint256 count)
```

Description

Returns the total number of addresses currently listed in the internal set.

Returns

Name	Type	Description
<code>count</code>	<code>uint256</code>	Total number of listed addresses.

contains

```
function contains(address targetAddress)
    public
    view
    override (IIIdentityRegistryContains)
    returns (bool isListed)
```

Description

Checks whether a specific address is listed.

Implements `IIIdentityRegistryContains`.

Parameters

Name	Type	Description
<code>targetAddress</code>	<code>address</code>	Address to check.

Returns

Name	Type	Description
<code>isListed</code>	<code>bool</code>	<code>true</code> if the address is listed, otherwise <code>false</code> .

isAddressListed

```
function isAddressListed(address targetAddress)
    public
    view
    returns (bool isListed)
```

Description

Returns whether a given address is included in the internal set.

Parameters

Name	Type	Description
<code>targetAddress</code>	<code>address</code>	Address to check.

Returns

Name	Type	Description
<code>isListed</code>	<code>bool</code>	Listing status.

areAddressesListed

```
function areAddressesListed(address[] memory targetAddresses)
    public
    view
    returns (bool[] memory results)
```

Description

Checks the listing status of multiple addresses in a single call.

Parameters

Name	Type	Description
<code>targetAddresses</code>	<code>address[]</code>	Array of addresses to check.

Returns

Name	Type	Description
<code>results</code>	<code>bool[]</code>	Array of boolean listing results, aligned by index.

Details

Null address

It is possible to add the null address (0x0) to the address list. In a whitelist, this enables mint/burn flows (since `from/to` can be zero). In a blacklist, adding `0x0` blocks mint/burn.

For `RuleWhitelist`, you can also pre-list `0x0` at deployment using the constructor parameter `allowMintBurn=true`.

Duplicate address

addAddress

If the address already exists, the transaction is reverted to save gas.

addAddresses

If one of the addresses already exist, there is no change for this address. The transaction remains valid (no revert).

NonExistent Address

removeAddress

If the address does not exist in the whitelist, the transaction is reverted to save gas.

removeAddresses

If the address does not exist in the whitelist, there is no change for this address. The transaction remains valid (no revert).

IERC7943NonFungibleCompliance

Compliance interface for ERC-721 / ERC-1155-style non-fungible assets. This is implemented by validation rules only. `RuleConditionalTransferLight` and `RuleMaxTotalSupply` are ERC-20 only and do not implement this interface.

For ERC-721, `amount` must always be `1`.

Functions

Name	Description
<code>canTransfer</code>	Verifies whether a transfer is permitted according to the token's compliance rules.

canTransfer

```
function canTransfer(  
    address from,  
    address to,  
    uint256 tokenId,  
    uint256 amount  
) external view returns (bool allowed)
```

Description

Verifies whether a token transfer is permitted according to the rule-based compliance logic.

Details

- Must not modify state.
- May enforce checks such as allowlists, blocklists, freezing, transfer limits, regulatory rules.
- Must return `false` if the transfer is not permitted.

Parameters

Name	Type	Description
<code>from</code>	<code>address</code>	Current token owner.
<code>to</code>	<code>address</code>	Receiving address.
<code>tokenId</code>	<code>uint256</code>	Token ID.
<code>amount</code>	<code>uint256</code>	Transfer amount (always <code>1</code> for ERC-721).

Returns

Name	Type	Description
<code>allowed</code>	<code>bool</code>	<code>true</code> if transfer is allowed; otherwise <code>false</code> .

IERC7943NonFungibleComplianceExtend

Extended compliance interface for ERC-721 / ERC-1155 non-fungible assets. This is implemented by validation rules only. `RuleConditionalTransferLight` and `RuleMaxTotalSupply` are ERC-20 only and do not implement this interface.

Adds restriction-code reporting, spender-aware checks, and a post-transfer hook.

For ERC-721, `amount` / `value` must always be `1`.

Functions

Name	Description
<code>detectTransferRestriction</code>	Returns a restriction code indicating why a transfer is blocked.
<code>detectTransferRestrictionFrom</code>	Returns a restriction code for a spender-initiated transfer.
<code>canTransferFrom</code>	Checks whether a spender-initiated transfer is allowed.
<code>transferred</code>	Notifies the compliance engine that a transfer has occurred.

`detectTransferRestriction`

```
function detectTransferRestriction(  
    address from,  
    address to,  
    uint256 tokenId,  
    uint256 amount  
) external view returns (uint8 code)
```

Description

Returns a restriction code describing whether and why a transfer is blocked.

Details

- Must not modify state.
- Must return `0` when the transfer is allowed.
- Non-zero codes should follow ERC-1404 or similar standards.

Parameters

Name	Type	Description
<code>from</code>	<code>address</code>	Current token holder.
<code>to</code>	<code>address</code>	Receiving address.
<code>tokenId</code>	<code>uint256</code>	Token ID.
<code>amount</code>	<code>uint256</code>	Transfer amount (<code>1</code> for ERC-721).

Returns

Name	Type	Description
<code>code</code>	<code>uint8</code>	<code>0</code> if allowed; otherwise a restriction code.

detectTransferRestrictionFrom

```
function detectTransferRestrictionFrom(  
    address spender,  
    address from,  
    address to,  
    uint256 tokenId,  
    uint256 value  
) external view returns (uint8 code)
```

Description

Returns a restriction code for a transfer initiated by a spender (approved operator or owner).

Details

- Must not modify state.
- Must return `0` when the transfer is permitted.

Parameters

Name	Type	Description
<code>spender</code>	<code>address</code>	Address performing the transfer.
<code>from</code>	<code>address</code>	Current owner.

Name	Type	Description
<code>to</code>	<code>address</code>	Recipient address.
<code>tokenId</code>	<code>uint256</code>	Token ID being checked.
<code>value</code>	<code>uint256</code>	Transfer amount (<code>1</code> for ERC-721).

Returns

Name	Type	Description
<code>code</code>	<code>uint8</code>	<code>0</code> if allowed; otherwise restriction code.

canTransferFrom

```
function canTransferFrom(
    address spender,
    address from,
    address to,
    uint256 tokenId,
    uint256 value
) external view returns (bool allowed)
```

Description

Checks whether a spender-initiated transfer is allowed under the compliance rules.

Details

- Must not modify state.
- Should internally use `detectTransferRestrictionFrom`.

Parameters

Name	Type	Description
<code>spender</code>	<code>address</code>	Address executing the transfer.
<code>from</code>	<code>address</code>	Current owner.
<code>to</code>	<code>address</code>	Recipient.
<code>tokenId</code>	<code>uint256</code>	Token ID.
<code>value</code>	<code>uint256</code>	Transfer amount (<code>1</code> for ERC-721 token).

Returns

Name	Type	Description
<code>allowed</code>	<code>bool</code>	<code>true</code> if transfer is allowed.

transferred

```
function transferred(  
    address spender,  
    address from,  
    address to,  
    uint256 tokenId,  
    uint256 value  
) external
```

Description

Signals to the compliance engine that a transfer has successfully occurred.

Details

- May modify compliance state.
- For stateful rules, should be called by the token contract or RuleEngine after a successful transfer.
- Rules may enforce access control on callers depending on their policy.

Parameters

Name	Type	Description
<code>spender</code>	<code>address</code>	Address executing the transfer.
<code>from</code>	<code>address</code>	Previous owner.
<code>to</code>	<code>address</code>	New owner.
<code>tokenId</code>	<code>uint256</code>	Token transferred.
<code>value</code>	<code>uint256</code>	Transfer amount (<code>1</code> for ERC-721 token).

RuleSanctionsList

Compliance rule enforcing sanctions-screening for token transfers.

Integrates a sanctions-oracle (e.g., Chainalysis) to block transfers when the sender, recipient, or spender is sanctioned.

Constructor

```
constructor(address admin, address forwarderIrrevocable, ISanctionsList  
sanctionContractOracle_)
```

Initializes access control, meta-transaction forwarder, and optionally the sanctions oracle.

setSanctionListOracle

```
function setSanctionListOracle(ISanctionsList sanctionContractOracle_)
    public
    virtual
    onlyRole (SANCTIONLIST_ROLE)
```

Set the sanctions-oracle contract used for transfer-restriction checks.

Parameters

Name	Type	Description
<code>sanctionContractOracle_</code>	<code>ISanctionsList</code>	Address of the sanctions-oracle. Zero address is not allowed; use <code>clearSanctionListOracle</code> .

Description

Updates the sanctions-oracle contract reference.

This function may only be called by accounts granted the `SANCTIONLIST_ROLE`.

Passing the zero address reverts; use `clearSanctionListOracle` to disable checks.

Emits

Event	Description
<code>SetSanctionListOracle(address)</code>	Emitted when the sanctions-oracle address is updated.

RuleMaxTotalSupply

Compliance rule that caps total token supply; only mints (`from == address(0)`) are restricted.

Constructor

```
constructor(address admin, address tokenContract_, uint256 maxTotalSupply_)
```

Initializes access control, the token contract, and the max supply.

setMaxTotalSupply

```
function setMaxTotalSupply(uint256 newMaxTotalSupply)
    public
    virtual
    onlyRole (DEFAULT_ADMIN_ROLE)
```

Updates the configured maximum supply.

setTokenContract

```
function setTokenContract(address tokenContract_)
    public
    virtual
    onlyRole(DEFAULT_ADMIN_ROLE)
```

Sets the token contract used to read `totalSupply()`.

RuleConditionalTransferLight

Operation rule requiring explicit approval before a transfer executes.

bindToken

```
function bindToken(address token)
    public
    onlyRole(COMPLIANCE_MANAGER_ROLE)
```

Binds a token so it may call `transferred()`.

unbindToken

```
function unbindToken(address token)
    public
    onlyRole(COMPLIANCE_MANAGER_ROLE)
```

Revokes the token binding.

approveTransfer

```
function approveTransfer(address from, address to, uint256 value)
    public
    onlyTransferApprover
```

Approves one transfer (consumed on execution).

cancelTransferApproval

```
function cancelTransferApproval(address from, address to, uint256 value)
    public
    onlyTransferApprover
```

Removes one approval for the transfer.

approveAndTransferIfAllowed

```
function approveAndTransferIfAllowed(address from, address to, uint256 value)
    public
    onlyTransferApprover
    returns (bool)
```

Approves then calls `SafeERC20.safeTransferFrom` on the bound token using this rule as spender.

approvedCount

```
function approvedCount(address from, address to, uint256 value)
    public
    view
    returns (uint256)
```

Returns the number of approvals for the transfer hash.

Security

Automated Analysis

Latest tool outputs for this release cycle (including feedback documents) are available in

[doc/security/audits/tools/v0.3.0/](#).

`v0.3.0` cleanup: removed unused `RuleConditionalTransferLight_TransferFailed` custom error after SafeERC20 migration.

Aderyn (v0.3.0)

Static analysis was performed with [Aderyn](#). The full report and the project team's feedback are available in [doc/security/audits/tools/v0.3.0/](#).

ID	Title	Instances	Verdict
L-1	Centralization Risk	46	Acknowledged — by design (regulated token issuer model)
L-2	Unspecific Solidity Pragma	54	Acknowledged — intentional for a library
L-3	Address State Variable Set Without Checks	1	False positive — check enforced in public-facing function
L-4	PUSH0 Opcode	54	Acknowledged — project targets Prague EVM
L-5	Modifier Invoked Only Once	2	Acknowledged — template method pattern; inlining would break abstraction
L-6	Empty Block	38	Acknowledged — <code>_authorize*()</code> hooks use modifiers; intentional no-op implementations in required interface paths
L-7	Costly operations inside loop	6	Acknowledged — unavoidable (<code>EnumerableSet</code> requires one <code>SSTORE</code> per element)
L-8	Unchecked Return	13	Mixed — mostly false positives (<code>void</code> helpers or pre-checked single-item paths); constructor <code>_grantRole</code> intentionally ignored

No high-severity issues were reported.

Slither (v0.3.0)

Static analysis was performed with [Slither](#). The full report and the project team's feedback are available in [doc/security/audits/tools/v0.3.0/](#).

Category	Severity	Instances	Verdict
arbitrary-send-erc20	High	1	False positive — <code>from</code> is guarded by <code>onlyTransferApprover</code> , ERC-20 allowance check, and a pre-recorded approval
unused-return	Medium	6	False positive — existence pre-checked at public layer before calling internal helper
calls-loop	Low	16	Acknowledged — by design; wrapper must query each child rule; child rules are read-only
assembly	Informational	1	Acknowledged — intentional gas optimisation in <code>_transferHash</code> ; minimal and well-scoped
naming-convention	Informational	2	Acknowledged — parameter names match ERC-2980 spec
unindexed-event-address	Informational	2	Out of scope (both in <code>lib/RuleEngine</code>); <code>IAddressList</code> events previously fixed
unused-state	Informational	8	False positive — <code>RuleNFTAdapter</code> constants used in base dispatch logic; Slither per-contract analysis limitation

Wake Arena (v0.2.0)

AI-assisted static analysis was performed with [Wake Arena](#) by Ackee Blockchain Security. The full report and the project team's feedback are available in [doc/security/audits/tools/v0.2.0/](#).

Ackee Blockchain Security, Wake Arena AI Report | CMTA: Rules, March 16, 2026 18:00 UTC.

ID	Title	Severity	Confidence	Verdict
H-1	ConditionalTransferLight approvals not scoped by token	High	High	Fixed — single-token binding enforced in <code>bindToken</code> ; <code>RuleConditionalTransferLight_TokenAlreadyBound</code> error added
M-1	Incomplete <code>supportsInterface</code> breaks ERC-165 discovery	Medium	High	Fixed — pre-computed constants + <code>IERC7551Compliance</code> + full ERC-3643 <code>ICompliance</code> ID (<code>IERC3643ComplianceFull</code> , <code>0x3144991c</code>) added
I-1	RuleERC2980 docs omit frozen spender on <code>transferFrom</code>	Informational	High	Fixed (doc only) — README, <code>AGENTS.md</code> , and <code>CLAUDE.md</code> updated to document spender freeze path

ID	Title	Severity	Confidence	Verdict
I-2	<code>hasRole</code> override: admin implicitly passes all role checks	Informational	High	Fixed (doc only) — dedicated section added to README documenting intentional design and off-chain monitoring guidance

Intellectual property

The code is copyright (c) Capital Market and Technology Association, 2022-2026, and is released under [Mozilla Public License 2.0](#).