

Workstream Comparison: NetworksElectoral-Competition (GPT-5 vs GPT-5-nano)

Inputs

- Baseline (archive): `reports/archived/workflow-report-cf1d92ff869046f39b7319007e9a7835.json`
- Variant (current): `reports/workflow-report-c52a4b6842704aac8c4258c71def4e29.json`

Schema

Field	Type	Purpose
<code>comparison_group_id</code>	<code>text</code>	Logical key that groups runs into one composed workstream comparison
<code>source_bucket</code>	<code>'enum(archive, current)'</code>	
<code>report_path</code>	<code>text</code>	Path to the source workflow-report JSON used for this row.
<code>run_id</code>	<code>text</code>	Unique workflow execution identifier.
<code>papers_dir</code>	<code>text</code>	Input paper path(s) processed by the run.
<code>started_at</code>	<code>timestampz</code>	Workflow start timestamp.
<code>finished_at</code>	<code>timestampz</code>	Workflow end timestamp.
<code>duration_sec</code>	<code>numeric</code>	Run duration in seconds for cost/latency comparison.
<code>chat_model</code>	<code>text</code>	Primary LLM used by the run.
<code>embedding_model</code>	<code>text</code>	Embedding model used for retrieval/chunk similarity.
<code>report_question_set</code>	<code>enum</code>	Question set mode (structured or agentic)
<code>report_question_count</code>	<code>integer</code>	Number of structured/agentic report question records emitted.
<code>agentic_status</code>	<code>text</code>	Top-level status for agentic stage.
<code>index_status</code>	<code>text</code>	Top-level status for index stage.
<code>index_reason_or_error</code>	<code>text</code>	Failure/skipped reason to diagnose differences.
<code>report_store_status</code>	<code>text</code>	Whether report was stored to Postgres.
<code>prep_corpus_hash</code>	<code>text</code>	Fingerprint of corpus content; validates same input set.
<code>config_hash</code>	<code>text</code>	Effective configuration hash; validates run comparability.
<code>confidence_mean</code>	<code>numeric</code>	Mean confidence score across structured questions.
<code>confidence_labels</code>	<code>text</code>	Label distribution summary for quick quality profile.
<code>final_answer_preview</code>	<code>text</code>	Truncated synthesis preview for side-by-side semantic comparison

Records

<code>comparison_group_id</code>	<code>source_bucket</code>	<code>report_path</code>
<code>networks-electoral-competition-gpt5-vs-gpt5-nano-v1</code>	<code>archive</code>	<code>reports/archived/workflow-report-cf1d92ff869046f39b7319007e9a7835.json</code>
<code>networks-electoral-competition-gpt5-vs-gpt5-nano-v1</code>	<code>current</code>	<code>reports/workflow-report-c52a4b6842704aac8c4258c71def4e29.json</code>

Comparison Notes

- Both runs process the same paper path: `papers\NetworksElectoralCompetition.pdf`.
- Baseline model: `gpt-5`; variant model: `gpt-5-nano`.

- Baseline duration: 691.0 sec; variant duration: 355.54 sec.
- Baseline confidence mean: 0.2921069186783523; variant confidence mean: 0.29217296599402814.
- Baseline index status: **skipped** (db_unreachable); variant index status: **indexed** (None).
- Baseline report store: **skipped**; variant report store: **stored**.