


	1	2	3	4
A				A
В				В
С				C
D	1	2	Title nav_main_connector.schdoc Size: A4 Number:1 Revision: Date: 9/29/2018 Time: 5:00:48 PM Sheet 2 File: C:\Users\Ryan Castle\Documents\git_repos\po	



Bill of N	/laterials	BADO	JER LC	OP											
Source Data From		power_project.PrjPCB		Calculate Pricing											
Project: /ariant:		power_project.PrjPCB None		Resize Rows/Shade											
					•										
	9/29/2018 29-Sep-18	5:00:52 PM 5:01:11 PM		Unhide/Hide Supplier 1											
		3.01.111 W	•	Unhide/Hide Supplier 2											
roduction Quantity: currency	1 <none></none>			Unhide/Hide Assem Manf											
		ı	-												
	Designator	Description		#Column Name Erro Quantity	#Column Name Error:Supplier 1	#Column Name Err #C	Column Name Err Supplier Unit Pri	e 1 Supplier 1 Subtota	#Column Name Error:Supplier 2	#Column Name Erro#Column Name E	ror: Supplier Unit Price 2	Supplier 2 Subtotal	#Column Name Error	#Column N #Column N Assem U	Uni Assem Sub
Parameter Referen			Murata Electronics North America		3	1		\$	•						
Parameter Referer Parameter Referer	C2, C4	CAP CER 100F 50V X5R 1206	Murata Electronics North America Murata Electronics North America		3			\$							
Parameter Refere			Murata Electronics North America		2			\$							
:Parameter Refere		0603	Murata Electronics North America		2			s							
	C9, C10, C16, C17		Murata Electronics North America		1										
Parameter Referen	C12, C13	CAP CER 4.7PF 50V NP0 0603	Murata Electronics North America		2			š							
Parameter Refere	C18, C19, C20, C22	CAP CER 0.047UF 16V X7R 0402	Murata Electronics North America		4			\$							
Parameter Refere	C21, C23		Murata Electronics North America		2			\$							
Parameter Refere	C24		Murata Electronics North America		1			\$							
Parameter Refere	C25, C26	CAP CER 10000PF 250V X7T	TDK Corporation		2			\$							
Parameter Refere	CLD1, CLD2, CLD3	0805 DIODE CURRENT LIMITING	Central Semiconductor Corp		3			\$							
Parameter Referer	D1	SINGLE SM Default Diode Typical RED, GREEN,			1			s ·							
		YELLOW, AMBER GaAs LED													
Parameter Referer Parameter Referer		XFL5030-102ME Header, 3-Pin			2	1		\$	•						
Parameter Refere	R1	RES SMD 15K OHM 5% 1/10W 0402	Panasonic Electronic Components		1			\$							
Parameter Referen	R2, R3, R4, R5, R6, R7, R12, R13, R14	RES SMD 1M OHM 1% 1/10W 0402, RES SMD 1M OHM 5%	Panasonic Electronic Components		9			\$							
Parameter Refere	R8, R9	1/10W 0402 RES SMD 191K OHM 1%	Panasonic Electronic Components		2			\$							
Parameter Refere	R10, R11		Panasonic Electronic Components		2			\$							
Parameter Refere	R15		Panasonic Electronic Components		1			\$							
Parameter Refere	R16		Panasonic Electronic Components		1			\$							
Parameter Refere	R17, R18		Panasonic Electronic Components		2			\$							
Parameter Refere	R19	1/10W 0402 RES SMD 36K OHM 1% 1/10W	Panasonic Electronic Components		1			\$							
Parameter Referen	TP1, TP2, TP3, TP4, TP5, TP6, TP7, TP8, TP9,	0402			14			\$							
	TP10, TP11, TP12, TP13, TP14														
Parameter Referen	1U1	LT8650S - Dual Channel 4A, 42V, Synchronous Step-Down Silent Switcher 2 with 6.2µA			1			\$	•						
:Parameter Refere	112	Quiescent Current Mosfet Array 2 N-Channel			1			•							
raiailielei Keielei	102	(Dual) 30V 8.5A 3.1W Surface Mount 8-SO			'										
Parameter Referen	U3	Overvoltage, Undervoltage and			1			\$							
		ReverseSupply Protection Controller			74							•			
pproved		Notes			74			\$				-			2 -
			I												
		<u> </u>													
				<u> </u>		-		-							