

Radiation Type	Location	Simulated Dose/ Fluence	SF _{sim}	SF _{other}	Target Dose/ Fluence
Total Ionizing Dose (TID) [Gy]	Barrel	53.6	1.5	5 (Low dose rate effects)	402 (80.4 for CMOS)
	End-caps	34.3	1.5	5 (Low dose rate effects)	257.2 (51.5 for CMOS)
	Average	43.9	1.5	5 (Low dose rate effects)	329.3 (65.9 for CMOS)
Non-Ionizing Energy Loss (NIEL) [n/cm²]	Barrel	3.66 x 10 ¹²	1.5	1.3 (Mono-energetic beam)	7.14 x 10 ¹²
	End-caps	9.58 x 10 ¹¹	1.5	1.3 (Mono-energetic beam)	1.87 x 10 ¹²
	Average	2.31 x 10 ¹²	1.5	1.3 (Mono-energetic beam)	4.5 x 10 ¹²
Single Event Effects (SEE) [p/cm²]	Barrel	5.3 x 10 ¹¹	1.5	2 (E _{cut} = 20 MeV)	1.59 x 10 ¹²
	End-caps	9.8 x 10 ¹⁰	1.5	2 (E _{cut} = 20 MeV)	2.94 x 10 ¹¹