#### VM5k and DVMS on Grid'5000

Deploying and Managing Thousands of Virtual Machines on Hundreds of Nodes Distributed Geographically

Jonathan Pastor<sup>1</sup> Laurent Pouilloux<sup>2</sup>

 $^1$ Héméra Phd ASCOLA - Mines Nantes / Inria

> <sup>2</sup>Hemera Engineer Inria / ENS Lyon

18-06-2014 / Grid'5000 School

#### Context

Cloud computing usage is becoming very popular.

- Ever-increasing demand ⇒ ever-increasing infrastructure size.
- Problems: scalability, reliability, network overhead, energy but also security, and juridiction
- Decentralise the computing ressources

concept of micro/nano datacenters [Greenberg2009] geographically spread.  $\Rightarrow$  nodes can be far from each other.

## Discovery project

http://beyondtheclouds.github.io/

- And we want to maximise cooperation between close nodes/micro DCs.
- Example: The DVMS case.

#### Grid'5000 as a testbed



- 10Gb interconnected network
- various hardware (cpu, memory size, disks, network bandwidth)
- KaVLAN: allow to have a single network over the sites
- full experiment stack control (hardware, OS, hypervisor)

Created by topo5k 2014-06-18 11:26:00+02:00 API commit 0b625b83fcdfefcfd2f8850cea0a875143388edc


## Experimental Workflow

- reserve many nodes on different sites, with a global-KaVLAN
- deploy thousants of Virtual Machines
- initiate stress process on them
- install DVMS
- use vivaldi to compute hosts distances
- generate random stress on the virtual machines
- live experiment visualization
- collect results

# (F)ind yo(U)r (N)ode on g5(K)


A advanced resources discovery tool for multisite reservation

```
funk -m free -r grid5000:200 -o "-t deploy" -w 12:00:00
-b helios,sagittaire,nantes,reims,graphite -k -c
```



## Automatic Virtual Machines deployment

Moving FLauncher (D. Balouek and F. Quesnel) to vm5k



Tested successfully up to 5 000 VMs on 300 nodes.

#### Stress initialization

On all running Virtual Machines and using execo

- upload the memtouch binary
- start a memtouch process
- set it's cpu usage to 1% using cpulimit

All VMs are ready to be stressed.

## Vivaldi

## **DVMS**

#### Live visualization

http://localhost:9000

- migration count
- infrastructure state (VM position and load)
- distance map from Vivaldi (used by DVMS to determine where to migrate the VMs)
- bonus: node live power usage

## Load events generation

#### We can tune:

- distribution of event load value
- events frequency

Use an execo script to set the value of the load using cpulimit

## Results Analysis

- Vivaldi map
- Migration statistics
- Bonus: fine-grained power consumption for some nodes

#### Conclusion

Large scale validation of DVMS taking into account node distance

- -almost- fully automatized experiment
- wide usage of Grid'5000 features (API, Kadeploy, KaVLAN, Kwapi)
- real execution up to 5000 Virtual Machines
- demo available on Challenge\_DVMS\_Live\_-\_School\_2014

Jonathan Pastor, Marin Bertier, Frédéric Desprez, Adrien Lèbre, Flavien Quesnel, and Cédric Tedeschi. *Locality-aware Cooperation for VM Scheduling in Distributed Clouds.* In Euro-Par 2014, Porto, Portugal, August 2014.

Thank your for your attention. Questions ?