Table 76. UFQFPN32 - Mechanical data

Symbol	Millimeters[1]			Inches[2]		
	Min	Typ	Max	Min	Typ	Max
A[3][4]	0.50	0.55	0.60	0.0197	0.0217	0.0236
A1[5]	0.00	-	0.05	0.000	-	0.0020
A3[6]	-	0.15	-	-	0.0060	-
b[7]	0.18	0.25	0.30	0.0071	0.010	0.0118
D[8][9]	5.00 BSC			0.1969 BSC		
D2	3.50	3.60	3.70	0.139	0.143	0.147
E[8][9]	5.00 BSC			0.1969 BSC		
E2	3.50	3.60	3.70	0.139	0.143	0.147
e[9]	-	0.50	-	-	0.02	-
N[10]	32					
K	0.15	-	-	0.006	-	-
L	0.30	-	0.50	0.0119	-	0.0199
R	0.09	-	-	0.004	-	-

1. *All dimensions are in millimeters. Dimensioning and tolerancing schemes are conform to ASME Y14.5M-2018 except European .*
2. *Values in inches are converted from mm and rounded to 4 decimal digits.*
3. *UFQFPN stands for Ultra thin Fine pitch Quad Flat Package No lead: A ≤ 0.60mm / Fine pitch e ≤ 1.00mm.*
4. *The profile height, A, is the distance from the seating plane to the highest point on the package. It is measured perpendicular to the seating plane.*
5. *A1 is the vertical distance from the bottom surface of the plastic body to the nearest metallized package feature.*
6. *A3 is the distance from the seating plane to the upper surface of the terminals.*
7. *Dimension b applies to metallized terminal. If the terminal has the optional radius on the other end of the terminal, the dimension b must not be measured in that radius area.*
8. *Dimensions D and E do not include mold protrusion, not to exceed 0,15mm.*
9. *BSC stands for BASIC dimensions. It corresponds to the nominal value and has no tolerance. For tolerances refer to Table 77*
10. *N represents the total number of terminals.*

Table 77. Tolerance of form and position

Symbol[1]	Tolerance of form and position[2] In millimeters	Tolerance of form and position[3] In inches
aaa	0.15	0.006
bbb	0.10	0.004
ccc	0.10	0.004
ddd	0.05	0.002
eee	0.10	0.004
fff	0.10	0.004

1. *For the tolerance of form and position definitions see Table 78.*
2. *All dimensions are in millimetres. Dimensioning and tolerancing schemes are conform to ASME Y14.5M-2018 except European .*
3. *Values in inches are converted from mm and rounded to 4 decimal digits.*