5.3.6.2 *Current consumption in Sleep mode*

Table 26. Typical and maximum current consumption in Sleep mode

Specified by design - not tested in production, unless otherwise stated.

Symbol	Parameter	Conditions	(MHz)	Typ	Max		Unit
					T_J = 30°C	T_J = 140°C	
$I_{DD(SLEEP)}$	Supply current in Sleep mode	All peripherals disabled, HSI	HSI 144	2.40	2.55	20.00	mA
			HSI 48	1.05	1.25	16.50	
		All peripherals enabled, HSI	HSI 144	19.50	21.00	34.00	
			HSI 48	6.90	7.10	22.00	

5.3.6.3 *Current consumption in Stop mode*

Table 27. Typical and maximum current consumption in Stop mode

Specified by design - not tested in production, unless otherwise stated.

Symbol	Parameter	Conditions		Typ	Max		Unit
					T_J = 30°C	T_J = 140°C	
$I_{DD(STOP)}$	FLASH ON	SRAM1/2 ON	STOP0	0.22	0.36	14.00	mA
			STOP1	0.07	0.15	9.00	
	FLASH IN LOW POWER	SRAM1/2 ON	STOP0	0.20	0.35	13.00	
			STOP1	0.06	0.13	8.60	
		SRAM1/2 OFF	STOP0	0.19	0.35	12.00	
			STOP1	0.06	0.12	8.75	

Table 28. Typical and maximum HSIKERON current consumption in Stop mode

Specified by design - not tested in production, unless otherwise stated.

Symbol	Parameter	Conditions		Typ	Max		Unit
					T_J = 30°C	T_J = 140°C	
$I_{DD(Stop)}$	FLASH IN LOW POWER	HSIKERON, STOP0	HSI144	0.51	0.65	12.00	mA
			HSI48	0.40	0.55	12.00	

5.3.6.4 *Current consumption in Standby mode*

Table 29. Typical and maximum current consumption in Standby mode

Specify by design - not tested in production, unless otherwise stated.

Symbol	Parameter	RTC and LSE (1)	Typ			Max		Unit
			2.7 V	3 V	3.3 V	T_J = 30°C	T_J = 140°C	
$I_{DD(Standby)}$	Supply current in Standby mode, IWDG OFF	OFF	2.75	2.90	3.00	4.00	105.00	µA
		ON	3.10	3.25	3.40	-	-	
	Supply current in Standby mode, IWDG ON	OFF	3.10	3.25	3.40	5.25	105.00	
		ON	3.40	3.55	3.75	-	-	

1. *LSE is in low drive mode.*