

Table 29. Typical current consumption in Run depending on code executed (continued)

| Symbol        | Parameter                  | Conditions                                                     |                             |                           | Typ   | Unit | Typ   | Unit                     |
|---------------|----------------------------|----------------------------------------------------------------|-----------------------------|---------------------------|-------|------|-------|--------------------------|
|               |                            | General <sup>(1)</sup>                                         | Code                        | Fetch from <sup>(2)</sup> | 25 °C |      | 25 °C |                          |
| $I_{DD(Run)}$ | Supply current in Run mode | $f_{HCLK} = f_{HSI48}/HSIDIV = 48 \text{ MHz}$<br>(HSIDIV = 1) | Reduced code <sup>(3)</sup> | Flash memory              | 3.75  | mA   | 78.1  | $\mu\text{A}/\text{MHz}$ |
|               |                            |                                                                | Coremark                    |                           | 3.50  |      | 72.9  |                          |
|               |                            |                                                                | Dhrystone                   |                           | 3.55  |      | 74.0  |                          |
|               |                            |                                                                | Fibonacci                   |                           | 2.75  |      | 57.3  |                          |
|               |                            |                                                                | WhileLoop                   |                           | 2.15  |      | 44.8  |                          |
|               |                            |                                                                | Reduced code <sup>(3)</sup> | SRAM                      | 3.15  |      | 65.6  |                          |
|               |                            |                                                                | Coremark                    |                           | 3.05  |      | 63.5  |                          |
|               |                            |                                                                | Dhrystone                   |                           | 3.05  |      | 63.5  |                          |
|               |                            |                                                                | Fibonacci                   |                           | 3.20  |      | 66.7  |                          |
|               |                            |                                                                | WhileLoop                   |                           | 2.50  |      | 52.1  |                          |
|               |                            | $f_{HCLK} = f_{HSI48}/HSIDIV = 12 \text{ MHz}$<br>(HSIDIV = 4) | Reduced code <sup>(3)</sup> | Flash memory              | 1.45  |      | 120.8 | $\mu\text{A}/\text{MHz}$ |
|               |                            |                                                                | Coremark                    |                           | 1.40  |      | 116.7 |                          |
|               |                            |                                                                | Dhrystone                   |                           | 1.40  |      | 116.7 |                          |
|               |                            |                                                                | Fibonacci                   |                           | 1.15  |      | 95.8  |                          |
|               |                            |                                                                | WhileLoop                   |                           | 1.00  |      | 83.3  |                          |
|               |                            |                                                                | Reduced code <sup>(3)</sup> | SRAM                      | 1.30  |      | 108.3 |                          |
|               |                            |                                                                | Coremark                    |                           | 1.25  |      | 104.2 |                          |
|               |                            |                                                                | Dhrystone                   |                           | 1.25  |      | 104.2 |                          |
|               |                            |                                                                | Fibonacci                   |                           | 1.30  |      | 108.3 |                          |
|               |                            |                                                                | WhileLoop                   |                           | 1.10  |      | 91.7  |                          |
|               |                            | $f_{HCLK} = f_{HSI48}/HSIDIV = 3 \text{ MHz}$<br>(HSIDIV = 16) | Reduced code <sup>(3)</sup> | Flash memory              | 0.855 |      | 285.0 | $\mu\text{A}/\text{MHz}$ |
|               |                            |                                                                | Coremark                    |                           | 0.835 |      | 278.3 |                          |
|               |                            |                                                                | Dhrystone                   |                           | 0.835 |      | 278.3 |                          |
|               |                            |                                                                | Fibonacci                   |                           | 0.780 |      | 260.0 |                          |
|               |                            |                                                                | WhileLoop                   |                           | 0.745 |      | 248.3 |                          |
|               |                            |                                                                | Reduced code <sup>(3)</sup> | SRAM                      | 0.810 |      | 270.0 |                          |
|               |                            |                                                                | Coremark                    |                           | 0.800 |      | 266.7 |                          |
|               |                            |                                                                | Dhrystone                   |                           | 0.800 |      | 266.7 |                          |
|               |                            |                                                                | Fibonacci                   |                           | 0.810 |      | 270.0 |                          |
|               |                            |                                                                | WhileLoop                   |                           | 0.770 |      | 256.7 |                          |

1.  $V_{DD} = 3.0 \text{ V}$ , all peripherals disabled

2. Prefetch and cache enabled when fetching from flash

3. Reduced code used for characterization results provided in [Table 27](#).