



Table 30. Current consumption in Sleep mode

Symbol	Parameter	Conditions		Typ				Max ⁽¹⁾				Unit
		General	f _{HCLK}	25 °C	85 °C	105 °C	125 °C	25 °C	85 °C	105 °C	125 °C	
I _{DD(Sleep)}	Supply current in Sleep mode	All peripherals disabled, f _{HCLK} = f _{HSI48/HSIDIV} (> 32 kHz), f _{HCLK} = f _{LSI} (= 32 kHz)		48 MHz	1.20	1.20	1.25	1.35	1.50	1.70	2.00	mA
				24 MHz	0.92	0.95	0.99	1.10	1.10	1.30	1.60	
				12 MHz	0.79	0.81	0.86	0.95	0.91	1.20	1.40	
				6 MHz	0.72	0.75	0.79	0.88	0.82	1.10	1.30	
				1.5 MHz	0.67	0.70	0.74	0.83	0.75	0.97	1.30	
				375 kHz	0.66	0.69	0.73	0.82	0.73	0.95	1.30	
				32 kHz	0.08	0.13	0.18	0.28	0.12	0.37	0.64	
		All peripherals disabled, f _{HCLK} = f _{HSE_bypass} (> 32.768 kHz), f _{HCLK} = f _{LSE_bypass} (= 32.768 kHz)	Flash memory enabled	48 MHz	0.820	0.875	0.930	1.05	1.20	1.40	1.70	
				32 MHz	0.575	0.630	0.680	0.785	0.800	1.10	1.40	
				24 MHz	0.450	0.500	0.555	0.655	0.630	0.880	1.20	
				16 MHz	0.325	0.380	0.430	0.535	0.460	0.710	0.980	
				8 MHz	0.205	0.250	0.305	0.405	0.300	0.540	0.820	
				2 MHz	0.110	0.160	0.210	0.310	0.170	0.420	0.690	
				500 kHz	0.0875	0.135	0.185	0.285	0.130	0.380	0.650	
				32.768 kHz	0.0805	0.125	0.180	0.280	0.120	0.370	0.640	
			Flash memory disabled (flash memory power-down sleep mode)	48 MHz	0.815	0.870	0.925	1.05	1.20	1.40	1.70	
				32 MHz	0.570	0.620	0.675	0.775	0.790	1.10	1.40	
				24 MHz	0.445	0.495	0.545	0.650	0.630	0.870	1.20	
				16 MHz	0.320	0.375	0.425	0.525	0.460	0.700	0.980	
				8 MHz	0.200	0.245	0.295	0.395	0.290	0.530	0.810	
				2 MHz	0.105	0.150	0.205	0.300	0.160	0.410	0.680	
				500 kHz	0.0815	0.130	0.180	0.280	0.120	0.370	0.650	
				32.768 kHz	0.0745	0.120	0.170	0.270	0.110	0.360	0.630	

1. Evaluated by characterization. Not tested in production.