

Table 12. Pin assignment and description (continued)

Pin Number					Pin name (function after reset)	Pin type	I/O structure	Notes	Alternate functions	Additional functions
WLCSP15	TSSOP20	UFQFPN28	LQFP32 UFQFPN32	LQFP48 UFQFPN48						
D3	4	3	4	6	VDD/VDDA	S	-	-	-	-
F3	5	4	5	7	VSS/VSSA	S	-	-	-	-
-	-	-	-	8	PF0- OSC_IN (PF0)	I/O	FT	-	TIM14_CH1	OSC_IN
-	-	-	-	9	PF1- OSC_OUT (PF1)	I/O	FT	-	OSC_EN	OSC_OUT
H3	6	5	6	10	PF2-NRST	I/O	RST, FT	(1)	MCO, TIM1_CH4	NRST
H3	7	6	7	11	PA0	I/O	FT_a	-	SPI2_SCK, USART2_CTS/USART2_NSS, TIM16_CH1, TIM2_ETR/TIM2_CH1, USART1_TX, TIM1_CH1	ADC_IN0, WKUP1
G2	8	7	8	12	PA1	I/O	FT_a	-	SPI1_SCK/I2S1_CK, USART2_RTS/ USART2_DE/USART2_CK, TIM17_CH1, TIM2_CH2, USART1_RX, TIM1_CH2, I2C1_SMB, EVENTOUT	ADC_IN1
G2	9	8	9	13	PA2	I/O	FT_a	-	SPI1_MOSI/I2S1_SD, USART2_TX, TIM16_CH1N, TIM3_ETR, TIM1_CH3, TIM2_CH3	ADC_IN2, WKUP4, LSCO
K3	10	9	10	14	PA3	I/O	FT_a	-	SPI2_MISO, USART2_RX, TIM1_CH1N, TIM2_CH4, TIM1_CH4, EVENTOUT	ADC_IN3
-	-	-	-	15	PA4	I/O	FT_a	-	SPI1_NSS/I2S1_WS, USART2_TX, TIM1_CH2N, SPI2_MOSI, TIM14_CH1, TIM17_CH1N, EVENTOUT	ADC_IN4, RTC_OUT2
K3	11	10	11	-	PA4	I/O	FT_a	-	SPI1_NSS/I2S1_WS, USART2_TX, TIM1_CH2N, SPI2_MOSI, TIM14_CH1, TIM17_CH1N, EVENTOUT	ADC_IN4, RTC_TS, RTC_OUT1, WKUP2
J2	12	11	12	16	PA5	I/O	FT_a	-	SPI1_SCK/I2S1_CK, USART2_RX, TIM1_CH3N, TIM2_ETR/ TIM2_CH1, TIM1_CH1, EVENTOUT	ADC_IN5
J2	13	12	13	17	PA6	I/O	FT_fa	-	SPI1_MISO/I2S1_MCK, TIM3_CH1, TIM1_BKIN, USART1_TX, TIM16_CH1, I2C2_SDA	ADC_IN6
H1	14	13	14	18	PA7	I/O	FT_fa	-	SPI1_MOSI/I2S1_SD, TIM3_CH2, TIM1_CH1N, USART1_RX, TIM14_CH1, TIM17_CH1, I2C2_SCL	ADC_IN7
-	-	14	15	19	PB0	I/O	FT_a	-	SPI1_NSS/I2S1_WS, TIM3_CH3, TIM1_CH2N	ADC_IN17
-	-	15	16	20	PB1	I/O	FT_a	-	TIM14_CH1, TIM3_CH4, TIM1_CH3N, TIM1_CH2N, EVENTOUT	ADC_IN18