

Table 31. Current consumption in Sleep mode

Symbol	Parameter	Conditions			Typ				Max ⁽¹⁾				Unit	
		General		f _{HCLK}	25 °C	85 °C	105 °C	125 °C	25 °C	85 °C	105 °C	125 °C		
I _{DD(Sleep)}	Supply current in Sleep mode	All peripherals disabled, f _{HCLK} = f _{HSI48/HSIDIV} (> 32 kHz), f _{HCLK} = f _{LSI} (= 32 kHz)	Flash memory enabled	48 MHz	0.780	0.830	0.885	0.980	1.15	1.33	1.62	2.06	mA	
				32 MHz	0.540	0.595	0.645	0.745	0.76	1.04	1.33	1.81		
				24 MHz	0.430	0.480	0.530	0.625	0.61	0.85	1.15	1.63		
				16 MHz	0.315	0.360	0.410	0.505	0.45	0.68	0.94	1.42		
				8 MHz	0.195	0.245	0.290	0.385	0.29	0.53	0.78	1.34		
				4 MHz	0.140	0.185	0.230	0.325	0.21	0.45	0.71	1.25		
				2 MHz	0.110	0.155	0.205	0.295	0.17	0.41	0.68	1.15		
		All peripherals disabled, f _{HCLK} = f _{HSE_bypass} (> 32.768 kHz), f _{HCLK} = f _{LSE_bypass} (= 32.768 kHz)		1 MHz	0.095	0.140	0.190	0.280	0.14	0.39	0.66	1.14		
				500 kHz	0.088	0.130	0.180	0.275	0.14	0.37	0.64	1.16		
				125 kHz	0.083	0.125	0.175	0.270	0.13	0.36	0.63	1.16		
				32,768 Hz	0.081	0.125	0.175	0.265	0.13	0.37	0.63	1.14		
				48 MHz	0.775	0.825	0.875	0.975	1.15	1.33	1.61	2.05		
				32 MHz	0.535	0.590	0.640	0.740	0.75	1.05	1.33	1.82		
				24 MHz	0.425	0.470	0.520	0.615	0.61	0.83	1.15	1.61		
				16 MHz	0.305	0.355	0.405	0.500	0.44	0.67	0.94	1.43		
				8 MHz	0.190	0.235	0.285	0.380	0.28	0.51	0.79	1.35		
				4 MHz	0.130	0.175	0.225	0.320	0.21	0.45	0.70	1.25		
				2 MHz	0.105	0.150	0.195	0.290	0.16	0.41	0.65	1.16		
				1 MHz	0.089	0.135	0.180	0.275	0.14	0.38	0.65	1.16		
				500 kHz	0.082	0.125	0.175	0.265	0.12	0.36	0.64	1.14		
				125 kHz	0.076	0.120	0.170	0.260	0.12	0.36	0.63	1.16		
				32,768 Hz	0.075	0.120	0.165	0.260	0.11	0.36	0.62	1.16		
				Flash memory disabled (flash memory power-down sleep mode)	48 MHz	0.965	0.995	1.050	1.100	1.21	1.41	1.68		2.04
					24 MHz	0.710	0.735	0.780	0.865	0.85	1.01	1.27		1.66
					12 MHz	0.585	0.610	0.650	0.735	0.68	0.91	1.03		1.47
					6 MHz	0.520	0.545	0.585	0.670	0.60	0.80	0.97		1.38
		1.5 MHz			0.470	0.495	0.535	0.625	0.53	0.69	0.94	1.36		
		375 kHz			0.460	0.485	0.525	0.610	0.51	0.67	0.94	1.34		
		32 kHz		0.082	0.125	0.175	0.270	0.13	0.36	0.63	1.16			

1. Evaluated by characterization. Not tested in production.