



Table 32. Current consumption in Stop mode

Symbol	Parameter	Conditions	V _{DD}	Typ				Max ⁽¹⁾				Unit
				25 °C	85 °C	105 °C	125 °C	25 °C	85 °C	105 °C	125 °C	
I _{DD(Stop)}	Supply current in Stop mode	All clocks off	2 V	78.0	125	170	260	110	350	610	1100	μA
			2.4 V	79.0	125	175	265	110	350	610	1100	
			3 V	80.5	125	175	270	110	350	610	1100	
			3.6 V	82.5	130	180	275	110	350	610	1100	
		All clocks off Flash memory in power-down stop mode	2 V	71.5	115	165	255	100	340	600	1100	
			2.4 V	72.5	120	165	255	100	340	600	1100	
			3 V	74.0	120	170	260	100	340	600	1100	
			3.6 V	76.0	120	170	265	110	340	600	1100	
		RTC enabled and supplied with LSE bypass (32.768 kHz)	2 V	78.0	125	175	260	110	350	610	1100	
			2.4 V	79.5	125	175	265	115	350	610	1100	
			3 V	81.0	125	175	270	115	350	610	1100	
			3.6 V	82.5	130	180	275	115	350	610	1100	
		RTC enabled and supplied with LSE bypass (32.768 kHz) Flash memory in power-down stop mode	2 V	72.0	115	165	255	100	330	600	1100	
			2.4 V	73.0	120	165	260	100	340	600	1100	
			3 V	74.5	120	170	260	110	340	600	1100	
			3.6 V	76.5	120	170	265	110	340	600	1100	
		HSI Kernel on	2 V	435	460	500	580	460	620	820	1220	
			2.4 V	435	460	505	585	460	620	830	1230	
			3 V	440	465	505	590	470	630	900	1240	
			3.6 V	440	465	510	595	470	630	900	1240	

1. Evaluated by characterization. Not tested in production.