

Table 33. Current consumption in Standby mode

Symbol	Parameter	Conditions	V _{DD}	Typ				Max ⁽¹⁾				Unit
				25 °C	85 °C	105 °C	125 °C	25 °C	85 °C	105 °C	125 °C	
I _{DD(Standby)}	Supply current in Standby mode	All clocks off	2 V	6.8	7.7	8.4	9.8	7.6	8.9	10.9	15.0	μA
			2.4 V	7.1	8.0	8.8	10.5	7.7	9.1	10.9	16.3	
			3 V	7.5	8.5	9.4	11.0	8.2	9.7	12.0	16.5	
			3.6 V	7.9	9.1	10.0	13.0	8.7	11.2	13.0	20.8	
		IWDG enabled and clocked by LSI	2 V	7.3	8.3	9.1	10.5	8.1	9.5	11.9	15.6	
			2.4 V	7.6	8.6	9.5	11.0	8.3	9.8	11.9	16.3	
			3 V	8.1	9.2	10.0	12.0	8.9	11.0	13.0	18.3	
			3.6 V	8.6	9.8	11.0	13.5	9.5	12.1	14.0	21.0	

1. Evaluated by characterization. Not tested in production.

Table 34. Current consumption in Shutdown mode

Symbol	Parameter	Conditions	V _{DD}	Typ				Max ⁽¹⁾				Unit
				25 °C	85 °C	105 °C	125 °C	25 °C	85 °C	105 °C	125 °C	
I _{DD(Shutdown)}	Supply current in Shutdown mode	All clocks off	2 V	10	320	910	2600	62	1010	2900	8400	nA
			2.4 V	14	340	940	2700	67	1030	2980	8700	
			3.0 V	21	400	1100	3200	79	1280	3450	9800	
			3.6 V	35	500	1400	3750	107	1520	4250	12300	

1. Evaluated by characterization. Not tested in production.