

Table 70. LQFP32 - Mechanical data

| Symbol                    | millimeters |      |      | inches <sup>(14)</sup> |        |        |
|---------------------------|-------------|------|------|------------------------|--------|--------|
|                           | Min         | Typ  | Max  | Min                    | Typ    | Max    |
| θ                         | 0°          | 3.5° | 7°   | 0°                     | 3.5°   | 7°     |
| θ1                        | 0°          | -    | -    | 0°                     | -      | -      |
| θ2                        | 10°         | 12°  | 14°  | 10°                    | 12°    | 14°    |
| θ3                        | 10°         | 12°  | 14°  | 10°                    | 12°    | 14°    |
| A                         | -           | -    | 1.60 | -                      | -      | 0.0630 |
| A1 <sup>(12)</sup>        | 0.05        | -    | 0.15 | 0.0020                 | -      | 0.0059 |
| A2                        | 1.35        | 1.40 | 1.45 | 0.0531                 | 0.0551 | 0.0571 |
| b <sup>(9)(11)</sup>      | 0.30        | 0.37 | 0.45 | 0.0118                 | 0.0146 | 0.0177 |
| b1 <sup>(11)</sup>        | 0.30        | 0.35 | 0.40 | 0.0118                 | 0.0128 | 0.0157 |
| c <sup>(11)</sup>         | 0.09        | -    | 0.20 | 0.0035                 | -      | 0.0079 |
| c1 <sup>(11)</sup>        | 0.09        | -    | 0.16 | 0.0035                 | -      | 0.0063 |
| D <sup>(4)</sup>          | 9.00 BSC    |      |      | 0.3543 BSC             |        |        |
| D1 <sup>(2)(5)</sup>      | 7.00 BSC    |      |      | 0.2756 BSC             |        |        |
| e                         | 0.80 BSC    |      |      | 0.0315 BSC             |        |        |
| E <sup>(4)</sup>          | 9.00 BSC    |      |      | 0.3543 BSC             |        |        |
| E1 <sup>(2)(5)</sup>      | 7.00 BSC    |      |      | 0.2756 BSC             |        |        |
| L                         | 0.45        | 0.60 | 0.75 | 0.0177                 | 0.0236 | 0.0295 |
| L1                        | 1.00 REF    |      |      | 0.0394 REF             |        |        |
| N <sup>(13)</sup>         | 32          |      |      |                        |        |        |
| R1                        | 0.08        | -    | -    | 0.0031                 | -      | -      |
| R2                        | 0.08        | -    | 0.20 | 0.0031                 | -      | 0.0079 |
| S                         | 0.20        | -    | -    | 0.0079                 | -      | -      |
| aaa <sup>(1)(7)(15)</sup> | 0.20        |      |      | 0.0079                 |        |        |
| bbb <sup>(1)(7)(15)</sup> | 0.20        |      |      | 0.0079                 |        |        |
| ccc <sup>(1)(7)(15)</sup> | 0.10        |      |      | 0.0039                 |        |        |
| ddd <sup>(1)(7)(15)</sup> | 0.20        |      |      | 0.0079                 |        |        |