

Table 2. STM32C071x8/xB family device features and peripheral counts (continued)

Peripheral	STM32C071_									
	F8 / _FB	F8xxN / _FBxxN	G8 / _GB	G8xxN / _GBxxN	K8 / _KB	K8xxN / _KBxxN	C8 / _CB	C8xxN / _CBxxN	R8 / _RB	R8xxN / _RBxxN
12-bit ADC channels (ext. + int.)	11 + 4		13 + 4		14 + 4		17 + 4		19 + 4	
Max. CPU frequency	48 MHz									
Operating voltage	2.0 to 3.6 V									
Operating temperature ⁽⁵⁾	Ambient: -40 to 85 °C / -40 to 105 °C / -40 to 125 °C Junction: -40 to 105 °C / -40 to 125 °C / -40 to 130 °C									
Packages	WLCSP19 TSSOP20	TSSOP 20	UFQPN28		UFQFPN32 LQFP32		UFQFPN48 LQFP48		LQFP 64	UFBGA64 LQFP64
Bootloader	USART1, USART2, I2C1, I2C2, SPI1, SPI2, and USB DFU									

1. Only 128 KB version is available for parts in WLCSP19 package.
2. Only 128 KB version is available for parts in UFBGA64 package.
3. The numbers in brackets denote the count of SPI interfaces configurable as I²S interface.
4. For WLCSP19 package
5. Depends on order code. Refer to [Section 7: Ordering information](#) for details.