



Table 28. Current consumption in Run mode from flash memory at different die temperatures

Symbol	Parameter	Conditions			Typ				Max ⁽¹⁾				Unit
		General ⁽²⁾	f _{HCLK}	Fetch from ⁽³⁾	25 °C	85 °C	105 °C	125 °C	25 °C	85 °C	105 °C	125 °C	
I _{DD(Run)}	Supply current in Run mode	f _{HCLK} = f _{HSE_bypass} (> 32.768 kHz), f _{HCLK} = f _{LSE_bypass} (= 32.768 kHz)	48 MHz	Flash memory	3.70	3.85	3.95	4.20	4.000	4.200	4.500	5.000	mA
			32 MHz		2.50	2.65	2.75	2.95	2.700	2.900	3.200	3.800	
			24 MHz		2.20	2.35	2.45	2.65	2.400	2.600	2.900	3.400	
			16 MHz		1.50	1.60	1.75	1.95	1.700	1.900	2.200	2.700	
			8 MHz		0.800	0.900	1.000	1.250	0.880	0.990	1.500	2.000	
			4 MHz		0.440	0.535	0.645	0.855	0.500	0.750	1.100	1.600	
			2 MHz		0.265	0.355	0.460	0.675	0.310	0.570	0.860	1.500	
			1 MHz		0.175	0.265	0.370	0.580	0.210	0.470	0.770	1.400	
			500 kHz		0.130	0.220	0.325	0.535	0.160	0.420	0.720	1.300	
			125 kHz		0.097	0.185	0.290	0.500	0.130	0.390	0.690	1.300	
			32.768 kHz		0.089	0.175	0.285	0.495	0.260	0.380	0.680	1.300	
		f _{HCLK} = f _{HSI48/HSIDIV} (> 32 kHz), f _{HCLK} = f _{LSI} (= 32 kHz)	48 MHz		3.90	4.00	4.10	4.30	4.200	4.300	4.500	5.000	
			24 MHz		2.50	2.60	2.70	2.90	2.700	2.800	3.100	3.600	
			12 MHz		1.50	1.60	1.70	1.90	1.600	1.800	2.100	2.600	
			6 MHz		1.00	1.05	1.15	1.35	1.000	1.300	1.600	2.100	
			3 MHz		0.740	0.800	0.900	1.10	0.770	0.990	1.300	1.900	
			1.5 MHz		0.610	0.670	0.770	0.970	0.640	0.870	1.200	1.700	
			750 kHz		0.545	0.605	0.705	0.905	0.570	0.800	1.100	1.700	
			375 kHz		0.515	0.575	0.675	0.875	0.540	0.770	1.100	1.600	
			32 kHz		0.089	0.175	0.285	0.495	0.120	0.380	0.680	1.300	
		f _{HCLK} = f _{HSIUSB48/SYSDIV}	48 MHz		3.900	4.050	4.200	4.400	4.200	4.300	4.600	5.100	
			24 MHz		2.000	2.100	2.250	2.450	2.100	2.300	2.600	3.200	

1. Evaluated by characterization. Not tested in production.

2. V_{DD} = 3.0 V for values in Typ columns and 3.6 V for values in Max columns, all peripherals disabled.

3. Prefetch disabled and cache enabled when fetching from flash memory.