

Table 31. Current consumption in Sleep mode

Symbol	Parameter	Conditions		Typ				Max ⁽¹⁾				Unit	
		General		f _{HCLK}	25 °C	85 °C	105 °C	125 °C	25 °C	85 °C	105 °C		125 °C
I _{DD(Sleep)}	Supply current in Sleep mode	All peripherals disabled, f _{HCLK} = f _{HSE_bypass} (> 32.768 kHz), f _{HCLK} = f _{LSE_bypass} (= 32.768 kHz)	Flash memory enabled	48 MHz	0.770	0.865	0.975	1.20	0.97	1.30	1.60	2.1	mA
				32 MHz	0.540	0.635	0.745	0.960	0.73	0.96	1.30	1.8	
				24 MHz	0.425	0.520	0.630	0.840	0.58	0.81	1.20	1.7	
				16 MHz	0.315	0.405	0.510	0.725	0.42	0.67	0.96	1.6	
				8 MHz	0.200	0.290	0.395	0.605	0.27	0.52	0.82	1.4	
				4 MHz	0.145	0.230	0.340	0.550	0.20	0.46	0.76	1.3	
				2 MHz	0.115	0.200	0.310	0.520	0.16	0.42	0.72	1.3	
				1 MHz	0.1	0.190	0.295	0.505	0.14	0.40	0.69	1.3	
				500 kHz	0.093	0.180	0.285	0.495	0.13	0.39	0.68	1.3	
				125 kHz	0.088	0.175	0.280	0.490	0.12	0.38	0.68	1.3	
			32,768 Hz	0.086	0.175	0.280	0.490	0.12	0.38	0.67	1.3		
			Flash memory disabled (flash memory power-down sleep mode)	48 MHz	0.765	0.860	0.970	1.20	0.96	1.30	1.60	2.1	
				32 MHz	0.535	0.630	0.740	0.955	0.72	0.95	1.30	1.8	
				24 MHz	0.420	0.515	0.620	0.835	0.57	0.81	1.10	1.7	
				16 MHz	0.305	0.395	0.505	0.715	0.42	0.66	0.96	1.5	
				8 MHz	0.195	0.280	0.390	0.600	0.27	0.52	0.81	1.4	
				4 MHz	0.135	0.225	0.330	0.540	0.19	0.45	0.75	1.3	
				2 MHz	0.110	0.195	0.300	0.510	0.15	0.41	0.71	1.3	
				1 MHz	0.094	0.180	0.285	0.495	0.13	0.40	0.69	1.3	
				500 kHz	0.087	0.175	0.280	0.490	0.12	0.38	0.68	1.3	
				125 kHz	0.081	0.170	0.275	0.485	0.11	0.37	0.67	1.3	
				32,768 Hz	0.08	0.165	0.275	0.485	0.11	0.37	0.67	1.3	