



Table 31. Current consumption in Sleep mode (continued)

Symbol	Parameter	Conditions		Typ				Max ⁽¹⁾				Unit	
		General		f _{HCLK}	25 °C	85 °C	105 °C	125 °C	25 °C	85 °C	105 °C		125 °C
I _{DD(Sleep)}	Supply current in Sleep mode	All peripherals disabled, f _{HCLK} = f _{HSI48/HSIDIV} (> 32 kHz), f _{HCLK} = f _{LSI} (= 32 kHz)	Flash memory enabled	48 MHz	1.00	1.05	1.15	1.35	1.20	1.40	1.70	2.2	mA
				24 MHz	0.74	0.80	0.90	1.10	0.83	1.10	1.40	1.9	
				12 MHz	0.61	0.67	0.77	0.97	0.67	0.90	1.20	1.8	
				6 MHz	0.55	0.61	0.71	0.91	0.59	0.81	1.10	1.7	
				3 MHz	0.52	0.58	0.67	0.88	0.55	0.78	1.10	1.6	
				1.5 MHz	0.50	0.56	0.66	0.86	0.53	0.76	1.10	1.6	
				750 kHz	0.50	0.55	0.65	0.85	0.52	0.75	1.10	1.6	
				375 kHz	0.49	0.55	0.65	0.85	0.51	0.74	1.10	1.6	
		f _{HCLK} = f _{HSIUSB48/SYSDIV}		32 kHz	0.09	0.18	0.28	0.49	0.12	0.38	0.67	1.3	
				48MHz	0.98	1.10	1.20	1.40	1.20	1.40	1.70	2.2	
				16MHz	0.80	0.90	1.00	1.20	0.87	1.20	1.40	2.0	

1. Evaluated by characterization. Not tested in production.