

Table 32. Current consumption in Stop mode

Symbol	Parameter	Conditions	V _{DD}	Typ				Max ⁽¹⁾				Unit
				25 °C	85 °C	105 °C	125 °C	25 °C	85 °C	105 °C	125 °C	
I _{DD(Stop)}	Supply current in Stop mode	All clocks off	2 V	82.5	170	275	485	110	360	650	1200	μA
			2.4 V	84.0	170	275	485	120	360	650	1200	
			3 V	85.5	175	280	490	120	360	650	1200	
			3.6 V	87.5	175	285	495	120	360	650	1200	
		All clocks off Flash memory in power-down stop mode	2 V	76.5	165	265	480	110	360	640	1200	
			2.4 V	78.0	165	265	480	110	360	640	1200	
			3 V	79.5	165	270	480	110	360	640	1200	
			3.6 V	81.0	170	275	485	110	360	640	1200	
		RTC enabled and supplied with LSE bypass (32.768 kHz)	2 V	83.0	170	275	485	110	360	650	1200	
			2.4 V	84.5	170	275	485	120	360	650	1200	
			3 V	86.0	175	280	490	120	360	650	1200	
			3.6 V	89.0	180	285	500	120	360	650	1200	
		RTC enabled and supplied with LSE bypass (32.768 kHz) Flash memory in power-down stop mode	2 V	76.5	165	265	480	110	360	650	1200	
			2.4 V	78.0	165	270	480	110	360	650	1200	
			3 V	79.5	165	275	485	110	360	650	1200	
			3.6 V	83.0	170	280	490	110	360	650	1200	
		HSI Kernel on	2 V	455	515	615	815	480	710	980	1500	
			2.4 V	455	515	615	815	490	710	980	1500	
			3 V	460	520	615	820	490	710	980	1500	
			3.6 V	460	520	620	825	490	710	980	1500	

1. Evaluated by characterization. Not tested in production.