

**Table 33. Current consumption in Standby mode**

Symbol	Parameter	Conditions	V _{DD}	Typ				Max ⁽¹⁾				Unit
				25 °C	85 °C	105 °C	125 °C	25 °C	85 °C	105 °C	125 °C	
I _{DD(Standby)}	Supply current in Standby mode	All clocks off	2 V	6.65	8.00	9.40	13.5	7.7	9.4	11.8	18.2	μA
			2.4 V	6.95	8.40	9.90	14.0	8.0	9.8	12.3	18.9	
			3 V	7.35	8.75	10.50	15.5	8.4	10.2	12.9	19.9	
			3.6 V	7.75	9.50	12.0	18.5	9.5	11.6	14.6	22.5	
		IWDG enabled and clocked by LSI	2 V	7.20	8.70	10.00	14.0	8.3	10.1	12.8	19.6	
			2.4 V	7.50	9.05	10.50	14.5	8.5	10.4	13.1	20.1	
			3 V	7.90	9.45	11.5	16.5	9.0	11.0	13.8	21.3	
			3.6 V	8.40	10.50	12.5	19.0	11.0	13.4	16.9	26.0	

1. Evaluated by characterization. Not tested in production.

Table 34. Current consumption in Shutdown mode

Symbol	Parameter	Conditions	V _{DD}	Typ				Max ⁽¹⁾				Unit
				25 °C	85 °C	105 °C	125 °C	25 °C	85 °C	105 °C	125 °C	
I _{DD(Shutdown)}	Supply current in Shutdown mode	All clocks off	2 V	12.00	515	1650	5250	82.0	1300	4100	11500	nA
			2.4 V	16.0	580	1850	5800	89.0	1350	4300	11700	
			3.0 V	23.0	720	2250	6950	91.0	1500	4600	12400	
			3.6 V	41.0	1000	3100	9300	130.0	1900	5800	16700	

1. Evaluated by characterization. Not tested in production.