

Table 73. UFQFPN32 - Mechanical data

Symbol	millimeters ⁽¹⁾			inches ⁽²⁾		
	Min	Typ	Max	Min	Typ	Max
A ⁽³⁾⁽⁴⁾	0.50	0.55	0.60	0.0197	0.0217	0.0236
A1 ⁽⁵⁾	0.00	-	0.05	0.000	-	0.0020
b ⁽⁶⁾	0.18	0.25	0.30	0.0071	0.0098	0.0118
D ⁽⁷⁾	5.00 BSC			0.1969 BSC		
D2 ⁽⁸⁾	See Table 75: Exposed pad variation					
E ⁽⁷⁾	5.00 BSC			0.1969 BSC		
E2 ⁽⁸⁾	See Table 75: Exposed pad variation					
e	0.50 BSC			0.0197 BSC		
N ⁽⁹⁾	32					
L	0.30	-	0.50	0.0118	-	0.0197
R	0.09	-	-	0.0035	-	-

1. All dimensions are in millimeters. Dimensioning and tolerancing schemes conform to ASME Y14.5M-2018 except European.
2. Values in inches are converted from mm and rounded to four decimal digits.
3. UFQFPN stands for ultra thin fine pitch quad flat package no lead: A ≤ 0.60 mm / Fine pitch e ≤ 1.00 mm.
4. The profile height, A, is the distance from the seating plane to the highest point on the package. It is measured perpendicular to the seating plane.
5. A1 is the vertical distance from the bottom surface of the plastic body to the nearest metalized package feature.
6. Dimension b applies to metalized terminal. If the terminal has the optional radius on the other end of the terminal, the dimension b must not be measured in that radius area.
7. BSC stands for BASIC dimensions. It corresponds to the nominal value and has no tolerance. For tolerances, refer to [Table 74](#).
8. Dimensions D2 and E2 refer to the exposed pad. For variance, refer to [Table 75](#).
9. N represents the total number of terminals.

Table 74. Tolerance of form and position

Symbol	Millimeters ⁽¹⁾	Inches ⁽²⁾
aaa	0.15	0.0059
bbb	0.10	0.0039
ccc	0.10	0.0039
ddd	0.05	0.0020
eee	0.08	0.0315
fff	0.10	0.0039

1. All dimensions are in millimeters. Dimensioning and tolerancing schemes conform to ASME Y14.5M-2018 except European.
2. Values in inches are converted from mm and rounded to four decimal digits.