

**Table 33. Current consumption in Standby mode**

Symbol	Parameter	Conditions	V _{DD}	Typ				Max ⁽¹⁾				Unit
				25 °C	85 °C	105 °C	125 °C	25 °C	85 °C	105 °C	125 °C	
I _{DD(Standby)}	Supply current in Standby mode	All clocks off	2 V	6.70	8.10	9.50	13.60	7.8	9.5	12.0	18.4	μA
			2.4 V	6.95	8.40	9.90	14.00	8.0	9.8	12.3	18.9	
			3 V	7.35	8.75	10.50	15.50	8.4	10.2	12.9	19.9	
			3.6 V	7.80	9.60	12.10	18.62	9.6	11.7	14.7	22.6	
		IWDG enabled and clocked by LSI	2 V	7.20	8.70	10.00	14.00	8.3	10.2	12.8	19.7	
			2.4 V	7.45	9.00	10.43	14.40	8.5	10.3	13.1	20.1	
			3 V	7.90	9.45	11.50	16.50	9.0	11.0	13.8	21.3	
			3.6 V	8.35	10.45	12.45	18.90	11.0	13.4	16.9	26.0	

1. Evaluated by characterization. Not tested in production.

Table 34. Current consumption in Shutdown mode

Symbol	Parameter	Conditions	V _{DD}	Typ				Max ⁽¹⁾				Unit
				25 °C	85 °C	105 °C	125 °C	25 °C	85 °C	105 °C	125 °C	
I _{DD(Shutdown)}	Supply current in Shutdown mode	All clocks off	2 V	14	550	1750	5570	93	1400	4350	12200	nA
			2.4 V	17	620	1970	6150	95	1450	4560	12400	
			3.0 V	25	770	2390	7370	99	1600	4900	13150	
			2 V	39	1060	3290	9860	134	2020	6150	17700	

1. Evaluated by characterization. Not tested in production.