

Table 67. WLCSP24 - Mechanical data

| Symbol               | millimeters |       |      | inches <sup>(1)</sup> |        |        |
|----------------------|-------------|-------|------|-----------------------|--------|--------|
|                      | Min         | Typ   | Max  | Min                   | Typ    | Max    |
| A <sup>(2)</sup>     | -           | -     | 0.60 | -                     | -      | 0.0236 |
| A1 <sup>(3)</sup>    | 0.12        | -     | -    | 0.0047                | -      | -      |
| A2                   | -           | 0.38  | -    | -                     | 0.0150 | -      |
| A3                   | -           | 0.025 | -    | -                     | 0.0010 | -      |
| b <sup>(4)</sup>     | 0.19        | 0.23  | 0.26 | 0.0075                | 0.0091 | 0.0102 |
| D <sup>(5)</sup>     | 2.61 BSC    |       |      | 0.1028 BSC            |        |        |
| D1 <sup>(5)</sup>    | 1.82 BSC    |       |      | 0.0717 BSC            |        |        |
| E <sup>(5)</sup>     | 1.73 BSC    |       |      | 0.0681 BSC            |        |        |
| E1 <sup>(5)</sup>    | 1.05 BSC    |       |      | 0.0413 BSC            |        |        |
| eD <sup>(5)(6)</sup> | 0.61 BSC    |       |      | 0.0240 BSC            |        |        |
| eE <sup>(5)(6)</sup> | 0.35 BSC    |       |      | 0.0138 BSC            |        |        |
| eS <sup>(5)(6)</sup> | 0.35 BSC    |       |      | 0.0138 BSC            |        |        |
| N <sup>(7)</sup>     | 24          |       |      |                       |        |        |
| SD <sup>(5)(8)</sup> | 0.61 BSC    |       |      | 0.0240 BSC            |        |        |
| SE <sup>(5)(8)</sup> | 0.35 BSC    |       |      | 0.0138 BSC            |        |        |
| aaa <sup>(9)</sup>   | 0.02        |       |      | 0.0008                |        |        |
| bbb <sup>(9)</sup>   | 0.06        |       |      | 0.0024                |        |        |
| ccc <sup>(9)</sup>   | 0.03        |       |      | 0.0012                |        |        |
| ddd <sup>(9)</sup>   | 0.015       |       |      | 0.0006                |        |        |

1. Values in inches are converted from mm and rounded to 4 decimal digits.
2. The profile height A is the distance from the seating plane to the highest point on the package. It is measured perpendicular to the seating plane.
3. A1 is defined as the distance from the seating plane to the lowest point on the package body.
4. Dimension b is measured at the maximum diameter of the terminal (ball) in a plane parallel to Datum C.
5. BSC stands for BASIC dimensions. It corresponds to the nominal value and has no tolerance. For tolerances, refer to form and position table. On the drawing, these dimensions are framed. For the tolerances, refer to form and position values.
6. e represents the solder balls grid pitch(es).
7. N represents the total number of balls.
8. Basic dimensions SD & SE are defining the ball matrix position with respect to datums A and B.
9. Tolerance of form and position drawing.