

Table 71. UFQFPN32 - Mechanical data

Symbol	Millimeters			Inches ⁽⁸⁾		
	Min	Typ	Max	Min	Typ	Max
A ⁽²⁾⁽³⁾	0.50	0.55	0.60	0.0197	0.0217	0.0236
A1 ⁽⁴⁾	0.00	-	0.05	0.000	-	0.0020
b ⁽⁶⁾⁽¹⁵⁾	0.18	0.25	0.30	0.0071	0.0098	0.0118
D ⁽⁷⁾	5.00 BSC			0.1969 BSC		
D2	3.40	3.50	3.60	0.1339	0.1378	0.1417
E ⁽⁷⁾	5.00 BSC			0.1969 BSC		
E2	3.40	3.50	3.60	0.1339	0.1378	0.1417
e	0.50 BSC			0.0197 BSC		
N ⁽¹²⁾	32					
L ⁽¹⁵⁾	0.30	-	0.50	0.0118	-	0.0197
R	0.09	-	-	0.0035	-	-

Table 72. Tolerance of form and position

Symbol	Millimeters	Inches ⁽⁸⁾
aaa	0.15	0.0059
bbb	0.10	0.0039
ccc	0.10	0.0039
ddd	0.05	0.0020
eee	0.08	0.0315
fff	0.10	0.0039