

Peripheral		STM32C53xFxP	STM32C53xFxU	STM32C53ExU	STM32C53KxT	STM32C53KxU	STM32C53CxT/ STM32C53CxU	STM32C3x2RxT
Timers	Basic					2		
	Low power					1		
	SysTick timer					1		
	Watchdog timers					2		
Comm. interfaces	SPI					2		
	I2C					1		
	I3C					1		
	USART					2		
	UART	1			2			
	LPUART					1		
	USB FS					1		
	FDCAN					2 ⁽¹⁾		
	TRACE	No						Yes
Cordic		Yes						
RTC		Yes (No LSE)					Yes	
Tamper pins		1		2			3	
Random generator		Yes						
HASH		Yes						
GPIOs		14		16	25	27	38	52
Wakeup pins		1	1	3	3		4	
12-bit ADC channels		4 ext. + 2 int.		5 ext. + 2 int.	8 ext. + 2 int.			12 ext. + 2 int.
12-bit DAC channels		2						
Analog comparator		2						
Operational amplifier		1						
Max. CPU frequency		144 MHz						
Operating voltage		2.7 V - 3.6 V						
Operating temperature		-40°C / 140°C						
Packages		TSSOP20	UFQFPN20	UFQFPN24	LQFP32	UFQFPN32	LQFP48 UFQFPN48	LQFP64

1. FDCAN is available only on STM32C532xx devices.