

5.3.6.5 Current consumption from peripherals

Table 28. Peripheral current consumption measured in Sleep mode

Bus	Peripheral	IDD(Typ)	Unit
AHB1	SRAM1	0.28	μA/MHz
	RAMCFG	0.82	
	ICACHE	0.57	
	CRC	0.94	
	FLASH	7.11	
	LPDMA1	1.20	
	LPDMA2	1.37	
	SRAM2	0.33	
AHB2	RNG	0.76	μA/MHz
	HASH	0.65	
	DAC1	1.00	
	ADC1	2.84	
	GPIOA	0.09	
	GPIOB	0.01	
	GPIOC	0.02	
	GIPOD	0.01	
	GPIOE	0.00	
	GPIOH	0.10	
APB1	FDCAN	2.64	μA/MHz
	CRS	0.23	
	I2C1	1.90	
	I3C1	0.41	
	UART5	3.27	
	UART4	3.30	
	USART2	3.73	
	COMP	0.03	
	SPI2/I2S2	1.56	
	OPAMP1	0.55	
	WWDG	0.19	
	TIM2	0.35	
	TIM6	0.26	
	TIM7	0.30	
	TIM12	0.32	
APB2	USB	1.95	μA/MHz
	USART1	3.34	
	SPI1/I2S1	1.41	
	TIM1	0.47	
	TIM8	0.41	