

Table 72. UFQFPN20 - Mechanical data

Symbol	Millimeters			Inches		
	Min	Typ	Max	Min	Typ	Max
A	0.500	0.550	0.600	0.0197	0.0217	0.0236
A1	0.000	0.020	0.050	0.0000	0.0008	0.0020
A3	0.152 reference			0.060 reference		
D	2.900	3.000	3.100	0.1142	0.1181	0.1220
E	2.900	3.000	3.100	0.1142	0.1181	0.1220
θ	0	-	12	0	-	0.0020
e	-	0.500 BSC ^(11.)	-	-	0.0197 BSC	-
b ^(4.)	0.180	0.250	0.300	0.0071	0.0098	0.0118
N ^(3.)	20			20		
ND ^(5.)	5			5		
NE ^(5.)	5			5		
La	0.300	0.350	0.400	0.0118	0.0138	0.0157
Lb	0.500	0.550	0.600	0.0197	0.0217	0.0236

Notes:

1. Dimensioning and tolerancing schemes conform to ASME Y14.5M-1994.
2. All dimensions are in millimeters except for θ, which is in degrees. Values in inches are converted from millimeters and rounded to four decimal digits.
3. N is the total number of terminals.
4. Dimension b applies to the metallized terminal and is measured between 0.15 and 0.30 mm from the terminal tip. If the terminal has an optional radius on the other end, dimension b should not be measured in that radius area.
5. ND and NE refer to the number of terminals on each D and E side, respectively.
6. The maximum package warpage is 0.05 mm.
7. The maximum allowable burrs are 0.076 mm in all directions.
8. Pin number 1 ID on top is laser marked.
9. Bilateral coplanarity zone applies to the terminals.
10. Allow chamfered corner lead.
11. BSC stands for basic dimensions.