

Table 74. LQFP32 - Mechanical data

Symbol	Millimeters			Inches ^(14.)		
	Min	Typ	Max	Min	Typ	Max
θ	0°	3.5°	7°	0°	3.5°	7°
θ_1	0°	-	-	0°	-	-
θ_2	10°	12°	14°	10°	12°	14°
θ_3	10°	12°	14°	10°	12°	14°
A	-	-	1.60	-	-	0.0630
A1 ^(12.)	0.05	-	0.15	0.0020	-	0.0059
A2	1.35	1.40	1.45	0.0531	0.0551	0.0571
b ^(9.) (11.)	0.30	0.37	0.45	0.0118	0.0146	0.0177
b1 ^(11.)	0.30	0.35	0.40	0.0118	0.0128	0.0157
c ^(11.)	0.09	-	0.20	0.0035	-	0.0079
c1 ^(11.)	0.09	-	0.16	0.0035	-	0.0063
D ^(4.)	9.00 BSC			0.3543 BSC		
D1 ^(2.) (5.)	7.00 BSC			0.2756 BSC		
e	0.80 BSC			0.0315 BSC		
E ^(4.)	9.00 BSC			0.3543 BSC		
E1 ^(2.) (5.)	7.00 BSC			0.2756 BSC		
L	0.45	0.60	0.75	0.0177	0.0236	0.0295
L1	1.00 REF			0.0394 REF		
N ^(13.)	32					
R1	0.08	-	-	0.0031	-	-
R2	0.08	-	0.20	0.0031	-	0.0079
S	0.20	-	-	0.0079	-	-
aaa ^(1.) (7.) ^(15.)	0.20			0.0079		
bbb ^(1.) (7.) ^(15.)	0.20			0.0079		
ccc ^(1.) (7.) ^(15.)	0.10			0.0039		
ddd ^(1.) (7.) ^(15.)	0.20			0.0079		