

Peripherals		STM32C55xKxT	STM32C55xKxU	STM32C55xCxT	STM32C55xCxU	STM32C55xRxT	STM32C55xRxTxJ	STM32C55xMxT	STM32C55xVxT
Timers	SysTick	1							
Window watchdog		2							
Communication interfaces	SPI (with I2S)	3 (3)							
	I2C	2							
	I3C	1							
	USART	3							
	UART	2							
	LPUART	1							
	USB	1							
	FDCAN	1 ⁽¹⁾							
	TRACE	No					Yes		
CORDIC		Yes							
RTC		Yes (without LSE)		Yes		Yes (without LSE)		Yes	
Tamper pins		2		3					
True random number generator (RNG)		Yes							
HASH		Yes							
GPIOs		25	27	38		52		66	86
Wake-up pins		3		4		6		6	7
12-bit ADC channels	External	9	10	11		17		18	19
	Internal	2	2	2	2	2		2	2
12-bit DAC channels		1							
Analog comparator		1							
Maximum CPU frequency (MHz)		144							
Operating voltage		2.7 V - 3.6 V							
Operating temperature		Junction temperature range: −40 to +140 °C							
Packages		LQFP32	UFQFPN32	LQFP48	UFQFPN48	LQFP64		LQFP80	LQFP100

1. Available only in STM32C552x devices.