

5.3.6.5 Current consumption from peripherals

Table 30. Peripheral current consumption measured in Sleep mode

Bus	Peripheral	I _{DD} (Typ)	Unit
AHB1	SRAM1	0.22	μA/MHz
	RAMCFG	0.70	
	ICACHE	0.20	
	CRC	0.70	
	FLASH	6.26	
	LPDMA1	1.22	
	LPDMA2	1.09	
	SRAM2	0.37	
AHB2	RNG	0.78	μA/MHz
	HASH	0.69	
	AES	0.92	
	DAC1	0.92	
	ADC12	5.51	
	GPIOA	0.07	
	GPIOB	0.07	
	GPIOC	0.09	
	GPIOD	0.07	
	GPIOE	0.08	
	GPIOH	0.06	
APB1	FDCAN1	4.86	μA/MHz
	CRS	0.23	
	I2C1	1.97	
	I2C2	2.00	
	I3C1	0.28	
	UART4	3.47	
	UART5	3.43	
	USART2	3.69	
	USART3	3.62	
	COMP	0.19	
	SPI2/I2S2	1.59	
	SPI3/I2S3	1.50	
	WWDG	0.14	
	TIM2	0.28	
	TIM5	0.31	
	TIM6	0.26	
	TIM7	0.29	
	TIM12	0.27	
APB2	USB	2.11	μA/MHz