

Peripherals		STM32C59xKxT	STM32C59xKxU	STM32C59xCxT STM32C59xCxU	STM32C59xRxT	STM32C59xMxT	STM32C59xVxT	STM32C59xZxT
Timers	General purpose	4 (32-bit) and 4 (16-bit)						
	Advanced-control	2						
	Basic	2 (16-bit)						
	Low-power	1 (16-bit)						
	SysTick	1						
	Watchdog	2						
Communication interfaces	SPI2S	3						
	I2C	2						
	I3C	1						
	USART	3			4			
	UART	2	3					
	LPUART	1						
	USB	1						
	FDCAN	0 (on STM32C591xx) or 2 (on STM32593xx)						
	Ethernet	No			No (on STM32C591xx) or yes (on STM32593xx)			
	TRACE	No			Yes			
CORDIC		Yes						
RTC		Yes (without LSE)		Yes				
Tamper pins		2		3				
True random number generator (RNG)		Yes						
HASH		Yes						
PKA (ECDSA signature verification)		Yes						
GPIOs		25	27	38	52	66	86	118
Wake-up pins		3		4	6		7	
12-bit ADC channels		9	10	11	17	22	28	
12-bit DAC channels		1						
Analog comparator		1						
Maximum CPU frequency (MHz)		144						
Operating voltage		2.7 V - 3.6 V						
Operating temperature		Junction temperature range: -40 to +140 °C						
Packages		LQFP32	UFQFPN32	LQFP48 UFQFPN48	LQFP64	LQFP80	LQFP100	LQFP144

Figure 1 shows the general block diagram of the device family.