

5.3.6.5 Current consumption from peripherals

Table 28. Peripheral current consumption measured in Sleep mode

Bus	Peripheral	IDD (TYP)	Unit
AHB1	CORDIC	1.35	$\mu\text{A}/\text{MHz}$
	CRC	1.3	
	ETH	13.6	
	FLASH	7.1	
	ICACHE1	0.495	
	LPDMA1	2.15	
	LPDMA2	2.25	
	RAMCFG	1.6	
	SRAM1	0.305	
	SRAM2	0.86	
AHB2	ADC12	5.6	$\mu\text{A}/\text{MHz}$
	ADC3	3.25	
	DAC1	0.54	
	GPIOA	0.215	
	GPIOB	0.085	
	GPIOC	0.099	
	GIOD	0.078	
	GPIOE	0.098	
	GPIOF	0.085	
	GPIOH	0.099	
	HASH	1.2	
	PKA	0.165	
	RNG	1.4	
	XSPI1	2.85	
APB1	COMP1	0.195	$\mu\text{A}/\text{MHz}$
	COMP12	0.002	
	CRS	0.205	
	FDCAN	9.4	
	I2C1	1.95	
	I2C2	2	
	I3C1	0.315	
	SPI2	1.55	
	SPI3	1.45	
	TIM12	0.27	
	TIM2	0.28	
	TIM3	0.295	
	TIM4	0.275	
	TIM5	0.305	