

Peripherals		STM32C5A3KxT	STM32C5A3KxU	STM32C5A3CxT STM32C5A3CxU	STM32C5A3RxT	STM32C5A3MxT	STM32C5A3VxT	STM32C5A3ZxT
Timers	General purpose	4 (32-bit) and 4 (16-bit)						
	Advanced-control	2						
	Basic	2 (16-bit)						
	Low-power	1 (16-bit)						
	SysTick	1						
	Watchdog	2						
Communication interfaces	SPI (with I2S)	3						
	I2C	2						
	I3C	1						
	USART	3			4			
	UART	2		3				
	LPUART	1						
	USB	1						
	FDCAN	2						
	Ethernet	No			Yes			
	TRACE	No			Yes			
CORDIC		Yes						
RTC		Yes (without LSE)		Yes				
Tamper pins		2		3				
True random number generator (RNG)		Yes						
HASH		Yes						
SAES, AES		Yes						
PKA		Yes						
GPIOs		25	27	38	52	66	86	118
Wake-up pins		3		4	6		7	
12-bit ADC channels		9	10	11	17	22	28	
12-bit DAC channels		1						
Analog comparator		1						
Maximum CPU frequency (MHz)		144						
Operating voltage		2.7 V - 3.6 V						
Operating temperature		Junction temperature range: -40 to +140 °C						
Packages		LQFP32	UFQFPN32	LQFP48 UFQFPN48	LQFP64	LQFP80	LQFP100	LQFP144

Figure 1 shows the general block diagram of the device family.