

5.3.6.5 Current consumption from peripherals
Table 30. Peripheral current consumption measured in Sleep mode

Bus	Peripheral	I _{DD} (Typ)	Unit
AHB1	CORDIC	1.35	μA/MHz
	CRC	1.3	
	ETH	13.6	
	FLASH	7.1	
	ICACHE1	0.495	
	LPDMA1	2.15	
	LPDMA2	2.25	
	RAMCFG	1.6	
	SRAM1	0.305	
	SRAM2	0.86	
AHB2	ADC12	5.6	
	ADC3	3.25	
	AES	1.2	
	CCB	0.8	
	DAC1	0.54	
	GPIOA	0.215	
	GPIOB	0.085	
	GPIOC	0.099	
	GPIOD	0.078	
	GPIOE	0.098	
	GPIOF	0.085	
	GPIOH	0.099	
	HASH	1.2	
	PKA	0.165	
	RNG	1.4	
	SAES	47.6	
	XSPI1	2.85	
APB1	COMP1	0.195	
	COMP12	0.002	
	CRS	0.205	
	FDCAN	9.4	
	I2C1	1.95	
	I2C2	2	
	I3C1	0.315	
	SPI2	1.55	
	SPI3	1.45	
	TIM12	0.27	
	TIM2	0.28	