



Galgotias College of Engineering and Technology, Greater
Noida (Affiliated to Dr. A.P.J Abdul Kalam Technical
University, Lucknow).

Department of Electronics and Communication Engineering
(B. Tech ECE 4 Accredited by NBA)

SMART HELMET SECURITY++

Submitted in partial fulfillment of the requirements for the degree of

Bachelor of Technology

in

Electronics and Communication Engineering

By

Ayush Dwivedi- 2400970310064

Badri Vishal Pandey-2400970310067

Under the Guidance of

Dr. Ravinder Kaur

Professor

Academic Year: 2025-2026

DECLARATION

We hereby declare that the thesis entitled "Smart Helmet Security++" submitted by us for the award of Bachelor of Technology in Electronics and Communication Engineering to Galgotias College of Engineering and Technology, Greater Noida, affiliated to Dr. A.P.J. Abdul Kalam Technical University, Lucknow, is a record of bona fide work carried out by us under the supervision of Dr. Ravinder Kaur .

We further declare that the work reported in this report has not been submitted and will not be submitted, either in part or in full, for the award of any other degree or diploma in this institute or any other institute or university.

Place: Greater Noida Signatures:

CERTIFICATE

This is to certify that the thesis entitled "Smart Helmet Security++ : submitted by Ayush Kumar ,Badri Vishal Pandey, Ankush Chaurasia Department of Electronics and Communication Engineering, Galgotias College of Engineering and Technology, Greater Noida affiliated to Dr. A.P.J. Abdul Kalam Technical University (AKTU), Lucknow, for the award of the degree of Bachelor of Technology in Electronics and Communication Engineering, is a record of bona fide work carried out by him/her under my supervision, as per AKTU code of academic and research ethics.

The contents of this report have not been submitted and will not be submitted either in part or in full, for the award of any other degree or diploma in this institute or any other institute or university. The thesis fulfils the requirements and regulations of the University and in my opinion meets the necessary standards for submission. Place: Greater Noida Signature of Guide:

Date: Internal Examiner : Approved By Head Of Department

ABSTRACT

The **Smart Helmet** is an innovative safety device designed to enhance road safety for two-wheeler riders. It integrates sensors and communication modules to detect accidents and automatically send alerts to emergency contacts. The system uses an **MPU6050 accelerometer and gyroscope sensor** to detect crashes, a **GPS module** to locate the accident, and a **GSM module** to send SMS alerts with location coordinates. The project aims to reduce emergency response time and save lives by providing instant accident notification.

ACKNOWLEDGEMENT

First of all, we would like to express our gratitude to our beloved Chairman Shri. Suneel Galgotia and CEO Shri Dhruv Galgotia for providing necessary facilities to carry out and finish the project successfully. We are grateful to our Director Prof. (Dr.) Vikram Bali for his Support and encouragement. Our special thanks goes to Dr. Rahul Vivek Purohit, M, Head of the Department, Electronics and Communication Engineering, for providing an environment that encouraged us in working towards our goal and supported in completion of our project. This project gave us an opportunity to apply creative and critical thinking skills. We would like to present our deep sense of gratitude to our project guide, Dr. Shilpi, Assistant Professor, Department of Electronics and Communication Engineering who has always been a source of motivation and firm support for carrying out the project. The supervision and support that she gave truly helped in the progression of the project. Her cooperation is much indeed appreciated. We are highly obliged to her for her valuable advices and moral support during research period. Finally, our greatest and special gratitude goes to our family for their love

CONTENT

[illegible]

CHAPTER 1

INTRODUCTION

N

Road accidents are a major cause of fatalities worldwide. Most deaths occur due to delayed emergency response after an accident. This project proposes a **Smart Helmet System** that detects accidents and automatically sends the rider's location to emergency contacts. The system uses an **MPU6050 sensor** to detect motion or fall, a **GPS module** to determine position, and a **GSM module** to send an SMS alert. Additionally, the system ensures that the rider cannot start the vehicle without wearing the helmet, enhancing safety

Circuit Diagram / Block Diagram **Block Diagram Components:** 1.**MPU6050 Sensor** 3 Detects crash and motion.

2.**Arduino UNO / R4 Microcontroller** 3 Processes sensor data.

3.**GPS Module (NEO-6M)** 3 Fetches real-time location.

4.**GSM Module (SIM800L/SIM900A)** 3 Sends SMS with coordinates.

5.**Power Supply (Battery)** 3 Powers the components.

6. **Buzzer** 3 Provides alert tone during testing or activation.

Working Principle:

- The MPU6050 constantly monitors tilt and acceleration.
- When a sudden impact exceeds a threshold, it is identified as a crash.
- The Arduino reads the data and triggers the GSM module.
- The GSM module sends an SMS containing latitude and longitude from GPS to predefined contacts.
- Optional features: Ignition lock when the helmet is not worn, alcohol detection, etc.

(iii) Result and Analysis

Observations:

- The system successfully detects abnormal tilt and acceleration.
- Upon impact, the GSM module sends an SMS in less than 10 seconds.
- The GPS coordinates received in the SMS can be opened in Google Maps for accurate tracking.
- The buzzer activates for quick feedback during testing.

Results:

- Crash detected 3 SMS sent to emergency number with coordinates.
- System accuracy improved by calibrating MPU6050 using I2Cdev library.
- Reliable location detection achieved with clear GPS satellite signal.

Performance Table:

Condition	Normal riding	Output	No alert	No alert	Alert	Time Taken
	Sudden stop (minor jerk)	triggered	Alert	sent	without	4 4 <10 sec 4
	Strong impact	No GPS	coordinates			
	signal					

(iv) Conclusion and Future Work

The **Smart Helmet** project demonstrates a practical and affordable solution for reducing accident response time. It can be integrated into modern helmets to improve rider safety. **Future Enhancements:**

- Integration of voice assistance and Bluetooth calling.
- Adding heartbeat sensor for rider health monitoring.
- IoT integration for cloud-based accident tracking.
- Solar-powered battery for long-term use.

CHAPTER 2


1.1 HISTORY OF IOT

The concept of the IoT dates back to the early 1980s when researchers began trying to connect everyday objects to the internet. One of the first known IoT devices was a Coca-Cola vending machine at Carnegie Mellon University, connected to the internet to report inventory levels and whether newly loaded drinks were cold. However, the idea of the interconnection of devices gained theoretical grounding in the 1990s, when Kevin Ashton, a British technologist working for Procter & Gamble at that time, came up with the term "Internet of Things" in 1999. He used the term in describing a system in which physical objects would be able to communicate via the internet, automatically collecting and sharing data by means of sensors and RFID technology.

IoT started materializing from an idea in the 2000s with the development of wireless communication, sensor technology, and microprocessors. With the introduction of IPv6, the number of possible addresses expanded immensely, and large-scale connectivity of devices became feasible. Tech companies like IBM, Cisco, and Google began developing IoT-based platforms, innovations such as smart homes, wearables, and industrial automation appeared. The fast growth of Wi-Fi and Bluetooth along with the expansion of mobile networks accelerated IoT adoption even further in different sectors.


By the 2010s, IoT became a major technological revolution, forming the backbone of smart cities, smart healthcare, and Industry 4.0. Billions of devices ranging from home appliances to industrial machines became interconnected, sharing real-time data to improve efficiency and decision-making. Today, IoT continues to evolve with the integration of artificial intelligence (AI), edge computing, and 5G technology, enabling faster communication, greater automation, and more intelligent systems that shape the foundation of a truly connected world.

RAW IMAGE



ARDUINO RAW IMAGE

Monitor at the time of crash



ALL COMPONENT

GSM+GPS+MPU6050 All are connected together

CHAPTER

3

1. Basic Concept

A **SmartHelmet** is an **intelligent safety device** designed to enhance the protection of two-wheeler riders by combining **mechanical safety** with **electronic sensing and communication technologies**. It not only provides physical protection during a crash but also **detects accidents automatically** and **alerts emergency contacts** with the rider's **exact GPS location** using GSM communication.

2. Principle of Operation

The Smart Helmet works on the **principle of real-time monitoring of motion, tilt, and acceleration** using sensors. When a sudden impact or abnormal movement occurs (beyond a defined threshold), it is identified as an **accident event**. The microcontroller processes this data and triggers the **GSM module** to send an **alert message** along with the **GPS coordinates** to registered contacts or emergency services.

Key Principle:

<Detection of unusual impact or motion ³ Processing ³ Communication of emergency alert.î

3. Core Components and Their Function

Component	Function
MPU6050 Sensor	Detects motion, tilt, and acceleration changes to identify a crash.
Arduino / Microcontroller	Acts as the brain of the system ⁴ reads sensor data, processes it, and sends commands.
GPS Module	Provides real-time latitude and longitude of the rider's location.
GSM Module	Sends SMS alerts with location details to emergency contacts.
Buzzer	Gives audio indication when a crash is detected or alert is triggered.
Power Supply	Provides operating voltage to all components (usually 5V/39V).

4. Working Flow

1. **Helmet Worn** ³ System activated.
2. **Sensors Active** ³ Continuously monitor rider's motion.
3. **Impact Detected** ³ MPU6050 senses sudden acceleration or tilt.
4. **Signal Sent to Microcontroller** ³ Arduino verifies and processes data.
5. **GSM Triggered** ³ Sends SMS alert with GPS coordinates.
6. **Rescue Response** ³ Emergency contact can track location via Google Maps.

5. Importance of Smart Helmet

- Provides **automatic accident detection** without human input.
- Reduces **emergency response time** by sending instant alerts. Ensures **rider**
- **compliance** (helmet-wearing detection). Helps **authorities and family members**
- locate accident victims quickly.
- Supports **road safety initiatives** and **IoT-based monitoring** in smart cities.

6. Applications

- Two-wheelers safety systems
- Smart transportation networks
- Emergency rescue systems Industrial
- worker safety helmets
- IoT-based healthcare monitoring

Conclusion

The **Smart Helmet for Accident Detection and Alert System** is an innovative solution designed to enhance the safety of two-wheeler riders. The system successfully integrates **sensors (MPU6050)**, **GPS**, **GSM**, and a **microcontroller (Arduino)** to detect accidents and automatically send emergency alerts with the rider's real-time location.

Through this project, we demonstrated how embedded systems and IoT technologies can be used to **save lives by reducing the response time after accidents**. The helmet continuously monitors motion and detects abnormal acceleration or tilt that indicates a crash. Once detected, the system immediately sends an SMS containing the GPS coordinates to predefined emergency contacts, ensuring quick assistance.

The Smart Helmet is **low-cost, efficient, and easy to implement**, making it suitable for large-scale use, especially in developing countries with high two-wheeler accident rates. It not only improves road safety but also promotes responsible riding by ensuring the rider wears the helmet.


Key Takeaways

- Successfully detects accident using MPU6050 sensor. Sends instant alert with
- GPS location via GSM. Reduces emergency response time. Portable, affordable,
- and can be upgraded with IoT and health sensors.
-


Future Scope

- Integration with **IoT** platforms for cloud-based accident monitoring.
- Addition of **heartbeat and alcohol sensors** for rider health and safety. **Voice-based**
- **communication** and **Bluetooth connectivity** for smart features.
- Integration with **mobile applications** for real-time tracking and rescue coordination.


DIAGRAM




MPU6050 MODULE



GPS + MPU6050




GSM + MPU6050



GPS + GSM + MPU6050

BLOCK DIAGRAM OF SMART HELMET SECURITY++ SYSTEM



This block diagram illustrates the operational flow of the Smart Helmet Security++ system. Each module plays a crucial role in sensing, processing, and communicating critical crash information. The helmet itself serves as the primary interface, housing the MPU6050 sensor. The MPU6050, an integrated accelerometer and gyroscope, is responsible for detecting sudden impacts or unusual changes in orientation, indicative of a crash. This raw sensor data is then transmitted to the Arduino microcontroller. The Arduino acts as the brain, processing the sensor input to determine the severity and nature of the incident. Upon confirming a crash, the Arduino activates the GPS module to pinpoint the exact geographical coordinates of the incident and the GSM module to send pre-configured alert messages. This critical information, including the precise location, is then relayed to a designated mobile phone, ensuring prompt notification and enabling rapid emergency response for the rider.

Technology Used

The **Smart Helmet** project is based on **embedded systems** and **IoT (Internet of Things)** technologies.

It combines **sensor-based accident detection**, **wireless communication**, and **location tracking** to ensure rider safety and quick emergency response.

1. Embedded System Technology

- The Smart Helmet is built using **Arduino UNO / R4 microcontroller**, which acts as the brain of the system. It processes real-time
- data from the sensors and controls all connected modules. Embedded C / Arduino programming is used to execute logical operations
- such as reading sensor values, detecting impacts, and triggering alerts.

Key Feature:

Enables real-time data processing and decision-making inside the helmet.

2. Sensor Technology

- The project uses an **MPU6050 sensor**, which combines a **3-axis accelerometer** and a **3-axis gyroscope**. It continuously
- monitors motion, tilt, and acceleration. When a sudden change in acceleration or angle is detected (beyond a threshold), it is
- identified as a crash or accident.

Key Role:

Detects crash impact and sends signal to the microcontroller.

3. GPS Technology (Global Positioning System)

- The **GPS module (NEO-6M)** provides real-time geographical coordinates (latitude and longitude). After an
- accident is detected, these coordinates are included in the alert message. This allows emergency responders or
- family members to locate the accident site precisely.

Key Role:

Provides the exact location of the rider during an accident.

4. GSM Communication Technology

- The **GSM module (SIM800L / SIM900A)** is used for wireless communication. It sends **SMS**
- **alerts** automatically to emergency contacts with the GPS location. The system does not require
- internet access, making it effective even in remote areas.

Key Role:

Sends automatic alert messages to registered phone numbers.

5. IoT (Internet of Things) Concept

- The system represents a **basic IoT architecture**, where physical sensors collect data, a microcontroller processes it, and communication modules transmit it to users.
- With IoT integration, the data could be sent to **cloud servers or mobile apps** for real-time monitoring in future versions.

Key Role:

Connects physical devices (helmet) with digital networks for smarter accident tracking.

6. Power Supply Technology

- The system operates on **DC power (5V-39V)** supplied by a rechargeable **Li-ion battery** or **9V battery**.
- Voltage regulation ensures safe and stable operation of all modules.

Key Role:

Provides uninterrupted power for real-time operation of sensors and modules.

7. Software and Programming Technology

- **Arduino IDE** is used for coding, compiling, and uploading the program to the microcontroller.
- Libraries like **Wire.h**, **I2Cdev.h**, **SoftwareSerial.h**, and **TinyGPS++** help in sensor communication and data handling. The system
- logic is implemented in **Embedded C / Arduino C language**.

Key Role:

Controls sensor data flow and communication between all modules.

Future Plan of Smart Helmet Project

The **Smart Helmet** project has shown how embedded systems and IoT can significantly improve rider safety by detecting accidents and sending automatic alerts. However, there is still room for enhancement and expansion. The future plan aims to make the system **more intelligent, connected, and user-friendly** using modern technologies.

1. Integration with IoT and Cloud

- Connect the helmet to **IoT platforms** for real-time data monitoring. Accident data and GPS coordinates can be **stored on cloud servers** and accessed by police, hospitals, or family members.
- Integration with **mobile apps** for instant notifications and live tracking.

Goal:

Enable 24×7 connectivity and centralized accident management.

2. Health Monitoring System

- Add **heartbeat and pulse sensors** to check the rider's vital signs. In case of abnormal heart rate or unconsciousness after an accident, alerts can be sent automatically. Can be integrated with hospital emergency systems for immediate action.

Goal:

Ensure not only accident detection but also post-crash health monitoring.

3. Alcohol Detection Feature

- Integrate an **alcohol sensor (MQ-3)** in the helmet or near the mouth area. If alcohol is detected, the ignition system can be disabled to prevent drunk driving.

Goal:

Promote responsible riding and prevent accidents due to intoxication.

4. Bluetooth and Voice Assistant Integration

- Add **Bluetooth** for wireless communication with smartphones. Include **voice command features** (e.g., Google Assistant) to control calls, messages, and navigation.

Goal:

Enhance comfort and convenience for the rider without compromising safety.

5. Solar-Powered System

- Use a **solar panel** on top of the helmet to recharge the internal battery. Helps in sustainable and continuous power supply during long rides.

Goal:

Achieve energy-efficient and eco-friendly operation.

6. AI-Based Accident Detection

- Implement **machine learning algorithms** to analyze sensor data more accurately.
- Reduce false alerts and improve crash detection reliability. AI can
- differentiate between small bumps and actual accidents.

Goal:

Increase detection accuracy using artificial intelligence.

7. Smart Traffic Integration

- In the future, helmets can communicate with **traffic management systems** to report accidents automatically.
- Enables **smart city integration**, where rescue vehicles are guided directly to the accident location.

Goal:

Build a connected ecosystem between riders, emergency services, and traffic systems.


8. Design Improvements

- Create a **compact and lightweight circuit** using a PCB instead of wires.
- Improve **ergonomics** for better comfort and durability.
- Use **waterproof and heat-resistant materials** to enhance usability.

9. Emergency Voice Call System

- Future versions may include **auto-dialing** features instead of SMS only.
- The system can directly call the nearest hospital, ambulance, or family contact after detecting a crash.

Circuit Diagram and Sensor Connections



Understanding the precise wiring is crucial for the reliable operation of the Smart Helmet Security++ system. Each sensor and module must be correctly interfaced with the Arduino microcontroller to ensure stable communication and data integrity.

- **MPU6050 Sensor**

Connects to the Arduino's dedicated I2C pins (Analog 4 for SDA, Analog 5 for SCL). This allows for efficient data transfer of accelerometer and gyroscope readings.

- **GSM Module**

Interfaced via SoftwareSerial on configurable TX/RX pins, typically Digital 2 and 3, to send SMS alerts and establish mobile network connectivity.

- **GPS Module**

Uses the Arduino's hardware TX/RX pins (Digital 0 and 1) for serial communication to transmit precise location data.

- **Power Supply**

The entire system can be powered efficiently using a 9V battery for portability or a USB connection for testing and development, ensuring consistent voltage supply.

Proper wiring and secure connections are paramount to prevent signal interference and ensure uninterrupted data flow between all components of the system, enabling prompt and accurate crash detection and alert dissemination.

Problems Faced During Smart Helmet Project

During the design and implementation of the **Smart Helmet for Accident Detection and Alert System**, several technical and practical challenges were encountered. These issues helped improve understanding of hardware integration, sensor calibration, and real-time communication.

1. Sensor Calibration Issues (MPU6050)

- The **MPU6050 accelerometer and gyroscope** were highly sensitive to small movements. It produced
- inaccurate readings or false accident detections if not properly calibrated. Adjusting threshold values
- and stabilizing sensor data using code filters was necessary.

Solution:

³ Used I2Cdev and Wire libraries for proper calibration and smoothing of readings.

2. GSM Module Network Problems

- The **SIM800L GSM module** required strong mobile network coverage to send SMS alerts. In some indoor or
- remote areas, the module failed to connect to the network or delayed messages.

Solution:

³ Tested with different SIM cards (Airtel, Jio, VI) and ensured stable power supply to GSM module.

3. GPS Signal Delay

- The **GPS module (NEO-6M)** sometimes took longer (132 minutes) to lock onto satellites, especially indoors. This caused
- delays in fetching coordinates after crash detection.

Solution:

³ Tested in open areas and used the TinyGPS++ library to handle incomplete GPS data efficiently.

4. Power Supply Fluctuations

- Modules like GSM and GPS require higher current during transmission. When powered by a 9V battery, sudden
- voltage drops caused system resets or communication errors.

Solution:

³ Used a regulated 5V/39V power supply and capacitors for current stabilization.

5. Hardware Mounting in Helmet

- Fitting all components (Arduino, sensors, GSM, GPS, battery) inside the helmet without affecting comfort and safety was challenging.
- Managing wires and ensuring secure connections in limited space was difficult.

Solution:

³ Used a mini breadboard, short jumper wires, and glued modules inside the helmet with proper insulation.

6. False Accident Detection

- During rough roads or sudden braking, the system sometimes detected false crashes.
- This required careful adjustment of sensor sensitivity and crash threshold values.

Solution:

³Performed multiple tests to find an optimal threshold level for accurate detection.

7. Software Integration and Debugging

- Interfacing **multiple serial devices (GSM and GPS)** on Arduino caused data overlap.
- Debugging required use of **SoftwareSerial library** and proper pin management.

Solution:

³Used different communication pins and verified outputs step by step on Serial Monitor.

8. Limited Range of GSM Alert

- The system depends on GSM coverage; in remote or hilly areas, alert messages may fail to send.

Solution:

³Future plan to integrate **IoT and internet-based alerting systems**.

9. Component Heating / Stability

- Long usage caused slight heating of GSM and GPS modules.
- Needed proper ventilation and short test durations during experiments.

10. Cost and Component Availability

- Some components like GSM and GPS modules were not easily available locally and took time to procure.
- Budget limitations restricted the use of more advanced IoT components.

Tools and Components Required for Smart Helmet Project

TheSmart Helmet project uses acombinationof**hardwaretools**,**softwaretools**,and**electronicmodules**to**detect** accidents and send emergency alerts.

Below is a brief overview

1. Hardware Components

Component	Description / Purpose
Arduino UNO R3	The main controller of the system. It reads data from sensors, processes the input, and controls the GSM and GPS modules. Detects sudden changes in motion, tilt, or impact
MPU6050 Sensor (Accelerometer + Gyroscope)	helps determine if an accident has occurred. Tracks the exact latitude and longitude of the rider
GPS Module (NEO-6M)	position and provides coordinates for alert messages. Sends SMS alerts with GPS location to predefined emergency contacts or numbers.
GSM Module (SIM800L)	Produces an alarm sound when an accident is detected or during testing.
Buzzer	Provides power supply to the entire circuit; ensures portability inside the helmet. The base platform
Battery (9V / Li-ion Rechargeable)	4 all components are fitted inside or attached to it safely. Used for circuit connections and testing during prototyping.
Helmet	Used for system ON/OFF control or helmet detection feature.
Connecting Wires & Breadboard	
Switch	

2. Software Tools

Software / Tool	Pur pose
Arduino IDE	Used to write, compile, and upload code into the Arduino board.
Embedded C / Arduino C Language	Programming language used to control sensors and communication modules.
I2Cdev Library & Wire.h	Helps communicate with MPU6050 sensor via I2C protocol.
TinyGPS++ Library	Used to read and process GPS data (latitude and longitude).
SoftwareSerial Library	Allows the Arduino to communicate with GSM and GPS simultaneously on different pins.
Serial Monitor (Arduino IDE)	Used for debugging and checking sensor values or messages during testing.

3. Additional Tools

Tool / Equipment	Use
Multimeter Soldering	For checking voltage, current, and connections. For making permanent connections. To mount components
Iron & Wire Glue Gun /	inside the helmet. As an external power source for
Tape Power Bank	testing. For receiving SMS alerts from the GSM
(Optional) Mobile Phone	module.

4. How These Tools Work Together

- The **MPU6050** continuouslymonitorsmovement.
- If an accident occurs, the **Arduino** detects abnormal sensor readings. **GPS module**
- fetches the current location. **GSM module** sends an SMS with coordinates to the
- emergency contact. **Buzzer** provides a sound alert.
-

How Smart Helmet Helps in Life Saving

The **Smart Helmet for Accident Detection and Alert System** is designed with the primary goal of **saving human lives** during road accidents. It uses advanced sensor and communication technologies to ensure that **immediate help reaches the victim**, even when they are unable to call for assistance.

1. Automatic Accident Detection

- The Smart Helmet is equipped with an **MPU6050 accelerometer and gyroscope sensor** that continuously monitors the rider's motion.
- When a severe impact or abnormal tilt is detected, the system identifies it as a **crash event**.
- Unlike traditional helmets, it **does not depend on manual operation** as the process is **fully automatic**, ensuring quick response even if the rider is unconscious.

Life-Saving Impact:

Early detection of accidents increases the chances of survival by reducing rescue delay.

2. Instant Alert Message to Emergency Contacts

- Once an accident is detected, the **GSM module** sends an **SMS alert** automatically to predefined contacts such as family members, police, or hospitals.
- The message contains the **exact GPS coordinates** provided by the **GPS module (NEO-6M)**.
- This enables rescuers to **locate the accident site immediately** using Google Maps.

Life-Saving Impact:

Immediate alert reduces the **<golden hour** delay, the critical time right after an accident when medical help can save a life.

3. Accurate Location Tracking

- The **GPS technology** ensures accurate real-time location tracking even in remote areas.
- Emergency services can reach the exact accident spot without wasting time in searching.
- This is extremely valuable when accidents occur at night or in isolated roads.

Life-Saving Impact:

Helps rescuers reach the victim's location faster and provide timely medical care.

4. Helmet-Wearing Detection (Optional Feature)

- The system can be expanded to include a **helmet detection switch** or **RF module** that ensures the rider cannot start the vehicle without wearing the helmet.
- This promotes safe driving behavior and reduces the risk of head injuries.

Life-Saving Impact:

Prevents riders from driving without helmets, thus minimizing fatal head trauma.

5. Prevention of Drunk Riding (Future Feature)

- By integrating an **alcohol sensor (MQ-3)**, the system can detect alcohol levels in the rider's breath.
- If alcohol is detected, the ignition can be automatically disabled.

Life-Saving Impact:

Prevents accidents caused by drunk driving, saving both the rider and others on the road.

6. Quick Emergency Response

- In many accidents, victims lose consciousness or are trapped. The Smart Helmet ensures help is requested automatically.
- This **shortens the emergency response time** and increases survival chances significantly.

Life-Saving Impact:

Timely medical assistance can reduce fatality rates and improve recovery chances.

7. Cost-Effective and Scalable Solution

- The system is affordable and easy to build using readily available components.
- It can be implemented on a large scale to improve national road safety programs.

Life-Saving Impact:

Affordable technology means more adoption leading to more lives saved on the road.

References (IEEE Format)

- [1] R. Kumar and M. Sharma, <IoT Based Smart Helmet for Accident Detection and Reporting System,î *IEEE Transactions on Intelligent Transportation Systems*, vol. 12, no. 3, pp. 45350, 2023.
- [2] A. Singh, P. Gupta, and N. Raj, <Smart Helmet for Rider Safety using GSM and GPS Technology,î *International Journal of Engineering Research & Technology (IJERT)*, vol. 10, no. 5, pp. 1123115, May 2022.
- [3] D. S. Reddy and B. S. Kumar, <Design and Implementation of Smart Helmet for Accident Detection,î *IEEE International Conference on Advanced Computing and Communication Systems (ICACCS)*, Coimbatore, India, 2021, pp. 2563260.
- [4] M. J. Binu and T. Joseph, <An IoT-Based Smart Helmet with Fall and Collision Detection,î *Proceedings of the 2020 IEEE Region 10 Symposium (TENSYP)*, Dhaka, Bangladesh, 2020, pp. 7803784.
- [5] S. P. Sahu, <Helmet Based Accident Detection and Alert System using Arduino,î *International Journal of Innovative Research in Computer and Communication Engineering (IJIRCCE)*, vol. 9, no. 4, pp. 983102, April 2021.
- [6] N. Patel and K. R. Sharma, <Real-Time Accident Alert and Detection Using GSM and GPS,î *International Journal of Advanced Research in Electrical, Electronics and Instrumentation Engineering (IJAREEIE)*, vol. 11, no. 2, pp. 2203224, Feb. 2022.
- [7] Datasheet: <MPU6050 3-Axis Accelerometer and Gyroscope Module,î InvenSense Inc., 2020. [Online]. Available: <https://invensense.tdk.com/products/motion-tracking/6-axis/mpu-6050/>
- [8] Datasheet: <SIM800L GSM/GPRS Module,î SIMCom Wireless Solutions, 2021. [Online]. Available: <https://simcom.ee/modules/gsm-gprs/sim800l>
- [9] Datasheet: <NEO-6M GPS Module,î u-blox AG, 2020. [Online]. Available: <https://www.u-blox.com/en/product/neo-6-series>
- [10] <Arduino Uno Rev3 Datasheet,î Arduino.cc, 2024. [Online]. Available: <https://store.arduino.cc/products/arduino-uno-rev3>