

Text Clustering

Applied Text Mining

Ayoub Bagheri

Contents


Lecture's plan	2
Unsupervised learning	3
Clustering versus classification	3
Clustering	4
Question	4
Clustering	4
Applications of text clustering	5
Applications of text clustering	5
Clustering algorithms	6
Clustering algorithms	6
Hard versus soft clustering	6
Partitional clustering	6
Partitional clustering algorithms	6
Partitional clustering algorithms	7
K-Means algorithm	7
K-Means algorithm	7
Hierarchical Clustering	8
Dendrogram: Hierarchical clustering	8
Clustering algorithms	8
Clustering algorithms	9
Hierarchical Agglomerative Clustering (HAC)	9
Closest pair of clusters	10

Topic Modeling	10
Topic models	10
Topic models Reality: Documents observed, infer topics	12
LDA graphical model	12
Probabilistic modeling	12
LDA: Identifying structure in text	13
Cluster Validation	13
Desirable properties of clustering algorithms	13
What is a good clustering?	13
Cluster validation	14
Internal validation	14
External criteria for clustering quality	14
Summary	14
Summary	14
Practical 4	14

Lecture's plan

1. What is text clustering?
2. What are the applications?
3. How to cluster text data?


Unsupervised learning



Clustering versus classification


CLASSIFICATION

- Labeled data points
- Want a “rule” that assigns labels to new points
- Supervised learning




CLUSTERING

- Data is not labeled
- Group points that are “close” to each other
- Identify structure or patterns in data
- Unsupervised learning



Clustering

- Clustering: the process of grouping a set of objects into clusters of similar objects
- Discover “natural structure” of data
 - What is the criterion?
 - How to identify them?
 - How to evaluate the results?



Question

Which one is not a text clustering task?

- Grouping Trump’s tweets and finding the main topics
- Finding similar patterns (demands) in customer reviews
- Grouping scientific articles
- Detection of heart failure (0 or 1) using discharge summaries


Please go to www.menti.com and use the code 7338 2184

Clustering

- Basic criteria
 - high intra-cluster similarity
 - low inter-cluster similarity
- No (little) supervision signal about the underlying clustering structure
- Need similarity/distance as guidance to form clusters


Applications of text clustering

- Organize document collections
 - Automatically identify hierarchical/topical relation among documents



Applications of text clustering

- Topic modeling
 - Grouping words into topics



Clustering algorithms

Clustering algorithms

- Partitional clustering
- Hierarchical clustering
- Topic modeling

Hard versus soft clustering

- Hard clustering: Each document belongs to exactly one cluster
 - More common and easier to do
- Soft clustering: A document can belong to more than one cluster.


Partitional clustering

Partitional clustering algorithms

- Partitional clustering method: Construct a partition of n documents into a set of K clusters
- Given: a set of documents and the number K
- Find: a partition of K clusters that optimizes the chosen partitioning criterion
 - Globally optimal
 - * Intractable for many objective functions
 - * Ergo, exhaustively enumerate all partitions
 - Effective heuristic methods: K-means and K-medoids algorithms

Partitional clustering algorithms

- Typical partitional clustering algorithms
 - k-means clustering
 - * Partition data by its closest mean



K-Means algorithm

- Assumes documents are real-valued vectors.
- Clusters based on centroids of points in a cluster, c :

$$\bar{\mu}(c) = \frac{1}{|c|} \sum_{\vec{a} \in c} \vec{x}$$

- Reassignment of instances to clusters is based on distance to the current cluster centroids.


K-Means algorithm

- Select K random docs $\{s_1, s_2, \dots, s_K\}$ as seeds.
- Until clustering converges (or other stopping criterion):
 - For each doc d_i :
 - * Assign d_i to the cluster c_j such that $dist(x_i, s_j)$ is minimal.
 - (Next, update the seeds to the centroid of each cluster)
 - For each cluster c_j
 - * $s_j = \mu(c_j)$

Hierarchical Clustering

Dendrogram: Hierarchical clustering

- Build a tree-based hierarchical taxonomy (dendrogram) from a set of documents.
- Clustering obtained by cutting the dendrogram at a desired level: each connected component forms a cluster.




Clustering algorithms

- Typical hierarchical clustering algorithms


- Bottom-up agglomerative clustering
 - * Start with individual objects as separated clusters
 - * Repeatedly merge closest pair of clusters

Most typical usage: gene sequence analysis



Clustering algorithms

- Typical hierarchical clustering algorithms
 - Top-down divisive clustering
 - * Start with all data as one cluster
 - * Repeatedly splitting the remaining clusters into two



Hierarchical Agglomerative Clustering (HAC)

- Starts with each doc in a separate cluster
 - then repeatedly joins the closest pair of clusters, until there is only one cluster.
- The history of merging forms a binary tree or hierarchy.

Closest pair of clusters

- Many variants to defining closest pair of clusters (linkage methods):
 - Single-link
 - * Similarity of the most cosine-similar
 - Complete-link
 - * Similarity of the “furthest” points, the least cosine-similar
 - Centroid
 - * Clusters whose centroids (centers of gravity) are the most cosine-similar
 - Average-link
 - * Average cosine between pairs of elements
 - Ward’s linkage
 - * Ward’s minimum variance method, much in common with analysis of variance (ANOVA)
 - * The distance between two clusters is computed as the increase in the “error sum of squares” (ESS) after fusing two clusters into a single cluster.

Topic Modeling

Topic models

- Three concepts: words, topics, and documents
- Documents are a collection of words and have a probability distribution over topics
- Topics have a probability distribution over words
- Model:
 - Topics made up of words used to generate documents

PROBABILISTIC GENERATIVE PROCESS






Image from Griffiths and Steyvers, 2007

Topic models | Reality: Documents observed, infer topics



LDA graphical model




Probabilistic modeling

1. Treat data as observations that arise from a generative probabilistic process that includes hidden variables: For documents, the hidden variables reflect the thematic structure of the collection.
2. Infer the hidden structure using posterior inference: What are the topics that describe this collection?

3. Situate new data into the estimated model: How does this query or new document fit into the estimated topic structure?

LDA: Identifying structure in text



Cluster Validation

Desirable properties of clustering algorithms

- Scalability
 - Both in time and space
- Ability to deal with various types of data
 - No/less assumption about input data
 - Minimal requirement about domain knowledge
- Interpretability and usability

What is a good clustering?

- Internal criterion: A good clustering will produce high quality clusters in which:
 - the intra-class (that is, intra-cluster) similarity is high
 - the inter-class similarity is low
 - The measured quality of a clustering depends on both the document representation and the similarity measure used

Cluster validation

- Criteria to determine whether the clusters are meaningful
 - Internal validation
 - * Stability and coherence
 - External validation
 - * Match with known categories

Internal validation

- Coherence
 - Inter-cluster similarity v.s. intra-cluster similarity
 - Davies–Bouldin index
 - * $DB = \frac{1}{k} \sum_{i=1}^k \max_{j \neq i} \left(\frac{\sigma_i + \sigma_j}{d(c_i, c_j)} \right) \leftarrow$ Evaluate every pair of clusters
 - where k is total number of clusters, σ_i is average distance of all elements in cluster i from the cluster center, $d(c_i, c_j)$ is the distance between cluster centroid c_i and c_j .

We prefer smaller DB-index!

External criteria for clustering quality

- Quality measured by its ability to discover some or all of the hidden patterns or latent classes in gold standard data
- Assesses a clustering with respect to ground truth ... requires labeled data
- Assume documents with C gold standard classes, while our clustering algorithms produce K clusters, $\omega_1, \omega_2, \dots, \omega_K$ with n_i members.

Summary

Summary

- Text clustering
- In clustering, clusters are inferred from the data without human input (unsupervised learning)
- Many ways of influencing the outcome of clustering: number of clusters, similarity measure, representation of documents
- Evaluation

Practical 4