

# Feature Engineering and Text Classification

Ayoub Bagheri

Introduction to Text Mining with R

## Table of Contents

Lecture's Plan.....	3
Text Classification.....	3
Text classification.....	3
Text classification?.....	4
Pipeline.....	4
Text Representation.....	5
How to represent a document.....	5
Vector space model .....	5
Vector space model .....	5
Vector space model .....	5
An illustration of VS model.....	5
Vector space model .....	6
Bag of Words (BOW).....	6
BOW representation .....	6
BOW weights: Binary.....	7
BOW weights: Term frequency.....	7
BOW weights: TFIDF .....	7
In R.....	7
In R.....	8
Feature Selection.....	8
Feature selection for text classification.....	8
Feature selection methods .....	8
Document frequency.....	9
Information gain.....	9
Gini Index .....	10
Gini Index .....	10
Classification Algorithms .....	11

How to classify this document? .....	11
Text Classification: definition .....	11
Hand-coded rules .....	11
Supervised Machine Learning .....	11
Rocchio Classifier (Nearest Centroid) .....	12
Rocchio Classifier (Nearest Centroid) .....	12
K-Nearest Neighbor .....	12
K-Nearest Neighbor .....	13
Naïve Bayes .....	13
Bayes' Rule .....	13
Multinomial Naïve Bayes Independence Assumptions .....	14
Multinomial Naïve Bayes Classifier .....	14
Parameter estimation .....	14
Problem with Maximum Likelihood .....	15
Laplace (add-1) smoothing for Naïve Bayes .....	15
Multinomial Naïve Bayes: Learning .....	15
Decision Tree .....	16
Random Forest .....	17
Support Vector Machine .....	17
Support Vector Machine .....	18
Evaluation .....	19
Data Splitting .....	19
Cross Validation .....	19
Confusion matrix .....	20
Accuracy .....	21
Precision and recall .....	22
A combined measure: F .....	23
The Real World .....	23
No training data? .....	23
Very little data? .....	24
A reasonable amount of data? .....	25
A huge amount of data? .....	26
Accuracy as a function of data size .....	27
How to tweak performance .....	28

Terminology .....	28
Some terminology .....	28
Summary .....	29
Summary.....	29
Practical 3.....	29

## Lecture's Plan

1. How to represent a document?
2. What are vector space and bag-of-words models?
3. Features in text? And how to do text feature selection?
4. How to classify text data?
5. How to evaluate a classifier?

## Text Classification

### Text classification

- Supervised learning: Learning a function that maps an input to an output based on example input-output pairs.
  - infer a function from labeled training data
  - use the inferred function to label new instances
- Human experts annotate a set of text data
  - Training set


Document	Class
Email1	Not spam
Email2	Not spam
Email3	Spam
...	...

### Text classification?

- Which problem is not a text classification task? (less likely to be)
  - Author's gender detection from text
  - Finding about the smoking conditions (yes/no) of patients from clinical letters
  - Grouping similar news articles
  - Classifying reviews into positive and negative sentiment

Go to [www.menti.com](https://www.menti.com) and use the code 9594 3321

### Pipeline



## Text Representation

### How to represent a document

- Represent by a string?
  - No semantic meaning
- Represent by a list of sentences?
  - Sentence is just like a short document (recursive definition)
- Represent by a vector?
  - A vector is an ordered finite list of numbers.

### Vector space model

- A vector space is a collection of vectors
- Represent documents by concept vectors
  - Each concept defines one dimension
  - k concepts define a high-dimensional space
  - Element of vector corresponds to concept weight

### Vector space model

- Distance between the vectors in this concept space
  - Relationship among documents
- The process of converting text into numbers is called Vectorization


### Vector space model

- Terms are generic features that can be extracted from text
- Typically, terms are single words, keywords, n-grams, or phrases
- Documents are represented as vectors of terms
- Each dimension (concept) corresponds to a separate term

$$d = (w_1, \dots, w_n)$$

### An illustration of VS model

- All documents are projected into this concept space



### Vector space model

- Bag of Words
- Topics
- Word Embeddings

### Bag of Words (BOW)

- With Bag of Words (BOW), we refer to a Vector Space Model where:
  - Terms: words (more generally we may use n-grams, etc.)
  - Weights: number of occurrences of the terms in the document

### BOW representation

- Term as the basis for vector space
  - Doc1: Text mining is to identify useful information.
  - Doc2: Useful information is mined from text.
  - Doc3: Apple is delicious.

	text	information	identify	mining	mined	is	useful	to	from	apple	delicious
Doc1	1	1	1	1	0	1	1	1	0	0	0
Doc2	1	1	0	0	1	1	1	0	1	0	0
Doc3	0	0	0	0	0	1	0	0	0	1	1

->

## BOW weights: Binary

- Binary
  - with 1 indicating that a term occurred in the document, and 0 indicating that it did not

## BOW weights: Term frequency

- Idea: a term is more important if it occurs more frequently in a document
- TF Formulas
  - Let  $t(c, d)$  be the frequency count of term  $t$  in doc  $d$
  - Raw TF:  $tf(t, d) = c(t, d)$

## BOW weights: TFIDF

- Idea: a term is more discriminative if it occurs a lot but only in fewer documents

Let  $n_{d,t}$  denote the number of times the  $t$ -th term appears in the  $d$ -th document.

$$TF_{d,t} = \frac{n_{d,t}}{\sum_i n_{d,i}}$$

Let  $N$  denote the number of documents and  $N_t$  denote the number of documents containing the  $t$ -th term.

$$IDF_t = \log\left(\frac{N}{N_t}\right)$$

TF-IDF weight:

$$w_{d,t} = TF_{d,t} \cdot IDF_t$$

## In R

```
library(tm)
```

```
## Loading required package: NLP
```

```
data <- c('Text mining is one of the Utrecht summer school courses.',
          'There are other data science courses in Utrecht summer school')
```

```
# convert data to vector space model
```

```
corpus <- VCorpus(VectorSource(data))

# create a dtm object
dtm <- DocumentTermMatrix(corpus,
                           list(removePunctuation = TRUE,
                                stopwords = TRUE,
                                stemming = TRUE,
                                removeNumbers = TRUE))
```

## In R

```
inspect(dtm)

## <<DocumentTermMatrix (documents: 2, terms: 9)>>
## Non-/sparse entries: 13/5
## Sparsity           : 28%
## Maximal term length: 7
## Weighting          : term frequency (tf)
## Sample            :
##      Terms
## Docs cours data mine one school scienc summer text utrecht
##   1     1    0    1    1     1      0      1    1      1
##   2     1    1    0    0     1      1      1    0      1
```

## Feature Selection

### Feature selection for text classification

- Feature selection is the process of selecting a specific subset of the terms of the training set and using only them in the classification algorithm.
- high dimensionality of text features
- Select the most informative features for model training
  - Reduce noise in feature representation
  - Improve final classification performance
  - Improve training/testing efficiency
    - Less time complexity
    - Fewer training data

### Feature selection methods

- Wrapper methods
  - Find the best subset of features for a particular classification method
  - Sequential forward selection or genetic search to speed up the search



- Filter methods
  - Evaluate the features independently from the classifier and other features
  - Feasible for very large feature sets
  - Usually used as a preprocessing step
- Embedded methods
- e.g. Regularized regression, Regularized SVM

## Document frequency

- Rare words: non-influential for global prediction, reduce vocabulary size




Figure 2.1. A plot of the hyperbolic curve relating  $f$ , the frequency of occurrence and  $r$ , the rank order (Adapted from Schultz, page 120)

## Information gain

- Decrease in entropy of categorical prediction when the feature is present or absent

$$\begin{aligned}
 IG(t) = & - \sum_c p(c) \log p(c) && \text{Entropy of class label along} \\
 & + p(t) \sum_c p(c|t) \log p(c|t) && \text{Entropy of class label if } t \text{ is} \\
 & && \text{present} \\
 & + p(\bar{t}) \sum_c p(c|\bar{t}) \log p(c|\bar{t}) && \text{Entropy of class label if } t \text{ is} \\
 & && \text{absent}
 \end{aligned}$$

probability of seeing class label  $c$  in documents where  $t$  occurs  
 probability of seeing class label  $c$  in documents where  $t$  does not occur

## Gini Index

Let  $p(c|t)$  be the conditional probability that a document belongs to class  $c$ , given the fact that it contains the term  $t$ . Therefore, we have:

$$\sum_{c=1}^k p(c|t) = 1$$

Then, the gini-index for the term  $t$ , denoted by  $G(t)$  is defined as:


$$G(t) = \sum_{c=1}^k p(c|t)^2$$

## Gini Index

- The value of the gini-index lies in the range  $(1/k, 1)$ .
- Higher values of the gini-index indicate a greater discriminative power of the term  $t$ .
- If the global class distribution is skewed, the gini-index may not accurately reflect the discriminative power of the underlying attributes.
- Other methods
  - Normalized gini-index
  - Mutual Information
  - $\chi^2$ -Statistic

## Classification Algorithms

### How to classify this document?



### Text Classification: definition

- Input:
  - A training set of  $m$  manually-labeled documents  $(d_1, c_1), \dots, (d_m, c_m)$
  - a fixed set of classes  $C = \{c_1, c_2, \dots, c_f\}$
- Output:
  - a learned classifier  $y: d \rightarrow c$

### Hand-coded rules

- Rules based on combinations of words or other features
- Rules carefully refined by expert
- But building and maintaining these rules is expensive
- Data/Domain specifics
- Not recommended!

### Supervised Machine Learning

- Logistic regression

- K-nearest neighbors
- Naïve Bayes
- Support vector machines
- Neural networks

## Rocchio Classifier (Nearest Centroid)

Each class is represented by its centroid, with test samples classified to the class with the nearest centroid. Using a training set of documents, the Rocchio algorithm builds a prototype vector, centroid, for each class. This prototype is an average vector over the training documents' vectors that belong to a certain class.

$$\mu_c = \frac{1}{|D_c|} \sum_{d \in D_c} \mathbf{d}$$

Where  $D_c$  is the set of documents in the corpus that belongs to class  $c$  and  $d$  is the vector representation of document  $d$ .

## Rocchio Classifier (Nearest Centroid)


The predicted label of document  $d$  is the one with the smallest (Euclidean) distance between the document and the centroid.

$$\hat{c} = \operatorname{argmin}_c ||\mu_c - \mathbf{d}||$$

## K-Nearest Neighbor

- Given a test document  $d$ , the KNN algorithm finds the  $k$  nearest neighbors of  $d$  among all the documents in the training set, and scores the category candidates based on the class of the  $k$  neighbors.
- After sorting the score values, the algorithm assigns the candidate to the class with the highest score.
- The basic nearest neighbors classification uses uniform weights: that is, the value assigned to a query point is computed from a simple majority vote of the nearest neighbors.  $C$
- Can weight the neighbors such that nearer neighbors contribute more to the fit.

## K-Nearest Neighbor



## Naïve Bayes

$$y\left(\begin{array}{|c|c|} \hline \text{great} & 2 \\ \hline \text{love} & 2 \\ \hline \text{recommend} & 1 \\ \hline \text{laugh} & 1 \\ \hline \text{happy} & 1 \\ \hline \dots & \dots \\ \hline \end{array}\right) = c$$

## Bayes' Rule

- Applied to documents and classes
- For a document  $d$  and a class  $c$

$$P(c|d) = \frac{P(d|c)P(c)}{P(d)}$$

## Multinomial Naïve Bayes Independence Assumptions

- Bag of Words assumption: Assume position doesn't matter
- Conditional Independence: Assume the feature probabilities  $P(w_i|c_j)$  are independent given the class  $c$ .

$$P(w_1, \dots, w_n|c) = P(w_1|c) \cdot P(w_2|c) \cdot P(w_3|c) \cdot \dots \cdot P(w_n|c)$$

## Multinomial Naïve Bayes Classifier

$$C_{MAP} = \operatorname{argmax}_{c \in C} P(w_1, w_2, \dots, w_n|c)P(c)$$

$$C_{NB} = \operatorname{argmax}_{c \in C} P(c_j) \prod_{w \in V} P(w|c)$$

$$C_{NB} = \operatorname{argmax}_{c \in C} P(c_j) \prod_{i \in \text{positions}} P(w_i|c_i)$$

## Parameter estimation

- First attempt: maximum likelihood estimates
  - simply use the frequencies in the data

$$\hat{P}(c_j) = \frac{\text{doccount}(C = c_j)}{N_{doc}}$$

$$\hat{P}(w_i|c_j) = \frac{\text{count}(w_i, c_j)}{\sum_{w \in V} \text{count}(w, c_j)}$$

- fraction of times word  $w_i$  appears among all words in documents of topic  $c_j$

## Problem with Maximum Likelihood

What if we have seen no training documents with the word coffee and classified in the topic positive (thumbs-up)?

$$\hat{P}(\text{"coffee"}|\text{positive}) = \frac{\text{count}(\text{"coffee"}, \text{positive})}{\sum_{w \in V} \text{count}(w, \text{positive})}$$

Zero probabilities cannot be conditioned away, no matter the other evidence!

$$C_{MAP} = \underset{c}{\operatorname{argmax}} \hat{P}(c) \prod_i \hat{P}(w_i|c)$$

## Laplace (add-1) smoothing for Naïve Bayes

$$\begin{aligned} \hat{P}(w_i|c) &= \frac{\text{count}(w_i, c) + 1}{\sum_{w \in V} (\text{count}(w, c) + 1)} \\ &= \frac{\text{count}(w_i, c) + 1}{(\sum_{w \in V} \text{count}(w, c) + |V|)} \end{aligned}$$

## Multinomial Naïve Bayes: Learning

- From training corpus, extract Vocabulary
- Calculate  $P(c_j)$  terms
  - For each  $c_j$  in  $C$  do

$docs_j \leftarrow$  all docs with class =  $c_j$

$$P(c_j) \leftarrow \frac{|docs_j|}{|total \# documents|}$$

- Calculate  $P(w_k|c_j)$  terms
  - $Text_j \leftarrow$  single doc containing all  $docs_j$
  - For each word  $w_k$  in Vocabulary

$n_k \leftarrow$  # of occurrences of  $w_k$  in  $Text_j$

$$P(w_k|c_j) \leftarrow \frac{n_k + \alpha}{n + \alpha|Vocabulary|}$$


## Decision Tree

- A decision tree is a hierarchical decomposition of the (training) data space, in which a condition on the feature value is used in order to divide the data space hierarchically.
- Top-down, by choosing a variable at each step that best splits the set of items.
- Different algorithms to measure the homogeneity of the target variable within the subsets.
  - Gini impurity
  - Information gain




## Random Forest

- Random forests are an ensemble learning method for classification, regression and other tasks that operates by constructing a multitude of decision trees at training time.
- Fit multiple trees to bootstrapped samples of the data AND at each node select best predictor from only a random subset of predictors. Combine all trees to yield a consensus prediction




## Support Vector Machine

- The main principle of SVM is to determine separators in the search space which can best separate the different classes.
- SVM tries to make a decision boundary in such a way that the separation between the two classes is as wide as possible.



## Support Vector Machine

- It is not necessary to use a linear function for the SVM classifier.
- With the kernel trick, SVM can construct a nonlinear decision surface in the original feature space by mapping the data instances non-linearly to a new space where the classes can be separated linearly with a hyperplane.
- In practice, linear SVM is used most often because of their simplicity and ease of interpretability.
- SVM is quite robust to high dimensionality.




## Evaluation

### Data Splitting

- Training set
  - Validation set (dev set)
    - A validation dataset is a dataset of examples used to tune the hyperparameters (i.e. the architecture) of a classifier. It is sometimes also called the development set or the “dev set”.
- Test set

### Cross Validation



[https://scikit-learn.org/stable/modules/cross\\_validation.html](https://scikit-learn.org/stable/modules/cross_validation.html)

## Confusion matrix

		Predicted Class		
		Positive	Negative	
Actual Class	Positive	True Positive (TP)	False Negative (FN) <b>Type II Error</b>	<b>Sensitivity</b> $\frac{TP}{(TP + FN)}$
	Negative	False Positive (FP) <b>Type I Error</b>	True Negative (TN)	<b>Specificity</b> $\frac{TN}{(TN + FP)}$
		<b>Precision</b> $\frac{TP}{(TP + FP)}$	<b>Negative Predictive Value</b> $\frac{TN}{(TN + FN)}$	<b>Accuracy</b> $\frac{TP + TN}{(TP + TN + FP + FN)}$

## Accuracy

- What proportion of instances is correctly classified?  
$$\frac{TP + TN}{TP + FP + FN + TN}$$
- Accuracy is a valid choice of evaluation for classification problems which are well balanced and not skewed.
- Let us say that our target class is very sparse. Do we want accuracy as a metric of our model performance? What if we are predicting if an asteroid will hit the earth? Just say “No” all the time. And you will be 99% accurate. The model can be reasonably accurate, but not at all valuable.

## Precision and recall

- Precision: % of selected items that are correct Recall: % of correct items that are selected
- Precision is a valid choice of evaluation metric when we want to be very sure of our prediction.
- Recall is a valid choice of evaluation metric when we want to capture as many positives as possible.

## A combined measure: F

A combined measure that assesses the P/R tradeoff is F measure (weighted harmonic mean):

$$F = \frac{1}{\alpha \frac{1}{P} + (1 - \alpha) \frac{1}{R}} = \frac{(\beta^2 + 1)PR}{\beta^2 P + R}$$

The harmonic mean is a very conservative average;

Balanced F1 measure - i.e., with  $\beta = 1$  (that is,  $\alpha = 1/2$ ):  $F = 2PR/(P + R)$

## The Real World

### No training data?

- Manually written rules
  - If (x or y) and not (w or z) then categorize as class1
  - Need careful crafting
  - Low accuracy
  - Domain-specific
  - Time-consuming
- Active learning
- Unsupervised methods

## Very little data?

- Use Naïve Bayes, KNN, Rocchio
  - Naïve Bayes is a “high-bias” algorithm (Ng and Jordan 2002 NIPS)
- Get more labeled data
- Find ways to label data for you
- Try semi-supervised methods:
  - e.g. active learning, bootstrapping



## A reasonable amount of data?

- Perfect for all the complex classifiers
  - SVM
  - Regularized Logistic Regression
  - Random forest

## A huge amount of data?

- Can achieve high accuracy!
- At a cost:
  - SVMs (train time) or KNN (test time) can be too slow
  - Regularized logistic regression
  - Naïve Bayes again!
  - Deep learning

## Accuracy as a function of data size

- With enough data
  - Classifier may not matter




Figure 1. Learning Curves for Confusion Set Disambiguation

<https://aclanthology.org/P01-1005.pdf>

## How to tweak performance

- Domain-specific features and weights: very important in real performance
- Sometimes need to collapse terms:
  - Part numbers, chemical formulas, ...
  - But stemming generally doesn't help
- Upweighting: Counting a word as if it occurred twice:
  - Title words
  - First sentence of each paragraph (Murata, 1999)
  - In sentences that contain title words
- Hyperparameter optimization

## Terminology

### Some terminology

Corpus: is a large and structured set of texts

Stop words: words which are filtered out before or after processing of natural language data (text)

Unstructured text: information that either does not have a pre-defined data model or is not organized in a pre-defined manner.

Tokenizing: process of breaking a stream of text up into words, phrases, symbols, or other meaningful elements called tokens (see also lexical analysis)

Natural language processing: field of computer science, artificial intelligence, and linguistics concerned with the interactions between computers and human (natural) languages

Term document (or document term) matrix: is a mathematical matrix that describes the frequency of terms that occur in a collection of documents

Supervised learning: is the machine learning task of inferring a function from labeled training data

Unsupervised learning: find hidden structure in unlabeled data

## Summary

### Summary

- Vector space model & BOW
- Feature Selection
- Text Classification
- Evaluation

## Practical 3