

KOLT Python

Containers, Aliasing & Mutability

Gül Sena Altıntaş

Monday 4th November, 2019

KOLT

Agenda

Functions

Lists

1. Data Model

2. Aliasing & Cloning

3. Objects


4. Mutability

5. Tuples


6. Sets

7. Dictionaries

Functions




Functions



```
def function_name(parameter2, parameter2, ...):  
    <expression>  
    ...  
    return value
```


Functions



```
def function_name(parameter2, parameter2, ...):  
    <expression>  
    ...  
    return value
```

```
fib_100 = fibonacci_series(100)
```

Functions



```
def function_name(parameter2, parameter2, ...):  
    <expression>  
    ...  
    return value
```

```
fib_100 = fibonacci_series(100)  
what_is_going_on = print(fib_100)
```



return Statement

Every function returns one value!



return Statement

Every function returns one value!
What type does each function return?

return Statement

Every function returns one value!
What type does each function return?

```
def square(x):  
    return x**2
```





Sponge Bob seeks for Sandy




Sponge Bob seeks for Sandy

```
cartoon_characters=['Tweety', 'Mickey', 'Sponge Bob', 'Jerry',  
'Minnie']
```



Sponge Bob seeks for Sandy


```
cartoon_characters=['Tweety', 'Mickey', 'Sponge Bob', 'Jerry',  
'Minnie']
```



```
cartoon_characters.append('Sandy')
```

Sponge Bob seeks for Sandy

```
cartoon_characters=['Tweety', 'Mickey', 'Sponge Bob', 'Jerry',  
'Minnie']
```



```
cartoon_characters.append('Sandy')
```



Let's play

But, what good is Mickey without being near to Minnie?

Let's play

But, what good is Mickey without being near to Minnie?

```
cartoon_characters.remove('Mickey')
```



Let's play

But, what good is Mickey without being near to Minnie?

```
cartoon_characters.remove('Mickey')
```



Let's play

But, what good is Mickey without being near to Minnie?

```
cartoon_characters.remove('Mickey')
```




```
cartoon_characters.insert(4, 'Mickey')
```

Let's play

But, what good is Mickey without being near to Minnie?

```
cartoon_characters.remove('Mickey')
```



0


1

2

3

4

```
cartoon_characters.insert(4, 'Mickey')
```



List Operations

Be quick!



`len(cartoon_characters) ⇒`

List Operations


Be quick!



`len(cartoon_characters) ⇒ 6`

List Operations


Be quick!



```
len(cartoon_characters) ⇒ 6  
cartoon_characters[6] ⇒
```


List Operations

Be quick!



```
len(cartoon_characters) ⇒ 6  
cartoon_characters[6] ⇒ Error
```

List Operations


Be quick!



```
len(cartoon_characters) ⇒ 6  
cartoon_characters[6] ⇒ Error  
'Jerry' in cartoon_characters ⇒
```

List Operations

Be quick!




`len(cartoon_characters) ⇒ 6`

`cartoon_characters[6] ⇒ Error`

`'Jerry' in cartoon_characters ⇒ False`

List Operations

Be quick!



```
len(cartoon_characters) ⇒ 6  
cartoon_characters[6] ⇒ Error  
'Jerry' in cartoon_characters ⇒ False  
cartoon_characters.index('Tweety') ⇒
```

List Operations

Be quick!



```
len(cartoon_characters) ⇒ 6  
cartoon_characters[6] ⇒ Error  
'Jerry' in cartoon_characters ⇒ False  
cartoon_characters.index('Tweety') ⇒ 0
```



Don't let me forget you

Don't let me forget you

Fill out the attendance form: tiny.cc/kolt-python

Don't let me forget you

Fill out the attendance form: tiny.cc/kolt-python

Password: **Recycle**

Don't let me forget you

Fill out the attendance form: tiny.cc/kolt-python

Password: **Recycle**



Python Data Model

Python Data Model

How did we represent data in Python?

Python Data Model

How did we represent data in Python? **Variables!**

Python Data Model


How did we represent data in Python? **Variables!**
How do they work?

Python Data Model

How did we represent data in Python? **Variables!**
How do they work? Do they store the data themselves?


Python Data Model

How did we represent data in Python? **Variables!**
How do they work? Do they store the data themselves?



Python Data Model

How did we represent data in Python? **Variables!**
How do they work? Do they store the data themselves?



Box Analogy

Box Analogy

```
my_age = 9  
my_age += 12  
print(my_age)    # => 21
```

Box Analogy


```
my_age = 9
my_age += 12
print(my_age)    # => 21
```

```
mickeys_leaving = cartoon_characters
mickeys_leaving.remove('Mickey')
mickeys_leaving.remove('Minnie')
print(cartoon_characters)
```

Box Analogy

```
my_age = 9
my_age += 12
print(my_age)    # => 21
```


```
mickeys_leaving = cartoon_characters
mickeys_leaving.remove('Mickey')
mickeys_leaving.remove('Minnie')
print(cartoon_characters)
```



Box Analogy

```
my_age = 9
my_age += 12
print(my_age)    # => 21
```

```
mickeys_leaving = cartoon_characters
mickeys_leaving.remove('Mickey')
mickeys_leaving.remove('Minnie')
print(cartoon_characters)
```




Did we just changed inside of a closed box?

Box Analogy

```
my_age = 9  
my_age += 12  
print(my_age)    # => 21
```

```
mickeys_leaving = cartoon_characters  
mickeys_leaving.remove('Mickey')  
mickeys_leaving.remove('Minnie')  
print(cartoon_characters)
```



Did we just changed inside of a closed box?
Box analogy **does not** work!

Python Data Model

```
cartoon_characters = ['Tweety',  
'Sponge Bob', 'Jerry', 'Minnie',  
'Mickey', 'Sandy']
```



Python Data Model

```
cartoon_characters = ['Tweety',  
                     'Sponge Bob', 'Jerry', 'Minnie',  
                     'Mickey', 'Sandy']  
mickeys_leaving =  
cartoon_characters
```



Python Data Model

```
cartoon_characters = ['Tweety',  
                     'Sponge Bob', 'Jerry', 'Minnie',  
                     'Mickey', 'Sandy']  
mickeys_leaving =  
cartoon_characters  
mickeys_leaving.remove('Mickey')
```

Python Data Model

```
cartoon_characters = ['Tweety',  
                     'Sponge Bob', 'Jerry', 'Minnie',  
                     'Mickey', 'Sandy']  
mickeys_leaving =  
    cartoon_characters  
mickeys_leaving.remove('Mickey')  
mickeys_leaving.remove('Minnie')
```

Python Data Model

```
cartoon_characters = ['Tweety',
'Sponge Bob', 'Jerry', 'Minnie',
'Mickey', 'Sandy']
mickeys_leaving =
cartoon_characters
mickeys_leaving.remove('Mickey')
mickeys_leaving.remove('Minnie')
print(cartoon_characters)
```



Python Data Model

```
cartoon_characters = ['Tweety',
'Sponge Bob', 'Jerry', 'Minnie',
'Mickey', 'Sandy']
mickeys_leaving =
cartoon_characters
mickeys_leaving.remove('Mickey')
mickeys_leaving.remove('Minnie')
print(cartoon_characters)
```



Python Data Model

```
cartoon_characters = ['Tweety',  
'Sponge Bob', 'Jerry', 'Minnie',  
'Mickey', 'Sandy']  
mickeys_leaving =  
cartoon_characters  
mickeys_leaving.remove('Mickey')  
mickeys_leaving.remove('Minnie')  
print(cartoon_characters)
```



Python Data Model

```
cartoon_characters = ['Tweety',  
'Sponge Bob', 'Jerry', 'Minnie',  
'Mickey', 'Sandy']  
mickeys_leaving =  
cartoon_characters  
mickeys_leaving.remove('Mickey')  
mickeys_leaving.remove('Minnie')  
print(cartoon_characters)
```



Python Data Model

```
cartoon_characters = ['Tweety',  
'Sponge Bob', 'Jerry', 'Minnie',  
'Mickey', 'Sandy']  
mickeys_leaving =  
cartoon_characters  
mickeys_leaving.remove('Mickey')  
mickeys_leaving.remove('Minnie')  
print(cartoon_characters)
```



Python Data Model

```
cartoon_characters = ['Tweety',
'Sponge Bob', 'Jerry', 'Minnie',
'Mickey', 'Sandy']
mickeys_leaving =
cartoon_characters
mickeys_leaving.remove('Mickey')
mickeys_leaving.remove('Minnie')
print(cartoon_characters)
```



Python Data Model

```
cartoon_characters = ['Tweety',  
                     'Sponge Bob', 'Jerry', 'Minnie',  
                     'Mickey', 'Sandy']  
mickeys_leaving =  
cartoon_characters  
mickeys_leaving.remove('Mickey')  
mickeys_leaving.remove('Minnie')  
print(cartoon_characters)
```



Variables are more like **labels** pointing to **values**!

Python Data Model


```
cartoon_characters = ['Tweety',  
'Sponge Bob', 'Jerry', 'Minnie',  
'Mickey', 'Sandy']  
mickeys_leaving =  
cartoon_characters  
mickeys_leaving.remove('Mickey')  
mickeys_leaving.remove('Minnie')  
print(cartoon_characters)
```



Variables are more like **labels** pointing to **values**!
Assignment links **variables** to **values**!

Aliasing & Cloning

- More than one variables can refer to **same object**!
- What if we want to clone/copy instead of aliasing?
- For lists, `list.copy()` \Rightarrow returns a shallow copy of the list.
- Shallow: only copy the references, not inner values.



What if we copied the cartoon characters

What if we copied the cartoon characters



Object

Everything is an object in Python.

Object

Everything is an object in Python. Even though variables **do not** have `types`, each object has a **fixed** `type`.

Object

Everything is an object in Python. Even though variables **do not** have `types`, each object has a **fixed** `type`.

↪ Values at the right side of our label analogy are objects!

Object

Everything is an object in Python. Even though variables **do not** have `types`, each object has a **fixed** `type`.

↪ Values at the right side of our label analogy are objects!

```
a = 5
```

Object

Everything is an object in Python. Even though variables **do not** have `types`, each object has a **fixed** `type`.

↪ Values at the right side of our label analogy are objects!

`a = 5`

5

Object

Everything is an object in Python. Even though variables **do not** have `types`, each object has a **fixed** `type`.

↪ Values at the right side of our label analogy are objects!

`a = 5`



Object

Everything is an object in Python. Even though variables **do not** have `types`, each object has a **fixed** `type`.

↪ Values at the right side of our label analogy are objects!

`a = 5`



Object

Everything is an object in Python. Even though variables **do not** have `types`, each object has a **fixed** `type`.

↪ Values at the right side of our label analogy are objects!

```
a = 5  
a = 10
```




Object

Everything is an object in Python. Even though variables **do not** have `types`, each object has a **fixed** `type`.

↪ Values at the right side of our label analogy are objects!

```
a = 5  
a = 10
```




Object

Everything is an object in Python. Even though variables **do not** have `types`, each object has a **fixed** `type`.

↪ Values at the right side of our label analogy are objects!

```
a = 5  
a = 10
```




Object

Everything is an object in Python. Even though variables **do not** have `types`, each object has a **fixed** `type`.

↪ Values at the right side of our label analogy are objects!

```
a = 5  
a = 10
```




Object

Everything is an object in Python. Even though variables **do not** have `types`, each object has a **fixed** `type`.

↪ Values at the right side of our label analogy are objects!

```
a = 5  
a = 10  
a += 3
```




Object

Everything is an object in Python. Even though variables **do not** have `types`, each object has a **fixed** `type`.

↪ Values at the right side of our label analogy are objects!

```
a = 5  
a = 10  
a += 3
```




Object

Everything is an object in Python. Even though variables **do not** have `types`, each object has a **fixed** `type`.

↪ Values at the right side of our label analogy are objects!

```
a = 5  
a = 10  
a += 3
```




Object

Everything is an object in Python. Even though variables **do not** have `types`, each object has a **fixed** `type`.

↪ Values at the right side of our label analogy are objects!

```
a = 5  
a = 10  
a += 3
```




Object

Everything is an object in Python. Even though variables **do not** have `types`, each object has a **fixed** `type`.

↪ Values at the right side of our label analogy are objects!

```
a = 5  
a = 10  
a += 3  
print(a)
```



Object

Each object has an `identity`,

Object

Each object has an `identity`, this value can be obtained by using `id()` function.



Object

Each object has an `identity`, this value can be obtained by using `id()` function.
`==` operator compares values, `is` operator compares identities.

Object

Each object has an `identity`, this value can be obtained by using `id()` function.

`==` operator compares values, `is` operator compares identities.

```
simba_2019 = 'Simba'
simba_cartoon = 'Simba'
simba_2019 == simba_cartoon      # => True
simba_2019 is simba_cartoon      # => False
```

Object

Each object has an `identity`, this value can be obtained by using `id()` function.

`==` operator compares values, `is` operator compares identities.

```
simba_2019 = 'Simba'
simba_cartoon = 'Simba'
simba_2019 == simba_cartoon      # => True
simba_2019 is simba_cartoon      # => False
```



Almost always use `==` to compare values!

Mutability

Immutable:

An `object` with a fixed value.

Mutability

Immutable:

An **object** with a fixed value. Immutable objects include **numbers**, **strings** and **tuples**. Such an object cannot be altered.

Mutability

Immutable:

An **object** with a fixed value. Immutable objects include **numbers**, **strings** and **tuples**. Such an object cannot be altered. A new object has to be created if a different value has to be stored.

Mutability

Immutable:

An **object** with a fixed value. Immutable objects include **numbers**, **strings** and **tuples**. Such an object cannot be altered. A new object has to be created if a different value has to be stored. They play an important role in places where a constant **hash value** is needed, for example as a **key** in a `dictionary`.

Mutability

Immutable:

An **object** with a fixed value. Immutable objects include **numbers**, **strings** and **tuples**. Such an object cannot be altered. A new object has to be created if a different value has to be stored. They play an important role in places where a constant **hash value** is needed, for example as a **key** in a dictionary.

```
a = 5  
a = 10  
a += 3
```

```
hello = 'hello'  
hallo = hello[0] + 'a' + hello[2:]
```

Tuples

- **Immutable** sequence(ordered) of elements.

Tuples

- **Immutable** sequence(ordered) of elements.
- Similar to `lists`, you can use **indexing**, **slicing**, and iterate over using `for` loops.

Tuples

- **Immutable** sequence(ordered) of elements.
- Similar to `lists`, you can use **indexing**, **slicing**, and iterate over using `for` loops.
- Elements cannot be added/removed/changed once the tuple is created.

Tuples

- **Immutable** sequence(ordered) of elements.
- Similar to `lists`, you can use **indexing**, **slicing**, and iterate over using `for` loops.
- Elements cannot be added/removed/changed once the tuple is created.
- How to create tuples?

Tuples

- **Immutable** sequence(ordered) of elements.
- Similar to `lists`, you can use **indexing**, **slicing**, and iterate over using `for` loops.
- Elements cannot be added/removed/changed once the tuple is created.
- How to create tuples? `my_tuple = (1, [1, 2], 'a')`

Tuples

- **Immutable** sequence(ordered) of elements.
- Similar to `lists`, you can use **indexing**, **slicing**, and iterate over using `for` loops.
- Elements cannot be added/removed/changed once the tuple is created.
- How to create tuples? `my_tuple = (1, [1, 2], 'a')`
- `len(my_tuple)` \Rightarrow

Tuples

- **Immutable** sequence(ordered) of elements.
- Similar to `lists`, you can use **indexing**, **slicing**, and iterate over using `for` loops.
- Elements cannot be added/removed/changed once the tuple is created.
- How to create tuples? `my_tuple = (1, [1, 2], 'a')`
- `len(my_tuple) ⇒ 3`
- `my_tuple.append(3) ⇒`

Tuples

- **Immutable** sequence(ordered) of elements.
- Similar to `lists`, you can use **indexing**, **slicing**, and iterate over using `for` loops.
- Elements cannot be added/removed/changed once the tuple is created.
- How to create tuples? `my_tuple = (1, [1, 2], 'a')`
- `len(my_tuple) ⇒ 3`
- `my_tuple.append(3) ⇒ AttributeError:`
`'tuple' object has no attribute 'append'`

Tuples

`() / tuple(): empty tuple,`

Tuples

```
() / tuple(): empty tuple,  
(3):
```

Tuples

```
() / tuple(): empty tuple,  
(3): int 3,
```

Tuples

```
() / tuple(): empty tuple,  
(3): int 3,  
(3,):
```

Tuples

`() / tuple():` empty tuple,
`(3):` int **3**,
`(3,):` tuple containing 3

Tuples

() / tuple(): empty tuple,
 (3): int 3,
 (3,): tuple containing 3

```
my_list = [1, 2, 3]
my_tuple = ('a', my_list) # ('a', [1, 2, 3, 4])
my_list.append(4)
print(my_tuple)
my_list += [5, 6, 7] # my_list.extend(...)
print(my_tuple)
my_tuple += (1, 2) # my_tuple = my_tuple + (1, 2)
print(my_tuple)
```

Sets

- **Unordered** sequence of **unique** elements.

Sets

- **Unordered** sequence of **unique** elements.
- **Cannot** use **indexing/slicing**, can iterate with `for` loops.

Sets

- **Unordered** sequence of **unique** elements.
- **Cannot** use **indexing/slicing**, **can** iterate with `for` loops.
- **Mutable**, `add(element)`, `remove(element)` methods.

Sets

- **Unordered** sequence of **unique** elements.
- **Cannot** use **indexing/slicing**, can iterate with `for` loops.
- **Mutable**, `add(element)`, `remove(element)` methods.
- Python also has **immutable** sets: `frozenset`

Sets

- **Unordered** sequence of **unique** elements.
- **Cannot** use **indexing/slicing**, **can** iterate with `for` loops.
- **Mutable**, `add(element)`, `remove(element)` methods.
- Python also has **immutable** sets: `frozenset`
- How to create sets?

Sets

- **Unordered** sequence of **unique** elements.
- **Cannot** use **indexing/slicing**, can iterate with `for` loops.
- **Mutable**, `add(element)`, `remove(element)` methods.
- Python also has **immutable** sets: `frozenset`
- How to create sets? `my_set = {1, 2, 3, 4, 2}`
- How to create empty sets?


Sets

- **Unordered** sequence of **unique** elements.
- **Cannot** use **indexing/slicing**, can iterate with `for` loops.
- **Mutable**, `add(element)`, `remove(element)` methods.
- Python also has **immutable** sets: `frozenset`
- How to create sets? `my_set = {1, 2, 3, 4, 2}`
- How to create empty sets? `set()` (`{ }` is reserved for `dict`)

Sets

- **Unordered** sequence of **unique** elements.
- **Cannot** use **indexing/slicing**, can iterate with `for` loops.
- **Mutable**, `add(element)`, `remove(element)` methods.
- Python also has **immutable** sets: `frozenset`
- How to create sets? `my_set = {1, 2, 3, 4, 2}`
- How to create empty sets? `set()` (`{ }` is reserved for `dict`)
- Can compute set operations: **union**, **intersection**, **difference**, **symmetric difference**.

Sets



Sets

```
ceren = {'Marco', 'Irem', 'Sunduz'}
gul_sena = {'Gamze', 'Ata', 'Zeynep'}
hasan_can = {'Gamze', 'Berker', 'Cemre'}
ahmet = {'Irem', 'Demet', 'Ekin'}

# intersection &
print(gul_sena.intersection(hasan_can)) # => {'Gamze'}
print(ceren & gul_sena) # => set()
# union |
print(ceren.union(ahmet)) # => {'Ekin', 'Irem', 'Demet',
                                # 'Marco', 'Sunduz'}
print(hasan_can | ceren | gul_sena | ahmet) # => all names
# difference -
print((gul_sena - hasan_can)) # => {'Zeynep', 'Ata'}
# symmetric_difference ^
print(ceren.symmetric_difference(ahmet))
# => {'Marco', 'Ekin', 'Sunduz', 'Demet'}}
```

Dictionaries

- Collection of **key–value** pairs.

Dictionaries

- Collection of **key–value pairs**.
- **Cannot** use **indexing/slicing**, can iterate with `for` loops.

Dictionaries

- Collection of **key–value** pairs.
- **Cannot** use **indexing/slicing**, can iterate with `for` loops.
- In general, they are not **ordered**.

Dictionaries

- Collection of **key–value** pairs.
- **Cannot** use **indexing/slicing**, can iterate with `for` loops.
- In general, they are not **ordered**.
- However, in Python 3.7 pairs are guaranteed to be in insertion order.

Dictionaries

- Collection of **key–value** pairs.
- **Cannot** use **indexing/slicing**, can iterate with `for` loops.
- In general, they are not **ordered**.
- However, in Python 3.7 pairs are guaranteed to be in insertion order.
- In other words, we will get pairs in insertion order if we loop over the `dict`.

Dictionaries

- Collection of **key–value** pairs.
- **Cannot** use **indexing/slicing**, can iterate with `for` loops.
- In general, they are not **ordered**.
- However, in Python 3.7 pairs are guaranteed to be in insertion order.
- In other words, we will get pairs in insertion order if we loop over the `dict`.
- How to create dictionaries?

Dictionaries

- Collection of **key–value** pairs.
- **Cannot** use **indexing/slicing**, can iterate with `for` loops.
- In general, they are not **ordered**.
- However, in Python 3.7 pairs are guaranteed to be in insertion order.
- In other words, we will get pairs in insertion order if we loop over the `dict`.
- How to create dictionaries? `{ }/dict()`: empty dictionary

Dictionaries

- Collection of **key–value** pairs.
- **Cannot** use **indexing/slicing**, can iterate with `for` loops.
- In general, they are not **ordered**.
- However, in Python 3.7 pairs are guaranteed to be in insertion order.
- In other words, we will get pairs in insertion order if we loop over the `dict`.
- How to create dictionaries? `{ }/dict()`: empty dictionary
- `d = {'one': 1, 'two': 2, 'three': 3, 'four': 4}`

Dictionaries

- Collection of **key–value** pairs.
- **Cannot** use **indexing/slicing**, can iterate with `for` loops.
- In general, they are not **ordered**.
- However, in Python 3.7 pairs are guaranteed to be in insertion order.
- In other words, we will get pairs in insertion order if we loop over the `dict`.
- How to create dictionaries? `{ }/dict()`: empty dictionary
- `d = {'one': 1, 'two': 2, 'three': 3, 'four': 4}`
- How to access values?

Dictionaries

- Collection of **key–value** pairs.
- **Cannot** use **indexing/slicing**, can iterate with `for` loops.
- In general, they are not **ordered**.
- However, in Python 3.7 pairs are guaranteed to be in insertion order.
- In other words, we will get pairs in insertion order if we loop over the `dict`.
- How to create dictionaries? `{ }/dict()`: empty dictionary
- `d = {'one': 1, 'two': 2, 'three': 3, 'four': 4}`
- How to access values? `print(d['one']) # ⇒ 1`

Confused Section Leader Gul Sena

```
# I need a way to keep track of my students
my_students = {'Ayse': ['economics', 'freshman'],
               'Emir': ['psychology', 'master'],
               'Emirhan': ['business administration', 'junior'],
               'Furkan': ['law', 'junior'],
               'Mahsa': ['material science', 'phd'],
               'Meva': ['international relations', 'freshman']}

for student, info in my_students.items():
    print(f'{student} studies {info[0]}')
# Emir left my class :(
my_students.pop('Emir')
# someone new in my class
my_students['Canan'] = ['industrial engineering', 'junior']
# Ayse passed another year
my_students['Ayse'][1] = 'sophomore'
```