

1. Recap  
○○○○○○

2. Strings  
○○○○

3. While Loops  
○○

4. Lists  
○○○○○○○○○○○○○○

5. For Loops  
○○○○

# KOLT Python

## Strings, Loops & Lists

Ahmet Uysal

Monday 7<sup>th</sup> October, 2019

# KOLT



1. Recap  
○○○○○○

2. Strings  
○○○○

3. While Loops  
○○

4. Lists  
○○○○○○○○○○○○○○

5. For Loops  
○○○○

# Agenda

1. Recap

2. Strings

3. While Loops

4. Lists

5. For Loops

# Branching

```
if <condition>:  
    <expression>  
    <expression>  
    ...
```

```
if <condition>:  
    <expression>  
    <expression>  
    ...  
else:  
    <expression>  
    <expression>  
    ...
```

```
if <condition>:  
    <expression>  
    <expression>  
    ...  
elif <condition>:  
    <expression>  
    <expression>  
    ...  
...  
else:  
    <expression>  
    <expression>  
    ...
```

- <condition> has a **bool** value (True or False)
- Which expressions will be evaluated in which conditions?

## Branching Example

```
if have_ideas_for_exciting_examples():  
    .  
    .  
    .  
elif gul_sena_has_awesome_ideas():  
    let_her_prepare_the_slides()  
else:  
    prepare_slides_about_your_misery()  
    apologize_to_class()
```

## Branching Example

```
if have_ideas_for_exciting_examples():  
    .  
    .  
    .  
elif gul_sena_has_awesome_ideas():  
    let_her_prepare_the_slides()  
else:  
    prepare_slides_about_your_misery()  
    apologize_to_class()
```

# Comparison Operators

- <: Strictly less than
- <=: Less than or equal
- >: Strictly greater than
- >=: Greater than or equal
- ==: Equal
- !=: Not equal

```
3.0 == 3    # => True
3.0 >= 3    # => True
# Small-case characters
# have bigger ASCII value
'Aa' > 'aa' # => False
'hi' == 'hi' # => True
'a' == None  # => True
3 > 'a'     # => TypeError
3 == 'a'    # => False
```

## bool Operators

How to represent logical operations in Python? (and, or, not)

A	B	A or B	A and B	not A
True	True	True	True	False
True	False	True	False	False
False	True	True	False	True
False	False	False	False	True

True or False and False  $\Rightarrow$  **True**

- and
- or
- not

## WHY?



# Assignment Operators

Operator	Usage	Equivalent
<code>+=</code>	<code>val += 3</code>	<code>val = val + 3</code>
<code>-=</code>	<code>val -= 3</code>	<code>val = val - 3</code>
<code>*=</code>	<code>val *= 3</code>	<code>val = val * 3</code>
<code>/=</code>	<code>val /= 3</code>	<code>val = val / 3</code>
<code>%=</code>	<code>val %= 3</code>	<code>val = val % 3</code>
<code>**=</code>	<code>val **= 3</code>	<code>val = val ** 3</code>
<code>//=</code>	<code>val //= 3</code>	<code>val = val // 3</code>



1. Recap  
○○○○○○

2. Strings  
●○○○

3. While Loops  
○○

4. Lists  
○○○○○○○○○○○○○○

5. For Loops  
○○○○

# Strings

# Strings

```
my_string = 'abcde'
```

# Strings

```
my_string = 'abcde'
```

```
    0 1 2 3 4  
    'a b c d e'
```

# Strings

```
my_string = 'abcde'
```

```
  0 1 2 3 4  
'a b c d e'  
-5 -4 -3 -2 -1
```

# Strings

```
my_string = 'abcde'
```

```
  0 1 2 3 4  
'a b c d e'  
-5-4-3-2-1
```

```
print(my_string[2])
```

# Strings

```
my_string = 'abcde'
```

```
  0 1 2 3 4  
  'a b c d e'  
 -5 -4 -3 -2 -1
```

```
print(my_string[2]) ⇒ prints c
```

# Strings

```
my_string = 'abcde'
```

```
    0 1 2 3 4  
    'a b c d e'  
   -5 -4 -3 -2 -1
```

```
print(my_string[2]) ⇒ prints c  
print(my_string[-2])
```

# Strings

```
my_string = 'abcde'
```

```
    0 1 2 3 4  
    'a b c d e'  
   -5 -4 -3 -2 -1
```

```
print(my_string[2]) ⇒ prints c
```

```
print(my_string[-2]) ⇒ prints d
```



1. Recap  
○○○○○○

2. Strings  
○●○○

3. While Loops  
○○

4. Lists  
○○○○○○○○○○○○○○

5. For Loops  
○○○○

# Indexing & Slicing

# Indexing & Slicing

Access specific characters using **indexing**, i.e, [**index**]

## Indexing & Slicing

Access specific characters using **indexing**, i.e, `[index]`  
**Slice** strings by using `[start:stop:step]`



## Indexing & Slicing

Access specific characters using **indexing**, i.e, `[index]`  
**Slice** strings by using `[start:stop:step]`

```
s = 'Python'
s[1] # => 'y'
s[0:4] # => 'Pyth'
s[:3] # => 'Pyt'
s[3:] # => 'hon'
s[:] # => 'Python'
```

## Indexing & Slicing

Access specific characters using **indexing**, i.e, `[index]`  
**Slice** strings by using `[start:stop:step]`

```
s = 'Python'
s[1] # => 'y'
s[0:4] # => 'Pyth'
s[:3] # => 'Pyt'
s[3:] # => 'hon'
s[:] # => 'Python'
```

```
s = 'Python'
s[:5:2] # => 'Pto'
s[1:4:3] # => 'y'
s[::3] # => 'Ph'
s[::-1] # => 'nohtyP'
```

1. Recap  
○○○○○○

2. Strings  
○○●○

3. While Loops  
○○

4. Lists  
○○○○○○○○○○○○○○

5. For Loops  
○○○○

# String Operations

## String Operations

```
print('This a simple calculator program.')  
number1 = input('Please enter the first number:')  
number2 = input('Please enter the second number:')  
print(f'{number1}+{number2} is {number1 + number2}')
```

## String Operations

```
print('This a simple calculator program.')
number1 = input('Please enter the first number:')
number2 = input('Please enter the second number:')
print(f'{number1}+{number2} is {number1 + number2}')
```

```
number1 = int(input('First number:'))
number2 = input('Please enter the second number:')
print(f'{number1}x{number2} is {number1 * number2}')
```



# String Operations

```
print('This a simple calculator program.')
number1 = input('Please enter the first number:')
number2 = input('Please enter the second number:')
print(f'{number1}+{number2} is {number1 + number2}')
```

```
number1 = int(input('First number:'))
number2 = input('Please enter the second number:')
print(f'{number1}x{number2} is {number1 * number2}')
```

**str1 + str2** ⇒ **Concatenate** str1 and str2



# String Operations

```
print('This a simple calculator program.')
number1 = input('Please enter the first number:')
number2 = input('Please enter the second number:')
print(f'{number1}+{number2} is {number1 + number2}')
```

```
number1 = int(input('First number:'))
number2 = input('Please enter the second number:')
print(f'{number1}x{number2} is {number1 * number2}')
```

**str1 + str2** ⇒ **Concatenate** str1 and str2

**str1 \* n** ⇒ Repeat str1 *n* times.



1. Recap  
○○○○○○

2. Strings  
○○○●

3. While Loops  
○○

4. Lists  
○○○○○○○○○○○○○○

5. For Loops  
○○○○

## Example: Evil Laughter



1. Recap  
○○○○○○

2. Strings  
○○○○

3. While Loops  
●○

4. Lists  
○○○○○○○○○○○○○○

5. For Loops  
○○○○

# While Loops

# While Loops

Repeat some <expression>s as long as a <condition> is True.



# While Loops

Repeat some <expression>s as long as a <condition> is True.

```
while <condition>:  
    <expression>  
    <expression>  
    ...
```



# While Loops

Repeat some <expression>s as long as a <condition> is True.

```
while <condition>:  
    <expression>  
    <expression>  
    ...
```

```
x = 15  
while x > 10:  
    print(x)  
    x-=1
```

# While Loops

Repeat some <expression>s as long as a <condition> is True.

```
while <condition>:  
    <expression>  
    <expression>  
    ...
```

```
x = 15  
while x > 10:  
    print(x)  
    x-=1
```

```
counter = 11  
while counter > 6:  
    counter -= 1  
    print(2**counter)  
    counter -= 1
```





# While Loops

Repeat some <expression>s as long as a <condition> is True.

```
while <condition>:  
    <expression>  
    <expression>  
    ...
```

```
x = 15  
while x > 10:  
    print(x)  
    x-=1
```

```
counter = 11  
while counter > 6:  
    counter -= 1  
    print(2**counter)  
    counter -= 1
```

<condition> is only checked **before** each execution.



1. Recap  
○○○○○○

2. Strings  
○○○○

3. While Loops  
○●

4. Lists  
○○○○○○○○○○○○○○

5. For Loops  
○○○○

## Example: Evil Laughter (Cont.)



1. Recap  
○○○○○○

2. Strings  
○○○○

3. While Loops  
○○

4. Lists  
●○○○○○○○○○○○○○○

5. For Loops  
○○○○

# Lists

1. Recap  
○○○○○○

2. Strings  
○○○○

3. While Loops  
○○

4. Lists  
●○○○○○○○○○○○○○○

5. For Loops  
○○○○

# Lists



1. Recap  
○○○○○○

2. Strings  
○○○○

3. While Loops  
○○

4. Lists  
●○○○○○○○○○○○○○○

5. For Loops  
○○○○

# Lists



Imagine variables, but with limitless capacity. . .

# Lists



Imagine variables, but with limitless capacity. . .

```
sunnyside = ['Mr. Potato Head', 'Hamm',  
'Buzz Lightyear', 'Slinky Dog']
```

1. Recap  
○○○○○○

2. Strings  
○○○○

3. While Loops  
○○

4. Lists  
●○○○○○○○○○○○○

5. For Loops  
○○○○

# Lists

## Lists

```
empty_list = []  
letters = ['a', 'b', 'c', 'd']  
numbers = [2, 3, 5]
```



## Lists

```
empty_list = []  
letters = ['a', 'b', 'c', 'd']  
numbers = [2, 3, 5]  
  
mixed_list = [4, 13, 'hello']
```

1. Recap  
○○○○○○

2. Strings  
○○○○

3. While Loops  
○○

4. Lists  
○○●○○○○○○○○○○

5. For Loops  
○○○○

# Accessing Elements

## Accessing Elements

0      1      2      3      4  
[ 1, 'hello', None, [3], True ]

## Accessing Elements

0	1	2	3	4
[ 1, 'hello', None, [3], True ]				
-5	-4	-3	-2	-1

## Accessing Elements

0	1	2	3	4
[ 1, 'hello', None, [3], True ]				
-5	-4	-3	-2	-1

Use **indexing**, to access and **update** elements.

## Accessing Elements

0	1	2	3	4
[ 1, 'hello', None, [3], True ]				
-5	-4	-3	-2	-1

Use **indexing**, to access and **update** elements.  
`print(values[2])`

## Accessing Elements

0	1	2	3	4
[ 1, 'hello', None, [3], True ]				
-5	-4	-3	-2	-1

Use **indexing**, to access and **update** elements.

```
print(values[2])  
values[2] = 'new value'
```

# Appending

Append elements at the end of a list by **append()**

```
numbers = [1, 2, 3]
numbers.append(7) # => numbers = [1, 2, 3, 7]
numbers.append(11) # => numbers = [1, 2, 3, 7, 11]

a_list = [1, 'a', 'python', 4.2]
a_list.append(3) # => a_list = [1, 'a', 'python', 4.2, 3]
a_list.append('hello') # => a_list = [1, 'a', 'python', 4.2, 3, 'hell
```



# Appending

Append elements at the end of a list by **append()**

```
numbers = [1, 2, 3]
numbers.append(7) # => numbers = [1, 2, 3, 7]
numbers.append(11) # => numbers = [1, 2, 3, 7, 11]

a_list = [1, 'a', 'python', 4.2]
a_list.append(3) # => a_list = [1, 'a', 'python', 4.2, 3]
a_list.append('hello') # => a_list = [1, 'a', 'python', 4.2, 3, 'hello']

x = [1, 2, 3]
y = [4, 5]
x.append(y) # => x = [1, 2, 3, [4, 5]]
```

# Removing An Element

Remove elements in a list by **remove()**

```
x = [1, 2, 3, 4]

x.remove(2) # => x = [1, 3, 4]

y = ['a', 'b', 'c']

y.remove('b') # => y = ['a', 'c']
```

# Removing An Element

Remove elements in a list by **remove()**

```
x = [1, 2, 3, 4]

x.remove(2) # => x = [1, 3, 4]

y = ['a', 'b', 'c']

y.remove('b') # => y = ['a', 'c']
```

```
x = [1, 2, 5, 4, 2, 6]

x.remove(2) # => x = [1, 5, 4, 2, 6]
```

# Inspecting List Elements

Slice lists by using `[start:stop:step]`

```
x = [1, 2, 3, 4, 5]
```

```
x[2:4] # => [3, 4]
```

```
x[3:4] # => [4]
```

```
x[1:-1] # => [2, 3, 4]
```

# Inspecting List Elements

Slice lists by using `[start:stop:step]`

```
x = [1, 2, 3, 4, 5]
```

```
x[2:4] # => [3, 4]
```

```
x[3:4] # => [4]
```

```
x[1:-1] # => [2, 3, 4]
```

```
y = ['a', 'b', 'c', 'd', 'e', 'f']
```

```
y[:3] # => ['a', 'b', 'c']
```

```
y[2:] # => ['c', 'd', 'e', 'f']
```

```
y[:-1] # => ['a', 'b', 'c', 'd', 'e']
```

```
y[:] # => ['a', 'b', 'c', 'd', 'e', 'f']
```

## Inspecting List Elements

```
y = ['a', 'b', 'c', 'd', 'e', 'f']  
  
y[1:5:2] # => ['b', 'd']  
y[::3] # => ['a', 'd']
```



## Inspecting List Elements

```
y = ['a', 'b', 'c', 'd', 'e', 'f']
```

```
y[1:5:2] # => ['b', 'd']
```

```
y[::3] # => ['a', 'd']
```

```
y = ['a', 'b', 'c', 'd', 'e', 'f']
```

```
y[::-1] # => ['f', 'e', 'd', 'c', 'b', 'a']
```

# Nested Lists

Lists can contain lists

```
x = [[15, 4, 20, 7], [3, 18, 9]]  
  
x[1] # => [3, 18, 9]  
x[1][2] # => 9  
x[0][2:] # => [20, 7]
```



# in Operator

Search an operand in the specified sequence by using **in**

```
0 in [] # => False
'y' in 'Python' # => True
23 in ['hello', 40, 'a', 5] # => False
23 in ['hello', 40, 'a', 23] # => True
23 in ['hello', 40, 'a', '23'] # => False
```

- Works with lists and strings
- Works with ranges

# len() Function

`len()` is an operator to determine the size of lists, strings, etc.

```
s = 'Python'
len(s) # => 6

my_list = [0, 1, 2, 3]
len(my_list) # => 4
```



## List Slicing

Access collection of elements by specifying

**[start:stop:step]**

Gives a list, even when number of elements is not bigger than 1.

```
numbers = [0, 1, 2, 3, 4, 5]
```

```
"""
```

```
ASCII art analogy :)
```

```
+---+---+---+---+---+---+
```

```
| 0 | 1 | 2 | 3 | 4 | 5 | => Indices
```

```
+---+---+---+---+---+---+
```

```
0   1   2   3   4   5   6 => Borders
```

```
-6  -5  -4  -3  -2  -1
```

```
"""
```

```
numbers[0::2] # => [0, 2, 4]
```

```
numbers[:] # => [0, 1, 2, 3, 4, 5]
```

```
numbers[1:] # => [1, 2, 3, 4, 5]
```

```
numbers[-2:] # => [4, 5]
```

```
numbers[1:4] # => [1, 2, 3]
```

```
numbers[1:1] # => []
```

```
numbers[-99:99] # => [0, 1, 2, 3, 4, 5]
```

```
numbers[::-1] # => [5, 4, 3, 2, 1, 0]
```

```
numbers[::-2] # => [5, 3, 1]
```

Slices with `step = 1` are called **Basic Slice**.

Slices with `step != 1` are called **Extended Slice**.

## List Mutation

**list.append(x)**: Append x to end of the sequence

**list.insert(i, x)**: Insert x to index i

**list.pop(i=-1)**: Remove and return element at index i

**list.remove(x)**: Remove first occurrence of x

**list.extend(iterable)**: Add all elements in iterable to end of list

**list[i] = new\_value**: Update value of index i with new value

**list[basic\_slice] = iterable**: Change elements in basic slice with elements in iterable, sizes can be different:

```
numbers[:] = []
```

**list[extended\_slice] = iterable**: Change elements in extended slice with elements in iterable 1-1, sizes must be equal.

## Some Other List Operations

**in** operator: Check whether an element is in list. `3 in numbers`  $\Rightarrow$  True

**len(list)**: Returns the length of list(and other collections).

**list.index(value, start=0, stop=len(list))**: Return first index of value.

**list.count(value)**: Count number of occurrences of value in list.

**list.reverse()**: Reverse the list (in-place)

**list.sort()**: Sort list elements (in-place)

For more, type `help(list)` in your interactive interpreter.

## range() Function

`range(start, stop, step)` is a function to create ranges

```
a = range(3) # => generates 0, 1, 2
b = range(0,3) # => generates 0, 1, 2
c = range(2,4) # => generates 2, 3
d = range(0,6,2) # => generates 0, 2, 4

0 in a # => True
1 in b # => True
4 in c # => False
2 in d # => True
6 in d # => False
```

# For Loops

```
for <item> in <iterable>:  
    <expression>  
    <expression>  
    ...
```

# For Loops

```
for <item> in <iterable>:  
    <expression>  
    <expression>  
    ...
```

```
for ch in 'Python':  
    print(ch)
```



# For Loops

```
for <item> in <iterable>:  
    <expression>  
    <expression>  
    ...
```

```
for ch in 'Python':  
    print(ch)
```

```
for num in [4,23,12,0,50]:  
    print(num * 3, sep=".")
```

# For Loops

```
for <item> in <iterable>:  
    <expression>  
    <expression>  
    ...
```

```
for ch in 'Python':  
    print(ch)
```

```
for num in [4,23,12,0,50]:  
    print(num * 3, sep=".")
```

```
for i in range(0,8):  
    print(i)
```

# Break, Continue & Pass

**break** immediately terminates the closest loop

```
for i in range(0, 5):  
    if i % 2 == 1:  
        break  
    print(i)
```

# Break, Continue & Pass

**break** immediately terminates the closest loop

```
for i in range(0, 5):  
    if i % 2 == 1:  
        break  
    print(i)
```

```
x = 1  
while x < 100:  
    x *= 2  
    if (x+1) % 3 == 0:  
        break  
    print(x)
```

# Break, Continue & Pass

**break** immediately terminates the closest loop

```
for i in range(0, 5):  
    if i % 2 == 1:  
        break  
    print(i)
```

```
x = 1  
while x < 100:  
    x *= 2  
    if (x+1) % 3 == 0:  
        break  
    print(x)
```

**Continue** continues with the next iteration of the loop

```
for i in range(0, 5):  
    if i % 2 == 1:  
        continue  
    print(i)
```

# Break, Continue & Pass

**break** immediately terminates the closest loop

```
for i in range(0, 5):  
    if i % 2 == 1:  
        break  
    print(i)
```

```
x = 1  
while x < 100:  
    x *= 2  
    if (x+1) % 3 == 0:  
        break  
    print(x)
```

**Continue** continues with the next iteration of the loop

```
for i in range(0, 5):  
    if i % 2 == 1:  
        continue  
    print(i)
```

```
x = 1  
while x < 100:  
    x *= 2  
    if (x+1) % 3 == 0:  
        continue  
    print(x)
```

# Break, Continue & Pass

**Pass** does not have an effect

```
for letter in 'Python':  
    if letter == 'y':  
        pass  
    print ('In pass case')  
print (letter)
```

- Loops, conditional statements, functions etc. cannot be empty
- Use when you have to create one